MIL-R-60862(MU)
10 April 1968

# MILITARY SPECIFICATION
# REMOVER, AIRCRAFT CANOPY
# OVERHAUL, MODIFICATION AND CONVERSION
# OF P/N 2218-17 TO P/N 2218-18

## 1. SCOPE

1.1 This specification covers the overhaul and modification required to convert Remover, Aircraft Canopy, P/N 2218-17 to the Remover, Aircraft Canopy, P/N 2218-18 configuration.

## 2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

Military

| | |
|---|---|
| MIL-A-2550 | - Ammunition and Special Weapons, General Specification for |
| MIL-G-4343 | - Grease, Pneumatic System |
| MIL-S-5002 | - Surface Treatment, and Metallic Coatings for Metal Surfaces of Weapons Systems |
| MIL-P-8585 | - Primer, Coating, Zinc Chromate, Low - Moisture Sensitivity |
| MIL-A-8625 | - Anodic Coatings, for Aluminum and Aluminum Alloys |
| MIL-G-23827 | - Grease, Aircraft and Instrument, Gear and Actuator Screw |
| MIL-L-8937 | - Lubricant, Solid Film, Heat Cured |
| MIL-C-26074 | - Coating, Nickel - Phosphorus, Electroless, Nickel Requirements For |

STANDARDS

Military

| | |
|---|---|
| MIL-STD-105 | - Sampling Procedures and Tables for Inspection by Attributes |
| MIL-STD-109 | - Quality Assurance Terms and Definitions |

FSC 1377

Source: https://assist.dla.mil -- Downloaded: 202610-23T01:02Z
Check the source to verify that this is the current version before use.

2.1 STANDARDS (Cont'd)

Military

MIL-STD-639 - Surface Roughness Values Preferred for Army Ordnance Material

MIL-STD-1167 - Ammunition Data Card

DRAWINGS

Munitions Command

C9233331 - Carton, Packing Ammunition for Remover, Aircraft Canopy, P/N 2218-18

C9233334 - Box, Packing, Ammunition for One (1) Remover, Aircraft Canopy, P/N 2218-18

Talley Industries (Code Ident. No. 98708)

2218-18 - Actuator, Electro Mechanical, Ballistic Emergency Removal

PUBLICATIONS

Air Force Technical Manual

T.O. 11P4-11-3 - Overhaul Instructions with Parts Breakdown, Canopy Actuator, Part No. 2218-18

(Copies of specifications, standards and drawings required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer.)

3. REQUIREMENTS

3.1 General.- Materials, parts and assemblies shall comply with the requirements specified in T.O. 11P4-11-3, referenced specifications and standards.

3.1.1 When converting Remover, Aircraft Canopy, P/N 2218-17 to Remover, Aircraft Canopy, P/N 2218-18, the following paragraphs contained in T.O. 11P4-11-3 shall not apply:

2-2, j thru m
2-4, j thru w
2-5, f thru u
2-6, e and f
2-7, c thru p
3-3, a thru h



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:02Z
Check the source to verify that this is the current version before use.

3.2 Assembly torque.- The assembly torques for the installation of actuator component parts shall be in accordance with requirements specified in Figure 2-7 of T.O. 11P4-11-3.

3.3 Remover assembly.- The overhauled remover shall contain new parts in accordance with Table I.

TABLE I

| Name of Part | Part Number |
|---|---|
| Seal, O-Ring | MS 9021-010 |
| Seal, O-Ring | MS 9021-012 |
| Seal, O-Ring | MS 9021-021 |
| Seal, O-Ring | MS 9021-029 |
| Seal, O-Ring | MS 9021-030 |
| Seal, O-Ring (2 each req'd) | MS 9021-034 |
| Seal, O-Ring | MS 9021-135 |
| Seal, O-Ring | 2-25 (Tetraflour, Inc.) |
| Seal, O-Ring | 2-26 (Tetraflour, Inc.) |
| Seal, O-Ring | 2-29 (Tetraflour, Inc.) |
| Seal, O-Ring | 2-30 (Tetraflour, Inc.) |
| Seal, O-Ring | 2-31 (Tetraflour, Inc.) |
| Gasket, Cover | 2218-53 (Talley Ind.) |
| Gasket | 2218-37 (Talley Ind.) |
| Grommet | MS 35490-4 |
| Spring | MS 24585-219 |
| Spring, Compression | 1145-57 (Talley Ind.) |
| Cartridge | 1146-221 (Talley Ind.) |
| Bushing (2 each req'd) | 2218-67 (Talley Ind.) |
| Retainer | 2218-24 (Talley Ind.) |
| Pin, Shear | 1605-50 (Talley Ind.) |
| Pin, Straight | 2218-60 (Talley Ind.) |
| Wiper, Tube | 2218-25 (Talley Ind.) |
| Wiper, Tube | 2218-27 (Talley Ind.) |
| Label, Identification | C10536008 |
| Label, Warning | 1424-128 (Talley Ind.) |
| Label, Warning | B8593294 |
| Set Screw | AN565D1032H5 |
| Cotter Pin | AN381-15-12 (replace with latest Standard MS 24665-88) |
| Set Screw | AN565D1032H5 |
| Set Screw | AN565A4H2 |
| Plug, Shipping | PD40 (Protective Closures Inc.) |
| Cap, Plug | 12 (Protective Closures Inc.) |



Source: https://assist.dla.mil -- Downloaded: 202610-23T01:02Z
Check the source to verify that this is the current version before use.

3.3.1 The following listed parts from Remover, P/N 2218-17, shall be removed, discarded and replaced as noted:

3.3.1.1 Replace Shear Pin, Piston, P/N 51700-30 with Pin, Retaining P/N 2218-111 (Talley Ind.), 2 each required.

3.3.1.2 Replace Motor D.C. P/N 2218-86 with Motor, D.C. P/N 2218-107.

3.3.2 The following listed parts from Remover, P/N 2218-17 shall be modified as noted below:

3.3.2.1 Modify Retainer P/N 2218-85 to contain a flat as depicted on Drawing 2218-108.

3.3.2.2 Modify Switch Housing, P/N 2218-48 in accordance with Drawing D10551939.

3.4 Functional.

3.4.1 Operating load.- The Remover shall be cycled electrically in accordance with the Alternative Actuator Test Procedure, paragraph 3-2, T.O. 11P4-11-3. The time required for linear extension, linear retraction and motor current drain shall comply with requirements in paragraph 3-2, T.O. 11P4-11-3.

3.4.2 Bearing center dimensions.- The bearing center dimensions of the Remover while subjected to the normal operating load shall comply with requirements of paragraph 3-1. f.(1) thru f.(4) of T.O. 11P4-11-3.

3.4.3 Air firing.- The Remover shall stroke in accordance with the requirements of paragraph 3-1. j, T.O. 11P4-11-3, when 375 - 450 pounds per square inch (psi) air pressure is applied to the firing head.

3.5 Protective finish.- Protective finish shall be in accordance with T.O. 11P4-11-3, applicable specifications and drawings, and shall apply to all surfaces of the component, regardless of configuration. Exterior components shall have the existing protective finish stripped and the specified protective finish reapplied (See 6.1).

3.6 Workmanship.- The requirements for workmanship are as specified in T.O. 11P4-11-3, referenced specifications and the following:

3.6.1 Metal defects.- The parts shall be free from cracks, splits or other metal defects.



Source: https://assist.dla.mil -- Downloaded: 202640-23T01:02Z
Check the source to verify that this is the currentversion before use.

3.6.2 Burr.- The part shall not have a burr which might interfere with assembly or function of the item or which might be injurious to personnel handling the item.

3.6.3 Foreign matter.- The part or assembly shall not contain chips, dirt, rust, corrosion or other foreign matter.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Quality assurance terms and definitions.- Reference shall be made to MIL-STD-109 to define quality assurance terms used.

4.1.2 Inspection.- Inspection shall be in accordance with MIL-A-2550 except as specified herein.

4.2 Inspection provisions.

4.2.1 Lot.

4.2.1.1 Submission of product.- The product shall be submitted in accordance with MIL-STD-105.

4.2.1.2 Size of lot.- A lot shall consist of an identifiable group of assembled units containing metal parts assemblies provided the homogeneity of the rebuild process has been retained. The assembly shall be loaded with accepted cartridges.

4.2.2 Examination.- One hundred percent examination shall be performed for all critical defects and defects indicated in paragraph 2.4, a thru i, T.O. 11P4-11-3 unless otherwise specified. Examination for major or minor defects shall be performed on a defect basis in accordance with the classification of defects contained herein, using the sampling plans and criteria in Tables II and III. For an individual defect (single characteristic), the criteria in Table II shall be used. For total defects within a major or minor group, the criteria in Table III shall be used. All nonconforming material shall be rejected. Four power (4X) magnification may be used in performing visual examination for such defects as burr and foreign matter.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:02Z
Check the source to verify that this is the current version before use.

4.2.2.1 Reclaimed parts.- Examination of reusable parts, which require no reprocessing shall be limited to inspection of defects that require visual type inspection. One hundred percent examination shall be performed for all such defects. All nonconforming parts shall be rejected.

4.2.2.2 Reprocessed parts.- Examination shall be limited to a visual type inspection unless otherwise specified. All nonconforming material shall be rejected.

TABLE II

| Lot Size | Sample Size | Major | | Minor | |
|---|---|---|---|---|---|
| | | Accept | Reject | Accept | Reject |
| 1 - 300 | 100% Examination | | | | |
| 301 - 1300 | 110 | 1 | 2 | 2 | 3 |
| 1301 - 3200 | 150 | 2 | 3 | 3 | 4 |
| 3201 - 8000 | 225 | 3 | 4 | 4 | 5 |
| 8001 - 22000 | 300 | 4 | 5 | 5 | 6 |

TABLE III

Total Allowable Defects Per Sample Size

| Sample Sizes for Major Defects | 110 | 150 | 225 | 300 |
|---|---|---|---|---|
| Number of Defects in Class | | | | |
| 2 - 3 | 1 | 2 | 3 | 4 |
| 4 - 7 | 2 | 3 | 4 | 5 |
| 8 - 19 | 3 | 4 | 5 | 7 |
| 20 - 43 | 4 | 5 | 8 | 10 |
| Over - 43 | 6 | 8 | 11 | 14 |
| **Sample Sizes for Minor Defects** | **110** | **150** | **225** | **300** |
| Number of Defects in Class | | | | |
| 2 - 3 | 2 | 3 | 4 | 5 |
| 4 - 7 | 3 | 4 | 5 | 7 |
| 8 - 16 | 4 | 5 | 8 | 10 |
| 17 - 48 | 6 | 8 | 11 | 14 |
| Over - 48 | 8 | 11 | 17 | 20 |



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:02Z
Check the source to verify that this is the current version before use.

4.2.2.3 Clevis, Mounting, Drawing 2218-22 covering a detail of Drawing 2218-18

| Defect | Method of Inspection |
|---|---|
| **CRITICAL** | |
| None defined | |
| **MAJOR** | |
| 101. Pitch diameter of thread, max. | Gage |
| 102. Minor diameter of thread, max. | Gage |
| 103. Diameter of inline holes | Gage |
| 104. Metal defective | Visual |
| 105. Protective finish inadequate or defective | Visual |
| 106. Surface finish improper | Visual |
| 107. Burr | Visual |
| 108. Foreign matter | Visual |
| **MINOR** | |
| None defined | |

4.2.2.4 Sleeve, Adjusting, Drawing 2218-23 covering a detail of Drawing 2218-18

| Defect | Method of Inspection |
|---|---|
| **CRITICAL** | |
| None defined | |
| **MAJOR** | |
| 101. Pitch diameter of thread, max. | Gage |
| 102. Minor diameter of thread, max. | Gage |
| 103. Metal defective | Visual |
| 104. Protective finish inadequate or defective | Visual |
| 105. Lacquer stripe missing | Visual |
| 106. Surface finish improper | Visual |
| 107. Burr | Visual |
| 108. Foreign matter | Visual |
| **MINOR** | |
| None defined | |



Source: https://assist.dla.mil -- Downloaded: 202610-23T01:02Z
Check the source to verify that this is the current version before use.

4.2.2.5 Tube, Intermediate, Drawing 2218-29 covering a detail of Drawing 2218-18

| Defect | Method of Inspection |
|---|---|
| CRITICAL | |
| None defined | |
| MAJOR | |
| 101. Pitch diameter of threads, max., 2 holes | Gage |
| 102. Minor diameter of thread, max. | Gage |
| 103. Metal defective | Visual |
| 104. Protective finish inadequate or defective | Visual |
| 105. Solid film lubricant inadequate or defective | Visual |
| 106. Surface finish improper | Visual |
| 107. Burr | Visual |
| 108. Foreign matter | Visual |
| MINOR | |
| None defined | |

4.2.2.6 Tube, Anti-Rotation, Drawing 2218-30 covering a detail of Drawing 2218-18

| Defect | Method of Inspection |
|---|---|
| CRITICAL | |
| None defined | |
| MAJOR | |
| 101. Pitch diameter of threads, max. | Gage |
| 102. Minor diameter of thread, max. | Gage |
| 103. Splines damaged | Visual |
| 104. Metal defective | Visual |
| 105. Protective finish inadequate or defective | Visual |
| 106. Solid film lubricant inadequate or defective | Visual |
| 107. Surface finish improper | Visual |
| 108. Burr | Visual |
| 109. Foreign matter | Visual |
| MINOR | |
| None defined | |



Source: https://assist.dla.mil -- Downloaded: 202610-23T01:02Z
Check the source to verify that this is the current version before use.

4.2.2.7 Tube, Ballnut Adapter, Drawing 2218-31 covering a detail of Drawing 2218-18

| Defect | | Method of Inspection |
|---|---|---|
| CRITICAL | | |
| None defined | | |
| MAJOR | | |
| 101. | Metal defective | Visual |
| 102. | Protective finish inadequate or defective | Visual |
| 103. | Solid film lubrication inadequate or defective | Visual |
| 104. | Surface finish improper | Visual |
| 105. | Burr | Visual |
| 106. | Foreign matter | Visual |
| MINOR | | |
| None defined | | |

4.2.2.8 Tube, Outside, Drawing 2218-34 covering a detail of Drawing 2218-18

| | | |
|---|---|---|
| CRITICAL | | |
| None defined | | |
| MAJOR | | |
| 101. | Pitch diameter of large outside thread, min. | Gage |
| 102. | Major diameter of large outside thread, min. | Gage |
| 103. | Pitch diameter of small outside thread, min. | Gage |
| 104. | Major diameter of small outside thread, min. | Gage |
| 105. | Splines damaged | Visual |
| 106. | Metal defective | Visual |
| 107. | Protective finish inadequate or defective | Visual |
| 108. | Surface finish improper | Visual |
| 109. | Burr | Visual |
| 110. | Foreign matter | Visual |
| MINOR | | |
| None defined | | |



Source: https://assist.dla.mil -- Downloaded: 202640-23T01:02Z
Check the source to verify that this is the currentversion before use.

4.2.2.9 End Cover, Drawing 2218-38 covering a detail of Drawing 2218-18

| | Defect | Method of Inspection |
|---|---|---|
| CRITICAL | | |
| | None defined | |
| MAJOR | | |
| 101. | Metal defective | Visual |
| 102. | Protective finish inadequate or defective | Visual |
| 103. | Surface finish improper | Visual |
| 104. | Burr | Visual |
| 105. | Foreign matter | Visual |
| MINOR | | |
| | None defined | |

4.2.2.10 Sleeve, Holder, Drawing 2218-46 covering a detail of Drawing 2218-18

| | | |
|---|---|---|
| CRITICAL | | |
| | None defined | |
| MAJOR | | |
| 101. | Pitch diameter of thread, max. | Gage |
| 102. | Minor diameter of thread, max. | Gage |
| 103. | Metal defective | Visual |
| 104. | Protective finish inadequate or defective | Visual |
| 105. | Surface finish improper | Visual |
| 106. | Burr | Visual |
| 107. | Foreign matter | Visual |
| MINOR | | |
| | None defined | |

4.2.2.11 Cover, Housing, Drawing 2218-54 covering a detail of Drawing 2218-18

| | | |
|---|---|---|
| CRITICAL | | |
| | None defined | |



Source: https://assist.dla.mil -- Downloaded: 202610-23T01:02Z
Check the source to verify that this is the current version before use.

4.2.2.11 (Cont'd)

| Defect | Method of Inspection |
|---|---|
| **MAJOR** | |
| 101. Metal defective | Visual |
| 102. Protective finish inadequate or defective | Visual |
| 103. Surface finish improper | Visual |
| 104. Burr | Visual |
| 105. Foreign matter | Visual |
| **MINOR** | |
| None defined | |

4.2.2.12 Gear, Housing, Drawing 2218-75 covering a detail of Drawing 2218-18

| | |
|---|---|
| **CRITICAL** | |
| None defined | |
| **MAJOR** | |
| 101. Pitch diameter of large inside thread, max. | Gage |
| 102. Minor diameter of large inside thread, max. | Gage |
| 103. Pitch diameter of outside thread on boss, min. | Gage |
| 104. Major diameter of outside thread on boss, min. | Gage |
| 105. Metal defective | Visual |
| 106. Protective finish inadequate or defective | Visual |
| 107. Surface finish improper | Visual |
| 108. Burr | Visual |
| 109. Foreign matter | Visual |
| **MINOR** | |
| None defined | |

4.2.2.13 Head, Firing, Drawing 2218-87 covering a detail of Drawing 2218-18

| | |
|---|---|
| **CRITICAL** | |
| None defined | |



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:02Z
Check the source to verify that this is the current version before use.

4.2.2.13 (Cont'd)

| Defect | Method of Inspection |
|---|---|
| **MAJOR** | |
| 101. Pitch diameter of large inside thread, max. | Gage |
| 102. Minor diameter of large inside thread, max. | Gage |
| 103. Pitch diameter of small inside thread, max. | Gage |
| 104. Minor diameter of small inside thread, max. | Gage |
| 105. Metal defective | Visual |
| 106. Protective finish inadequate or defective | Visual |
| 107. Surface finish improper | Visual |
| 108. Burr | Visual |
| 109. Foreign matter | Visual |
| **MINOR** | |
| None defined | |

4.2.2.14 Retainer, Drawing 2218-108 covering a detail of Drawing 2218-18

| | |
|---|---|
| **CRITICAL** | |
| None defined | |
| **MAJOR** | |
| 101. Distance from flat to center of hole | Gage |
| 102. Angle of flat incorrect | Gage |
| 103. Any part missing | Visual |
| 104. Improper assembly | Visual |
| 105. Metal defective | Visual |
| 106. Protective finish inadequate or defective | Visual |
| 107. Surface finish improper | Visual |
| 108. Burr | Visual |
| 109. Foreign matter | Visual |
| **MINOR** | |
| None defined | |



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:02Z
Check the source to verify that this is the current version before use.

4.2.2.15 Switch, Housing Assembly, Drawing 2218-48 and D10551939 covering a detail of Drawing 2218-18

| Defect | | Method of Inspection |
|---|---|---|
| CRITICAL | | |
| | None defined | |
| MAJOR | | |
| 101. | Width of slots | Gage |
| 102. | Length of slots | Gage |
| 103. | Any part missing | Visual |
| 104. | Improper assembly | Visual |
| 105. | Metal defective | Visual |
| 106. | Protective finish inadequate or defective | Visual |
| 107. | Surface finish improper | Visual |
| 108. | Burr | Visual |
| 109. | Foreign matter | Visual |
| MINOR | | |
| | None defined | |

4.2.2.16 Cartridge Assembly, Drawing 1146-221 covering a detail of Drawing 2218-18

| | | |
|---|---|---|
| CRITICAL | | |
| 1. | Mixed cartridges | Visual |
| 2. | Metal defective | Visual |
| 3. | Sealing disc missing or damaged | Visual |
| 4. | Marking missing, incorrect or illegible | Visual |
| MAJOR | | |
| 101. | Foreign matter | Visual |
| MINOR | | |
| 201. | Case scratched, wrinkled, bulged or dented | Visual |
| 202. | Protective finish missing or inadequate | Visual |



Source: https://assist.dla.mil -- Downloaded: 202610-23T01:02Z
Check the source to verify that this is the current version before use.

4.2.2.17 Assembly, Drawing 2218-18

| Defect | Method of Inspection |
|---|---|
| **CRITICAL** | |
| 1. Improper assembly | Visual |
| 2. Any part missing | Visual |
| 3. Labels missing, incorrect or illegible | Visual |
| **MAJOR** | |
| 101. Improper alignment | Visual |
| 102. Set screw missing, loose, above flush, or not covered with sealing compound | Visual |
| **MINOR** | |
| 201. Location of labels incorrect | Visual |
| 202. Protective finish missing or inadequate | Visual |
| 203. Shipping cap missing | Visual |

4.2.2.18 Carton, Ammunition, Fiber, Drawing C9233331

| | |
|---|---|
| **CRITICAL** | |
| None defined | |
| **MAJOR** | |
| None defined | |
| **MINOR** | |
| 201. Flaps or cover loose or distorted | Manual and Visual |
| 202. Contents loose | Manual |
| 203. Sealing strips missing, loose or improperly applied | Visual |
| 204. Cut or damaged through all impregnated layers | Visual |
| 205. Marking missing, incorrect or illegible | Visual |



Source: https://assist.dla.mil -- Downloaded: 202610-23T01:02Z
Check the source to verify that this is the current version before use.

4.2.2.19 Box, Packing, Ammunition, Drawing C9233334

| Defect | Method of Inspection |
|---|---|
| CRITICAL | |
| None defined | |
| MAJOR | |
| None defined | |
| MINOR | |
| 201. Contents loose | Manual |
| 202. Hardware missing, loose, broken, or improperly engaged | Manual and Visual |
| 203. Strapping missing, loose, broken or improperly assembled | Manual and Visual |
| 204. Contents of box exposed | Visual |
| 205. Marking missing, incorrect or illegible | Visual |
| 206. Number of units incorrect | Visual |
| 207. Car seal missing, unsealed or improperly positioned | Visual |

4.2.3 Inspection.- The following tests shall be performed in accordance with 4.3.

4.2.3.1 Assembly torque.- Torque settings of each assembly as shown in Figure 2-7, T.O. 11P4-11-3 shall be subjected to the torque application. Failure of any assembly to comply with the requirement of 3.2 shall be cause for rejection of the assembly.

4.2.3.2 Protective finish, replated components.- The number of specimens and acceptance criteria for protective finish tests shall be in accordance with the applicable Military Standard listed on the drawing or T.O. 11P4-11-3.

4.2.3.3 Functional tests.

4.2.3.3.1 Air firing.- One Remover of each twenty shall be subjected to the air firing test specified in 4.3.3. Failure of remover to comply with the requirements of 3.4.3 shall be cause for rejection of the lot.



Source: https://assist.dla.mil -- Downloaded: 20260-23T01:02Z
Check the source to verify that this is the current version before use.

4.2.3.3.2 Operating load.- Each remover shall be cycled electrically as specified in 4.3.4 to the number of cycles required by T.O. 11P4-11-3 to determine compliance with the requirements specified in 3.4.1 and T.O. 11P4-11-3. Failure of any remover to comply with the requirements of 3.4.1 and T.O. 11P4-11-3 shall be cause for rejection of the remover.

4.2.3.3.3 Bearing center dimensions.- Each remover shall be subjected to the test for center dimensions during the cycling test specified in 4.3.4. Failure of any remover to comply with the requirements of 3.4.2 and T.O. 11P4-11-3 shall be cause for rejection.

4.2.4 Inspection equipment.- The examination and tests shall be made using equipment listed in T.O. 11P4-11-3 and as specified herein.

4.3 Test methods and procedures.

4.3.1 Assembly torque.- A torque wrench, set at the applicable torque requirements specified in Figure 2-7, T.O. 11P4-11-3 shall be used in conjunction with a special adapter to determine the adequacy of the settings. The remover shall be secured in a holding device and the assembly torque applied.

4.3.2 Protective finish, replated components.- Test procedures for protective finish shall be in accordance with the applicable Military Standards referenced on the drawing or T.O. 11P4-11-3.

4.3.3 Air firing test.- Utilize the air firing test fixture specified in T.O. 11P4-11-3. An air pressure hose shall be connected to the fixture to actuate the remover under test. A pressure sensitive device shall be used to measure the pressure exerted to actuate the remover under test. The pressure sensitive device shall be inserted into the system by means of a Tee coupling between the remover and the hose connection. The remover shall be tested in accordance with the functional requirements of 3.4.3 and T.O. 11P4-11-3 and the results recorded.

4.3.4 Operating load test.- The remover shall be installed in test fixture 10553501 or in the test fixture specified in paragraph 3.2, T.O. 11P4-11-3 with special adapters associated control panels for this test. The fixture shall completely cycle the remover in accordance with the functional requirements of 3.4.1 with the time to linear extension and motor current drain recorded. Dimensional measuring equipment shall be used to measure the bearing center dimensions during each cycle and the results recorded.



Source: https://assist.dla.mil -- Downloaded: 202640-23T01:02Z
Check the source to verify that this is the currentversion before use.

5. PREPARATION FOR DELIVERY

5.1 Packing and marking (Level A).- Packing and marking shall be in accordance with drawings C9233331 and C9233334.

5.2 Data cards.- Data card information shall be as specified in MIL-STD-1167.

6. NOTES

6.1 Remanufactured exterior components are listed in Table II:

TABLE II

| Name of Part | Part Number (Talley Ind.) |
|---|---|
| Clevis, Mounting | 2218-22 |
| Sleeve, Adjusting | 2218-23 |
| Tube, Intermediate | 2218-29 |
| Tube, Anti-Rotation | 2218-30 |
| Tube, Ballnut Adapter | 2218-31 |
| Tube, Outside | 2218-34 |
| End Cover | 2218-38 |
| Sleeve, Holder | 2218-46 |
| Cover, Housing | 2218-54 |
| Gear, Housing | 2218-75 |
| Head, Firing | 2218-87 |
| Retainer | 2218-108 |
| Switch Housing | 2218-109 |

6.2 Outside tube 2218-34 and gear housing assembly 2218-105 must be marked as matched set and reassembled as a set.

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1377-A230



Source: https://assist.dla.mil -- Downloaded: 202610-23T01:02Z
Check the source to verify that this is the current version before use.

FOLD

Department of the Army

Frankford Arsenal
Philadelphia, Pa. 19137

OFFICIAL BUSINESS

POSTAGE AND FEES PAID
Department of the Army

Commanding Officer
Frankford Arsenal
ATTN: SMUFA-N1100
Philadelphia, Pa. 19137

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:02Z
Check the source to verify that this is the current version before use.

# SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity *(as indicated on reverse hereof)*.

SPECIFICATION

| ORGANIZATION *(Of submitter)* | CITY AND STATE |
|---|---|

| CONTRACT NO. | QUANTITY OF ITEM PROCURED | DOLLAR AMOUNT |
|---|---|---|
| | | $ |

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

| SUBMITTED BY *(Printed or typed name and activity)* | DATE |
|---|---|
| | |

DD FORM 1 APR 63 1426 REPLACES NAVSHIPS FORM 4863, WHICH IS OBSOLETE PLATE NO. 15419

Source: https://assist.dla.mil -- Downloaded: 202640-23T01:02Z
Check the source to verify that this is the current version before use.