METRIC

MIL-DTL-38999/33C
11 June 2001
SUPERSEDING
MIL-C-38999/33B
7 May 1990

DETAIL SPECIFICATION SHEET

CONNECTOR, ELECTRICAL CIRCULAR, COVER, PROTECTIVE, RECEPTACLE, SERIES III, METRIC

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification and MIL-DTL-38999.



FIGURE 1. Protective cover, receptacle, all classes.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:49Z
Check the source to verify that this is the current version before use.



Dimensions						
Shell size	A THD-2B	B max dia	C dia max	D min dia	E	F + 13.0 - 7.0
9	.6250-0.1P-0.3L-TS	23.0	27.0	17.64	21.00 18.00	127.00
11	.7500-0.1P-0.3L-TS	28.0	32.0	21.97	22.50 18.50	127.00
13	.8750-0.1P-0.3L-TS	31.0	37.0	25.12	25.00 23.50	127.00
15	1.0000-0.1P-0.3L-TS	32.0	40.0	29.92	31.00 25.00	127.00
17	1.1875-0.1P-0.3L-TS	37.0	44.0	32.00	32.50 26.50	127.00
19	1.2500-0.1P-0.3L-TS	39.0	46.0	36.27	34.00 28.00	127.00
21	1.3750-0.1P-0.3L-TS	42.0	49.0	38.25	35.50 30.00	127.00
23	1.5000-0.1P-0.3L-TS	45.0	54.0	42.62	37.50 31.50	127.00
25	1.6250-0.1P-0.3L-TS	49.0	56.0	44.45	39.00 33.00	127.00

NOTES:

1. Dimensions are in millimeters, except “A threads” which are in inches.
2. Method of attachment to cover and or ring is optional.

FIGURE 1. Protective cover, plug, all classes - Continued

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:49Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configuration: See figure 1.

Material:

Cover - Classes C, F, G, R, W and X: Impact extruded or machined aluminum alloy.
Classes H, K, N, S and Y: Corrosion resistant steel.
Classes J and M: High performance resin in accordance with MIL-DTL-38999.
(Class F is inactive for new design.)

Gasket - Silicone elastomer.

Ring - Corrosion resistant steel, passivated, 1.020 maximum thickness.

Rope - Insulated stainless steel, passivated.
Insulation shall withstand 200°C environment.

Fastener - Stainless steel, passivated.
Option: Aluminum integral to cover.

Mating connectors: MIL-DTL-38999, series III.

Gasket shall be bonded to cover, or mechanically retained.

Rope shall rotate freely on fastener.

Fastener tensile strength: Both axial and longitudinal directions shall be 25 pounds. The load shall be applied to the end of the rope.

Part or Identifying Number (PIN) example:



Specification restrictions:

Navy	Army	Air Force
Entire specification sheet inactive for new design	For ground equipment only.	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:49Z
Check the source to verify that this is the current version before use.

Qualification:
Examination of product.
Mating and unmating forces.
Moisture resistance.
Salt spray (corrosion).
Fastener tensile strength (see requirement).
Altitude immersion.

For classes J and M also perform temperature cycling and hydrolytic stability.

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - AS
Air Force – 11
DLA - CC

Review activities:
Army - MI
Navy - EC, MC, OS
Air Force - 19, 99

Preparing activity:
DLA - CC

(Project 5935-4301-14)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:49Z
Check the source to verify that this is the current version before use.