

FED SUP CLASS
5340



TURNBUCKLE ASSEMBLY



SECTION Z-Z



END PULL JAW
VIEW Y-Y

USER ACTIVITIES
ARMY - ME
NAVY - AS, MC, OS, YD

REVIEWER ACTIVITIES
ARMY-CR
AIR FORCE - 82
DLA - IS

TABLE I DASH NUMBERS AND DIMENSIONS

DASH NUMBER	NOMINAL THREAD SIZE	INCH				
		A MIN	B MIN	ØC MIN	D MIN	E MIN
1	.250-20	4	.625	.250	.375	.125
2	.312-18	4.5	.719	.250	.469	.125
3	.375-16	6	.812	.312	.500	.187
4 5 6	.500-13	6 9 12	1.032	.375	.625	.250
7 8 9 10	.625-11	6 9 12 18	1.250	.500	.750	.312
11 12 13 14 15	.750-10	6 9 12 18 24	1.500	.625	.937	.375
16 17 18	.875-9	12 18 24	1.750	.750	1.125	.437
19 20 21 22	1.000-8	12 18 24 36	2.000	.875	1.187	.500

DISTRIBUTION STATEMENT A Approved for public release; distribution is unlimited

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document, when applicable.

NSRC N/A

P.L. ARMY-AR Other Cust NAVY-SH AIR FORCE-99	INTERNATIONAL INTEREST	TITLE TURNBUCKLE, ROUND BODY, JAW AND JAW (TYPE I, FORM I, CLASS 7)	MILITARY STANDARD MS51562
PROCUREMENT SPECIFICATION FF-T-791	SUPERSEDES		PAGE 1 OF 3

DD FORM 672-1 (COORDINATED) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

5340-1802

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T18:07Z
Check the source to verify that this is the current version before use.

TABLE I DASH NUMBERS AND DIMENSIONS - CONTINUED

DASH NUMBER	NOMINAL THREAD SIZE	JAW A MIN	JAW B MIN	JAW ØC MIN	JAW D MIN	JAW E MIN
23 24 25 26	1 250-7	12 18 24 36	2.375	1.125	1.750	.625
27 28 29 30 31	1 500-6	12 18 24 36 48	2 750	1.375	2.062	.687
32 33 34 35	1 750-5	18 24 36 48	3.000	1.625	2.375	750
36 37 38	2.000-4 5	24 36 48	3.750	1 875	2 500	.812
39 40 41	2.250-4.5	24 36 48	4.000	2.062	2.625	.875
42 43 44	2.500-4	24 36 48	4 250	2.250	2.875	1.000

REQUIREMENTS:

1 MATERIAL: TURNBUCKLE BODY AND JAW PULLS SHALL BE MANUFACTURED FROM STEEL OF A COMPOSITION CAPABLE OF WITHSTANDING THE SPECIFIED BREAKING STRENGTH IN THE PROCUREMENT SPECIFICATION.

2 FABRICATION METHOD: THE TURNBUCKLE BODY AND JAW PULLS SHALL BE HOT FORGED

3 FINISH

RUST INHIBITOR - TURNBUCKLE BODY AND JAW PULLS SHALL BE TREATED WITH RUST INHIBITOR IN ACCORDANCE WITH MIL-C-85054 OR EQUIVALENT.

ZINC COATING - TURNBUCKLE BODY AND END PULLS SHALL BE ZINC COATED AS SPECIFIED IN PROCUREMENT SPECIFICATION, ASTM B633, TYPE II, Fe/Zn 13.

4. THREADS: ONE END PULL AND THE CORRESPONDING HEAD BODY SHALL HAVE RIGHT HAND THREAD AND THE OTHER LEFT HAND. THE THREAD SHALL BE MACHINED AFTER FABRICATION OF END PULL AND THE HEAD BODY.

5. LENGTH OF HEAD: THE LENGTH OF THE HEAD OF THE TURNBUCKLE BODY SHALL BE NOT LESS THAN 1 1/2 TIMES THE NOMINAL THREAD SIZE FOR SIZES UP TO 1.250, AND 1 1/4 TIMES FOR SIZES GREATER THAN 1.250 NOMINAL THREAD SIZE.

6 BREAKING STRENGTH: THE BREAKING STRENGTH OF THE TURNBUCKLE SHALL BE NOT LESS THAN THE VALUE SPECIFIED IN THE PROCUREMENT SPECIFICATION FOR TYPE I, FORM 1, WITH JAW END PULLS

7. BENDING STRENGTH: THE BENDING STRENGTH SHALL BE AS SPECIFIED IN THE PROCUREMENT SPECIFICATION

8 LENGTH OF THREAD: THE LENGTH OF THE THREAD ON THE TWO END PULLS SHALL BE GREAT ENOUGH SO THAT THE ENDS OF THE END PULLS CAN BE BROUGHT INTO CONTACT WITH EACH OTHER AT THE MIDDLE OF THE BODY LENGTH.

9. PART NUMBER: THE PART NUMBER SHALL CONSIST OF THE BASIC MS NUMBER, FOLLOWED BY A DASH NUMBER FROM TABLE I AND THE FINISH CODE BELOW

FINISH CODE.

F - RUST INHIBITOR TREATMENT
Z - ZINC COATED.

EXAMPLE: MS51562-7Z

- BASIC MS NUMBER
- DASH NUMBER
- FINISH CODE

MS51562-7Z INDICATES TURNBUCKLE, ROUND BODY, JAW ENDS; .625-11 THREAD, 6-INCH CLEAR OPENING BETWEEN HEADS; ZINC COATED

AMSC N/A FSC 5340 DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

USER ACTIVITIES:
ARMY - ME
NAVY - AS, MC, OS, YD

REVIEW ACTIVITIES:
ARMY - CR
AIR FORCE - 82
DLA - IS

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from the documents cited applicable

PREPARING ACTIVITY: ARMY-AR Other Cust: NAVY-SH AIR FORCE-99	INTERNATIONAL INTEREST	TITLE: TURNBUCKLE, ROUND BODY, JAW AND JAW (TYPE I, FORM I, CLASS 7)	MILITARY STANDARD MS51562
PROCUREMENT SPECIFICATION: FF-T-791	SUPERSEDING		PAGE 2 OF 3

DD FORM 1426 (COORDINATED) — Previous editions of this form are obsolete — 9340-1802

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T18:07Z
Check the source to verify that this is the current version before use.

FED SUP CLASS
5340

NOTES.

1. ALL DIMENSIONS ARE IN INCHES. TOLERANCES SHALL BE IN ACCORDANCE WITH STANDARD MANUFACTURING PRACTICES FOR TURNBUCKLES.
2. IN THE EVENT OF A CONFLICT BETWEEN THE TEXT OF THIS STANDARD AND THE REFERENCES CITED HEREIN, THE TEXT OF THIS STANDARD SHALL TAKE PRECEDENCE.
3. REFERENCED GOVERNMENT (OR NON-GOVERNMENT) DOCUMENTS OF THE ISSUE LISTED IN THAT ISSUE OF THE DEPARTMENT OF DEFENSE INDEX OF SPECIFICATIONS AND STANDARDS (DODISS) SPECIFIED IN THE SOLICITATION FORM A PART OF THIS STANDARD TO THE EXTENT SPECIFIED HEREIN.
4. DIMENSION "A" IS THE TAKE UP LENGTH OR CLEAR OPENING OF THE BODY.

APPROVED 9 FEB 1988 AMSC N/A

REVIEW ACTIVITIES:
ARMY - CR
AIR FORCE - 82
DLA - IS

USER ACTIVITIES:
ARMY - ME
NAVY - AS, MC, OS, YD

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from the documents cited herein.

P. A. ARMY - AR Other Cust NAVY - SH AIR FORCE - 99	INTERNATIONAL INTEREST	TITLE TURNBUCKLE, ROUND BODY, JAW AND JAW (TYPE I, FORM I, CLASS 7)	MILITARY STANDARD MS51562
PROCUREMENT SPECIFICATION FF-T-791	SUPERSEDES		PAGE 3 OF 3

DD FORM 672-1 (COORDINATED) PREVIOUS EDITION OF THIS FORM ARE OBSOLETE 5340-1802

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T18:07Z
Check the source to verify that this is the current version before use.