MIL-B-44038A
28 November 1986
SUPERSEDING
MIL-B-44038
31 December 1980

MILITARY SPECIFICATION

BATTER BREADER MACHINE, ELECTRIC

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers an electrically powered batter breader machine.

1.2 Part numbers. The part number for the machine covered by this specification shall be M44038-01.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standard. The following specifications and standard form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

MILITARY

MIL-V-173	-	Varnish, Moisture-and-Fungus-Resistant (For Treatment of Communications, Electronic and Associated Electrical Equipment).
MIL-B-2316	-	Bakery Equipment, Including Units, Assemblies Repair Parts, and Tools, Preparation and Delivery of.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer (Code 156), Naval Construction Battalion Center, Port Hueneme, CA 93043, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A

FSC 7320

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:29Z
Check the source to verify that this is the current version before use.

STANDARD

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.

2.1.2 Other Government documents. The following other Government document(s) form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

U.S. DEPARTMENT OF AGRICULTURE (USDA)

Accepted Meat and Poultry Equipment.

(Application for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

(Copies of specifications, standards, and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of the documents not listed in the DODISS shall be the issue of the non-Government documents which is current on the date of the solicitation.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

A167 - Stainless and Heat-Resisting Chromium-Nickel Steel Plate, Sheet, and Strip.
A240 - Heat-Resisting Chromium and Chromium-Nickel Stainless Steel Plate, Sheet, and Strip for Fusion-Welded Unfired Pressure Vessels.
A276 - Stainless and Heat-Resisting Steel Bars and Shapes.
A582 - Free-Machining Stainless and Heat-Resisting Steel Bars, Hot-Rolled or Cold-Finished.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:29Z
Check the source to verify that this is the current version before use.

NATIONAL ELECTRICAL MANUFACTURERS ASSOCIATION (NEMA)

WC 5 - Thermoplastic-Insulated Wire and Cable for the Transmission and Distribution of Electrical Energy.
WC 7 - Cross-Linked-Thermosetting-Polyethylene-Insulated Wire and Cable for the Transmission and Distribution of Electrical Energy.
WD 1 - General-Purpose Wiring Devices.

(Application for copies should be addressed to the National Electrical Manufacturers Association, 2101 L Street, NW, Washington, DC 20037.)

UNDERWRITERS LABORATORIES INC. (UL)

UL 498 - Electrical Attachment Plugs and Receptacles.

(Application for copies should be addressed to the Underwriters Laboratories Inc., 333 Pfingsten Road, Northbrook, IL 60062.)

(Non-Government standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets of MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Standard commercial product. The machine shall, as a minimum, be in accordance with the requirements of this specification and shall be the manufacturer's standard commercial product. Additional or better features which are not specifically prohibited by this specification but which are a part of the manufacturer's standard commercial product, shall be included in the machine being furnished. A standard commercial product is a product which has been sold or is being currently offered for sale on the commercial market through advertisements or manufacturer's catalogs, or brochures, and represents the latest production model.

3.2 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.2.1 and 6.4).

3.3 Codes and standards. The machine shall conform to the requirements of the USDA for Accepted Meat and Poultry Equipment.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:29Z
Check the source to verify that this is the current version before use.

3.4 Materials. Materials used shall be free from defects which would adversely affect the performance or maintainability of individual components or of the overall assembly. Materials not specified herein shall be of the same quality used for the intended purpose in commercial practice. Unless otherwise specified herein, all equipment, material, and articles incorporated in the work covered by this specification are to be new and fabricated using materials produced from recovered materials to the maximum extent possible without jeopardizing the intended use. The term "recovered materials" means materials which have been collected or recovered from solid waste and reprocessed to become a source of raw materials, as opposed to virgin raw materials. None of the above shall be interpreted to mean that the use of used or rebuilt products are allowed under this specification unless otherwise specified.

3.4.1 Stainless steel. Stainless steel sheet, plate, and strip shall conform to any type in the 300 series of ASTM A167 or ASTM A240. Stainless steel bars and shapes shall conform to any type in the 300 series of ASTM A276 or ASTM A582.

3.5 Design and construction. The machine shall be designed to completely cover poultry, meat, and fish pieces with liquid dip and bread crumbs. The machine shall be designed for dresser or counter mounting and shall consist of a main tank assembly, conveyor frame assembly, batter tank assembly, blow-off assembly, drives, and controls. The machine shall be electrically operated. All components shall be fabricated from stainless steel. The overall dimensions shall be 43 inches [1092 millimeters (mm)] long, 16.50 inches (419 mm) wide, and 24 inches (610 mm) high. Overall dimensional tolerance shall be ±1 inch (25 mm). The conveyor frame assembly, batter tank assembly, and blow-off assembly shall be capable of disassembly from the main tank assembly without the use of tools.

3.5.1 Main tank assembly. The main tank assembly shall consist of sides, base plate with sloping bottom, and frame assembly. The main tank components shall be fabricated from stainless steel specified in 3.4.1. The sides, bottom, and frame assembly shall have a nominal thickness of 0.050 inch (1.3 mm) and the base plate shall have a nominal thickness of 0.078 inch (2.0 mm). The bread crumb storage capacity shall not be less than 35 pounds [16 kilograms (kg)].

3.5.2 Conveyor frame assembly. The conveyor frame assembly shall be compatible with the main tank assembly and shall consist of side and bottom, main bread conveyor wire belt, belt vibrators, drive shaft, drive sprockets, supports and means for conveyor belt adjustment. The sides and bottom of the conveyor frame assembly and the enclosure of the drive shaft and all moving driving components shall be fabricated from stainless steel specified in 3.4.1 having a nominal thickness of 0.050 inch (1.3 mm). The main bread conveyor belt shall be 12 inches (305 mm) wide and fabricated of 0.072 inch (1.8 mm) stainless steel wire and have a 0.500 inch (13 mm) pitch. The conveyor frame assembly shall be provided with four stainless steel belt vibrators with nylon tips mounted on cross supports.

Source: https://assist.dla.mil -- Downloaded: 202610-21T23:29Z
Check the source to verify that this is the current version before use.

3.5.3 Batter tank assembly. The batter tank assembly shall be attached to the conveyor frame assembly. The batter tank assembly shall consist of a batter tank, batter conveyor wire belt, submerger wheel, drive shafts and sprockets. The batter tank shall be fabricated from type 304 stainless steel having a nominal thickness of 0.050 inch (1.3 mm), and have a capacity of not less than 5 quarts [4.7 liters (L)]. The batter conveyor belt shall be fabricated of 0.050 inch (1.3 mm) stainless steel wire 6 inches (152 mm) wide and have a 0.375 inch (10 mm) pitch. The submerger wheel shall be 6 inches (152 mm) wide, 6 inches (152 mm) in diameter, fabricated of 0.050 inch (1.3 mm) stainless steel wire.

3.5.4 Blow-off assembly. The blow-off assembly shall be attached to the top of the batter pan and down stream from the submerger wheel. The blow-off assembly shall consist of a 1/20 horsepower (hp) [37 Watts (W)] blower motor, blower tube with air discharge slot located on the bottom, and a power supply cord with an on-off switch, and attachment plug.

3.5.5 Electrical requirements. The machine shall be designed for operation on 115 volts, 60 Hertz (Hz), single phase power supply. The machine shall be provided with 1/6 hp (124 W) main drive motor, 3-position switch (forward-off reverse) and power supply cord(s). The power supply cord shall be 2-wire with ground. The plug shall conform to NEMA WD 1 configuration 5-15P and shall meet the requirements of UL 498. Wiring shall be in accordance with NEMA WC 5 or NEMA WC 7.

3.6 Performance.

3.6.1 Operation. The machine's conveyors, mechanical devices, switches, and electrical motors shall operate without binding, excessive vibration, failure or malfunction of any component, or any defect affecting efficient and safe operation.

3.6.2 Normal operation. The machine shall be capable of operating as specified in 3.6.1, while coating 500 pounds (227 kg) of cut up chicken per hour with liquid dip and bread crumbs.

3.6.3 Inclined operation. The machine shall be capable of operating as specified in 3.6.1 and 3.6.2 while inclined at an angle of 15 degrees each side of the vertical in each of two vertical planes at right angles to each other, with no spillage of fluid or product.

3.7 Interchangeability. All units of the same classification furnished with similar options under a specific contract shall be identical to the extent necessary to insure interchangeability of component parts, assemblies, accessories, and spare parts.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:29Z
Check the source to verify that this is the current version before use.

3.8 Data name plates. Data name plates shall be made of minimum 20 gauge corrosion-resisting metal and attached to each item in such a manner as to meet the applicable sanitary requirements for this equipment. The plate shall contain the following information stamped, engraved or applied by photosensitive means:

National Stock Number
Procurement Instrument Identification Number
Manufacturer's Name, Address, Phone Number
Manufacturer's Model Number

Each plate shall be placed so that it is readily visible to the operator during normal operating use. Each plate shall be placed in a manner so as to not adversely affect the life and utility of the item.

3.9 Lubrication. Unless otherwise specified (see 6.2), means for lubrication shall be in accordance with the manufacturer's standard practice. The lubricating points shall be easily visible and accessible. Where use of high-pressure lubricating equipment, 1,000 pound-force per square inch or higher, will damage grease seals or other parts, a suitable warning shall be affixed to the equipment in a conspicuous location. The unit shall be lubricated prior to delivery with type of lubricant specified in the operator's manual and grade of lubricant recommended for ambient temperature at the delivery point. The unit shall be conspicuously tagged to identify the lubricants and their temperature range.

3.10 Treatment and painting. Unless otherwise specified (see 6.2), the machine shall be treated and painted in accordance with the manufacturer's standard practice. All surfaces of the machine other than corrosion-resisting steel shall be protected against corrosion and present a neat appearance.

3.11 Fungus resistance. When specified (see 6.2), electrical components and circuit elements, including terminal and circuit connections, shall be coated with varnish conforming to MIL-V-173, except that:

a. Components and elements inherently inert to fungi or in hermetically sealed enclosures need not be coated.
b. Current-carrying contact surfaces, such as relay contact points, shall not be coated.

3.12 Workmanship.

3.12.1 Steel fabrication. The steel used in fabrication shall be free from kinks, sharp bends, and other conditions which would be deleterious to the finished product. Manufacturing processes shall not reduce the strength of the steel to a value less than intended by the design. Manufacturing processes shall be done neatly and accurately. All bends shall be made by controlled means to insure uniformity of size and shape.

Source: https://assist.dla.mil -- Downloaded: 202640-21T23:29Z
Check the source to verify that this is the current version before use.

3.12.2 Bolted connections. Boltholes shall be accurately punched or drilled and shall have the burrs removed. Washers or lockwashers shall be provided in accordance with good commercial practice, and all bolts, nuts, and screws shall be tight.

3.12.3 Riveted connections. Rivet holes shall be accurately punched or drilled and shall have the burrs removed. Rivets shall be driven with pressure tools and shall completely fill the holes. Rivet heads, when not countersunk or flattened, shall be of approved shape and of uniform size for the same diameter of rivet. Rivet heads shall be full, neatly made, concentric with the rivet holes, and in full contact with the surface of the member.

3.12.4 Welding. Welding procedures shall be in accordance with a nationally recognized welding code. The surface of parts to be welded shall be free from rust, scale, paint, grease, or other foreign matter. Welds shall be of sufficient size and shape to develop the full strength of the parts connected by the welds. Welds shall transmit stress without permanent deformation or failure when the parts connected by the weld are subjected to proof and service loadings.

3.12.5 Castings. All castings shall be sound and free from patching, misplaced coring, warping, or any other defect which reduces the castings ability to perform its intended function.

3.12.6 Finish. The machine shall be smooth on all surfaces and edges and shall be free from discoloration.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

Source: https://assist.dla.mil -- Downloaded: 202640-21T23:29Z
Check the source to verify that this is the currenversion before use.

4.1.2 Component and material inspection. Components and materials shall be inspected in accordance with all the requirements specified herein and in applicable referenced documents.

4.1.3 Standards compliance. The contractor shall make available to the contracting officer or his authorized representative evidence of compliance with the applicable standard(s) cited in 3.3 and 6.5. The Government reserves the right to examine and test all machines to determine the validity of the certification.

4.1.3.1 USDA. Acceptable evidence of meeting the requirements of the USDA shall be the USDA certification symbol or label, listing in the Accepted Meat and Poultry Equipment edition, or a certified test report acceptable to the contracting officer with the advice of the Army Surgeon General, indicating that the machines conform to the USDA.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.2.1).
b. Quality conformance inspection (see 4.2.2).

4.2.1 First article inspection. The first article inspection shall be performed on one complete machine when a first article is required (see 3.2 and 6.2). This inspection shall include the examination of 4.4, the tests of 4.5, and, when specified, the preproduction pack inspection of 4.6 (see 4.6 and 6.2). The first article may be either a first production item or a standard production item from the supplier's current inventory provided the item meets the requirements of the specification and is representative of the design, construction, and manufacturing technique applicable to the remaining items to be furnished under the contract.

4.2.2 Quality conformance inspection. The quality conformance inspection shall include the examination of 4.4, the tests of 4.5, and the packaging inspection of 4.6. This inspection shall be performed on the samples selected in accordance with 4.3.

4.3 Sampling. Sampling and inspection procedures shall be in accordance with MIL-STD-105. The unit of product shall be one complete machine. All the machines offered for delivery at one time shall be considered a lot for the purpose of inspection. If an inspection lot is rejected, the contractor may rework it to correct the defects, or screen out the defective units, and resubmit for a complete reinspection. Resubmitted lots shall be reinspected using tightened inspection. If the rejected lot was screened, reinspection shall be limited to the defect causing rejection. If the lot was reprocessed, reinspection shall be performed for all defects. Rejected lots shall be separate from new lots, and shall be clearly identified as reinspected lots.

Source: https://assist.dla.mil -- Downloaded: 202640-21T23:29Z
Check the source to verify that this is the currentversion before use.

4.3.1 Sampling for dimensional examination. Dimensional examination shall be based on inspection level S-2 and an Acceptable Quality Level (AQL) of 4.0 percent defective.

4.3.2 Sampling for visual examination. Visual examination shall be based on inspection level II and an AQL of 2.5 for major defects and 6.5 for total defects.

4.4 Examination. Each machine shall be examined for compliance with the requirements specified in section 3 of this specification. Any redesign or modification of the contractor's standard product to comply with specified requirements, or any necessary redesign or modification following failure to meet specified requirements shall receive particular attention for adequacy and suitability. This element of inspection shall encompass all visual examinations and dimensional measurements. Noncompliance with any specified requirement shall constitute one defect.

4.4.1 Dimensional measurement examination. Each machine shall be examined for the dimensional measurement requirements in section 3 of this specification. Any dimension not within the specified requirement shall constitute one defect.

4.4.2 Visual examination. Each machine shall be examined for defects listed in Table I. Each attribute with each classification of multiple defects shall constitute one defect.

TABLE I. Classification of defects.

Classification	Defects	Requirement paragraph
MAJOR		
101	Not in accordance with manufacturer's standard product, except for changes necessary to comply with the requirements of this specification.	3.1
102	Not in accordance with codes and standards.	3.3
103	Materials not as specified.	3.4
104	Components missing.	3.5 through 3.5.5
105	Any wearing part not accessible for adjustment or replacement.	3.5 through 3.5.5
106	Any component fractured, buckled, bent, dented, punctured, or malformed.	3.5 through 3.5.5
107	Any component misplace or not not in alignment.	3.5 through 3.5.5
108	Functioning component that is inoperative or will not operate as intended.	3.5 through 3.5.5

Source: https://assist.dla.mil -- Downloaded: 202610-21T23:29Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of defects - (Continued).

Classification	Defects	Requirement paragraph
MAJOR (continued)		
109	Any adjustable assembly not properly adjusted to perform the intended function.	3.5 through 3.5.5
110	Base plate assembly of main tank assembly not sloping.	3.5.1
111	Sides and one end of main tank assembly not closed.	3.5.1
112	Conveyor drive shaft, drive sprocket, and belt vibrator missing from conveyor frame assembly.	3.5.2
113	Belt adjustment not provided on conveyor frame assembly.	3.5.2
114	Submerger wheel for batter tank assembly not as specified.	3.5.3
115	Submerger wheel of batter tank assembly missing.	3.5.3
116	Batter tank assembly not aligned.	3.5.3
117	Blow-off assembly not installed on top of batter tank.	3.5.4
118	Blow-off assembly not aligned.	3.5.4
119	Blower unit tube not provided with slot on bottom.	3.5.4
120	Electrical switch or other electrical components missing or not the type specified.	3.5.5
121	Electrical switch not accessible to operator.	3.5.5
122	Any burr, sliver, sharp edge, rough die, tool, gouge, trim, or grind marks.	3.12 through 3.12.5
123	Fastening devices missing, cracked, or stripped.	3.12.2 and 3.12.3
124	Fasteners loose.	3.12.2 and 3.12.3
125	Rivets not peened properly.	3.12.3
126	Welding not free from rust, scale, paint, grease, and other foreign matter.	3.12.4
127	Scale and flux deposits not removed from welds.	3.12.4
128	Welds not smooth and free of cracks, burn holes, undercuts, or incomplete fusion.	3.12.4

Source: https://assist.dla.mil -- Downloaded: 202610-21T23:29Z
Check the source to verify that this is the current version before use.

TABLE 1. Classification of defects - (Continued).

Classification	Defects	Requirement paragraph
MAJOR (continued)		
129	Castings not as specified.	3.12.5
130	Finish does not have smooth edges and surfaces.	3.12.6
131	Finish not free of discoloration or stains.	3.12.6
MINOR		
201	Identification missing, incomplete, or not legible.	3.7

4.5 Tests. The first article shall receive the tests of 4.5.1, 4.5.2, and 4.5.3. Each production unit selected shall receive the test of 4.5.1. Failure of this test shall be cause for rejection of the machine failing the test. One representative machine of the lot offered for acceptance shall receive the tests of 4.5.2 and 4.5.3. Failure to pass the tests of 4.5.2 and 4.5.3 shall be cause for rejection of the lot.

4.5.1 Operational test. Connect the machine electrical cord(s) to an electrical power source having the same characteristics specified in 3.5.5 and check to assure that all moving components function as intended. Observe that the conveyors operate satisfactorily when the conveyor motor electrical systems are activated, for compliance with 3.6.1. Inability of the machine to operate as specified herein shall constitute failure of the test.

4.5.2 Normal operational test. After successfully passing the test of 4.5.1, the machine shall be subjected to the normal operational test. Using the same power source as in 4.5.1, load the batter breader with 5 quarts (94.7 L) of liquid dip and 35 pounds (16 kg) of bread crumbs in accordance with the manufacturer's standard procedure. With blow-off motor energized, place selector switch in forward-position, add chicken pieces on the batter conveyor for 15 minutes. Observe that the pieces of chicken are completely covered with liquid dip and then covered with bread crumbs to meet capacity requirements specified in 3.6.2. Failure to meet batter pan capacity of 3.5.3 and bread crumb capacity of 3.5.1 shall constitute failure of this test. The leakage of the batter pan or any component malfunction shall constitute failure of this test.

4.5.3 Inclined operational test. After successfully passing the test of 4.5.2 the machine shall be subjected to the inclined operational test. For this test the batter tank shall be filled to 75 percent capacity with water. Position the machine with the base set at an angle of 15 degrees, then operate the machine for 5 minutes each at each side of the vertical in each of two

Source: https://assist.dla.mil -- Downloaded: 202610-21T23:29Z
Check the source to verify that this is the current version before use.

vertical planes at right angles to each other. At each of these positions, continuously load conveyor with pieces of chicken for 5 minutes to determine conformance with specified requirements of 3.6.3. Any nonconformance with specified requirements shall constitute failure of this test.

4.6 Packaging inspection. The inspection of the preservation, packing, and marking shall be in accordance with the requirements of section 4 of MIL-B-2316. The inspection shall consist of the quality conformance inspection; and, when specified (see 6.2), a preproduction pack shall be furnished for examination and test within the time frame required (see 6.2).

5. PACKAGING

5.1 Preservation, packing, and marking. Preservation, packing, and marking shall be in accordance with the requirements of MIL-B-2316 with the level of preservation and the level of packing as specified (see 6.2).

6. NOTES

6.1 Intended use. The machine is intended to cover poultry, meat, and fish pieces with liquid dip and bread crumbs prior to cooking.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this specification.
b. When treatment and painting is other than as specified (see 3.10).
c. When treatment for fungus-resistance is required (see 3.11).
d. When a first article sample and inspection is required. When a preproduction pack inspection is required and the time frame required (see 4.2.1 and 4.6).
e. Level of preservation and level of packing (see 5.1).

6.3 Data requirements. When this specification is used in an acquisition which incorporates a DD Form 1423, Contract Data Requirements List (CDRL), and invokes the provisions of DOD Federal Acquisition Regulations (FAR) Supplement 27.410-6, the data requirements will be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the approved CDRL (DD Form 1423) incorporated into the contract. When the provisions of DOD FAR 27.410-6 are not invoked, the data shall be in accordance with the contract requirements.

6.4 First article. When a first article inspection is required, the item will be tested and should be a first article sample or it may be a standard production item from the contractor's current inventory as specified in 4.2.1. The first article should consist of one unit. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examination, test, and approval of the first article.

Source: https://assist.dla.mil -- Downloaded: 202610-21T23:29Z
Check the source to verify that this is the current version before use.

6.5 Subject term (keyword) listing.

Appliance, commercial
Batter breader machine
Food service equipment

6.6 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:

Navy - YD

Preparing activity:

Navy - YD

(Project 7320-0781)

Review Activity:

Navy - SA

Source: https://assist.dla.mil -- Downloaded: 202610-21T23:29Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:29Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE NAVY
Commanding Officer (Code 156)
Naval Construction Battalion Center
Port Hueneme, CA 93043-5000

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12503 WASHINGTON D C

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

Commanding Officer (Code 156)
Naval Construction Battalion Center
Port Hueneme, CA 93043-5000

Source: https://assist.dla.mil -- Downloaded: 202610-21T23:29Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER: MIL-B-44038A

2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION

b. ADDRESS *(Street, City, State, ZIP Code)*

4. TYPE OF ORGANIZATION *(Mark one)*

- ☐ VENDOR
- ☐ USER
- ☐ MANUFACTURER
- ☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional

b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional

c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional

8. DATE OF SUBMISSION *(YYMMDD)*

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

DD FORM 82 MAR 1426

PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 202610-21T23:29Z
Check the source to verify that this is the current version before use.