MILITARY SPECIFICATION

CASE, LASER PROTECTIVE SPECTACLES

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers one type and size of case.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

L-P-390	-	Plastic, Molding and Extrusion Material, Polyethylene and Copolymers (Low, Medium, and High Density)
V-T-285	-	Thread, Polyester
UU-P-268	-	Paper, Kraft, Wrapping
DDD-L-20	-	Label: for Clothing, Equipage, and Tentage (General Use)
PPP-B-636	-	Boxes, Shipping, Fiberboard

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Natick Research and Development Command, Natick, MA 01760, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:25Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-W-4088	-	Webbing, Textile, Woven Nylon
MIL-T-5038	-	Tape, Textile and Webbing, Textile, Reinforcing, Nylon
MIL-C-7219	-	Cloth, Duck, Nylon
MIL-H-9890	-	Hardware, Individual Load Carrying Equipment: And Hardware, Miscellaneous
MIL-A-13550	-	Antifogging Kit
MIL-E-20652/3-		Eyelets, Metallic, Telescope Type
MIL-F-21840	-	Fastener Tapes, Hooks and Pile, Synthetic
MIL-W-27265	-	Webbing, Textile, Woven Nylon Impregnated
MIL-C-43358	-	Cloth, Knitted, Nylon/Triacetate, Tricot, OG-106
MIL-F-43514	-	Fastener, Plastic, For Equipage Items

STANDARDS

FEDERAL

FED-STD-751	-	Stitches, Seams, and Stitchings

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	-	Marking for Shipment and Storage
MIL-STD-147	-	Palletized Unit Loads for 40" x 48" Pallets
MIL-STD-1188	-	Commercial Packaging of Supplies and Equipment

DRAWING

US ARMY NATICK RESEARCH AND DEVELOPMENT COMMAND

2-2-354	-	Case, Laser Protective Spectacles; Assembly and Details

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Guide sample. Samples, when furnished, are solely for guidance and information to the contractor (see 6.3). Variations from this specification may appear in the sample in which case this specification shall govern.

3.2 First article. When specified (see 6.2), the contractor shall furnish a sample for first article inspection and approval (see 4.3 and 6.4).

3.3 Materials.

3.3.1 Cloth, nylon. The nylon cloth shall be Olive Green 106 conforming to type III, class 3 of MIL-C-7219 (see 6.5).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:25Z
Check the source to verify that this is the current version before use.

3.3.2 Cloth, knitted. The knitted cloth shall be nylon/triacetate, tricot, Olive Green 106 conforming to MIL-C-43358.

3.3.3 Tape, nylon. The nylon tape shall conform to type III, one inch (2.5 cm) or 1-1/2 inches (3.8 cm) wide, as applicable, of MIL-T-5038 and shall be dyed Olive Drab 7.

3.3.4 Webbing, nylon. The nylon webbing, before treatment, shall be Olive Drab 7 conforming to type VIIIc of MIL-W-4088.

3.3.4.1 Treatment. The nylon webbing shall be resin impregnated to conform to class R of MIL-W-27265.

3.3.5 Thread, polyester. The polyester thread shall conform to type I, class 1, sub-class B of V-T-285. The thread size shall be size E for type 301 stitching, and size B or E for bartacking.

3.3.5.1 Color. The thread shall be dyed Olive Drab S-1, C.A. 66022 and shall show fastness to weathering equal to or better than the standard sample (see 6.3).

3.3.6 Keeper, with slide. The keeper with slide shall conform to type X of MIL-H-9890.

3.3.7 Eyelet and washer. The eyelet and washer shall conform to MIL-E-20652/3. The eyelet and washer shall also conform to dash numbers BBT307 and BBT308 respectively, except that the eyelet barrel shall be of sufficient length to provide a proper clinch.

3.3.8 Fastener, plastic. The plastic fastener shall conform to MIL-F-43514.

3.3.9 Polyethylene stiffener. The stiffener shall be made from 0.040 $\pm$ .007 inch thick, high density virgin polyethylene of natural color conforming to type I, class H, grade 3, category optional, of L-P-390. The stiffener may be fabricated from sheet stock or molded to size with its edges finished smooth. The stiffeners fabricated from sheet stock shall be produced in such a manner that the long edges of the pieces shall be parallel with the direction of extrusion (the long edges) of the roll of material from which they are fabricated. The finished pieces shall be uniform in texture and finish and the edge shall be smooth and free from cracks and sharp corners.

3.3.10 Fastener tape, hook and pile, nylon. The nylon fastener tape shall be 1-1/2 inches wide, Olive Green 106 conforming to type II, class 1 of MIL-F-21840.

3.3.11 Antifogging kit. Unless otherwise specified (see 6.2), an antifogging kit conforming to MIL-A-13550 shall be furnished within the case.

3.4 Construction. The construction shall conform in all respects to Drawing 2-2-354 and as specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:25Z
Check the source to verify that this is the current version before use.

3.4.1 Stitching, machine. All stitching, except bartacking, shall conform to FED-STD-751 as follows:

For all straight stitching - Type 301, 8 to 10 stitches per inch

3.4.1.1 Type 301 stitching. Ends of type 301 stitching shall be backstitched or overstitched 1/2 inch minimum for attaching keeper retainer webbing and 1 inch minimum for all other stitching except where ends are turned under in a hem or held down by other stitching. Thread tension shall be maintained so that there will be no loose stitching resulting in loose bobbin or top thread, or excessively tight stitching resulting in puckering of the materials sewn. The lock shall be embedded in the material sewn.

3.4.1.1.1 Repairs of type 301 stitching. Repairs of type 301 stitching shall be as follows:

a. Unless otherwise specified, when thread breaks or bobbin run-outs occur during sewing, the stitching shall be repaired by restarting the stitching a minimum of 1 inch back of the end of the stitching. 1/

b. Unless otherwise specified, thread breaks, two or more consecutive skipped stitches or run-offs noted during inspection of the item (in-process or end item) shall be repaired by overstitching. he stitching shall start a minimum of 1 inch in back of the defective area, continue over the defective area and continue a minimum of 1 inch beyond the defective area onto the existing stitching. Loose or excessively tight stitching shall be repaired by removing the defective stitching, without damaging the materials, and re-stitching in the required manner. 1/

1/ When making the above repairs, the ends of the stitching are not required to be backstitched and for making repairs on the box stitching and cross box stitching substitute 1/2 inch for 1 inch wherever 1 inch appears.

3.4.1.2 Lubrication of thread. There shall be no lubrication of the thread prior to or during sewing (see 4.4.1.1).

3.4.1.3 Automatic stitching. Automatic machines may be used to perform any of the required stitch patterns provided the requirements for the stitch pattern, stitches per inch, size and type of thread are met; and at least three or more tying overlapping or backstitches are used to secure the ends of the stitching.

3.4.1.4 Bartacking. Bartacks shall be 3/4 ± 1/16 inch long, 1/8 ± 1/32 inch wide and shall contain 42 stitches. Bartacks shall be free from thread breaks and loose stitching.

3.4.1.5 Thread ends. All thread ends shall be trimmed to a length of not more than 1/4 inch.

3.4.2 Setting of plastic fastener. Holes for assembling the fastener components shall be prepunched and shall be smaller than the diameter of the posts of the latch and latch receptable components so that the posts must be forced through the holes. The posts shall be securely set to provide a tight clinch of the assembled components

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:25Z
Check the source to verify that this is the current version before use.

3.4.3 Fusing of nylon tape and webbing ends. All ends of nylon webbing and the exposed ends of the nylon tape shall be fused. The apparatus used to fuse the tape and webbing ends shall be capable of providing sufficient heat to provide a smooth edge with the cut ends of the tape and webbing yarns all fused together.

3.4.4 Location marks. Location marks shall not be drilled except for locating the plastic fastener post holes and the eyelet.

3.4.5 Repairs. Except as otherwise specified herein, repairs are not allowed to be made to the case.

3.4.6 Replacement of defective components. During the spreading, cutting and manufacturing process, components having material defects or damages that are classified as defects in 4.4.3.1 shall be removed from production and replaced with non-defective and properly matched components.

3.5 Marking. The identification marking shall be applied in the location shown on the drawing and shall conform to type IV, class 5 of DDD-L-20 except the size of the characters shall approximate 1/8 inch. The letters "US" shall be applied in the location and in the size characters indicated on the drawing and shall conform to type IV, class 9 of DDD-L-20. Fastness of the class 9 marking shall be as specified for class 5 marking.

3.6 Instruction label. The case shall have an instruction label conforming to type II, class 7 of DDD-L-20 except that the color of the label shall be medium green (see 6.6). The location of the label for attachment to the case shall be as shown on Drawing 2-2-354 with the label contents reading along the length of the label. The size of the label shall be approximately 2 by 2-1/2 inches. The contents shall be entirely legible and shall be as described below.

FOR RUBY, ND OR GA-AS
LASERS ONLY. THEY ARE
NOT SUNGLASSES. Do not
look into laser beam, or
wear where you must see
color red. To clean,
wash and rinse. Avoid
scratching. Keep in
case. Adjust for snug
fit by forming earpiece.
OD is at ruby wavelength.
Max energy on lens is
0.01 j/cm^2; Q-SW ruby.

3.7 Workmanship. The finished case shall conform to the quality and grade of product established by this specification and the occurrence of defects shall not exceed the applicable acceptable quality levels.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:25Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Certificate of compliance. Where certificates of compliance are submitted, the Government reserves the right to check test such items to determine the validity of the certification.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required (see 6.2), the case shall be examined for the defects specified in 4.4.3.1 and 4.4.3.2. The presence of any defect shall be cause for rejection of the first article.

4.4 Quality conformance inspection. Sampling for inspection shall be performed in accordance with MIL-STD-105, except when otherwise indicated hereinafter.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced specifications, drawings and standards unless otherwise excluded, amended, modified or qualified in this specification or applicable purchase document.

4.4.1.1 Certification. The contractor shall furnish a certificate of compliance for the thread lubrication requirement specified in 3.4.1.2.

4.4.2 In-process inspection. Inspection of sub-assemblies shall be made to ascertain that construction details which cannot be examined in the finished product are in accordance with specified requirements. The Government reserves the right to exclude from consideration for acceptance any material or service for which in-process inspection has indicated nonconformance.

4.4.3 End item inspection. The classification of defects found during examination shall be as specified in 4.4.3.1 and 4.4.3.2. The sample unit for these examinations shall be one finished case. The inspection levels and acceptable quality levels for these examinations shall be in accordance with 4.4.3.3. Unless otherwise specified, defects are to be scored on an individual basis, i.e., each seam, each stitching end, each dimension, etc.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:25Z
Check the source to verify that this is the current version before use.

4.4.3.1 Visual examination.

Examine	Defect	Classification Major	Minor
Cloth	Any hole, cut, tear or abrasion.	X	
	Smash, open place, broken or missing yarn or multiple floats.	X	
Webbing and tape	Cut ends not fused or not fused correctly, i.e., yarn ends not fused together or not smooth.		X
	Frayed or scalloped edges; not firmly and tightly woven.		X
	Any hole, cut or tear.	X	
Hardware, general	Broken or malformed, protective finish omitted or not as specified; corroded area, burr or sharp edge.	X	
Keeper	Slide component of keeper jams in open, partly closed, or closed position.	X	
NOTE:	Check operation of keeper by fully opening and closing.		
Eyelet and washer	Clinched excessively tight, cutting surrounding material, or split.	X	
	Insecurely clinched to a degree that washer or eyelet may be detached.	X	
	Insecurely clinched permitting washer or eyelet to be freely rotated.		X
	Washer or eyelet omitted.	X	
Plastic fastener	Fastener does not function properly, i.e., fails to snap closed, to provide a secure closure or to open freely.	X	
NOTE:	The fastener shall be snapped and unsnapped twice to determine whether parts of fastener separate freely and also effect a secure closure.		
	Insecurely clinched.	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:25Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification Major	Classification Minor
Open seams	Less than 1/2 inch.		X
	1/2 inch or more.	X	
	NOTE: A seam shall be classified as open when one or more stitches joining a seam are broken or when two or more consecutive skipped stitches or runoffs occur.		
Raw edges (except where required)	More than 1/2 inch when securely caught in stitching.		X
	NOTE: Raw edges not securely caught in stitching shall be classified as open seams.		
Seams and stitch type	Wrong seam or stitch type.	X	
Stitch tension	Loose tension, resulting in a loose top or bobbin thread.		X
	Tight tension, resulting in puckering of material.		X
Stitches per inch	One to two stitches less than minimum specified.		X
	Three or more stitches less than minimum specified.	X	
	One or more stitches in excess of maximum specified.		X
	NOTE: Variation in the number of stitches per inch, caused by the operator's speeding up the machine and pulling the material in order to sew over heavy places, or in turning corners, shall be classified as follows: (a) Within the minor defect classification - no defect. (b) Within the major defect classification - minor defect.		
Stitching ends (on stitch type 301)	Not secured as specified (except where ends are held down by other stitching or turned under in a hem).		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:25Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification Major	Minor
Thread breaks, skipped stitches or runoffs (except bartacks)	Thread breaks, or two or more consecutive skipped stitches or runoffs overstitched less than specified.		X
NOTE:	Thread breaks, or two or more consecutive skipped stitches or runoffs not overstitched shall be classified as open seams.		
Bartacks	Loose, stitching incomplete or broken.		X
	Any omitted.	X	
Box stitching	One row of stitching omitted.		X
	Two or more rows of stitching omitted.	X	
Cleanness	Grease, ink or oil stains clearly noticeable.		X
	Thread ends not trimmed throughout as specified.		X
Components and assembly, general	Antifogging kit missing.	X	
	Any component or required operation omitted (unless otherwise classified herein).	X	
	Mend, darn or patch.	X	
	Needle chews:		
	- Up to 1/8 inch in length.		X
	- Over 1/8 inch in length.	X	
Binding tape	Loosely applied but not exposing raw edge of material.		X
	Loosely applied exposing raw edge of material.	X	
Keeper retainer webbing	Attached with one row of stitching omitted (applicable each stitch pattern).		X
	Attached with two or more rows of stitching omitted (applicable each stitch pattern).	X	
Keeper with slide	Installed in reverse position.		X
Identification, marking and instruction label	Omitted, incorrect, illegible, misplaced, or size of characters not as specified.		X
	Color of instruction label not green.		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:25Z
Check the source to verify that this is the current version before use.

4.4.3.2 Dimensional examination. Examination shall be made for compliance with all dimensions shown on the drawing that can be examined on the end item excluding reference dimensions. Any dimension exceeding the applicable tolerance shall constitute a defect.

4.4.3.3 Inspection levels and acceptable quality levels (AQLs). The inspection levels and AQLs expressed in defects per hundred units shall be as follows:

Examination	Inspection level	AQL
For defects applicable to 4.4.3.1, visual examination	II	2.5 Major 15.0 Total (major and minor defects combined)
For defects applicable to 4.4.3.2, dimensional examination	S-3	10.0 (one class)

4.4.4 Packaging inspection.

4.4.4.1 Examination of packing and marking. An examination shall be made to determine that packing and marking comply with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one shipping container fully packaged except that it need not be closed. Defects of closure listed below shall be examined on shipping containers fully packaged. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 and the AQL shall be 2.5 defects per hundred units.

Examine	Defect
Marking (exterior)	Omitted; incorrect; illegible; of improper size, location, sequence or method of application.
Materials	Any component missing, damaged or not as specified.
Workmanship	Inadequate application of components, such as: incomplete closure of container flaps, improper taping, inadequate stapling or loose strapping. Bulged or distorted container.
Content	Number of cases per shipping container is more or less than required. 1/

1/ For this defect one shipping container in the sample shall be examined.

4.4.4.2 Examination for palletization. An examination shall be made to determine that the palletization complies with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one palletized unit load fully prepared for delivery. The lot size shall be the number of palletized unit loads in the end item inspection lot. The inspection level shall be S-1 and the AQL shall be 6.5 defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:25Z
Check the source to verify that this is the current version before use.

Examine	Defect
Finished dimensions	Length, width, or height exceeds maximum requirement.
Palletization	Pallet pattern not as specified. Interlocking of loads not as specified. Load not bonded with required straps as specified.
Weight	Exceeds maximum load limits.
Marking	Omitted; incorrect; illegible; of improper size, location, sequence or method of application.

5. PACKAGING

5.1 Packing. Packing shall be level A, B, or Commercial as specified (see 6.2).

5.1.1 Level A. One hundred cases, each with fasteners closed, shall be neatly arranged within a snug-fitting fiberboard shipping container conforming to style RSC-L, grade V2s of PPP-B-636. The inside of each fiberboard container shall be fitted with a box liner conforming to type CF, class weather resistant, variety DW, grade V15c of PPP-B-636. Each container shall have the contents completely covered on the top and bottom with a sheet of 30-pound minimum basis weight kraft paper conforming to type I, grade B of UU-P-268. Each shipping container shall be closed in accordance with method III, waterproofed in accordance with method V, and reinforced as specified in the appendix of the container specification, except that the inspection shall be in accordance with 4.4.4.1.

5.1.2 Level B. One hundred cases, each with fasteners closed, shall be neatly arranged within a snug-fitting fiberboard shipping container conforming to style RSC-L, type CF (variety SW) or SF, class domestic, grade 275 of PPP-B-636. The inside of each fiberboard container shall be fitted with a box liner conforming to type CF, class domestic, variety DW, grade 275 of PPP-B-636. Each container shall have the contents completely covered on the top and bottom with a sheet of 30-pound minimum basis weight kraft paper conforming to type I, grade B of UU-P-268. Each shipping container shall be closed in accordance with method II as specified in the appendix of the container specification, except that the inspection shall be in accordance with 4.4.4.1.

5.1.2.1 Weather-resistant containers. When specified (see 6.2), the fiberboard shipping containers shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III of the appendix of the container specification, except that the inspection shall be in accordance with 4.4.4.1.

5.1.3 Commercial. Cases shall be packed in accordance with MIL-STD-1188.

5.2 Palletization. When specified (see 6.2), cases, packed as specified in 5.1, shall be palletized in accordance with load type I of MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L. Pallet patterns shall be in accordance with the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course. If the container is of a size which does not conform to any of the pallet patterns specified in MIL-STD-147, the pallet pattern used shall first be approved by the contracting officer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:25Z
Check the source to verify that this is the current version before use.

5.3 Marking. In addition to any special marking required by the contract or order, shipping containers and palletized unit loads shall be marked in accordance with MIL-STD-129 or MIL-STD-1188, as applicable.

6. NOTES

6.1 Intended use. The case is used to carry one pair of laser protective spectacles (MIL-S-44025) and anti-fogging kit.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) When a first article sample is required (see 3.2, 4.3 and 6.4).
(c) When antifogging kit is not required (see 3.3.11).
(d) Selection of the applicable level of packing (see 5.1).
(e) When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.1.2.1).
(f) When palletization is required (see 5.2).

6.3 Samples. For access to samples, address the procuring activity issuing the invitation for bid.

6.4 First article. When a first article sample is required, it shall be inspected and approved under the appropriate provisions of ASPR 7-104-55. The first article should be a preproduction sample consisting of one completed case. The contracting officer should include specific instructions in all procurement instruments, regarding arrangements for examination, test and approval of the first article.

6.5 Fusing of cut edges. The cut edges of the nylon cloth specified in 3.3.1 are subject to fraying during the process of handling the cut parts and during fabrication of the case. It has been found that fusing of the cut edges of the cloth will prevent fraying.

6.6 Label color. The following cable numbers of the Standard Color Card of America are furnished for information and guidance as to the intensity of the shade of medium green desired for the label specified in 3.6.

Cable No. 70034
Cable No. 70130
Cable No. 70131

6.7 Supersession. This specification supersedes LP/P.DES 19-76 dated 8 November 1976 for Case, Laser Protective Spectacles.

Custodians:

Army - GL
Navy - NU

Review activities:

Army - MD
DLA - CT

User activity:

Navy - MC

Preparing activity:

Army - GL

Project No. 8465-0806

☆ U.S. GOVERNMENT PRINTING OFFICE: 1980—603-121/2350

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:25Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE MIL-C-44026
CASE, LASER PROTECTIVE SPECTACLES

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1426 1 OCT 76

EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:25Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
US ARMY NATICK RESEARCH and DEVELOPMENT COMMAND
NATICK, MASSACHUSETTS 01760

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

DRDNA-ES

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD-314

U.S.MAIL

Commander
US Army Natick Research and Development Command
ATTN: DRDNA-ES
Natick, MA 01760

NATICK OP 1 AUG 78
FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:25Z
Check the source to verify that this is the current version before use.