MILITARY SPECIFICAION

CASE, CARRYING, PLATOON EARLY WARNING DEVICE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements for a carrying case with sling fabricated from nylon duck cloth, webbing, tape and hardware.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

UU-P-268	-	Paper, Kraft, Wrapping
DDD-L-20	-	Label: For Clothing, Equipage and Tentage (General Use)
PPP-B-636	-	Boxes, Shipping, Fiberboard

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	-	Marking for Shipment and Storage
MIL-STD-1188	-	Commercial Packaging of Supplies and Equipment

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Natick Research and Development Laboratories, Natick, MA 01760 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 5895

Source: https://assist.dla.mil -- Downloaded: 202610-21T23:33Z
Check the source to verify that this is the current version before use.

DRAWINGS

US ARMY NATICK RESEARCH AND DEVELOPMENT LABORATORIES

2-2-414	- 1 of 4	-	Case, Carrying, Platoon, Early Warning Device
2-2-414	- 2 of 4	-	Case, Carrying, Platoon, Early Warning Device
2-2-414	- 3 of 4	-	Case, Carrying, Platoon, Early Warning Device
2-2-414	- 4 of 4	-	Case, Carrying, Platoon, Early Warning Device
2-2-415		-	Accessory Equipment Case
2-2-419		-	Sling

(Copies of specifications, standards, and drawings required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Samples.

3.1.1 Guide samples. Guide samples of the end item are solely for guidance and information to the contractor (see 6.6). Variations from this specification may appear in the sample, in which case this specification shall govern.

3.1.2 First article. When specified (see 6.2), the contractor shall furnish a sample for first article inspection and approval (see 4.3 and 6.4).

3.2 Materials and components. Materials and components shall conform to the specifications, standards and drawings and as specified herein (see 6.5).

3.3 Construction. Construction of the carrying case shall conform to the drawings and as specified herein.

3.3.1 Stitching, machine.

3.3.1.1 Type 301 stitching. Ends of stitching shall be backstitched or back-tacked no less than 1 inch (1/2 inch) for box, cross-box and W-W stitching) except where ends are caught in other seams or stitching. Thread tension shall be maintained so that there will be no loose stitching resulting in loose bobbin or top thread or excessively tight stitching resulting in puckering of the material sewn. The lock shall be imbedded in the materials sewn.

3.3.1.2 Repairs of type 301 stitching. Repairs of type 301 stitching shall be as follows:

a. When thread breaks or bobbin run-outs occur during sewing, the stitching shall be repaired by restarting the stitching a minimum of 1 inch (1/2 inch) for box, cross-box and W-W stitching) back of the end of the stitching. 1/

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:33Z
Check the source to verify that this is the current version before use.

b. Thread breaks, or two or more consecutive skipped or run-off stitches noted during inspection of the item (in-process or end item) shall be repaired by overstitching. The stitching shall start a minimum of 1 inch in back of the defective area (1/2 inch) for box, cross-box and W-W stitching), continue over the defective area to a minimum of 1 inch beyond the defective area onto the existing stitching. Loose or excessively tight stitching shall be repaired by removing the defective stitching without damaging the materials and restitching in the manner stated above. 1/

1/ When making the repairs, the ends of the stitching do not require backstitching.

3.3.1.3 Bartacking. Unless otherwise specified, bartacks shall be 3/4 and 1 inch in length, 1/8 inch ± 1/32 inch wide. The 3/4 and 1 inch bartacks shall contain 42 stitches. Bartacks shall be free from thread breaks and loose stitching.

3.3.1.4 Automatic stitching. Automatic machines may be used to perform any of the stitch patterns, provided the requirements for the stitch pattern, stitches per inch and size and type of thread are met; and at least three tying, overlapping or backstitches are used to secure the ends of stitching.

3.3.1.5 Thread ends. All thread ends shall be trimmed to 1/4 inch maximum length.

3.3.1.6 Lubrication of thread. There shall be no lubrication of the thread by any means, prior to or during sewing (see 4.4.2).

3.3.2 Setting of eyelets.

3.3.2.1 Aluminum eyelets. The eyelets shall be securely set in a manner that will prevent detachment from, or cutting of, the surrounding material (see 6.7). The clinched portion of the eyelet shall be on the inside of the assembly. Holes shall be prepunched to receive the eyelets. Holes prepunched to receive the eyelets shall be smaller than the outside diameter of the eyelet barrel so that the barrel must be forced through the hole.

3.3.2.2 Brass eyelets. The eyelets shall be securely set in a manner that will prevent detachment from, or cutting of, the surrounding material. The eyelets shall be clinched without splitting.

3.3.3 Setting of snap fasteners. Holes shall be prepunched to receive the snap fasteners. The hole shall be smaller than the outside diameter of the fastener tube so that the tube must be forced through the hole. Prepunched holes shall not be accomplished by using the stud or eyelet tubes. Fastener components shall be securely clinched without cutting the material. The roll of the clinched eyelet of the assembled fastener components shall not possess more than two scores (splits).

3.3.4 Location marks. Location marks shall not be drilled. Printed markings shall not be more than 1/32 inch in width.

Source: https://assist.dla.mil -- Downloaded: 202610-21T23:33Z
Check the source to verify that this is the current version before use.

3.3.5 Repairs. Repairs such as mends, darns, patches or splices are not permitted on the carrying case.

3.3.6 Attachment of cord. The accessory equipment case shall be attached to the carrying case by passing the ends of the cord through the eyelets provided on the cases. Overhand knots shall then be tied to each end of the cord preventing the cord from slipping through the eyelets.

3.4 Marking. The identification marking shall be applied in the location shown on Drawing 2-2-414, sheet 3 of 4 and shall conform to type IV, class 5 of DDD-L-20. The item description shall read, "Case, Carrying, Platoon Early Warning Device". The letters "US" shall be applied in the location and in the size characters indicated on the drawing and shall conform to type IV, class 9 of DDD-L-20. Fastness of the class 9 marking shall be as specified for class 5 marking.

3.5 Patterns. Standard patterns for textile components other than tape or webbing are shown full scale on drawings and provide allowance for all seams and shall be used for making working patterns. The standard patterns shall not be altered in any way.

3.6 Workmanship. The carrying case shall conform to the quality of product established by this specification. Occurrence of defects shall not exceed the applicable quality levels.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Certificate of compliance. Where certificates of compliance are submitted, the Government reserves the right to check test items to determine the validity of the certification.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

* 4.3 First article inspection. When a first article is required (see 6.2), it shall be examined for the defects specified in 4.4.3.1 and 4.4.3.2. The presence of any defect shall be cause for rejection of the first article.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:33Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.4.2 In-process inspection. Inspection shall be made at any point or during any phase of the manufacturing process to determine whether cut lengths, cut parts, markings for location of components, and location of assembled component parts are in accordance with specified requirements. In addition, inspection shall be made to determine that prepunched or predrilled holes for receiving snap fasteners or eyelets, are smaller than the outside diameter of the hardware tube or barrel. Whenever nonconformance is noted, correction shall be made to the items affected and the operation. The contractor shall furnish a certificate of compliance for the requirement specified in 3.3.1.6.

4.4.3 End item examination. The end item shall be examined in accordance with 4.4.3.1 and 4.4.3.2. The lot size shall be expressed in units of one carrying case. The sample unit shall be one carrying case.

4.4.3.1 Visual examination. The end item shall be examined for the defects listed below. The inspection level shall be II and the acceptable quality level (AQL) shall be 4.0 major and 15.0 total (major and minor combined) defects per hundred units.

Examine	Defect	Classification Major	Minor
Cloth, nylon	Any hole, cut, tear, smash, broken or missing yarns, or open place.	X	
	Shade bar, or fine or coarse filling bar.		X
Webbing or tape	Any hole, cut, tear or smash.	X	
	Frayed or scalloped edge; not firmly or tightly woven.	X	
	Cut ends of webbing not fused.		X
Tape	Abrasion mark, slub, broken end or pick.	X	
Webbing	Abrasion mark, slub, broken end or pick.		X
Fastener tape, hook and pile	Any cut, hole or tear.	X	
	Missing hooks.	X	
	Hooks flattened.	X	
	Hook or pile surfaces not located as specified.	X	

Source: https://assist.dla.mil -- Downloaded: 202610-21T23:33Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification Major	Minor
Cord	Cut, chaped, or abraded.	X	
	Ends not fused.		X
Hardware	Broken or malformed, failing to serve intended purpose; corroded area, burr, or sharp edge.	X	
	Finish omitted or not as specified on steel components.	X	
	Area of partial or no finish.		X
	Any required component improperly installed causing failure to serve intended purpose.	X	
	Not assembled as specified.	X	
Eyelet, brass	Clinched excessively tight, cutting surrounding material.	X	
	Insecurely clinched to a degree that grommet or eyelet may be detached from material.	X	
	Washer installed on incorrect side of material.		X
	Eyelet barrel split.		X
Eyelet, aluminum	Insecurely clinched, clinched excessively tight cutting fabric.	X	
	Not set with scored setting dies.	X	
	Installed with scored side on outside.		X
Snap fastener	Any fastener not functioning properly, i.e., fails to snap closed, provide a secure closure or open freely.	X	
	Improper or insecure clinching.	X	
	Clinched excessively tight, cutting adjacent material.	X	
	Clinched loosely, permitting components to rotate freely in the hole of the material.	X	
	Incorrect style.	X	
	Roll of clinched eyelet fastener assembly contains more than two scores (splits).		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:33Z
Check the source to verify that this is the current version before use.

Examine		Defect	Classification Major	Minor
Snap fastener (cont'd)	NOTE:	a. Incomplete roll of the end of the socket eyelet tube or stud eyelet tube is evidence of improper and insecure clinching. Fasteners evidencing incomplete roll will separate in use.		
		b. The fasteners shall be snapped and unsnapped twice to determine whether parts of fastener separate freely and also effect a secure closure.		
Open seam		1/2 inch or less.		X
		More than 1/2 inch	X	
	NOTE:	A seam shall be classified as open when one or more stitches joining a seam are broken, or when two or more continuous skipped or run-off stitches occur. On double stitched seams, a seam shall be considered open when either one or both sides of the seam are open.		
Raw edge (or edge required to be finished)		More than 1/2 inch when securely caught in stitching.		X
	NOTE:	Raw edge not securely caught in stitching shall be classified as an open seam.		
Run-off (see open seam)				
Seam and stitch type		Wrong seam or stitch type.	X	
Stitch tension		Loose, resulting in loose top or bobbin thread.		X
		Tight, resulting in excessive tightness or puckering of cloth on seams.		X

Source: https://assist.dla.mil -- Downloaded: 202610-21T23:33Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification Major	Minor
Stitches per inch (except on bartack)	Up to two stitches less than minimum specified.		X
	Three or more stitches less than minimum specified.	X	
	One or more stitches in excess of maximum specified.		X
	NOTE: Variation in the number of stitches per inch caused by the operator speeding up the machine and pulling the fabric in order to sew over heavy seams or in turning corners, shall be classified as follows: (a) Within the minor defect classification - no defect. (b) Within the major defect classification - minor defect.		
Stitching margin, stitching gage	Larger than specified by more than 1/16 inch.		X
	Less than specified.		X
Stitching ends (not held down by other stitching or turned under in a hem)	Not backstitched or secured as specified (or not secured as specified where automatic machine are used,)		X
Thread breaks	Not overstitched as specified.		X
	NOTE: Thead breaks not overstitched shall be classified as an open seam.		
Box stitching	Incomplete: - one row of stitching omitted.		X
	- two or more rows of stitching omitted.	X	
W-W stitching	Imcomplete.	X	

Source: https://assist.dla.mil -- Downloaded: 202610-21T23:33Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification Major	Classification Minor
Components and assembly	Any component or required operation omitted (unless otherwise classified herein).	X	
	One or more rows of stitching omitted.	X	
	Mend, darn, or patch.	X	
	Needle chew.	X	
	Location of stitching not as specified on drawings.	X	
Binding	Ends of binding not turned under or not finished as specified.	X	
	Improperly or loosely applied, puckered.		X
	Binding not stitched to cloth for 1/2 inch or more.	X	
NOTE:	Broken or run-off stitching, or material not caught in binding shall be classified under open seams.		
Handle	Not set to flap flat and smooth.		X
Bartack	Omitted.	X	
	Stitching loose, imcomplete, or broken.	X	
	Number of stitches not as specified.		X
Cleanness	Grease or oil stains clearly noticeable; thread ends not trimmed to 1/4 inch maximum length.		X
Location marking	Drilled.		X
	Inked marking more than 1/32 inch wide.		X
Markings "US" and identification	Omitted, incorrect, illegible, or misplaced.		X

* 4.4.3.2 Dimensional examination. Examination shall be made to determine whether the box, cross-box and W-W stitching patterns are located in accordance with applicable drawings. Any box, cross-box or W-W stitch patterns improperly located by more than 1/2 inch shall be scored as a defect. Any dimension not within specified tolerance shall be classified as a defect. The inspection level shall be S-3 and the AQL shall be 6.5 defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 202610-21T23:33Z
Check the source to verify that this is the current version before use.

4.4.4 Packaging inspection. An examination shall be made to determine that preservation, packing and marking comply with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one shipping container fully packaged except that it need not be closed. Shipping containers fully packaged shall be examined for defects of closure. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 and the AQL shall be 2.5 defects per hundred units.

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.
Materials	Any component missing. Any component damaged.
Workmanship	Inadequate application of components, such as incomplete closure of flaps, loose strapping or taping, or inadequate strapping. Bulged or distorted container.
Content	Number of bags per shipping container is more or less than required.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial as specified (see 6.2).

5.1.1 Level A. Each case shall have the two slings and the one equipment accessory case placed inside the body. The outside flap shall then be snap fastened in a closed position. The top shall be folded back down even with the bottom edge. Securely tie the case girthwise with tape or twine. Each tied case should measure approximately 14 inches in length, 6-1/4 inches in width, and 3-1/2 inches in depth.

5.1.2 Commercial. The cases shall be preserved in accordance with MIL-STD-1188.

5.2 Packing. Packing shall be level A, B, or Commercial as specified (see 6.2).

5.2.1 Level A packing. Thirty cases, preserved as specified in 5.1, shall be packed in a fiberboard shipping container conforming to style RSC-L, grade V2s of PPP-B-636. The inside of each shipping container shall be fitted with a box liner conforming to type CF, class weather-resistant, variety DW, grade V15c of PPP-B-636. Cases, preserved level A, shall be placed flat, arranged two in length, three in width, and five in depth within a shipping container. Inside dimensions of the shipping container shall approximate 28-1/2 inches in length, 19-1/4 inches in

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:33Z
Check the source to verify that this is the current version before use.

width, and 15 inches in depth. Approximate dimensions are furnished as a guide only. Each container shall have the contents completely covered on the top and bottom with a sheet of 30-pound minimum basis weight kraft paper conforming to type I, grade B of UU-P-268. Each shipping container shall be closed in accordance with method III, waterproofed in accordance with method V, and reinforced as specified in the appendix of PPP-B-636, except that the inspection shall be in accordance with 4.4.4.

5.2.2 Level B packing. Thirty cases, preserved as specified in 5.1, shall be packed in a fiberboard shipping container conforming to style RSC-L, type CF (variety SW) or SF, class domestic, grade 275 of PPP-B-636. The inside of each shipping container shall be fitted with a box liner conforming to type CF, class domestic, variety DW, grade 275 of PPP-B-636. Cases, preserved level A, shall be placed flat, arranged two in length, three in width, and five in depth within a shipping container. Inside dimensions of the shipping container shall approximate 28-1/2 inches in length, 19-1/4 inches in width, and 15 inches in depth. Approximate dimensions are furnished as a guide only. Each container shall have the contents covered on the top and bottom with a sheet of 30-pound minimum basis weight kraft paper conforming to type I, grade B of UU-P-268. Each shipping container shall be closed in accordance with method II as specified in the appendix of PPP-B-636, except that the inspection shall be in accordance with 4.4.4.

5.2.2.1 Weather-resistant fiberboard containers. When specified (see 6.2), the shipping container shall be a grade V3c, V3s or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of the container specification, except that the inspection shall be in accordance with 4.4.4.

5.2.3 Commercial packing. Cases, preserved as specified in 5.1, shall be packed in accordance with MIL-STD-1188.

5.3 Marking. In addition to any special marking required by the contract, shipping containers shall be marked in accordance with MIL-STD-129 or MIL-STD-1188, as applicable.

6. NOTES

6.1 Intended use. The carrying case is intended to carry a platoon early warning device. The bag can be carried by the carrying sling or by the handle.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) When a first article is required (see 3.1.2, 4.3 and 6.4).
(c) Selection of applicable levels of preservation and packing (see 5.1 and 5.2).
(d) When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).

☆U.S. GOVERNMENT PRINTING OFFICE: 1981—703-023/3719

Source: https://assist.dla.mil -- Downloaded: 202610-21T23:33Z
Check the source to verify that this is the currentversion before use.

6.3 Fusing of edges. The edges of the nylon cloth may become frayed by handling during fabrication. This condition may be prevented by fusing the edges of the material.

6.4 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of DAR 7-104.55. The first article should be a preproduction sample. The first article should consist of one finished carrying case. The contracting officer should include specific instructions in all procurement instruments regarding arrangements for inspection, and approval of the first article.

6.5 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of the specification (see 3.2).

6.6 Samples. For access to samples, address the procuring activity issuing the invitation for bids.

6.7 Commercial products. The score setting dies conforming to J. C. Rhodes and Company, New Bedford, MA 02745, part number 1-KW-1KL and 101KLOM or equal has been found to provide the aluminum eyelet setting requirements specified in 3.3.2.1.

6.8 Supersession data. This specification includes the requirements of US Army Natick Research and Development Command(GL), Limited Production Purchase Description LP/P. DES 3-79 dated 15 February 1979.

Custodians:

Army - GL
Navy - MC

Review activity:

Army - CR

Preparing activity:

Army - GL

Project No. 5895-0288

Source: https://assist.dla.mil -- Downloaded: 202610-21T23:33Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-C-44045 - Case, Carrying, Platoon Early Warning Device

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1426 1 OCT 76

EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 202640-21T23:33Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY CARD

FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research and Development
Laboratories
ATTN: DRDNA-ES
Natick, MA 01760

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:33Z
Check the source to verify that this is the current version before use.