INCH-POUND

MIL-C-44046A
18 July 1989
SUPERSEDING
MIL-C-44046
26 June 1981

MILITARY SPECIFICATION

CONTAINER, HIGH SPEED, AERIAL DELIVERY

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

2. Scope. This specification covers one type of disposable aerial delivery container.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1670

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-21T23:33Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

PPP-B-601	- Boxes, Wood, Cleated-Plywood
PPP-B-621	- Boxes, Wood, Nailed and Lock-Corner
PPP-B-636	- Boxes, Shipping, Fiberboard

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	- Marking for Shipment and Storage
MIL-STD-1186	- Cushioning, Anchoring, Bracing, Blocking and Waterproofing; With Appropriate Test Methods

Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Naval Publications and Forms Center, (ATTN: NPODS), 5801 Tabor Avenue, Philadelphia, PA 19120-5099.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS

U.S. ARMY NATICK RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER
11-1-2819 Aerial Delivery Container-Disposable

(Copies of drawings are available from the U.S. Army Natick Research, Development, and Engineering Center, ATTN: STRNC-EMSS, Natick, MA 01760-5014.)

2.2 Non-Government publications. The following document forms a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:33Z
Check the source to verify that this is the current version before use.

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection (see 6.3) in accordance with 4.3.

3.2 Materials. The materials used in the manufacture of the disposable aerial delivery container shall conform to the requirements specified or shown on Drawing 11-1-2819 and the detail drawings subsidiary thereto. It is encouraged that recycled material be used when practical as long as it meets the requirements of this specification.

3.3 Construction. Construction details shall conform to the requirements of Drawing 11-1-2819 and to the subsidiary drawings, specifications, and standards applicable thereto.

3.3.1 Painting. Preparation and painting shall be as specified on the individual drawings.

3.3.2 Marking. Marking shall be as indicated on the individual drawings.

3.4 Workmanship. The end item shall conform to the quality of product established by this specification.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:33Z
Check the source to verify that this is the current version before use.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.1.2 Responsibility for dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for ensuring that all specified dimensions have been met. When dimensions cannot be examined on the end item, inspection shall be made at any point, or at all points in the manufacturing process necessary to ensure compliance with all dimensional requirements.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required (see 3.1 and 6.2), it shall be examined for the defects specified in 4.4.2 and 4.4.3.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.4.2 End item visual examination. The end items shall be examined for the defects listed in table I. The lot size shall be expressed in units of completed containers. The sample unit shall be one complete container. The inspection level shall be II (see 6.4).

Source: https://assist.dla.mil -- Downloaded: 20260-21T23:33Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects

Examine	Defect	Classification Major	Minor
Painting	Not color specified		201
	Incomplete		202
	Nonadherent		203
	Imbedded dirt		204
	Creeps, wrinkles, sags, or runs		205
Construction	Part missing	101	
	Any component malformed		206
Fasteners	Not type specified	102	
Material	Not as specified	103	
Marking	Missing, incomplete, illegible, or otherwise not as specified		207
Workmanship	Any sharp edges, burrs, or metal slivers		208
	Fasteners, turnbuckles not tight		209

4.4.3 End item dimensional examination. The end items shall be examined for conformance to the dimensions specified on the drawings. Only those dimensions that can be evaluated without damaging or disassembling the end items shall be examined. Any dimension not within the specified tolerance shall be classified as a defect. The lot size shall be expressed in units of completed containers. The sample unit shall be one complete container. The inspection level shall be S-2 (see 6.4).

4.4.4 Packaging examination. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 (see 6.4).

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application
Materials	Any component missing, damaged, or not as specified

Source: https://assist.dla.mil -- Downloaded: 202610-21T23:33Z
Check the source to verify that this is the current version before use.

Examine	Defect
Workmanship	Inadequate application of components
Content	Number per container is more or less than required

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial, as specified (see 6.2).

5.1.1 Level A preservation. Prior to assembly of each complete aerial delivery container, the four tail fins shall be neatly stacked and completely wrapped together in single-face non-corrosive corrugated paperboard, cellulosic cushioning, or other suitable non-corrosive cushioning material. The wrap shall be secured with tape or a mechanical tie. The initiator cable, cable harness, and parts list sheet shall be unit packed in a polyethylene bag. Final closure of the bag shall be effected by heat sealing. The tail fins, initiator cable, cable harness, and parts list, unit packed as specified, shall be packed in a snug-fitting intermediate fiberboard box conforming to style RSC, type CF, variety SW, class domestic, grade 200 of PPP-B-636. The box shall be closed with minimum 2-inch width pressure-sensitive tape. The packed and closed box shall be placed in a parachute compartment cap and immobilized.

5.1.2 Commercial preservation.

5.1.2.1 Complete aerial delivery container. Each complete aerial delivery container shall be preserved in accordance with ASTM D 3951.

5.1.2.2 Spare parts. Each spare part shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B, or Commercial, as specified (see 6.2).

5.2.1 Level A packing. Each completely assembled aerial delivery container, preserved as specified in 5.1, shall be packed in a snug-fitting wood-cleated plywood or nailed wood shipping container conforming to overseas type, style A or J, grade A or B, type 2 load of PPP-B-601, or class 2, style 2 or 4, grade A or B, type 2 load of PPP-B-621. Each container shall be provided with skids as specified in the applicable container specification. Blocking and bracing shall be in accordance with MIL-STD-1186 to prevent movement of the contents while in transit. Shipping containers shall be closed and strapped in accordance with the appendix of the applicable container specification.

Source: https://assist.dla.mil -- Downloaded: 202610-21T23:33Z
Check the source to verify that this is the current version before use.

5.2.2 Level B packing. Each completely assembled aerial delivery container, preserved as specified in 5.1, shall be packed in a snug-fitting wood-cleated plywood or nailed wood shipping container conforming to domestic type, style A or J, type 2 load of PPP-B-601, or class 1, style 2 or 4, type 2 load of PPP-B-621. Each container shall be provided with skids as specified in the applicable container specification. Blocking and bracing shall be in accordance with MIL-STD-1186 to prevent movement of the contents while in transit. Shipping containers shall be closed and strapped in accordance with the appendix of the applicable container specification.

5.2.3 Commercial packing.

5.2.3.1 Complete aerial delivery container. Each complete aerial delivery container, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

5.2.3.2 Spare parts. Spare parts, preserved as specified in 5.1.2.2, shall be packed in accordance with ASTM D 3951.

5.3 Marking.

5.3.1 Complete aerial delivery container. In addition to any special marking required by the contract, unit packs, intermediate packs, and shipping containers shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

5.3.2 Spare parts. In addition to any special marking required by the contract, shipping containers shall be marked in accordance with ASTM D 3951. The term "component parts for" shall precede the identification data.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The container is designed for use with high performance aircraft, for delivery of supplies from low altitudes.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this specification.
b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
c. When a first article is required (see 3.1, 4.3, and 6.3).
d. Levels of preservation and packing (see 5.1 and 5.2).
e. Acceptance criteria required (see 6.4).

Source: https://assist.dla.mil -- Downloaded: 202610-21T23:33Z
Check the source to verify that this is the current version before use.

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

6.4 Acceptance criteria. The acceptance criteria below is recommended for use. The acceptance criteria as specified in the contract or purchase order shall be binding. Unless otherwise specified, the following acceptance criteria are in accordance with MIL-STD-105.

6.4.1 For end item visual examination. An acceptable quality level (AQL), expressed in terms of defects per hundred units, of 2.5 for major defects and 6.5 for minor defects is recommended.

6.4.2 For end item dimensional examination. An AQL, expressed in terms of defects per hundred units, of 4.0 is recommended.

6.4.3 For packaging examination. An AQL, expressed in terms of defects per hundred units, of 2.5 is recommended.

6.5 Subject term (key word) listing.

Air drop
CTU-2A
Capsule, cargo
Low altitude delivery
Supply delivery

6.6 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:

Army - GL
Navy - AS

User activity:

Navy - MC

Preparing activity:

Army - GL

(Project 1670-0769)

☆U.S. GOVERNMENT PRINTING OFFICE 1989: - 604-033/13865

Source: https://assist.dla.mil -- Downloaded: 202640-21T23:33Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

U.S. ARMY NATICK RESEARCH, DEVELOPMENT
and ENGINEERING CENTER
ATTN: STRNC-ES
Natick, MA 01760-5014

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
U.S. Army Natick Research, Development
and Engineering Center
ATTN: STRNC-ES
Natick, MA 01760-5014

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:33Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-C-44046A	Container, High Speed, Aerial Delivery

3a. NAME OF SUBMITTING ORGANIZATION

b. ADDRESS *(Street, City, State, ZIP Code)*

4. TYPE OF ORGANIZATION *(Mark one)*

- ☐ VENDOR
- ☐ USER
- ☐ MANUFACTURER
- ☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

Source: https://assist.dla.mil -- Downloaded: 2026-0-21T23:33Z
Check the source to verify that this is the current version before use.