MILITARY SPECIFICATION

TIEDOWN ASSEMBLY, CARGO, AERIAL DELIVERY, LOAD BINDER TYPE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the reuqirements for one type of load binding system in cargo aircraft.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

T-T-871	-	Twine, Cotton, Wrapping
PPP-B-566	-	- Boxes, Folding, paperboard
PPP-B-601	-	Boxes, Wood, Cleated-Plywood
PPP-B-636	-	Boxes, Shipping, Fiberboard
PPP-B-676	-	- Boxes, Setup
PPP-P-291	-	Paperboard, Wrapping and Cushioning
PPP-T-45	-	Tapes Gummed, Paper, Reinforced and Plain, for Sealing and Securing

MILITARY

MIL-B-43021	-	Binder, Load, Cargo Tie-Dow, 10,000 pounds (44.5 kN) Capacity
MIL-W-43342	-	Webbing Assembly, General Specification for

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Natick Research and Development Laboratories, Natick, MA 01760 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 1670

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:29Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-147 - Palletized Unit Loads
MIL-STD-1188 - Commercial Packaging of Supplies and Equipment
MS 22046 - Ring - Parachute Harness "D"

DRAWING

US ARMY NATICK RESEARCH AND DEVELOPMENT LABORATORIES

11-1-892 - Scrap, Tie Down, Cargo, Heavy Duty

(Copies of specificaitons, standards and drawings required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials and construction. Materials and construction details shall conform to the requirements of the applicable specification or standard and as specified herein. A Tie-down assembly shall consist of one each of the following items.

3.1.1 Load binder. The load binder shall be in accordance with the requirements of MIL-B-43021.

3.1.2 Tie-down strap. The tie-down strap shall be in accordance with the requirements of MIL-W-43342 and Drawing 11-1-892.

3.1.3 "Dee" ring. The "Dee" Ring shall conform to the requirements of Military Standard MS 22046-8.

3.2 Marking. Identification marking of each component shall be in accordance with the applicable specification or standard.

3.3 Workmanship. The workmanship shall conform to the quality established by the applicable specification or standard.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:29Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Quality conformance inspection. 4.2 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.2.1 Compoment and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced specifications drawings, and standards unless otherwise excluded, amended, modified or qualified in this specification or applicable purchase document.

4.2.2 End item examination. Each assembly shall be inspected to determine that all of the components specified in 3.1 are present. Any incomplete assembly shall be rejected.

4.2.3 Packaging inspection. An examination shall be made to determine that preservation, packing and marking comply with the section 5 requirements. Defects shall be scored as set forth in table I. The lot shall be the number of shipping containers offered for inspection at one time. The sample unit shall be one container fully packaged except it need not be closed. The inspection level shall be S-2 and the AQL shall be 6.5 defects expressed in terms of defects per hundred units.

TABLE I. Packaging defects

Examine	Defect
Binder cushioning material	Omitted, incorrect, improperly secured.
Tie down strap and "D" ring	"D" ring missing. Strap missing, not properly secured.
Content	Number per container snore or less than required.
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:29Z
Check the source to verify that this is the current version before use.

4.2.3.1 Examination of palletization. An examination shall be made to determine that palletization complies with section 5 requirements. Defects shall be as listed in table II. The sample unit for this examination shall be one palletized unit load ready for shipment. The lot shall be the number of palletized unit loads offered for inspection at one time. The inspection level shall be S-1 with an AQL of 6.5 expressed in terms of defects per hundred units.

TABLE II. Examination of palletization

Examine	Defect
Finished dimension	Length, width or height exceeds specified maximum requirement.
Palletization	Not as specified. Pallet pattern not as specified. Load not bonded with required strap specified.
Weight	Exceeds maximum load limits.
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Load binder. Each binder shall be completely wrapped in paperboard cushioning material conforming to type I, style 1 of PPP-P-291. The wrap shall be secured with 2-inch (51 mm) minimum width gummed paper tape conforming to type III, grade B of PPP-T-45.

5.1.1.2 Tie-down strap. Each strap with the unattached “D” ring looped onto the end of the strap opposite the fixed "D" ring shall be wound starting from the unattached "D" ring. The wound strap shall be securely tied with twind conforming to type I or II, 8-ply of T-T-871.

5.1.1.3 Unit packing. Each tiedown assembly consisting of one binder and one strap, preserved as specified in 5.1, shall be unit packed (binder on bottom, strap on top) in a snug-fitting folding paperboard box conforming to variety 2, style III, type G, class i of PPP-B-566; setup paperboard box conforming to type I, variety 2, class A, style 4 of PPP-B-676; or fiberboard box conforming to style RSC (end-opening), type CF, class WR, grade W6c of PPP-B-636. Box closure shall be secured with waterproofed or water resistant tape in accordance with the appendix of the applicable box specification.

Source: https://assist.dla.mil -- Downloaded: 202610-21T23:29Z
Check the source to verify that this is the current version before use.

5.1.2 Commercial. Each tiedown assembly shall be preserved-packaged in accordance with MIL-STD-1188.

5.2 Packing. Packing shall be level A, B or Commercial as specified (see 6.2).

5.2.1 Level A packing. Twelve tiedown assemblies, preserved as specified in 5,1, shall be packed in a snug-fitting shipping container conforming to style RSC, type SR, grade V2s of PPP-B-636; or overseas type, style A or J, grade A, or B, type 2 load of PPP-B-601. Each fiberboard shipping container shall be closed in accordance with Method III, waterproofed in accordance with Method V and reinforced as specified in the appendix of PPP-B-636. Each wood container shall be closed and reinforced in accordance with the appendix of PPP-B-601.

5.2.2 Level B packing. Twelve tiedown assemblies, preserved-packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, type CF (variety SW) or SF, class domestic, grade 275 of PPP-B-636. Each shipping container shall be closed in accordance with method II as specified in the appendix of PPP-B-636.

5.2.2.1 Weather-resistant fiberboard container. When specified (see 6.2), the fiberboard shipping container shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of the container specification.

5.2.3 Commercial packing. 5.2.3 Commercial packing. Tiedown assemblies, preserved as specified in 5.1, shall be packed in accordance with MIL-STD-1188.

5.3 Palletization. Unless otherwise specified (see 6.2), tiedown assemblies, packed as speciied in 5.2, shall be palletized in accordance with Load Type I of MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L. Pallet patterns shall be in accordance with the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course. If the container is of a size which does not conform to any of the pallet patterns specified in MIL-STD-147, the pallet pattern used shall first be approved by the contracting officer.

5.4 Marking. In addition to any special marking required by the contract, shipping containers, and palletized unit loads shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The cargo tiedown assembly is intended for securing general cargo and equipment for transport and air delivery. It will exert a binding force of up to 10,000 pounds.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:29Z
Check the source to verify that this is the current version before use.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Item Federal Stock Number.
(c) Item quantity required.
(d) Selection of applicable levels of preservation and packing (see 5.1}.
(e) Type of shipping container desired for level A packing (see 5.2.1).
(f) When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).
(g) When palletization is (see 5.3).

Custodians:

Army - GL
Air Force - 99

Review activities:

Army - AV
Air Force - 11

User activity:

Navy - MC

Preparing activity:

Army - GL

Project No. 1670-0639

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:29Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE
MIL-T-44036 Tiedown Assembly, Cargo, Aerial Delivery, Load Binder Type

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 202640-21T23:29Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY CARD

FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research and Development Command
ATTN: DRDNA-ES
Natick, MA 01760

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:29Z
Check the source to verify that this is the current version before use.