INCH-POUND

MIL-P-44012A(GL)
12 January 1994
SUPERSEDING
MIL-P-44012(GL)
24 August 1979

MILITARY SPECIFICATION

PACK, PARACHUTIST'S, DRAGON MISSILE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers one type and size of a reinforced and padded jump pack for the dragon missile. The jump pack is fabricated from camouflage green cotton or nylon duck and nylon webbing.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be used in improving this document should be sent to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5017, by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1670

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:21Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-147 - Palletized Unit Loads
MIL-STD-20731-1 - DoD Material Procedures for Development and Application of Packaging Requirements.

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS

U.S. ARMY NATICK RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER

11-1-2714 - Jump Pack, Dragon Missile, Parachutist
11-1-2715 - Muzzle Pocket Assembly
11-1-2716 - Pocket Assembly, Lowering Line

(Copies of drawings are available from the U.S. Army Natick Research, Development, and Engineering Center, ATTN: SATNC-ICB, Natick, MA 01760-5017.)

2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:21Z
Check the source to verify that this is the current version before use.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection (see 6.3) in accordance with 4.3.

3.2 Materials and components. Materials and components shall be as specified on the applicable drawings. It is encouraged that recycled material be used when practical as long as it meets the requirements of this specification.

3.3 Construction. The construction shall conform in all respects to the applicable drawings and all subsidiary drawings pertaining thereto, and as specified herein.

3.3.1 Type 301 stitching. Ends of all type 301 stitching shall be backstitched or overstitched not less than 1/2 inch in accordance with the required stitch pattern.

3.3.1.1 Repairs of type 301 stitching. Repairs of type 301 stitching shall be as follows:

a. When thread breaks or bobbin run-outs occur during the sewing, the stitching shall be repaired by restarting the stitching a minimum of 1 inch back (1/2 inch for box-x and W-W stitching) from the end of the stitching. 1/

b. Thread breaks or two or more consecutive skipped or run-off stitches noted during inspection of the item (in-process or end item) shall be repaired by overstitching. The stitching shall start a minimum of 1 inch in back of the defective area, (1/2 inch for box-x and W-W stitching), continue over the defective area, and continue a minimum of 1 inch (1/2 inch for box-x and W-W stitching) beyond the defective area on to the existing stitching. Loose or excessively tight stitching shall be repaired by removing the

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:21Z
Check the source to verify that this is the current version before use.

defective stitching, without damaging the materials, and restitching in the required manner. 1/

1/ When making the above repairs, the ends of the stitching are not required to be backstitched.

3.3.1.2 Automatic Stitching. Automatic Stitching machines may be used to perform any of the required stitch patterns provided the requirements for the stitch pattern, stitches per inch, and size and type of thread are met, and at least three or more tying, overlapping, or back stitches are used to secure the ends of the stitching.

3.3.3 Thread ends. All thred ends shall be trimmed to a length of not more than 1/4 inch.

3.4 Repairs. Repairs such as mends, darns, patches, or splices are not permitted on the pack.

3.5 Workmanship. The finished pack shall conform to product established by this specification and the occurrence of defects shall not exceed the applicable acceptable quality levels.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements examination and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the perfor-mance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perfom any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of section 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.1.2 Responsibility for dimensional remitments. Unless otherwise specified in the contract or purchase order, the contractor is responsible for ensuring that all specified dimensions have been met. When dimensions

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:21Z
Check the source to verify that this is the current version before use.

cannot be examined on the end item, inspection shall be made at any point, or at all points in the manufacturing process necessary to ensure compliance with all dimensional requirements.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required (see 3.1 and 6.2), it shall be examined for the defects specified in 4.4.2 and 4.4.3. Any nonconformance shall be cause for rejection of the first article.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase documents.

4.4.2 End item visual examination. The end items shall be examined for the defects listed in table I. The lot size shall be expressed in units of packs. The sample unit shall be one pack. The inspection level shall be II. The finding of any defect shall be cause for the rejection of the lot.

TABLE I. End item visual defects

Examine	Defect	Classification Major	Classification Minor
Fabric (duck)	Any hole (except drill holes) cut or tear, weak places or broken yarns	101	
	Exposed drill holes		201
Felt	Any hole, cut or tear		202
Webbing and tape	Not firmly and tightly woven; edge frayed or scalloped	102	
	Exposed end of tie down tapes not dipped in wax as required		203
	Exposed end of nylon webbing and tape not seared smooth as required		204

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:21Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Classification Minor
Fastener tape, hook and pile	Any hole, cut or tear. Hooks missing or flattened, foreign matter or dirt impairing proper function	103	
Hardware	Broken or bent; corroded areas; burrs or sharp edges	104	
	Any required component not specified type or size	105	
	Any required component not functioning, improperly set or reversed	106	
Open seams and run-offs	1/2 inch or less		205
	More than 1/2 inch	107	
NOTE:	A seam shall be classified as open when one or more stitches joining a seam are broken or when two or more skipped stitches or run-offs occur. On double stitching seams, a seam shall be considered open when either one or both sides of the seam are open.		
Binding	Improperly or loosely applied showing raw edge of fabric	108	
	End of binding not finished as specified or overlapped less than 1 inch		206
Sean and stitch type	Wrong seam or stitch type	109	
Stitch tension	Loose, resulting in a loosely exposed top or bobbin thread; tight, resulting in excessive tightness of fabric on seams	110	
Stitches per inch	One stitch less than minimum specified		207
	Two or more stitches less than minimum specified	111	
	One or two stitches in excess of maximum specified		208

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:21Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Classification Minor
Stitches per inch (cont'd)	More than two stitches in excess of maximum specified	112	
	NOTE: Variation in the number of stitches per inch, caused by the operator speeding up the machine and pulling the fabric in order to sew over heavy places, heavy seams or in turning corners, shall be classified as follows: a. Within the major defect classification - minor defect b. Within the minor defect classification - no defect		
Stitching margins	Larger than specified by more than 3/16 inch for more than 2 inches		209
Thread breaks	Overstitched less than 1/2 inch		210
	NOTE: Thread breaks not overstitched shall be classified as open seams.		
Stitching ends	Ends of stitching backstitched less than 1/2 inch (except where ends are turned under in a hem or held down by other stitching)		211
	Ends of stitching not backstitched	113	
Stitching	Any required row of stitching omitted (except on WW stitching)	114	
	WW stitching: One or more rows of stitching omitted	115	
	Stitching extends off chapes		212
	Length of stitching less than specified by more than 1/4 inch	116	
Components and assembly	Any component or required operation omitted or not as specified (unless otherwise classified herein)	117	
	Needle chews	118	
	Mends, darns or patches	119	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:21Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Classification Minor
Components and assembly (cont'd)	Any turn under on stitched ends of webbing not securely caught in WW stitching	120	
	Turn under on ends of straps, chapes, and loops less than specified by more than 1/8 inch		213
Lowering line pocket	Construction or formation of pocket not as indicated on drawings, obstructing free use of lowering line	121	
Adapter web	Not of specified material	122	
Marking and identification	Omitted, incorrect, illegible, misplaced, or size characters not as specified		214
Cleanness	Noticeable spots or stains, i.e., grease, oil, ink, dirt not removed; thread ends not trimmed to 1/4 inch or less		215

4.4.3 End item dimensional examination. The end items shall be examined for the defects listed in table II. Only those dimensions that can be evaluated without damaging or disassembling the end items shall be examined. The lot size shall be expressed in units of packs. The sample unit shall be one pack. The inspection level shall be S-3. The finding of any defect shall be cause for rejection of the lot.

TABLE II. End item dimensional defects

Examine	Defect	Classification Major	Classification Minor
Overall dimensions	Smaller than nominal dimensions, less applicable minus tolerance, but not smaller than twice the applicable minus tolerance		201
	Smaller than nominal dimensions, less twice the applicable minus tolerance	101	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:21Z
Check the source to verify that this is the current version before use.

TABLE II. End item dimensional defects (cont'd)

Examine	Defect	Classification Major	Minor
Overall dimensions (cont'd)	Larger than nominal dimensions and applicable plus tolerance	102	
Component and location dimensions (not otherwise classified herein)	Not within specified tolerance		202

4.4.4 Packaging examination. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2. The finding of any defects shall be cause for rejection of the lot.

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application
Materials	Any component missing, damaged, or not as specified
Preservation	Naphthalene flakes missing
Workmanship	Inadequate application of components, such as: incomplete sealing or closure of flap, improper taping, loose strapping, or inadequate stapling
Content	Number per container is more or less than required

4.4.5 Palletization examination. The fully packaged and palletized end items shall be examined for the defects listed below. The lot size shall be expressed in units of palletized unit loads. The sample unit shall be one palletized unit load, fully packaged. The inspection level shall be S-1. The finding of any defects shall be cause for rejection of the lot.

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirement
Palletization	Pallet pattern not as specified Load not bonded as specified

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:21Z
Check the source to verify that this is the current version before use.

Weight	Exceeds maximum load limits
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application

5. PACKAGING

5.1 Preservation and packing. Levels of preservation and packing shall be in accordance with the procurement order/contract or in accordance with MIL-STD-2073-1 and ASTM-D-3951 (see 6.2).

5.2 Palletization. When specified (see 6.2), palletization shall be in accordance with the procurement order/contract or MIL-STD-147.

5.3 Marking. Marking shall be in accordance with the procurement order/contract or MIL-STD-129.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The dragon jump pack is used by individuals as a protective carrying container for the dragon missile during airborne operations. A lowering line is not furnished with this assembly.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this specification.
b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
c. When a first article is required (see 3.1, 4.3, and 6.3).
d. Levels of preservation and packing (see 5.1).
e. When palletization is required (see 5.2).

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of Federal Acquisition Regulation (FAR) 52.209-4. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:21Z
Check the source to verify that this is the current version before use.

6.4 Subject term (keyword listing).

Air delivery
Antiaircraft
Carrier

6.5 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:

Army - GL

Review activity:

Army - AV

Preparing activity:

Army - GL

(Project 1670-A809)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:21Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-P-44012A(GL)	94/01/12

3. DOCUMENT TITLE
PACK, PARACHUTIST'S, DRAGON MISSILE

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code) (1) Commercial	(2) AUTOVON/DSN
U.S. Army Natick RD&E Center	508-651-5235	256-5235
c. ADDRESS (Include Zip Code) Commander, U.S. Army Natick RD&E Center ATTN: SATNC-UC Natick, MA 01760-5017	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

Source: https://assist.dla.mil -- Downloaded: 2026-10-31T23:21Z
Check the source to verify that this is the current version before use.