MIL-P-44019A
21 December 1984
SUPERSEDING
MIL-P-44019
15 January 1980

MILITARY SPECIFICATION

PIE FILLING, MIX, LEMON

This specification is approved for use by all Department and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers lemon pie filling mix for use by the Department of Defense as an item of general use.

2. APPLICABLE DOCUMENTS

2.1 Government documents. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research and Development Center, Natick, MA 01760-5014 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document by letter.

FSC 8940

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:23Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

TT-C-495	- Coatings, Exterior, For Tinned Food Cans
PPP-B-636	- Boxes, Shipping, Fiberboard
PPP-C-29	- Canned Subsistence Items, Packaging Of
PPP-C-96	- Cans, Metal, 28 Gage and Lighter

MILITARY

MIL-L-1497	- Labeling of Metal Cans for Subsistence Items
MIL-L-35078	- Loads, Unit: Preparation of Nonperishable Subsistence, General Specification for

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	- Marking for Shipment and Storage
MIL-STD-900	- Bacterial Standards for Starches, Flours, Cereals, Alimentary Pastes, Dry Milks, and Sugars Used in the Preparation of Canned Foods to the Armed Forces

(Copies of documents required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

OTHER GOVERNMENT DOCUMENTS

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES

Federal Food, Drug, and Cosmetic Act and Regulations Promulgated Thereunder (21, CFR Parts 1-199)

(Application for copies should be addressed to the Superintendent of Docu-ments, U.S. Government Printing Office, Washington, DC 20402.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:23Z
Check the source to verify that this is the current version before use.

U.S. DEPARTMENT OF AGRICULTURE (USDA)

Regulations Governing the Inspection of Egg and Egg Products

(Application for copies should be addressed to the Poultry Division, Agricultural Marketing Service, U.S. Department of Agriculture, Washington, DC 20250.)

ENVIRONMENTAL PROTECTION AGENCY (EPA)

National Interim Primary Drinking Water Regulations

(Application for copies should be addressed to the Office of Drinking Water WH550, Environmental Protection Agency, Washington, DC 20460.)

2.2 Other publications. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

ASSOCIATION OF OFFICIAL ANALYTICAL CHEMISTS (AOAC)

Official Methods of Analysis of the Association of Official Analytical Chemists

(Application for copies should be addressed to the Association of Official Analytical Chemists, 1111 No. 19th Street, Suit 210, Arlington, VA 22209.)

NATIONAL ACADEMY OF SCIENCES

Food Chemicals Codex (F.C.C.)

(Application for copies should be addressed to the National Academy Press, 2101 Constitution Avenue, N.W., Washington, DC 20418.)

AMERICAN OIL CHEMISTS SOCIETY

Official and Tentative Methods of the American Oil Chemists Society

(Application for copies should be addressed to the American Oil Chemists Society, 508 South Sixth Street, Champaign, IL 61820.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:23Z
Check the source to verify that this is the current version before use.

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., Traffic Department, 1616 P Street, N.W., Washington, DC 20036.)

UNIFORM CLASSIFICATION COMMITTEE

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Suite 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

(Technical society and technical association documents are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence.

3. REQUIREMENTS

3.1 Bid sample approval. Duplicate, individually packaged samples, each consisting of not less than two 2-pound samples of pie filling mix, which the bidder proposes to furnish and which comply with the document requirements, shall be submitted to the contracting officer prior to the bid opening and will be inspected to the extent necessary to properly evaluate the bids. One sample of each duplicate shall be evaluated by a technical group to determine compliance with 3.4.2 for the subjective characteristics (flavor, odor, color and texture). In addition, the technical group shall rate the samples as to overall quality, taking into consideration all the subjective characteristics. The remaining sample shall be used as a standard for the subjective characteristics in determining acceptance of intended delivery products. The approval of any bid sample for the aforementioned characteristics shall not constitute approval of the product as meeting the other requirements of this document.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:23Z
Check the source to verify that this is the current version before use.

3.2 Ingredients. All ingredients shall be clean, sound, wholesome, free from foreign materials, evidence of rodent and insect infestation, extraneous material, off-odors, off-flavors, and off-colors.

3.2.1 Sugar. Sugar shall be clean, white, refined, sucrose, liquid or granulated, cane or beet, or a combination thereof. The sugar shall comply with MIL-STD-900.

3.2.2 Egg, yolk, dried. Dried egg yolk shall have been produced in accordance with 7 CFR Part 59, Regulations Governing the Inspection of Eggs and Egg Products and be identified with the USDA Egg Products shield mark. The dried egg yolk shall not exceed six months of age at the time of incorporation.

3.2.3 Starch waxy maize, modified. The starch shall be white, odorless, finely pulverized modified waxy maize food starch for use in canned foods. The modified starch shall demonstrate initial viscosity development in the temperature range 140°-170°F and a typical viscosity (be fully developed) at common retort temperatures. It shall resist breakdown at low pH, under sheer stress and conditions of cold storage. The starch shall be bland with essentially no cereal or starch taste and shall comply with MIL-STD-900.

3.2.4 Hydrogenated vegetable shortening. Hydrogenated vegetable shortening shall be refined hydrogenated vegetable oil of 60 hours or greater stability as determined by the Active Oxygen Method (AOM) in Method Ca 12-57 of the Official and Tentative Methods of the American Oil Chemists Society. If soybean oil is used, it shall have a stability of not less than 100 hours AOM. The vegetable oil may contain an anti-oxidant or combination of antioxidants permitted by the FDA. Alternatively, powdered shortening of equivalent stability may be substituted. The powdered shortening shall be spray dried and free of burnt or scorched aroma. It shall be partially hydrogenated vegetable oil with fillers such as corn syrup solids, soy protein isolate, sodium caseinate and other ingredients normally used. Unless otherwise specified (see 6.1), a certificate of compliance shall be submitted and will be acceptable for the stated requirement.

3.2.5 Coloring materials. Coloring materials shall be FD&C Yellow #5 and titanium dioxide.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:23Z
Check the source to verify that this is the current version before use.

3.2.6 Salt. Salt shall be white, refined sodium chloride, with or without anti-caking agent. Iodized salt shall not be used.

3.2.7 Lemon flavor. Lemon flavor shall be natural flavor. Lemon flavor shall be entrapped or encapsulated by incorporating it in vegetable gum, sorbitol, dextrose, or other edible material, in such a manner that the flavor is protected from oxidation, rancidity, evaporation, or other types of deterioration. The flavor shall be of such quality that it can be readily identified.

3.2.8 Lemon juice powder. Lemon juice powder shall be spray dried powder prepared from unfermented juice obtained from clean, sound mature lemons of one or more of the high acid varieties. Typical analysis of lemon juice powder is as follows:

Oil content (100 g powder)	- 1.4 to 1.6 mL
Juice solids	- 18.0 to 18.5%
Corn syrup solids	- 81.5 to 82.0%
Titratable acidity (as citric)	- 13.3 to 13.6%
pH (5 grams of powder in 30 mL of distilled water)	- 2.4 to 2.65

3.2.9 Acids. Acids shall be fumaric or citric, and shall be white, odorless granules or crystalline powder conforming to the Food Chemicals Codex. When fumaric is used, it shall be used at the ratio of 2 parts of fumaric acid for 3 parts citric acid.

3.2.10 Tricalcium phosphate. Tricalcium phosphate shall conform to the Food Chemicals Codex.

3.3 Preparation and processing.

3.3.1 Formulation. The lemon pie filling shall be prepared according to the formulation below. Based on this formula, the yield per No. 10 can shall be 8 quarts.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:23Z
Check the source to verify that this is the current version before use.

Ingredients	Percent by weight
Sugar	70.06
Egg yolk, dried	4.00
Starch, modified	23.00
Acid	1.0
Lemon flavor, natural	0.25
Lemon juice, powder	1.4
Salt	0.25
Titanium Oxide	0.01
FD&C Yellow No. 5	0.02
Hydrogentated vegetable shortening	0.01
Tricalcium phosphate	1/
	100.00

1/ Tricalcium phosphate may be used as an optional flowing agent in quantity of not more than 0.5 percent. The amount used shall be removed from the sugar.

3.4 Finished product.

3.4.1 Pie filling mix. The pie filling mix shall be a uniform, free flowing powder with a moisture content not greater than 3.0 percent. The pie filling mix shall be free from metal, glass, wood, paint, filth, grit, dirt, and other extraneous material.

3.4.2 Prepared lemon filling. When prepared as specified in 5.4.1, the pie filling shall have a flavor, odor, texture and color characteristic of lemon pie filling and shall contain no free liquid. The lemon filling shall not be watery and shall not weep. It shall have no ungelatinized pockets, and shall be uniformly distributed over the bottom crust. It shall contain no cracks or crevices, and shall be easily sliced into portions and transferred to serving dishes without breaking. The finished filling shall not be tough or rubbery.

3.5 Plant qualification. The product shall be prepared, processed, and packaged under sanitary conditions in accordance with good manufacturing practice. The product shall be processed in establishments meeting the sanitary requirements of the applicable Government inspection agency.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:23Z
Check the source to verify that this is the current version before use.

3.6 Federal Food, Drug, and Cosmetic Act. All deliveries shall conform in every respect to the provisions of the Federal Food, Drug and Cosmetic Act and regulations promulgated thereunder.

4. QUALITY ASSURANCE PROVISIONS

4.1 Contractor's responsibility. Inspection and acceptance by the USDA shall not relieve the contractor of obligation and responsibility to deliver a product complying with all requirements of this document. The contractor shall assure product compliance prior to submitting the product to the USDA for any inspection.

4.2 Inspection and acceptance service. Product acceptability shall be determined by the USDA. The USDA will determine the degree of acceptance service necessary to assure compliance with the requirements of this document. The cost of grading and acceptance services performed by the USDA involving inspection, official documentation, and related services shall be borne by the contractor.

4.3 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.3.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

4.3.1.1 Ingredient examination. Conformance of ingredients to identity and condition requirements shall be determined by examination of pertinent labels, markings, U.S. Grade certificates, invoices, certificates of analysis, or other valid documents. In addition, each ingredient shall be examined organoleptically as necessary to determine conformance to the condition requirements. Any nonconformance to an identity, condition, or other requirement shall be cause for rejection of the ingredient lot or of any involved product.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:23Z
Check the source to verify that this is the current version before use.

4.3.1.2 Unfilled can inspection. Conformance of unfilled cans to the requirements specified in 5.1.1 shall be determined by examination of certificates of conformance or other valid documents. Any non-conformance shall be cause for rejection of the can lot or of any involved product.

4.3.2 In-process inspection.

4.3.2.1 In-process examination. In-process examination shall be performed to determine conformance to the preparation, processing, filling, sealing, and packing requirements. Any nonconformance revealed by actual examination or by review of records of time, temperature and formulation or of other valid documents shall be cause for rejection of the involved product.

4.3.3 Net weight examination. The cans of product shall be examined for net weight and the results shall be reported to the nearest 0.1 ounce. Any individual sample with a net weight of less than 86.5 ounces shall be scored as a minor defect. The lot size shall be expressed in numbers of cans. The sample unit shall be one can of product. The inspection level shall be S-3 and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 2.5. In addition, the lot shall be rejected if the sample average net weight is less than 88.0 ounces.

4.3.4 Product examination. The finished product shall be examined for the defects listed in table I. The lot size shall be expressed in cans. The sample unit shall be the contents of one filled and sealed can. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 1.5.

TABLE I. Product defects 1/

Category	Defect
Major	Dry product
101	Not uniform in appearance
102	Not free flowing

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:23Z
Check the source to verify that this is the current version before use.

TABLE I. Product defects 1/ (cont'd)

Category	Defect
Major	
	Prepared product 2/
103	Product not equal to prepared bid sample for flavor, odor, texture, or color (see 3.4.2). 3/
104	Reconstituted yield less than specified on label (see 5.4.1).
105	Presence of cracks or crevices, not easily sliced portions, breaks when transferred to serving dishes; the presence of ungelatinized areas.
106	Sliced portion shows evidence of weeping within 3 hours after preparation.
107	Not uniformly distributed over the bottom crust.
108	Filling watery, free liquid present.
109	Finished filling tough or rubbery.

1/ The presence of any foreign material (e.g. glass, dirt, insect parts, hair, wood, metal, etc.), foreign odor or flavor (e.g. burnt, scorched, moldy, rancid, sour, stale, etc.) or foreign color shall be cause for rejection of the lot.

2/ Reconstitute and cook contents of each can in sample in accordance with the label instructions in 5.4.1 and examine for yield. From each sample unit, prepare one pie without meringue in accordance with label instructions and examine for defects 103 and 104.

3/ When reference standard is not available for comparison, a sample chosen from an approved lot by the USDA inspector may be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:23Z
Check the source to verify that this is the current version before use.

4.3.5 Can condition examination. Examination of filled and sealed can shall be in accordance with the United States Standards for Condition of Food Containers, except that inspection for labeling shall be in accordance with MIL-L-1497 (see 5.4).

4.3.6 Leakage testing. The cans of pie filling shall be tested for leakage as specified in 4.4.1. The lot size shall be expressed in cans. The sample unit shall be one can. The inspection level shall be S-3. Any test failure shall be a major defect and shall be cause for rejection of the lot.

4.3.7 Moisture test. The cans of mix shall be tested as specified in 4.4.2 for conformance to the moisture content requirements in 3.4.1. The sample for testing shall be an 8 ounce (230 gms) composite of the mix taken from the number of cans indicated by inspection level S-2. Results shall be reported to the nearest 0.1 percent. A test failure shall be cause for rejection of the lot.

4.3.8 Shipping container examination. When shipping containers are required to be in accordance with PPP-B-636, examination for defects in assembly, closure and reinforcement shall be in accordance with the appendix of PPP-B-636. In addition, the following defects shall be classified as follows:

Major: National stock number, item description, contract number, or date of pack markings missing, incorrect, or illegible.

Minor: Any component missing, damaged, or not as specified.
Other required markings missing, incorrect, or illegible.
Reinforcement with nonmetallic strapping or tape is not used.
Arrangement or number or cans not as specified.

Level C shipping containers shall be examined for the marking, arrangement, and number of cans defects specified above and for the closure method specified in 5.2.3.

4.3.9 Unit load inspection. Inspection of unit loads shall be in accordance with quality assurance provisions MIL-L-35078.

4.4 Methods of inspection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:23Z
Check the source to verify that this is the current version before use.

4.4.1 Leakage test. The seams of the filled and closed cans shall be examined as follows: Submerge can in water contained in a vacuum desiccator, Mead tester, or equivalent device, and draw a vacuum of 10 inches for 30 seconds and observe for leakage. A leak consists of a steady progression of bubbles, and shall be considered a test failure. Isolated bubbles that can be caused by the release of air entrapped in the double seam are not considered as signs of leaks.

4.4.2 Moisture test. Under low humidity conditions, a relative humidity of 20 percent or less, extract two 3 to 4 gram samples and weigh in aluminum weighing dishes (approximately 2 to 2-1/2 inches in diameter and 3/4 inch in depth) with tight fitting covers. Place the dishes with cocked lids in a vacuum oven and dry for 6 hours at 70°C under a pressure of not more than 100 milliliters of mercury. During drying, the oven shall be purged by a slow current of air (approximately two bubbles per second) which has been dried by passage through concentrated sulfuric acid. Remove the dishes and allow them to cool in a desiccator before weighing. Calculate the loss as percent moisture and report to the nearest 0.1 percent.

5. PACKAGING

5.1 Preservation. The product shall be preserved in accordance with level A or C, as specified (see 6.1).

5.1.1 Level A. A net weight of 88 ounces of the product shall be unit packed in a size 603 by 700 can. A minus tolerance of 1.5 ounces will be permitted in any individual can provided that the average net weight of cans examined in accordance with 4.3.3 is not less than 88.0 ounces. The can shall be an open top style, round, metal can with soldered or welded side seam and compound-lined, double-seamed ends. The can shall be made throughout from not less than commercial 0.25-pound per base box electrolytic tin plate (see 4.3.1.2), and shall be coated overall on the outside with a coating conforming to type I or when specified (see 6.1) type III of TT-C-495. The can shall have a sufficient base plate weight and temper to protect the product during shipment and storage. The can shall not leak when examined in accordance with 4.3.6.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:23Z
Check the source to verify that this is the current version before use.

5.1.2 Level C. The product shall be preserved as specified in 5.1.1 except that cans with or without commercial exterior coating will be acceptable. Alternatively, cans may be made from 0.20 pound per base box electrolytic tinplate, provided the cans have an exterior commercial coating.

5.2 Packing. Six cans of product, arranged 3 in length, 2 in width, and 1 in depth, shall be packed on end in a snug-fitting shipping container in accordance with level A, B or C as specified (see 6.1).

5.2.1 Level A packing. The shipping container shall be a fiberboard box, constructed and closed in accordance with style RSC, V2s of PPP-B-636. Each fiberboard box shall be reinforced with nonmetallic strapping or pressure-sensitive filament reinforced tape in accordance with the appendix of PPP-B-636. Shipping containers shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.1). Strapping shall be limited to nonmetallic strapping, except for type V, class F loads.

5.2.2 Level B packing. The shipping container shall be a fiberboard box, constructed and closed in accordance with style RSC, V3c, V3s, or V4s of PPP-B-636. Each fiberboard box shall be reinforced with nonmetallic strapping or pressure-sensitive filament reinforced tape in accordance with the appendix of PPP-B-636.

5.2.3 Level C packing. The shipping container shall comply with the National Motor Freight Classification or Uniform Freight Classification, as applicable, except fiberboard containers shall be closed in accordance with Method II as specified in the appendix of PPP-B-636.

5.3 Unit loading. When specified (see 6.1), the product, packed as specified in 5.2.2 and 5.2.3, shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified. When unit loads are strapped, the strapping shall be limited to nonmetallic strapping.

5.4 Labeling and marking.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:23Z
Check the source to verify that this is the current version before use.

5.4.1 Cans. Cans shall be labeled in accordance with MIL-L-1497. In addition, the following directions for use shall be lithographed on the body or on one end of the can.

DIRECTIONS FOR USE - LEMON PIE FILLING MIX

Combine 1-1/4 qt. cool water and 88 ounces (1 No. 10 can) Lemon Pie Filling Mix. Add mixture to 5-1/4 qt. boiling water, mix well. Cook at medium heat, stirring constantly, until mixture comes to a boil. Remove from heat. Yield: 8 qts. pie filling. For Lemon Meringue Pie: Prepare a 9" pie shell. Pour 2-3/4 cups lemon pie filling into each baked pie shell. Prepare meringue topping. Spread 2-1/2 cups meringue over warm filling (at least 122°F) in each pie. Bake 15-20 minutes in 350°F oven. Refrigerate at least 3 hours before cutting. Yield: 10-11 pies.

5.4.2 Shipping containers. Shipping containers shall be marked in accordance with MIL-STD-129.

5.4.3 Unit loads. Unit loads shall be marked in accordance with MIL-L-35078.

6. NOTES

6.1 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. When certificate of compliance for hydrogenated vegetable shortening is not authorized (see 3.2.4).
c. Level of preservation and packing required (see 5.1 and 5.2).
d. When type III exterior coating of cans is desired (see 5.1.1).
e. Type and class of unit load required (see 5.2.1 and 5.3).

6.2 Appropriate level of pack. Based on the conditions known or expected to be encountered during shipment, handling, and storage of the specific item being procured, the procuring activity should select the appropriate level pack in accordance with the criteria established in AR 700-15/NAVSUPINST 4030.28/AFR 71-6/MCO 4030.33A/DLAR 4145.7.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:23Z
Check the source to verify that this is the current version before use.

6.3 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:

Army - GL
Navy - SA
Air Force - 50

Preparing activity:

Army - GL

Project No. 8940-0448

Review activities:

Army - MD
Navy - MC, MS
DP - SS

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:23Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

US ARMY NATICK RESEARCH
and DEVELOPMENT CENTER
ATTN: STRNC-ES
Natick, MA 01760-5014

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research
and Development Center
ATTN: STRNC-ES
Natick, MA 01760-5014

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:23Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-P-44019A	Pie Filling, Mix, Lemon

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

NATICK OP, 20 Nov 84

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:23Z
Check the source to verify that this is the current version before use.