INCH-POUND

MIL-S-44021A(GL)
22 August 1989
SUPERSEDING
MIL-S-44021(GL)
19 February 1980

MILITARY SPECIFICATION

SURVIVAL VEST, INDIVIDUAL, OV-1 AIRCRAFT

This specification is approved for use by the Natick Research, Development, and Engineering Center, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements of one type of survival vest in two sizes.

1.2 Classification. The survival vest shall be of the following sizes as specified (see 6.2):

Large
Small

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8415

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:24Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

PPP-B-566	- Boxes, Folding, Paperboard
PPP-B-636	- Boxes, Shipping, Fiberboard
PPP-B-676	- Boxes Setup
PPP-P-291	- Paperboard, Wrapping and Cushioning
PPP-T-45	- Tape, Gummed, Paper, Reinforced and Plain, for Sealing and Securing

MILITARY

MIL-B-131	- Barrier Materials, Watervaporproof, Greaseproof, Flexible, Heat-Sealable
MIL-W-1053	- Whistle, Ball, Plastic
MIL-L-3454	- Life Preservers; Packaging of
MIL-K-8662	- Knife, Hunting, Sheathed, Survival, Pilot's
MIL-M-18371	- Mirrors, Emergency Signaling, Mark 3
MIL-K-25594	- Knife, Pocket, Hook Blade and Snap Blade MC-1
MIL-L-35078	- Loads, Unit: Preparation of Semiperishable Subsistence Items; Clothing, Personal Equipment and Equipage; General Specification For
MIL-L-38217	- Light, Marker Distress
MIL-L-38484	- Life Preservers, Underarm, Pneumatic
MIL-L-81941	- Survival Kit, Individual, Airman's
MIL-S-83352	- Signal Kit, Personnel, Distress, A/P255-5A

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	- Marking for Shipment and Storage
MIL-STD-147	- Palletized Unit Loads
MIL-STD-731	- Quality of Wood Members for Containers and Pallets

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Naval Publications and Forms Center, (ATTN: NPODS), 5801 Tabor Avenue, Philadelphia, PA 19120-5099.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:24Z
Check the source to verify that this is the current version before use.

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS

U.S. ARMY NATICK RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER

11-1-468	- Survival Vest, Individual, OV-1 Aircraft, Assembly Instruction Sheet
11-1-1795	- Survival Vest, Individual, OV-1 Aircraft (Large or Small); Assembly, Complete

(Copies of drawings are available from the U.S. Army Natick Research, Development, and Engineering Center, ATTN: STRNC-EMSS, Natick, MA 01760-5014.)

2.2 Non-Government publications. The following document forms a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

(Non-Government standards and other publications are normally available from organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection (see 6.3) in accordance with 4.3.

3.2 Materials. Materials shall conform to the requirements specified herein and on the applicable drawings. It is encouraged that recycled material be used when practical as long as it meets the requirements of this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:24Z
Check the source to verify that this is the current version before use.

3.3 Construction.

3.3.1 Vest. Construction of the vest shall conform to the requirements specified herein and on Drawing 11-1-1795 as applicable.

3.3.1.1 Type 301 stitching. Stitching defects, such as skipped or broken stitches and runoffs, shall be overstitched not less than 1 inch past ends of the defect in accordance with the required stitch pattern. Stitching shall be backstitched 1/2 inch minimum at the ends, except where ends are turned under in a hem or held down by other stitching. Thread tension shall be maintained so that there will be no loose stitching and the lock will be imbedded in the materials sewed. All thread ends shall be trimmed.

3.3.1.2 Automatic stitching. Automatic stitching machines may be used to perform any of the required stitch patterns provided the requirements for the stitch pattern, stitches per inch, and size and type of thread are met, and at least three or more tying, overlapping or back stitches are used to secure the ends of the stitching. Certification of equivalency, supported by engineering data may be required.

3.3.1.3 Setting of grommets. Holes shall be prepunched or drilled to receive the grommets. Holes prepunched to receive the grommets shall be smaller than the outside diameter of the grommet barrel so that the barrel must be forced through the hole. The grommet shall be securely clinched without cutting the adjacent material.

3.3.1.4 Setting of snap fasteners. A hole shall be prepunched or drilled to receive the button and eyelet components of the snap fasteners. The hole shall be smaller than the outside diameter of the button and eyelet barrels so that the barrel must be forced through the hole. The hole shall not be punched in the setting operation with the button or eyelet barrel. The fasteners shall be securely clinched without cutting the adjacent materials and no more than three splits shall occur in the button or eyelet barrels.

3.3.1.5 Thread ends. All thread ends shall be trimmed to a maximum length of 1/4 inch.

3.4 Contents and assembly of components. The vest shall be comprised of the contents specified in table I. Each component shall conform to the applicable specification cited therein, or as otherwise specified. In assembling components of the vest, each vest shall include the items listed in table I except for items 11, 12, 13, and 14 (see note 2 to table I). For assembling and inspection purposes, items themselves or assemblies of those items shall be provided by the contracting officer (see 6.4 and 6.5). The items shall be stowed in the vest as shown on Drawing 11-1-468.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:24Z
Check the source to verify that this is the current version before use.

TABLE I. Vest contents list

Item No.	Nomenclature	Applicable specification	Unit	Qty	Other requirements
1	Vest		Each	1	--
2	Light, marker, distress SDU-5/E	MIL-L-38217	Each	1	--
3	Signal kit, personnel distress A/P 25S-5A	MIL-S-83352	Each	1	--
4	Survival kit, individual, airmans	MIL-S-81941	Each	1	--
5	Life preservers, underarm, pneumatic LPU-10/P	MIL-L-38484	Each	1	--
6	Knife, hunting, sheathed, survival, pilots	MIL-K-8662	Each	1	--
7	Knife, pocket, hook blade and snap blade, MC-1	MIL-K-25594	Each	1	--
8	Whistle, ball plastic	MIL-W-1053	Each	1	Tissue wrapped or polyethylene bag
9	Mirror, emergency signaling, Mark 3, type I	MIL-M-18371	Each	1	Tissue wrapped
10	Assembly instruction sheet	P/N 11-1-468	Each	1	1/ 9x12 inch reproduction of Dwg No. 11-1-468
11	Revolver, cal. 38 special	--	Each	1	2/

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:24Z
Check the source to verify that this is the current version before use.

TABLE I. Vest contents list (cont'd)

Item No.	Nomenclature	Applicable specification	Unit	Qty	Other requirements
12	Cartridge, cal. 38 special ball M-41	--	Each	6	2/
13	Cartridge, cal. 38 special tracer, M-41	--	Each	6	2/
14	Radio set AN/PRC-90	--	Each	1	2/
15	Fire starter aviation survival, magnesium	NSN 1670-01-160-5618	Each	1	Sealed in polyethlene bag

1/ Item will be furnished by the Government (see 6.5).

2/ Item procured separately and issued by unit commanders in the field (see 3.4).

3.5 Age of vest components. Unless otherwise specified by the contracting officer (see 6.2), the vest components shall have been manufactured within one year prior to the date of delivery.

3.6 Workmanship. The finished vest shall be clean and free of all loose thread, lint, and any other foreign matter; shall not contain any unspecified hole, abraded area, tear, cut, mend, needle chew, spots or stains and shall conform to the quality of product established by this specification.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:24Z
Check the source to verify that this is the current version before use.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.1.2 Responsibility for dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for ensuring that all specified dimensions have been met. When dimensions cannot be examined on the end item, inspection shall be made at any point, or at all points in the manufacturing process necessary to ensure compliance with all dimensional requirements.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required (see 3.1 and 6.2), it shall be examined for the defects specified in 4.4.3, 4.4.4, 4.4.4.1 and 4.4.4.2. The presence of any defect shall be cause for rejection of the first article.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.4.2 In-process inspection. Inspection shall be made at any point or during any phase of the manufacturing operation to determine whether cut lengths, cut parts, markings for location of components, and location of assembled component parts are in accordance with the specified requirements. In addition, inspection shall be made to determine that prepunched holes for receiving grommets, and snap fasteners, are smaller than the outside diameter of the hardware barrel. Whenever nonconformance is noted, corrections shall be made to the parts affected and the lot in process. Parts which cannot be corrected shall be removed from production.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:24Z
Check the source to verify that this is the current version before use.

4.4.3 End item visual examination. The end items shall be examined for the defects listed in table II. The lot size shall be expressed in units of survival vests. The sample unit shall be one survival vest. The inspection level shall be II (see 6.6).

TABLE II. End item visual defects

Examine	Defect	Classification Major	Minor
Materials	Mesh net containing any cut, tear, burn or smash	101	
	Mesh net containing any abrasion, broken, or missing yarns resulting in a broken mesh opening	102	
	Mesh net containing any abrasion, broken, or missing yarns but not resulting in a broken mesh opening		201
	Mesh net containing any mend, darn, patch or splice	103	
	Nylon cloth containing any hole except drill holes 1/16 inch or less, cut, tear, smash, multiple floats, missing yarns, or open places	104	
	Exposed drill holes 1/16 inch in diameter or less in nylon cloth		202
	Tape or webbing containing any cut, hole, or tear	105	
	Tape or webbing not firmly or tightly woven or edges of tape or webbing frayed or scalloped		203
	Color of mesh net, tape, webbing, slide fastener tapes, or hook or pile fastener tapes not as specified		204
	Any cut, damage, kink, or knot in nylon cords, seriously affecting serviceability	106	
	Ends of nylon cords not seared		205
	Nylon cords contain core ends projecting through the core sleeve		206

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:24Z
Check the source to verify that this is the current version before use.

TABLE II. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor
Hardware	Hardware not type specified	107	
	Any required component improperly set or reversed, failing to serve intended purpose	108	
	Hardware broken, damaged, or malformed or containing corroded areas, burrs, or sharp edges	109	
	Any snap fastener omitted or not closing or opening freely	110	
	Any snap fastener not properly clinched, i.e., components of stud or socket separating when snap fasteners are snapped or unsnapped, or clinched excessively, cutting surrounding material		207
	Any lift-a-dot fastener not positioned as specfified	111	
Seams and stitching	Open seam more than 1/2 inch but not more than 1 inch 1/		208
	Open seam more than 1 inch 1/	112	
	Raw edges (except where required) more than 1/4 inch but not more than 1 inch but securely caught in stitching 1/		209
	Raw edges (except where required) more than 1 inch but securely caught in stitching 1/	113	
	Any raw edge including inside of pockets not seared or overedge stitched	114	
	Not specified seam or stitch type	115	
	Loose stitch tension resulting in loosely exposed bobbin or top thread		210
	Tight stitch tension resulting in tightness or puckering of fabric		211
	One stitch per inch less than minimum specified		212
	Two or more stitches per inch less than minimum specified	116	
	One or more stitches in excess of maximum stitches per inch specified		213

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:24Z
Check the source to verify that this is the current version before use.

TABLE II. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor
Seams and stitching (cont'd)	Stitching margins not as specified		214
	Stitching ends backstitched less than 1/2 inch unless held down by other stitching or turned under in a hem 2/		215
	Thread breaks overstitched less than 1 inch for stitch type 301 1/		216
	Any required row of straight stitching omitted	117	
	Seam twisted or pleated		217
	Binding loosely or improperly applied, badly pleated, or ends not finished as specified or not securely caught in stitching		218
	Needle chews resulting in damage to fabric	118	
Construction details	Center joining seam or shoulder seams not reinforced by tape.	119	
	Any pocket not constructed or positioned on vest as specified	120	
	Any slide fasteners not attached to pocket as specified, i.e., distorted, failing to effect a smooth closure, or direction of pull not as specified on drawings	121	
	Pile portion of fastener tape attached to pocket flap		219
	Hook portion of fastener tape attached to pocket		220
	Fastener tape not specified size		221
	Fastener tape misplaced, not serving intended purpose	122	
	Nylon cords not secured in pocket stitching as specified	123	
	Ends of loop adjustment tapes not properly turned under, resulting in loop end not securely caught in stitching	124	
	Loop tape cord not laced through loop tapes as specified and tied in square knot		222
	Loops not securely anchored to the tapes by stitching along edge of tape, catching tape and loops		223

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:24Z
Check the source to verify that this is the current version before use.

TABLE II. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor
Construction details (cont'd)	Any required component omitted or any required operation omitted or not as specified (unless otherwise classified herein)	125	
Slide fasteners and assemblies	Slide fastener not specified type or size	126	
	Slider of slide fastener jamming or failing to interlock chain scoops		224
	Thong omitted from slide fastener	127	
	Ends of thongs not seared		225
	Slide fastener tapes improperly stitched on vest fronts, preventing slider from operating freely	128	
	Bottom corners of vest uneven more than 1/4 inch but not more than 1/2 inch when slide fastener is engaged		226
	Bottom corners of vest uneven by more than 1/2 inch	129	
Pistol holster assembly	Any required component of pistol holster assembly omitted or detail of construction of pistol holster assembly not as specified (unless otherwise specified herein)	130	
Label	Information on label incomplete, incorrect, or illegible		227
	Stitching omitted on one or more edges of contractor's label		228
	Label missing	131	
General	Spots or stains not removable, or thread ends not trimmed throughout vest to 1/4 inch or less.		229

1/ A seam shall be classified as open if one or more stitches joining the seam are broken or if two or more continuous skipped stitches or runoffs occur. Thread breaks that are not overstitched and raw edges that are not securely caught in stitching shall be classified as open seams.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:24Z
Check the source to verify that this is the current version before use.

2/ Stitching at the end of binding not backstitched shall not be classified as a defect, provided the binding is overlapped at least 1 inch and the overlapped end is backstitched or bartacked.

4.4.4 End item dimensional examination. The end items shall be examined for conformance to the dimensions specified on the drawings. Only those dimensions that can be evaluated without damaging or disassembling the end items shall be examined. Any dimension not within the specified tolerance shall be classified as a defect. The lot size shall be expressed in units of survival vests. The sample unit shall be one survival vest. The inspection level shall be S-3 (see 6.6).

4.4.4.1 Vest component examination. The vest components shall be examined for items 2 thru 10 of table I and for the defects listed in table III. The lot size shall be expressed in units of grouped vest components. The sample unit shall be one group of vest components. The inspection level shall be S-3 (see 6.6).

TABLE III. Vest components defects

Examine	Defect
Items and packaging (as applicable)	Any item missing, broken, rusted, corroded, torn or punctured. Any item older than the age limit specified, except when specifically exempted by the procuring activity (see 3.5). Packaging, where required, torn, punctured or damaged.

4.4.4.2 Survival vest assembly examination. Each survival vest shall be examined to determine conformance with the requirements in 3.4. This examination may be performed together with the assembly operation to preclude repacking of the vest contents. Any nonconforming vest assemblies shall be rejected.

4.4.5 Packaging examination. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 (see 6.6).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:24Z
Check the source to verify that this is the current version before use.

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application
Materials	Any component missing, damaged, or not as specified
Workmanship	Inadequate application of components, such as: incomplete sealing or closure of flap, improper taping, loose strapping or inadequate stapling Bulged or distorted container
Content	Number per container is more or less than required

4.4.6 Palletization examination. The fully packaged and palletized end items shall be examined for the defects listed below. The lot size shall be expressed in units of palletized unit loads. The sample unit shall be one palletized unit load, fully packaged. The inspection level shall be S-1 (see 6.6).

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirement
Palletization	Pallet pattern not as specified Load not bonded as specified
Weight	Exceeds maximum load limits
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial, as specified (see 6.2).

5.1.1 Level A preservation.

5.1.1.1 Unit packing.

5.1.1.1.1 Vest. Each vest, with all fasteners closed, shall be folded to measure approximately 12 inches in length, 9 inches in width and 2 inches in depth.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:24Z
Check the source to verify that this is the current version before use.

Each vest shall then be unit packed in a close-fitting flat (or square) style clear polyethylene film bag of 0.003-inch thickness (± 20 percent tolerance). The bag may be fabricated from polyethylene film tubing or sheeting. The polyethylene bag shall be formed with heat sealed seams that are straight, continuous, and parallel to each other and the formed edges of the bag. The final closure of the bag shall be heat sealed with the heat seal made as close as possible to the open end. A 1/4 inch hole may be made at one corner of the bag to allow excess air to escape. Excess air shall be removed from each bag before the final closure.

5.1.1.1.2 Light. Each light shall have the battery removed from the case. The nylon cord shall be tied to one of the attachment loops of the light. The flash guard shall be fitted full depth over the light. The light (with flash guard) and battery shall be unit packed in a snug-fitting folding paperboard box conforming to variety 1, style II, type and class optional of PPP-B-566. The design of the box shall be such that the battery is compartmented, immobilized, and not in physical contact with the light. The box shall be closed and sealed with gummed paper tape conforming to type III, grade B of PPP-T-45. Alternatively, the battery shall be completely wrapped in paperboard cushioning material conforming to type I, style 1 or 2 of PPP-P-291 and then unit packed together with the light (with flash guard) in a snug-fitting folding paperboard box conforming to variety 1, style III, type G, class i of PPP-B-566 or setup paperboard box conforming to type I, variety 1, class A, style 4 of PPP-B-676. The box shall be securely closed with gummed paper tape conforming to type III, grade B of PPP-T-45, applied at the center of the length opening along the bottom and up each side a minimum of one-half the depth dimension of the box.

5.1.1.1.3 Signal kit. Each signal kit shall be placed in a close-fitting sealed water-vaporproof bag fabricated from material conforming to class 1 or 2 of MIL-B-131. The bagged signal kit shall then be unit packed in a snug-fitting folding paperboard box conforming to variety 1, style III, type G, class i of PPP-B-566 or setup paperboard box conforming to type I, variety 1, class A, style 4 of PPP-B-676. The box shall be securely closed with gummed paper tape conforming to type III, grade B of PPP-T-45, applied at the center of the length opening along the bottom and up each side a minimum of one-half the depth dimension of the box.

5.1.1.1.4 Survival kit. Each survival kit shall be unit packed in accordance with the level A packaging requirements specified in MIL-S-81941.

5.1.1.1.5 Life preserver. Each life preserver shall be unit packed in accordance with the applicable level A packaging requirements specified in MIL-L-3454. Alternatively, each life preserver shall be boxed in a paperboard box and the box closed as specified in 5.1.1.1.3.

5.1.1.1.6 Knife, hunting, sheathed. Each knife shall be unit packed in accordance with the level A packaging requirements of MIL-K-8662, except one bagged knife shall be boxed in a paperboard box and the box closed as specified in 5.1.1.1.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:24Z
Check the source to verify that this is the current version before use.

5.1.1.1.7 Knife, pocket. Each knife shall be unit packed in accordance with the level A packaging requirements of MIL-K-25594, except one wrapped knife shall be boxed in a paperboard box and the box closed as specified in 5.1.1.1.3.

5.1.1.1.8 Whistle. Each whistle shall be unit packed in accordance with the level A unit packaging requirements of MIL-W-1053. One unit packed whistle shall then be boxed in a paperboard box and the box closed as specified in 5.1.1.1.3.

5.1.1.1.9 Mirror. Each mirror shall be unit packed in accordance with the applicable level A unit packaging requirements specified in MIL-M-18371.

5.1.1.1.10 Assembly instruction sheet. Unit packing is not required.

5.1.1.1.11 Fire starter. One magnesium fire starter, complete with instructions, shall be unit packed in a clear polyethylene film bag of 0.003 inch thickness. The bag shall be formed with heat sealed seams that are straight, continuous and parallel with each other to form the edges of the bag.

5.1.1.2 Intermediate packing. One complete survival vest assembly, unit packed as specified in 5.1.1.1, shall be intermediate packed in a snug-fitting fiberboard box conforming to style RSC, grade W6c of PPP-B-636. The components of each assembly shall be neatly and compactly arranged within the interior box. The instruction sheet shall be placed on top with the printed matter facing up. Voids within the box shall be fitted with cushioning to immobilize the contents while the box is in transit. Each fiberboard box shall be closed in accordance with method IV as specified in the appendix of PPP-B-636.

5.1.2 Commercial preservation. The survival vest assemblies shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B, or Commercial, as specified (see 6.2).

5.2.1 Level A packing.

5.2.1.1 Complete vest assemblies. Survival vest assemblies of one size only, preserved as specified in 5.1, shall be packed in a snug-fitting shipping container conforming to style RSC-L, grade V2s of PPP-B-636. The weight of the contents shall not exceed 65 pounds. Each box shall be closed, waterproofed, and reinforced with strapping or tape banding in accordance with the appendix of PPP-B-636. Boxes shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.2). Strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:24Z
Check the source to verify that this is the current version before use.

5.2.1.2 Vest (when procured separately). Forty vests of one size only, preserved as specified in 5.1, shall be packed in a shipping container. The shipping container shall be a fiberboard box conforming to style RSC-L, grade V2s of PPP-B-636. The inside of each box shall be fitted with a box liner conforming to type CF, class weather-resistant, variety DW, grade V15c of PPP-B-636. Inside dimensions of the box shall be approximately 36 inches in length, 12 inches in width and 20 inches in depth. Each box shall be closed, waterproofed, and reinforced with strapping or tape banding in accordance with the appendix of PPP-B-636. Boxes shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.2). Strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

5.2.2 Level B packing.

5.2.2.1 Complete vest assembly. Survival vest assemblies of one size only, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, type CF (variety SW) or SF, class domestic, grade 275 of PPP-B-636. Each shipping container shall be closed in accordance with method II as specified in the appendix of the container specification. The weight of contents of each PPP-B-636 container shall not exceed 65 pounds. Each box shall be closed in accordance with method II as specified in the appendix of PPP-B-636.

5.2.2.2 Vests (when procured separately). Forty vests of one size only, preserved as specified in 5.1, shall be packed in a shipping container. The shipping container shall be a fiberboard box conforming to style RSC-L, type CF (variety SW) or SF, class domestic, grade 275 of PPP-B-636. The inside of each box shall be fitted with a box liner conforming to type CF, class domestic, variety DW, grade 275 of PPP-B-636. Inside dimensions of the box shall be approximately 36 inches in length, 12 inches in width and 20 inches in depth. Each box shall be closed in accordance with method II as specified in the appendix of PPP-B-636.

5.2.2.3 Weather-resistant containers. When specified (see 6.2), the fiberboard shipping container shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with the appendix of the container specification.

5.2.3 Commercial packing. Survival vest assemblies, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

5.3 Palletization. When specified (see 6.2), vest assemblies or vests, packed as specified in 5.2.2 and 5.2.3, shall be palletized on a 4-way entry pallet in accordance with load type Ia of MIL-STD-147. Pallet types shall be type I (4-way entry), type IV or type V in accordance with MIL-STD-147. Pallets shall be fabricated from wood groups I, II, III, or IV of MIL-STD-731. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means C and D or film bonding means F or G. Pallet patterns shall be in accordance with the appendix of MIL-STD-147.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:24Z
Check the source to verify that this is the current version before use.

5.4 Marking. In addition to any special marking required by the contract, unit packs, intermediate packs, shipping containers, and palletized unit loads shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

5.4.1 Polyethylene bagged unit packs. Polyethylene bagged unit packs shall have the required identification information legibly printed or stamped in black directly on the bag across the center face or on a white label inserted within the bag so as to permit ready identification.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The survival vest is designed to be worn by pilots of OV-1 Aircraft and is intended to supplement the ejection seat survival kit.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this specification.
b. Size of vest required (see 1.2).
c. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
d. When a first article is required (see 3.1, 4.3, and 6.3).
e. Any waiver that is allowed for the vest content age requirement (see 3.5).
f. Levels of preservation and packing (see 5.1 and 5.2).
g. Type and class of unit load required (see 5.2.1.1 and 5.2.1.2).
h. When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).
i. When palletization is required (see 5.3).
j. Acceptance criteria required (see 6.6).

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

6.4 Government-loaned property. The contracting officer should arrange to loan items 11, 12, 13 and 14 as listed in table I of 3.4, or facsimilies thereof.

6.5 Government-furnished property. The contracting officer should arrange to furnish the Assembly Instruction Sheet Drawing No. 11-1-468 as listed in table I of 3.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:24Z
Check the source to verify that this is the current version before use.

6.6 Acceptance criteria. The acceptance criteria recommended below is furnished only for guidance to the procuring activity. The acceptance criteria as specified in the contract or purchase order shall be binding. Unless otherwise specified, the following acceptance criteria are in accordance with MIL-STD-105.

6.6.1 For end item visual examination. An acceptable quality level (AQL), expressed in terms of defects per hundred units, of 2.5 for major defects and 6.5 for total (major and minor combined) defects is recommended.

6.6.2 For end item dimensional examination. An AQL, expressed in terms of defects per hundred units, of 6.5 is recommended.

6.6.3 For vest component examination. An AQL, expressed in terms of defects per hundred units, of 6.5 is recommended.

6.6.4 For packaging examination. An AQL, expressed in terms of defects per hundred units, of 2.5 is recommended.

6.6.5 For palletization examination. An AQL, expressed in terms of defects per hundred units, of 6.5 is recommended.

6.7 Subject term (key word) listing.

Airman's
Distress
Emergency
Personnel

6.8 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:

Army - GL

Review activities:

Army - MD, AV
DLA - CT

Preparing activity:

Army - GL

(Project 1680-A557)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:24Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-S-44021A(GL)	SURVIVAL VEST, INDIVIDUAL, OV-1, AIRCRAFT

a. NAME OF SUBMITTING ORGANIZATION

b. ADDRESS *(Street, City, State, ZIP Code)*

4. TYPE OF ORGANIZATION *(Mark one)*

- ☐ VENDOR
- ☐ USER
- ☐ MANUFACTURER
- ☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:24:27
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

U.S. ARMY NATICK RESEARCH, DEVELOPMENT
and ENGINEERING CENTER
ATTN: STRNC-ES
Natick, MA 01760-5014

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
U.S. Army Natick Research, Development
and Engineering Center
ATTN: STRNC-ES
Natick, MA 01760-5014

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:24Z
Check the source to verify that this is the current version before use.