MIL-S-44041A(GL)
AMENDMENT-2
26 March 1986
SUPERSEDING
AMENDMENT-1
10 January 1984

MILITARY SPECIFICATION

SHIRT, MANS'S, SHORT SLEEVE, POLYESTER/COTTON,

ARMY GREEN 415, DURABLE PRESS

This amendment forms a part of Military Specification MIL-S-44041A(GL), dated 7 October 1982, and is approved for use by the U.S. Army Natick Research, Development and Engineering Center, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

* 2.1, under "SPECIFICATIONS FEDERAL": Delete "UU-P-268 - Paper, Kraft, Wrapping".

PAGE 2

* 2.1, under "STANDARDS MILITARY": Delete "MIL-STD-1188 - Commercial Packaging of Supplies and Equipment" and add "MIL-STD-147 - Palletized Unit loads"

PAGE 3

2.2, under "AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)": Add "D 3951 - Standard Practice for Commercial Packaging".

3.3.1: Add "When cloth woven on shuttleless looms is used, the selvage for all types (leno, frayed, mono-filament) shall not be used as part of the shirt and must be removed prior to shirt fabrication."

PAGE 5

* 3.3.3.3, line 10: Delete "2. DO NOT STARCH OR BLEACH." and substitute "2. DO NOT STARCH, BLEACH OR USE FABRIC SOFTENERS."

PAGE 7

* 3.6.3, line 2, after delamination: Add "or curling". At the end of paragraph: Add "See 6.10 for recommended ultrasonic welding conditions."

AMSC N/A FSC 8405

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:31Z
Check the source to verify that this is the current version before use.

PAGE 10

Table II, operation 1.a., line 10, after "looms": Add "see 3.3.1".

PAGE 13

* Table II, operation 5.b.(3), at the end of the paragraph: Add "and should not cause the collar stay to curl either lengthwise or widthwise. See 6.10 for recommended ultrasonic welding conditions."

PAGE 16

* Table II, operation 8, line 4: Delete "1-1/8" and substitute "1-3/8".
Line 8: Delete "1-1/8" and substitute "1-5/8".

PAGE 17

* Table II, operation 10.b., line 5: Delete "not".

PAGE 24

Table III: Delete the 1/2 Chest measurements and substitute: "1/2 Chest 18 19 20 21 22 23 24 25 26 27 28" respectively.

PAGE 26

4.4.2.1, at the end of paragraph: Add "A rejected lot may not be used in assembly of shirts to be presented to the Government. A rejected lot must be disposed of or set aside with clear markings to avoid accidental use. A rejected lot may be replaced with a lot which has been fused correctly and each part must be properly shade matched to the shirt to which it will be joined. A shaded part defect will be scored on all improperly shade matched shirts."

PAGE 27

* Add new paragraph:

"4.4.5 Palletization examination. An examination shall be made to determine that the palletization complies with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one palletized unit load fully packaged. The lot size shall be the number of palletized unit loads in the inspection lot. The inspection level shall be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:31Z
Check the source to verify that this is the current version before use.

Examine	Defects
Finished dimensions	Length, width, or height exceeds specified maximum requirement.
Palletization	Pallet pattern not as specified. Interlocking of loads not as specified. Load not bonded with required straps as specified.
Weight	Exceeds maximum load limits.
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application."

PAGE 29

* 4.5.1.6, line 4, after "delamination": Add "and curling".

* 5.1.2: Delete "MIL-STD-1188" and substitute "ASTM D 3951".

PAGE 30

* 5.2.1 and 5.2.2: Delete sentence six entirely.

* 5.2.3, line 2: Delete "MIL-STD-1118" and substitute "ASTM D 3951".

PAGES 30 and 31

5.3, 5.3.1, and 5.3.2: Delete and substitute:

* "5.3 Palletization. When specified (see 6.2), shirts, packed as specified in 5.2, shall be palletized on a 4-way entry pallet in accordance with load type Ia of MIL-STD-147. Pallet type shall be type I (4-way entry), type IV, or type V in accordance with MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with the bonding means K or L or film bonding means O or P. Pallet pattern shall be number 3 in accordance with the appendix of MIL-STD-147. Interlocking of leads shall be effected by reversing the pattern of each course.

* 5.4 Marking. In addition to any special marking required by the contract or purchase order, unit packs, shipping containers, and palletized unit loads shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

5.4.1 Polyethylene bagged unit packs. Polyethylene bagged unit packs shall have the required identification information legibly printed or stamped in black directly on the bag across the center face or on a white paper label inserted within the bag so as to permit ready identification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:31Z
Check the source to verify that this is the current version before use.

PATES 30 and 31 (cont'd)

* 5.4.2 Labels, mixed sizes. Each shipping container, packed with mixed sizes only, shall have securely attached to the end and side, directly under the printing or stenciling, a white paper label 5 by 4 inches with the words "MIXED NSN's" plainly stamped or printed thereon and under these words shall be legibly stamped or printed the correct quantity and NSN's contained therein."

* 6.2: Add "(f) When palletization is required (see 5.3)."

PAGE 33

* Add: "6.10 Ultrasonic welding conditions. The following ultrasonic welding conditions have been found to provide welds meeting the requirements of this document. These limits are furnished for guidance only. For optimum results with a particluar ultrasonic machine used, specific machine settings should be obtained from the manufacturer of the ultrasonic equipment.

	Minimum	Maximum
Pressure, psi	35	40
Weld time, seconds	0.2	0.3
Down speed, inches/minute	10.0	12
Trigger pressure, pounds	8.0	10.0
Hold time, seconds	0.0	0.05

Changes from previous issue. The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:

Army - GL

Review activities:

Army - MD
DLA - CT

Preparing activity:

Army - GL

Project No. 8405-A996

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:31Z
Check the source to verify that this is the current version before use.