REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

The public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Department of Defense, Washington Headquarters Services, Directorate for information on Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.
PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.

1. REPORT DATE *(DD-MM-YYYY)*	2. REPORT TYPE	3. DATES COVERED *(From - To)*
11-05-2017	Final	

4. TITLE AND SUBTITLE
Test Operations Procedure (TOP)
03-2-812 Change Notice 1 Field of Vision - Vehicles

5a. CONTRACT NUMBER

5b. GRANT NUMBER

5c. PROGRAM ELEMENT NUMBER

6. AUTHORS

5d. PROJECT NUMBER

5e. TASK NUMBER

5f. WORK UNIT NUMBER

7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)
US Army Aberdeen Test Center (TEDT-AT-WFS)
400 Colleran Road
Aberdeen Proving Ground, MD 21005-5059

8. PERFORMING ORGANIZATION REPORT NUMBER
TOP 03-2-812 CN1

9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)
Policy and Standardization Division (CSTE-TM)
U.S. Army Test and Evaluation Command
2202 Aberdeen Boulevard
Aberdeen Proving Ground, MD 21005-5001

10. SPONSOR/MONITOR'S ACRONYM(S)

11. SPONSOR/MONITOR'S REPORT NUMBER(S)
Same as item 8

12. DISTRIBUTION/AVAILABILITY STATEMENT
Approved for public release; distribution unlimited.

13. SUPPLEMENTARY NOTES
Defense Technical Information Center (DTIC), AD No.: AD1033981

This TOP supersedes TOP 03-2-812 Field of Vision – Vehicles, dated 16 December 2009

14. ABSTRACT
The Field of Vision Test Operating Procedure provides the methodology by which testers quantitatively determine the fields of vision both above and below the horizon on each angle of azimuth around the vehicle for each operator.

15. SUBJECT TERMS
Turning Circle, Stadia Rod, Ground intercept point, Lateral angle.

16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON
a. REPORT	B. ABSTRACT	C. THIS PAGE			19b. TELEPHONE NUMBER *(include area code)*
Unclassified	Unclassified	Unclassified	SAR	20	

Standard Form 298 (Rev. 8-98)
Prescribed by ANSI Std. Z39-18

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T14:49Z
Check the source to verify that this is the current version before use.

(This page is intentionally blank.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T14:49Z
Check the source to verify that this is the current version before use.

TEST OPERATIONS PROCEDURE

Change Notice 1 11 May 2017
TOP 03-2-812

FIELD OF VISION - VEHICLES

TOP 03-2-812, 16 December 2009, is changed as follows:

1. The following elements of TOP 03-2-812, 16 December 2009, are changed (equations, page 4):

$$\Theta = \arctan((E_h / S_r) / S_d)$$

where S_r is the stadia rod reading and S_d is the Stadia rod distance from the center of the origin. Once the visual angle of declination is calculated the ground intercept and ground distance values can be calculated. The ground intercept value can be defined as:

$$G_i = E_h / \sin \Theta$$

Changed to:

$$\Theta = \arctan((E_h - S_r) / S_d)$$

where S_r is the stadia rod reading and S_d is the stadia rod horizontal distance from the center of the origin. Once the visual angle of declination is calculated the ground distance value can be calculated. The ground distance value can be defined as:

$$G_d = E_h / \tan \Theta$$

2. The proponent of this change is the Policy and Standardization Division (CSTE-TM), U.S. Army Test and Evaluation Command, 2202 Aberdeen Boulevard, Aberdeen Proving Ground, Maryland 21005-5001.

3. After posting the new change, file subject change notice in front of every electronic or printed paper copy of subject TOP in your possession, for reference purposes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T14:49Z
Check the source to verify that this is the current version before use.

(This page is intentionally blank.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T14:49Z
Check the source to verify that this is the current version before use.

U.S. ARMY TEST AND EVALUATION COMMAND
TEST OPERATIONS PROCEDURE

*Test Operations Procedure 03-2-812 Change Notice 1 11 May 2017
DTIC AD No. AD1033981

FIELD OF VISION - VEHICLES

			Page
Paragraph	1.	SCOPE	2
	1.1	Purpose	2
	1.2	Background	2
	1.3	Limitations	2
	2.	FACILITIES AND INSTRUMENTATION	2
	3.	REQUIRED TEST CONDITIONS	3
	3.1	General	3
	3.2	Pre-Test	3
	4.	TEST PROCEDURES	3
	4.1	Minimum Ground Intercept Visibility	3
	4.2	Forward Looking Visibility	4
	4.3	Total Lateral Visibility	5
	5.	DATA REQUIRED	5
	6.	PRESENTATION OF DATA	5
APPENDIX	A.	GLOSSARY	A-1
	B.	ABBREVIATIONS	B-1
	C.	REFERENCES	C-1
	D.	APPROVAL AUTHORITY	D-1

*This TOP supersedes TOP 03-2-812 Field of Vision – Vehicles, dated 16 December 2009

Approved for public release; distribution unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T14:49Z
Check the source to verify that this is the current version before use.

1. SCOPE.

1.1 Purpose.

This Test Operations Procedure summarizes the field of vision (FOV) for the all crew positions of combat vehicles.

1.2 Background.

Analysis of the field of view for each crew member is particularly important for combat vehicles where effectiveness of equipment may depend largely upon the operator's ability to see his surroundings. The Commander's ability to detect targets and direct the crew's effort to engage is very important. Close-in vision should permit observation of the vehicle itself when looking downward and the sky when looking upward. Because of heavy protective shielding, combat vehicles have areas of restricted visibility which need to be quantified. Also, some combat vehicles require indirect or protected observation through various devices that accommodate the observers in their constricted positions. The FOV through these devices also needs to be quantified.

1.3 Limitations.

These procedures can be utilized for attaining FOV measurements of all crew positions of a combat vehicle with the understanding that the measurements will be limited by natural head and eye rotation limits.

2. FACILITIES AND INSTRUMENTATION.

a. A turning circle.

b. Two stadia rods or some instrument that provides measurement references from the ground to above the horizontal line of sight of the user.

c. Tape measure.

d. Small cones or similar distinguishable markers.

Note: It is recommended that human observer be replaced with an imaging system that can provide point measurements, azimuth readings, and elevation readings.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T14:49Z
Check the source to verify that this is the current version before use.

3. REQUIRED TEST CONDITIONS.

3.1 General.

a. Location. Testing must be performed on a level area such as a large concrete turning circle. The radius of the turning circle should be larger than the length of the vehicle under test. This is done to ensure all crew positions can be centered on the turning circle without the ends of the vehicle impeding the edge of the turning circle. Mark the circle with radial lines from the center point of the circle outward at 10 degree intervals.

b. Orientation. Position the vehicle such that the longitudinal axis of the vehicle is aligned with the 0 degree point of the turning circle. The portion of the vehicle which houses the designated crew position under test should be centered on the center point of the turning circle.

c. Measurements. Measurements should be taken in 10 degree intervals. Measurements taken which are at intervals less than the designated 10 degree intervals shall be interpolated.

3.2 Pre-test.

a. Position the vehicle on the turning circle such that the crew position under test is centered above the center point of the turning circle.

b. Use a tape measure to measure the eye height of the seated observer to the ground for a 95th percentile male and a 5th percentile female. The dimensions of the vehicle should also be taken.

4. TEST PROCEDURES.

4.1 Minimum Ground Intercept Visibility.

Determine the minimum distance at which the operator can visually identify the ground closest to the vehicle. It is recommended that the FOV for each window configuration be plotted separately.

a. Define the closest visible ground intercept points, lateral angle, and distance from origin for each point measured. When the ground is not visible, record the lowest stadia rod reading that can be seen. Obstructions should be outlined by taking readings at all corners of the obstruction.

b. Measurements should be taken in 10 degree intervals. Measurements taken which are at intervals less than the designated 10 degree intervals shall be interpolated.

c. Calculate the visual angle of declination and the ground intercept distance from the eye height point. The visual angle of declination can be easily calculated by looking at the FOV projection as a right triangle. The vertical distance between the ground and the observer's eye is the height of the triangle. This distance represents the eye height or *Eh*. The horizontal distance

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T14:49Z
Check the source to verify that this is the current version before use.

from the center of origin out to the point where the ground intercept makes contact with the ground represents the ground distance or *Gd*. The ground intercept is the segment that connects the two lines. When the values of both distances are known the visual angle of declination or Θ can be solved using the Arctangent of the eye height over the ground distance.

$$\Theta = \arctan(E_h / G_d)$$

If the ground is not visible due to performing this method in restricted areas such as enclosed buildings and a stadia rod reading must be taken, the process will be slightly altered. The stadia rod reading must be subtracted from the eye height. This new calculation will serve as the height of the triangle. The horizontal distance from the center of origin to the stadia rod will serve as the base of the triangle. Although the triangle is different in size the angle remains the same. This yields:

$$\Theta = \arctan((E_h - S_r) / S_d)$$

where S_r is the stadia rod reading and S_d is the stadia rod horizontal distance from the center of the origin. Once the visual angle of declination is calculated the ground distance value can be calculated. The ground distance value can be defined as:

$$G_d = E_h / \tan \Theta$$

d. Plot the polar coordinates using the ground intercept as the radius and the lateral angle as the angular coordinate.

4.2 Forward Looking Visibility.

Determine the maximum left/right lateral angles and the corner edges of each window and obstruction that can be seen by the observer while retaining visual acuity on the zero degree mark.

a. The observer is limited to 0 degrees of head elevation and a maximum lateral head rotation not to exceed 60 degrees with additional lateral eye rotation not to exceed 35 degrees.

b. Record the maximum ground intercept edge point from the stadia rod reading. This edge point represents the maximum ground intercept within the turning circle that can be seen by the observer from the referenced eye height position.

c. Using one stadia rod as a reference marker at 0 degrees use the other stadia rod to record the closest visible ground intercepts, lateral angles, and distance from origin for each point measured. Record the measurements for the corner edges of all windows and obstructions within the predetermined Forward Looking FOV.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T14:49Z
Check the source to verify that this is the current version before use.

d. Calculate the ground intercept of each point and plot the polar graph.

4.3 Total Lateral Visibility.

Determine the maximum lateral angles that can be seen by the observer with 0 degrees of head elevation and the maximum acceptable head and eye rotation based upon Figure 25 of Military Standard (MIL-STD)-1472G[1**]. This angle represents the total field of vision that can be seen by the observer.

a. The observer is limited to a maximum lateral head and eye rotation not to exceed 95 degrees to the left or right of the 0 degree reference.

b. Record the lowest and highest stadia rod reading that can be seen from the corners of each window. Record the lateral angles, and distances from origin. Readings should also be taken for the corners of all obstructions.

c. Calculate the ground intercept of each point and plot the polar graph.

5. DATA REQUIRED.

The following data shall be recorded:

a. Minimum distance that can be seen by the observer.

b. Lateral angles.

c. Visual angle of declination.

d. Ground distance.

e. Photographs. Photographs of the test vehicle, its window configuration, and any obstructions that are present should be taken.

6. PRESENTATION OF DATA.

Field of vision data shall be plotted on polar graphs with the FOV shown for all windows. Analysis of plotted data is based upon vehicle specifications and its effect on the visibility of the individual crew members. Because there are several calculations to be made, it is recommended that an Excel spreadsheet be created to do the calculation. Figure 1 is a template of an Excel sheet used to record data and Figure 2 is a polar plot graph by the excel sheet.

** Superscript numbers correspond to those in Appendix C, References.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T14:49Z
Check the source to verify that this is the current version before use.

FOV/FOF

	feet		feet
Eye Height:		Max radius:	120
Stadia distance:		Interval:	20
vehicle width:		Trailer	
vehicle length:		Trailer width:	
drivers position width:		Trailer length:	
drivers position length:		Trailer gap:	

input field

Window (placement)	stadia height (ft)	(in)	Cone (ft)	Angle (deg)		ground distance (ft)		X	Y

Figure 1. Excel Template.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T14:49Z
Check the source to verify that this is the current version before use.




Figure 2. Example of Polar Plot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T14:49Z
Check the source to verify that this is the current version before use.

(This page is intentionally blank.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T14:49Z
Check the source to verify that this is the current version before use.

APPENDIX A. GLOSSARY.

Term	Definition
Arctangent	Mathematical function that produces the visual angle of declination when provided an eye height and ground distance.
Eye Height	Distance from the crew member's eye to the ground or surface below the vehicle.
Ground Distance	The horizontal distance from the center of origin out to the point where the ground intercept makes contact with the ground.
Stadia Rod	A graduated wooden or aluminum rod, the use of which permits the determination of differences in elevation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T14:49Z
Check the source to verify that this is the current version before use.

(This page is intentionally blank.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T14:49Z
Check the source to verify that this is the current version before use.

APPENDIX B. ABBREVIATIONS.

Θ	visual angle of declination
arctan	Arctangent
Eh	eye height
FOV	field of vision
G*d*	ground distance
MIL-STD	Military Standard
SAE	Society of Automotive Engineers
S_d	stadia rod distance from the center of the origin
S_r	stadia rod reading
TOP	Test Operations Procedure

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T14:49Z
Check the source to verify that this is the current version before use.

(This page is intentionally blank.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T14:49Z
Check the source to verify that this is the current version before use.

APPENDIX C. REFERENCES.

1. MIL-STD-1472G, Department of Defense Design Criteria Standard, Human Engineering, 11 January 2012.

For information only (related publications).

a. Society of Automotive Engineers (SAE) Standard J1050, Describing and Measuring the Driver's Field of View, 13 February 2009.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T14:49Z
Check the source to verify that this is the current version before use.

(This page is intentionally blank.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T14:49Z
Check the source to verify that this is the current version before use.

APPENDIX D. APPROVAL AUTHORITY.

CSTE-TM 11 May 2017

MEMORANDUM FOR

Commanders, All Test Centers
Technical Directors, All Test Centers
Directors, U.S. Army Evaluation Center
Commander, U.S. Army Operational Test Command

SUBJECT: Test Operations Procedure (TOP) 03-2-812 (Change Notice 1) Field of Vision - Vehicles, Approved for Publication

1. TOP 03-2-812 (Change Notice 1) Field of Vision - Vehicles, has been updated to correct errors in the formulas used for field of vision calculations. The scope of the document is as follows:

This TOP describes the procedures by which testers quantitatively determine the fields of vision both above and below the horizon on each angle of azimuth around the vehicle for each operator. These procedures can be utilized for attaining field of vision measurements of all crew positions of a combat vehicle with the understanding that the measurements will be limited by natural head and eye rotation limits.

2. This document is approved for publication and will be posted to the Reference Library of the ATEC Vision Digital Library System (VDLS). The VDLS website can be accessed at https://vdls.atc.army.mil/.

3. Comments, suggestions, or questions on this document should be addressed to U.S. Army Test and Evaluation Command (CSTE-TM), 2202 Aberdeen Boulevard-Third Floor, Aberdeen Proving Ground, MD 21005-5001; or e-mailed to usarmy.apg.atec.mbx.atec-standards@mail.mil.

HUBNER.MICHAEL.WINFRIED.1042880147

MICHAEL W. HUBNER
Associate Director, Test Management Directorate (G9)

FOR

RAYMOND G. FONTAINE
Director, Test Management Directorate (G9)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T14:49Z
Check the source to verify that this is the current version before use.

(This page is intentionally blank.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T14:49Z
Check the source to verify that this is the current version before use.

Forward comments, recommended changes, or any pertinent data which may be of use in improving this publication to the following address: Policy and Standardization Division (CSTE-TM), U.S. Army Test and Evaluation Command, 2202 Aberdeen Boulevard, Aberdeen Proving Ground, Maryland 21005-5001. Technical information may be obtained from the preparing activity: US Army Aberdeen Test Center (TEDT-AT-WFS), 400 Colleran Road, Aberdeen Proving Ground, MD 21005-5059. Additional copies can be requested through the following website: http://www.atec.army.mil/publications/topsindex.aspx, or through the Defense Technical Information Center, 8725 John J. Kingman Rd., STE 0944, Fort Belvoir, VA 22060-6218. This document is identified by the accession number (AD No.) printed on the first page.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T14:49Z
Check the source to verify that this is the current version before use.