MIL-S-9320C
AMENDMENT 2
26 May 1976
SUPERSEDING
AMENDMENT 1
31 January 1972

MILITARY SPECIFICATION

SIGNAL, WARNING, AUDIBLE, FOR HEADSET, TYPE MA-1

This amendment forms a part of Military Specification MIL-S-9320C, dated 29 April 1971, and is approved for use by all Departments and Agencies of the Department of Defense.

Page 5

3.6.2.3: After second sentence add:

"When not energized and the +28 VDC is applied to Pin B and Pin C is grounded the continuous current flow is to be less than 1.0 milliampere."

After 3.6.2.3, add new paragraph:

"3.6.2.4 Power output requirement. When operating on 28 volt DC, the warning signal shall be capable of delivering 25 milliamperes average direct current minimum into 150 ohms load."

Page 9

4.6.5: Add: "The current between Pin B and Pin C, with the unit unenergized, shall be measured with +28 VDC applied to Pin B, and an ammeter connected between Pin C and ground. This current shall be less than 1.0 milliampere."

Custodians:
Army - AV
Air Force - 82

Review Activities:
Army - AV
Air Force - 11

Preparing Activity:
Air Force - 82

Project No. 6340-0062

FSC 6340

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T12:07Z
Check the source to verify that this is the current version before use.