MIL-R-9221 (USAF)
AMENDMENT 2
19 March 1959
Superseding
AMENDMENT 1
10 July 1956

MILITARY SPECIFICATION

RELAY, FIELD CONTROL, GENERATOR, 24 VOLT DC, TYPE M-2

This amendment forms a part of Military Specification MIL-R-9221 (USAF) dated 3 September 1953.

Page 3, paragraph 3.2.4: Delete and substitute:

"3.2.4 INTERNAL CONNECTIONS.- The various coils and contacts shall be connected to a connector as shown on figure 2. The ground connection shown on figure 2 shall be a secure, low-resistance connection to the relay case. An area of 3/4-inch diameter around the mounting holes shall have all nonconductive material removed from both sides of the mounting holes in order to insure a positive ground connection between the relay case and the aircraft structure."

Page 11, paragraph 4.3.3.3.7, second sentence: Delete and substitute: "The potential drop of each of the contacts listed below shall be measured. The potential drop before testing shall not exceed the applicable value specified below and the potential drop after testing shall not exceed the specified value by more than 10 percent."

Page 11, paragraph 4.3.3.3.8: Delete and substitute:

"4.3.3.3.8 The cycling test specified in 4.3.3.3.7 shall be repeated at a pressure corresponding to an altitude of approximately 50,000 feet."

Page 12, paragraph 4.4.2.2.7, third sentence: Delete and substitute: "The potential drop before and after testing shall conform to the values specified in 4.3.3.3.7."

FSC 5945

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T12:04Z
Check the source to verify that this is the current version before use.