MIL-C-20354B (MU)
16 September 1966
SUPERSEDING
MIL-C-20354A (MU)
30 April 1965

MILITARY SPECIFICATION

CARTRIDGE, 105MM, ILLUMINATING,
M314A2E1, ASSEMBLING AND PACKING

1. SCOPE

1.1 This specification covers the assembling and packing for one type of cartridge designated as Cartridge, 105MM, Illuminating, M314A2E1 for use in 105MM Howitzer.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-2550 - Ammunition and Special Weapons, General Specification for.
MIL-I-45607 - Inspection Equipment, Supply and Maintenance of
MIL-P-46565 - Primer, Percussion, M28A2 and M28B2, Loading, Assembling and Packing

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)
MIL-STD-109 - Quality Assurance Terms and Definitions
MIL-STD-1168 - Lot Numbering of Ammunition
MIL-STD-1235 - Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

FSC: 1315

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:41Z
Check the source to verify that this is the current version before use.

DRAWINGS

ARMY

7549072 - Box, Packing, Ammo., for 105MM How. Ammo. in Fiber Container M105A2
7549073 - Container, Ammo., Fiber, M105A2, for 105MM Howitzer Ammunition
9206744 - Projectile, 105MM: Illum., M314A2E1, Loading Assembly.
9206821 - Cartridge, 105MM: Illum., M314A2E1.

PUBLICATIONS

ARMY

ET-9206821 - Equipment Tabulation

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Material.-Materials shall be in accordance with applicable drawings and specifications.

3.2 Cartridges.-The cartridges shall comply with all requirements specified on drawing (dwg.) 9206821, and with all requirements specified in applicable specifications.

3.3 Proving ground.-The cartridge shall comply with the following requirements when tested as specified in 4.3.1.

3.3.1 Functioning.-The cartridge shall function satisfactorily (see 6.4) and shall provide effective illumination (see 6.5) for 45 seconds.

3.3.2 Premature bursts.-There shall be no premature burst in the bore of the weapon or in the first 100 yards of flight.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:41Z
Check the source to verify that this is the current version before use.

3.3.3 Safety.-There shall be no premature burst or indication of metal parts separation in the gun or in flight when fired with propellant adjusted to give 112 percent of the rated maximum pressure of the cartridge in a new tube.

3.4 Workmanship.-All manufacturing, processing and assembly operations of the cartridge shall be correctly performed in a thorough, workmanlike manner. Parts shall be free of burrs, chips, dirt, cracks, grease, rust and other foreign material. The cleaning method shall not be injurious to any or the parts nor shall the parts be contaminated by the cleaning agents.

4. QUALITY ASSURANCE PROVISIONS

4.1 General quality assurance provisions.-Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to MIL-STD-109 in order to define terms used herein. The provisions of MIL-A-2550 shall apply.

4.1.1 Submission of product.-At the time the completed lot of product is submitted to the Government for acceptance, the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies with all of the quality assurance provisions specified within this specification.
b. Number of units of product inspected.
c. Results obtained, by defect code, for all inspections performed.
d. Drawing, specification number and date, together with an identification and date of changes.
e. Certificates of conformance on all material purchased by the contractor when such material is controlled by Government or commercial specifications referenced in any of the contractual documents.
f. Number of items in the lot.
g. Date submitted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:41Z
Check the source to verify that this is the current version before use.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.1.2 Government verification.-Using the contractor's written quality assurance procedure, this detail specification, the applicable drawings and other contractual documents as a guide, the Government inspector shall verify at unscheduled intervals all quality assurance operations performed by the contractor. Verification will be performed to the extent necessary to assure compliance with the contractual requirements. Severity of Government inspection of individual characteristics will be directly related to the seriousness of the classification assigned. In no instance will a characteristic classified "critical" be accepted solely on the basis of the contractor's records.

4.2 Inspection provisions

4.2.1 Lot formation.-The term "lot" as used throughout this specification refers to an inspection lot, which is defined as an essentially homogeneous collection of units of product from which a representative sample is drawn and inspected to determine conformance of the lot with applicable requirements. The sample selected shall represent only that quantity of units from which the sample was drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the lot has been produced by one manufacturer, in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision. Changes to the process, specification, or drawing not affecting safety, performance, interchangeability, or storage, as determined by the Government, shall not be deemed to alter the homogeneity of the lot. Inspection lots shall comply with MIL-STD-105 and shall be numbered in accordance with MIL-STD-1168. Unless otherwise approved by the contracting officer, the inspection lot size of end items deliverable under the contract shall be not less than the smallest weekly estimate of quantities

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:41Z
Check the source to verify that this is the current version before use.

contractually scheduled for production during the contract period nor more than the largest monthly quantity contractually scheduled for delivery during the contract period. Inspection lots for components or subassemblies, other than the items of delivery, shall be homogeneous and of a size mutually convenient to both the contractor and the Government inspector. Each lot shall contain:

a. Cartridge cases of one lot interfix number from one manufacturer.

b. Loaded illuminant canister assemblies from one manufacturer in accordance with the same drawing, same drawing revision, same specification and same specification revision.

c. Propelling charges from not more than one lot.

d. Loaded primers of one lot interfix number from one manufacturer.

e. Fuzes of one lot interfix number from one manufacturer.

f. Expelling charges of one lot interfix number from one manufacturer.

4.2.2 Examination.-Inspection for Critical defects (and Major defects, when so specified) shall be 100 percent. Sampling plans and procedures for Major and Minor defects shall be in accordance with MIL-STD-105, except that continuous sampling plans in accordance with MIL-STD-1235 may be used if approved by the procuring activity. Also, at the option of the procuring activity, AQL's and sampling plans may be applied to individual characteristics listed using an AQL of 0.65 percent for each Minor defect and an AQL of 0.40 percent for each Major defect, except where 100 percent inspection is specified. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.2.4.

4.2.2.1 Illuminating Canister and Parachute Assembly, prior to crimping (see dwg. 9206746, covering a detail of dwg. 9206744).

Categories	Defects	Method of Inspection	Code No. (see 6.2)
Critical:	None defined.		

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:41Z
Check the source to verify that this is the current version before use.

Categories	Defects	Method of Inspection	Code No.
Major:	AQL 0.40 percent		
101.	Length of center wire.....	Gage	01001
Minor:	AQL 1.0 percent		
201.	Staking missing or improper assembly of swivel pin nut.....	Visual	01002
202.	Wire not frayed or improperly soldered.....	Visual	01003

4.2.2.2 Illuminating Canister and Parachute Assembly (see dwg. 9206746, covering a detail of dwg. 9206744).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 1.0 percent		
101.	Any component or operation missing or improper.....	Visual	02001
102.	Swivel fails to rotate freely..	Visual	02002
103.	Crimp missing or not 360 degrees.....	Visual	02003
104.	Parachute torn.....	Visual	02004
105.	Evidence of poor workmanship (see 3.4).....	Visual	02005
Minor:	None defined.		

4.2.2.3 Projectile loading assembly, prior to assembling illuminating canister and parachute assembly (see dwg. 9206744).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.40 percent		
101.	Any component or operation missing or improper.....	Visual	03001
102.	Parachute improperly folded....	Visual	03002
Minor:	None defined.		

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:41Z
Check the source to verify that this is the current version before use.

4.2.2.4 Projectile loading assembly, prior to securing base plug and closing plug (see dwg. 9206744).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.40 percent		
101.	Any component or operation missing or improper	Visual	04001
102.	Parachute wrapper torn	Visual	04002
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.4)	Visual	04003

4.2.2.5 Projectile loading assembly (see dwg. 9206744).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 1.0 percent		
101.	Position of shear pin	Gage	05001
102.	Position of twist pin	Gage	05002
103.	Diameter of bourrelet and rear of rotating band, maximum (if retouched)	Gage	05003
104.	Gap between base plug and base, maximum	Gage	05004
105.	Total length	Gage	05005
Minor:	AQL 1.5 percent		
201.	Color of band incorrect	Visual	05006
202.	Protective coating with bare spot in excess of 1/4 square inch	Visual	05007
203.	Marking missing, misleading or unidentifiable	Visual	05008
204.	Evidence of poor workmanship (see 3.4)	Visual	05009

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:41Z
Check the source to verify that this is the current version before use.

4.2.2.6 Primer, prior to assembly to Cartridge Case (see dwg. 8838130, covering a detail of dwg. 9206821).

Categories	Defects	Method of Inspection	Code No.
Critical:			
1.	One or more flash holes missing	Visual	06001
Major:	None defined.		
Minor:	None defined.		

4.2.2.7 Cartridge Case, prior to assembling to projectile assembly (see dwg. 9206821).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.65 percent		
101.	Propelling charge bag missing or torn	Visual	07001
102.	Foil side of charge No. 5 not facing primer	Visual	07002
103.	Propelling charge assembled incorrectly	Visual	07003
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.4)	Visual	07004

4.2.2.8 Cartridge assembly (see dwg. 9206821).

Categories	Defects	Method of Inspection	Code No.
Critical:			
1.	Primer above flush	Gage	08001

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:41Z
Check the source to verify that this is the current version before use.

Major:		AQL 0.65 percent	
101.	Fuze fails to withstand the required disassembly torque....	Torque Test	08002
102.	Total length, maximum.....	Gage	08006
103.	Primer loose or missing.....	Visual-Manual	08003
104.	Fuze setting incorrect.....	Visual	08005
Minor:		AQL 2.5 percent	
201.	Projectile not free in cartridge case.....	Manual	08007
202.	Gap between fuze and projectile.	Visual	08016
203.	Fuze not staked.....	Visual	08009
204	Rotating band damaged.....	Visual	08010
205.	Marking missing, misleading or unidentifiable.....	Visual	08011
206.	Evidence of poor workmanship (see 3.4).....	Visual	08012

4.2.2.9 Unsealed fiber container (see dwg. 7549073).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:		AQL 0.40 percent	
101.	Packing component missing.....	Visual	09001
Minor:		AQL 1.5 percent	
201.	Cartridge cannot be removed by hand.....	Manual	09002
202.	Container cap cannot be removed by hand.....	Manual	09003
203.	Glue or asphalt on cartridge...	Visual	09004
204.	Packing components improperly assembled.....	Visual	09005

4.2.2.10 Sealed fiber container (see dwg. 7549073).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:41Z
Check the source to verify that this is the current version before use.

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.65 percent		
101.	Container cut or damaged through all asphalt impregnated layers.	Visual	10001
102.	Metal end loose or distorted...	Visual	10002
103.	Tape incomplete or badly wrinkled.....	Visual	10003
Minor:	AQL 2.5 percent		
201.	Tear tab length, minimum.....	Gage	10004
202.	Contents loose.....	Manual	10005
203.	Gap between cover and body container exceeding 1/8 inch...	Manual	10006
204.	Cuts, scuffs, or gouges in outer layers.....	Visual	10007
205.	Marking missing, misleading or unidentifiable.....	Visual	10008

4.2.2.11 Sealed wood packing box (see dwg. 7549072).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.65 percent		
101.	Box damaged exposing contents..	Visual	11001
102.	Hardware or strapping missing, broken or loose.....	Visual	11002
103.	Board broken.....	Visual	11003
Minor:	AQL 1.5 percent		
201.	Strapping or hardware improperly assembled.....	Visual-Manual	11004
202.	Handle missing or insecure.....	Visual-Manual	11005
203.	Car seal missing, unsealed or improperly positioned.....	Visual	11006
204.	Marking missing, misleading or unidentifiable.....	Visual	11007

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:41Z
Check the source to verify that this is the current version before use.

4.2.3 Testing

4.2.3.1 Check test for possible deterioration of Primer, Percussion, M28 (see MIL-P-46565 (MU)), Code No. 06002.-If the total elapsed time between original acceptance of the M28 primer lot and the assembly of that lot into the complete round cartridges exceeds two years, or if the M28 primers have been subjected to adverse conditions, however brief, at any time since previous tests, the applicable lot shall be subjected to and must satisfactorily pass the check test for deterioration specified in MIL-P-46565 (MU) immediately before the M28 primer lot is assembled into the cartridges. The test shall be performed by the contractor on assemblies selected by the Government inspector at the facility assembling the complete cartridges (see 6.6).

4.2.3.2 Proving ground.-The following test shall be performed as specified in 4.3.1.

4.2.3.2.1 Functioning (see 3.3.1), Major defect, Code No. 08013.

4.2.3.2.1.1 Beginning with the first lot produced and continuing until three consecutive lots have complied with the applicable requirements specified, 80 cartridges shall be selected for this test. If eleven or more fail to comply with the applicable requirements the lot shall be rejected.

4.2.3.2.1.2 After the three consecutive lots have met the criteria of 4.2.3.2.1.1, 32 cartridges shall be selected for this test. If six or more fail to comply with the applicable requirements the lot shall be rejected.

4.2.3.2.2 Premature bursts (see 3.3.2), Critical defect, Code No. 08014.-If any of the sample cartridges used in any of the tests fail to comply with the requirements for premature bursts the lot shall be rejected.

4.2.3.2.3 Safety (see 3.3.3), Critical defect, Code No. 08015.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:41Z
Check the source to verify that this is the current version before use.

4.2.3.2.3.1 Beginning with the first lot produced and continuing until three consecutive lots have complied with the applicable requirements specified, 15 cartridges shall be selected for this test. If any cartridge fails to comply with the applicable requirements the lot shall be rejected.

4.2.3.2.3.2 After three consecutive lots have met the criteria of 4.2.3.2.3.1, 5 cartridges shall be selected from each lot for this test. If any cartridge fails to comply with the applicable requirements the lot shall be rejected.

4.2.3.2.4 Refiring.-If for any reason the proof director considers that the test conditions have detrimentally affected the test results, he shall declare the results invalid and perform a new test on additional rounds as required.

4.2.4 Inspection Equipment.-Equipment Tabulation Number ET-9206821 identifies the inspection equipment required to perform the examinations and tests prescribed in this section. The contractor shall design inspection equipment in accordance with the instructions in 6.3.

4.2.4.1 Government rights to documentation.-Inspection equipment drawings and lists provided and revised in accordance with the requirements of the ET may be used by DOD activities for design, procurement, manufacture, testing, evaluation, production and receiving inspection, overhaul, shipping, storage, identification of stock, ordering and storage of replacement parts, inspection of items at overhaul, general maintenance of equipment, construction, survey and whenever inspection equipment drawings are needed.

4.2.4.2 Supply and maintenance.-Supply and maintenance of the equipment listed in the ET shall be in accordance with Specification MIL-I-45607.

4.2.4.3 Government use of contractor's inspection equipment.-The contractor shall make available to the Government all inspection equipment necessary for determining conformance with contract requirements. Personnel for operating the equipment and verification of its accuracy, shall be supplied by the contractor for the performance of examination or test by the Government.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:41Z
Check the source to verify that this is the current version before use.

4.3 Test methods and procedures.

4.3.1 Proving ground.-These tests shall be conducted at a Government proving ground in accordance with the applicable Acceptance Test Procedure. The sample cartridges shall be fired with M67 propelling charges in a gun for which the ammunition is standard and observation made for conformance to all requirements (see 6.7).

4.3.1.1 Functioning.-The sample cartridges shall be fired at zone 7.

4.3.1.2 Safety.-The sample cartridges shall be fired with propelling charges adjusted to give 112 percent of the rated maximum pressure for the cartridge. In addition, for the first three production lots from each manufacturer (loading facility), a smear camera shall be used to observe the projectile in flight in order to record any possible malfunctioning.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging

5.1.1 Level A.-The cartridges shall be packaged in accordance with dwg. 7549073.

5.2 Packing

5.2.1 Level A.-The containers shall be packed in accordance with dwg. 7549073.

5.3 Marking.-Marking shall be in accordance with dwg. 7549072 and 7549073, as applicable.

6. NOTES

6.1 Ordering data.-Procurement documents shall specify the following:

a. Title, number and date of this specification.

b. Data cards.-Data cards shall be prepared for each lot in accordance with the information specified in Standard MIL-STD-1167.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:41Z
Check the source to verify that this is the current version before use.

6.2 Inspection code numbers.-The five digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government.

6.3 Inspection equipment.-The contractor shall design inspection equipment as required by the referenced inspection Equipment Lists (EL) in accordance with the instructions of paragraphs 6.3.1 through 6.3.7.

6.3.1 Inspection equipment lists.-Inspection equipment lists indicate the availability of inspection equipment designs by showing in the "number" column of the list of inspection equipment (SMUPA Form 1010) the numbers of drawings of existing equipment designs or codes as indicated in paragraph 6.3.2. Design action required of the contractor with respect to the different types of drawings that may be listed is described in paragraphs 6.3.3 and 6.3.4. Action required by the contractor with respect to commercial inspection equipment is described in 6.3.5. The contractor will be required to prepare detailed drawings in accordance with 6.3.6 for all the equipment coded as "Contractor Design" in the number column. These contractor designs must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.7.

6.3.2 Inspection equipment list codes.-The inspection equipment as defined in 6.3.3, 6.3.4, 6.3.5 and 6.3.6 will be designated in the EL by the following codes:

CDAF - Contractor's design responsibility on Army format in accordance with MIL-D-45608.
CDCF - Contractor's design responsibility on contractor format.
AD - Army design.
ADMU - Army design, mandatory for use.
CE - Commercial equipment.
SCD - Specification control drawing.

6.3.3 Army designs.-Army designs are reflected on detailed drawings which completely depict all the information necessary for the fabrication of the item of inspection equipment. The contractor need provide no design when an Army design is listed for an item

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:41Z
Check the source to verify that this is the current version before use.

of inspection equipment. Army designs fall into two basic classifications, mandatory and non-mandatory. When an inspection equipment list references mandatory Army designs, the contractor shall comply with, and use these designs accordingly. The contractor may, however, in connection with non-mandatory designs and with the approval of the Government, design alternate inspection equipment or use comparable commercial equipment to facilitate his operations. Such contractor-prepared designs (see 6.3.6) or commercial equipment selections (see 6.3.5) must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.7.

6.3.4 Specification control drawing.-Specification control drawings depict the minimum equipment requirements in outline, descriptive, diagrammatic or pictorial form only and specify the required performance or other characteristics. Contractors must prepare detailed drawings (see 6.3.6) of their designs in support of specification control drawings. These contractor-prepared designs must be approved by the Government prior to the fabrication or procuring of the equipment. Commercial equipment meeting the requirements of specification control drawings must be described in sufficient detail to permit identification and evaluation by the Government (see 6.3.5). Designs shall be submitted for approval as specified in 6.3.7.

6.3.5 Commercial equipment.-Commercial equipment is inspection equipment that has universal application for a specific function. It is comprised of items commonly used by industry and Government. Contractors normally are not required to furnish drawings of commercial inspection equipment, but a list of such equipment must be approved by the Government. When commercial inspection equipment requires the use of special fixturing, the design of this fixturing shall be considered as part of the total design, and 6.3.6 shall apply. In the latter case, only those portions of the commercial equipment need be detailed in the designs as are necessary to completely fabricate, calibrate, and operate the total item of inspection equipment. Lists and fixturing designs shall be submitted for approval as specified in 6.3.7.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:41Z
Check the source to verify that this is the current version before use.

6.3.6 Contractor designs.-Contractor designs are designs of inspection equipment for which the Government has assigned design responsibility to the contractor. Contractor designs shall be supported by detailed drawings which depict all information necessary to completely fabricate, calibrate and operate an item of inspection equipment. This requires that the necessary views, dimensions, materials, finish, notes, operating and calibration instructions be properly depicted in accordance with approved practices to the extent that further calculation or clarification will not be required. Contractor designs identified as CDCF may be developed on the format the contractor normally employs in his equipment design procedure provided such format reflects the detail and information specified above. Contractor designs identified as CDAF shall comply with the format and requirements of MIL-D-45608, and in addition, contain the detail and information specified above. Final approved contractor designs identified as CDCF shall be suitable for microfilming. They must be non-reproducible diazo or electrostatic prints of top quality full size with black lines on white background and shall provide a legible print produced via the 35mm microfilm process. Contractors shall submit one copy of the final design as a rolled set or flat set. Designs shall be submitted for approval as specified in 6.3.7.

6.3.7 Submission of contractor designs.-Unless otherwise specified on the EL, all designs of equipment for inspection of defects classified as critical and major shall be submitted for approval to the Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-ND. All other designs of inspection equipment shall be approved by the inspection element of the agency administering the contract; submission shall be as directed by the Contracting Officer. Partial submission of inspection equipment designs is permissible and encouraged. However, the Arsenal completion date for design review will be based on the date of the final submission of designs. Picatinny Arsenal design review will be accomplished normally within one month after receipt.

6.4 Functioning.-"Satisfactory functioning" shall be defined as functioning of the fuze, ejection of the parachute and illuminant assembly, and proper suspension and ignition of the illuminant.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:41Z
Check the source to verify that this is the current version before use.

6.5 Illumination.-"Effective illumination" is defined as burning of the canister with normal cnadle-power, with respect to a standard projectile, without exploding or breaking up while suspended by the parachute (the showering of sparks should not be considered a defect unless continued and excessive). Burning of the canister after striking the ground shall not be considered "effective illumination".

6.6 Cost of check test.-The contracting officer shall arrange for the contractor to be reimbursed for the expense incurred in the performance of the check tests. The test shall be conducted at Government expense without cost to the contractor who loaded the primers or to the contractor assembling the cartridges, and shall not constitute a basis for rejection against either contractor, except where deterioration has occurred as a direct result of carelessness in handling, storage, etc., permitted while the primer lot was under the jurisdiction of either contractor.

6.7 Submission of test data.-In addition to the normal distribution of records, when the cartridge is procured by the Department of the Army, one copy of all ballistic test data will be forwarded to the Commanding Officer, Picatinny Arsenal, Dover, New Jersey, ATTN: SMUPA-ND2.

Custodian:
Army-MU

Preparing activity:
Army-MU

Project No. 1315-A-493

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:41Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity.

SPECIFICATION

ORGANIZATION	CITY AND STATE

CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE

DD FORM 1 OCT 64 1426

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:41Z
Check the source to verify that this is the current version before use.