MILITARY SPECIFICATION

FUZE, BASE DETONATING, M91A2
METAL PARTS FOR

This Amendment forms a part of Military Specification MIL-F-20405C(PA) dated 9 July 1974.

Page 10

Paragraph 4.3.2.9 - Delete Major 106 and substitute the following:

"106 Position of charge cavity to datums A and B .....Gage 09006".

Add Major 109 as follows:

"109 Incorrect angle of charge cavity .....Gage 09020".

Page 11

Paragraph 4.3.2.10 - Add Minor 204 as follows:

"Minor 204 Reduced diameter both ends incorrect .....Gage 10007".

Page 14

Paragraph 4.3.2.13 - Major 106 - Delete "min" and substitute "max."

Delete Major 115 and substitute the following:

"Major 115 Position of head pitch diameter to datums A and C.....Gage 13015".

Delete Major 116 and substitute the following:

"Major 116 Position of head pitch diameter to datum D.....Gage 13016".

Delete Major 117 and substitute the following:

"Major 117 Position of detonator holder to datums A and E.....Gage 13017".

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:45Z
Check the source to verify that this is the current version before use.

AMENDMENT 1

Delete Major 120 and substitute the following:

"Major 120 Runout booster cup threads to datum A.....Gage 13020".

Add Major 126 as follows:

"Major 126 Position of retaining screw threads to slider shoulder cavity .....Gage 13042".

Add Major 127 as follows:

"Major 127 Slider cavity centerline angle incorrect.....Gage 13043".

Add Minor 217 as follows:

"Minor 217 Runout of booster cavity to datum diameter.....Gage 13044".

Custodian:

Army-AR

Preparing Activity:

Army-AR

Project Number; 1390-A209

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:45Z
Check the source to verify that this is the current version before use.