MIL-T-20371
28 November 1951

# MILITARY SPECIFICATION

## TUBES, BURSTER FOR SHELL, METAL PARTS

This specification was approved by the Departments of the Army, the Navy, and the Air Force for use of procurement services of the respective Departments, and supersedes the following specification:

Army AXS-1131
15 November 1943

This specification consists of this cover sheet and Specification AXS-1131, dated 15 November 1943, attached hereto, without modification.

When a request for this specification is received by a supplying activity it will be necessary to attach this cover sheet to the pertinent specification before issue.

(Copies of specifications required by contractors in connection with specific procurement functions should be obtained from the procuring agency or as directed by the contracting officer).

Custodian:
Army- O

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:42Z
Check the source to verify that this is the current version before use.

Ordnance Department
U. S. Army
Tentative Specification

AXS-1131
15 November 1943

# TUBES, BURSTER FOR SHELL, METAL PARTS

## A. APPLICABLE SPECIFICATIONS.

A-1. The Ordnance Department drawing pertaining to the burster tube and all specifications listed or referred to thereon, together with the following United States Army specification, form a part of this specification:

100-2—Standard Specifications for Marking Shipments.

A-2. The drawing and specifications shall be of the issue in effect on the date of invitation for bids.

## B. TYPE.

B-1. This specification covers metal parts for burster tubes for shell.

## C. MATERIAL AND WORKMANSHIP.

C-1. The materials and parts shall be in accordance with applicable specifications and the drawing.

C-2. All parts shall be free from chips, dirt, grease, and other foreign material. When cleaning is necessary, the method used shall not be injurious to any of the parts nor shall the parts be contaminated by the cleaning agents used.

## D. GENERAL REQUIREMENTS.

D-1. See section E.

## E. DETAIL REQUIREMENTS.

E-1. The burster tubeshall meet all requirements prescribed on the drawing and in applicable specifications.

E-2. Varnished parts. --No varnished part shall show any rust after being subjected to a salt -spray for a period of 12 hours.

## F. METHODS OF SAMPLING, INSPECTION, AND TESTS.

F-1. Inspection.—

F-1a. Inspection shall be as specified in United States Army General Specification for Ammunition Except Small Arms Ammunition, No. 50-0-1.

F-1b. Gaging of burster tube. --After the burster tubes have been coated, the contractor shall gage each tube with a chamber gage as specified on the drawing. If the tube fails to enter the gage freely, the tube shall be rejected subject to correction and retest.



Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:42Z
Check the source to verify that this is the current version before use.

F - 2. Size of lots. -- One hundred thousand maximum. A smaller quantity may constitute a lot at the discretion of the inspector. Two thousand plus or minus 500 shall constitute the first lot manufactured on any contract, except when a new contract immediately follows the manufacture of satisfactory material of the same character.

F - 3. Test of varnished parts. ---Thirty of each varnished part selected by the inspector form each lot shall be subject to the following test:

Parts protected by varnish shall be thoroughly washed in a neutral soap solution and dried prior to testing. Subject the parts to a salt-spray for 12 continuous hours, at a room temperature of $95^{\circ} \pm 3^{\circ}$ F., using a 20 percent (by weight) C. P. sodium chloride solution. Conduct the test in a closed tank of material nonreactive to the salt-spray, such as Alberene stone. The spray shall be finely divided. The tank shall be so designed that there will be no direct impinging of spray upon the test specimen. The spray shall circulate freely about all the specimens to the same degree and no liquid which has come in contact with the test specimen shall return to the aspirator to be resprayed.

G. PACKAGING, PACKING, AND MARKING.

G-1. Packing.—

G-1a. Unless otherwise specified, the burster tubes shall be delivered in standard commercial containers so constructed as to insure acceptance by common and other carriers for safe transportation, at the lowest rate, to the point of delivery. The packing container shall be sufficiently rigid to withstand transportation and permit storing in tiers at least 10 feet high without damage to the contaners or contents. The gross weight of any container shall not exceed 200 pounds.

G -1b. Data card.—Data cards, 5 x 8 inches, made of commerical manila tag board, approximately 200 pounds ream weight, shall be prepared for each lot of accepted burster tubes in accordance with the form specified below. Two of these cards completely filled out for each lot shall accompany each shipping ticket, and six cards completely filled out shall be furnished the inspector.

DATA CARD

Kind_____ Lot No._____
Quantity in Lot_____
Drg. No._____Rev._____ Spec. No._____Rev._____
Mfgd. by_____ Date_____
Contract No._____ Order No._____
Packed_____in a box.
Remarks_____
Certified to by_____, Inspector
(Print here name of inspector, District, Arsenal, or Loading Plant, and Sub-District where applicable.)

G-2. Marking.- The marking for shipment shall be in accordance with United States Army Standard Specifications for Marking Shipments, No. 100-2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:42Z
Check the source to verify that this is the current version before use.

NOTICE: This specification, together with specifications and drawings pertaining to it and bearing a "Notice" of similar restrictions, is intended for the use only in connection with procurement by the United States Government; and shall not be reproduced either wholly or in part except when authorized in connection with Government procurement, nor be used for any other purpose except when specifically authorized by the Chief of Ordnance.

Note.- Copies of this specification may be obtained from the Office, Chief of Ordnance, Army Service Forces, Washington, D. C.



Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:42Z
Check the source to verify that this is the current version before use.