INCH-POUND

MIL-W-16878/26A
AMENDMENT 1
8 June 1994

MILITARY SPECIFICATION SHEET

WIRE, ELECTRICAL, POLYTETRAFLUOROETHYLENE (PTFE) INSULATED,
260°C, 600 VOLTS, WRAPPED INSULATION

This amendment forms a part of MIL-W-16878/26A(NAVY), dated 11 September 1992 and is approved for use by the Department of the Navy and is available for use by all departments and agencies of the Department of Defense.

PAGE 2

TABLE I, column 1: Delete all references to "-" after /26.

PAGE 3

TABLE I, column 1: Delete all references to "-" after /26.

Impulse dielectric test; add the following: "or 4.6 kV using the 3.0 kHz spark test.

PAGE 4

Toxicity: Delete in its entirety.

Soldering: Delete and substitute "Shrinkage."

Add: "Wire length requirements: See appendix B."

Under PIN example: Delete the "-" after /26.

Delete "Preparing activity", and substitute the following:

CONCLUDING MATERIAL

Custodian:
Navy - SH

Review activities:
Navy - AS

Preparing activity:
DLA - ES

(Project 6145-N346-25)

AMSC N/A

FSC 6145

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T09:31Z
Check the source to verify that this is the current version before use.