INCH-POUND

MIL-V-87991 (84)

29 November 89

MILITARY SPECIFICATION

VAN, MULTI-PURPOSE MORTUARY SERVICE: COMMERCIAL

This specification is approved for use within WR-ALC, Code 84, Department of the Air Force, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE.

1.1 This specification covers a commercial multi-purpose funeral service vehicle utilizing a commercial van chassis with full window body. Vehicles procured under this specification are commercial items which shall be warranted by the manufacturer as specified in procurement documents.

1.2 Classification. *Multi-purpose mortuary vehicles shall be of the following:*

Type I - Full size standard van, two rear wheel driven
Type II - Mini-size van, two front or rear wheel driven

2. APPLICABLE DOCUMENTS.

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified, the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation of the extent specified herein (see 6.2).

SPECIFICATIONS

Federal

W-B-131	*Battery, Storage* (Vehicular, Ignition, Lighting and Starting)

Military

MIL-B-46176	Brake Fluid, Silicone, Automotive all Weather, Operational and Preservative
MIL-C-83286	Coating Urethane, Aliphatic Isocyanate, for Aerospace Applications

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: WR-ALC/MMVRS, Robins AFB, GA 31088 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A

FSC 2320

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:29Z
Check the source to verify that this is the current version before use.

STANDARDS

Federal

FED-STD-307	Trucks, Light Commercial, Gasoline/Diesel Fueled, Two Wheel Driven (4 X 2, 3,000 to 14,500 Pounds GVW)
FED-STD-595	Colors

Military

MIL-STD-130	Identification Marking of US Military Property
MIL-STD-889	Selection of Dissimilar Metals
MIL-STD-970	Standards and Specifications, Order of Precedence for the selection of
MIL-STD-1223	Non-Tactical Wheeled Vehicle Treatment Painting, Rustproofing, Identification Marking and Data Plate Standards

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Naval Publications and Forms Center, (ATTN: NPODS), 5801 Tabor Avenue, Philadelphia, PA 19120-5099).

2.1.2 Other Government documents, drawings and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

LAWS AND REGULATIONS

DEPARTMENT OF TRANSPORTATION (DOT)

49 CFR 393 Federal Motor Carrier Safety Regulations (FMCSR)
49 CFR 571 Federal Motor Vehicle Safety Standards (FMVSS)

(The Code of Federal Regulations (CFR) and the Federal Register (FR) are for sale on a subscription basis by the Superintendent of Documents, US Printing Office, Washington D.C. 20402. When indicated, reprints of certain regulations may be obtained from the federal agency responsible for the assurance thereof).

ENVIRONMENTAL PROTECTION AGENCY (EPA)

Control of air pollution from new motor vehicles and new motor vehicle engines (application for copies should reference the code of federal regulations, 40 CFR, and the federal register and should be addressed to the Superintendent of Documents, US Government Printing Office, Washington, D.C. 20402).

2.2 Non-Government publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

SOCIETY OF AUTOMOTIVE ENGINEERS (SAE)

J 551 - Limits and methods of measurement of radio interference characteristics of vehicles and devices (20 - 1000 MHZ) (DoD adopted).

J 552 - External Electromagnetic Radiation Suppressors (application for copies should be addressed to SAE, Inc., 400 Commonwealth Drive, Warrendale, PA 15096.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:29Z
Check the source to verify that this is the current version before use.

TIRE AND RIM ASSOCIATION

Yearbook

(Application for copies should be addressed to the Tire and Rim Association, Inc., 3200 W. Market Street, Akron, OH 44313).

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS.

3.1 Design. Except as specified in 3.8 through 3.9, the vehicles components, assemblies and accessories to be delivered under the contract shall meet or exceed the requirements of FED-STD-307 Type II, Class C for full size van and Class B for mini-van, except as specified herein. Technical data shall be limited to specifications and technical material identical to that furnished to the vehicle manufacturer's authorized representatives for selection of chassis models and other components and shall be on file in the engineering offices of the procuring activity prior to delivery of the items.

3.1.1 Selection of specifications and standards. Specifications and standards, necessary commodities, and services not specified herein shall be selected in accordance with MIL-STD-970.

3.1.2 Materials. Materials shall be as specified herein. Materials not specifically covered by this specification or referenced document shall be suitable in every respect for this type equipment. Except as otherwise specified, wood shall not be used. Recycled and recovered raw materials should be used to the maximum extent possible in lieu of virgin raw materials as long as these materials do not jeopardize the intended use and fully comply with all contract requirements. Materials used shall be free from defects which could affect the performance or maintainability of individual components of the overall assembly.

3.1.2.1 Protective treatment. Materials that are subject to deterioration shall be protected in such a manner that shall in no way prevent compliance with the performance requirements of this specification. Protective coatings that will chip, crack, or scale with age or extremes of climatic conditions shall not be used.

3.1.2.2 Dissimilar metals. Unless protected against electrolytic corrosion, dissimilar metals shall not be used in intimate contact with each other. Dissimilar metals are defined in MIL-STD-889.

3.1.3 Design and construction. The vehicle shall be constructed so that parts do not work loose in service and shall withstand the loads, shocks, vibrations and other conditions incident to operation, shipping and storage with minimum loss of time for maintenance, repair and servicing. The design of the vehicle shall ensure safe, efficient, and economical operation. All assemblies, controls, and installed equipment shall be located so that there is no adverse interference with each other, or with the operation and shall be readily accessible for maintenance, operation and replacement.

3.1.3.1 Fastening devices. All screws, bolts, nuts, pins and other fastening devices shall be properly designed, manufactured, and installed with adequate means of preventing loss of torque or adjustment. Cotter pins, lock washers or nylon patches shall not be used for this purpose except for attachment of trim items or as provided in commercial components. Tapped aluminum threads shall have a minimum thread engagement of at least two times the nominal fastener diameter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:29Z
Check the source to verify that this is the current version before use.

3.1.3.2 Servicing provisions. Drains, grease fittings, lines and check points for all components shall be so located that they are readily accessible and do not require special tools for proper servicing.

3.1.3.3 Lubrication. All parts are normally requiring periodic lubrication with grease shall be provided with lubrication fittings.

3.1.3.4 Component protection. All space which is occupied during operation, service and maintenance of the vehicle shall be free of hazardous protrusions, sharp edges or other features which may cause injury to personnel.

3.1.5 Weight distribution. The weight distribution of the vehicle in any loading condition shall not be unbalanced or improperly distributed.

3.1.6 Vehicle lean. The vehicle shall not lean to either side more than one percent of the maximum width in either fully loaded or unloaded condition.

3.1.7 Electromagnetic interference. The vehicle shall be suppressed to limit electromagnetic radiation in accordance with SAE J551. Suppressors where used, shall conform to SAE J 552. Any body equipment emitting electromagnetic radiation shall be suppressed to the same level as the vehicle chassis.

3.1.8 Federal motor vehicle safety standards. The vehicle and furnished accessories shall comply with all federal motor vehicle safety standards in effect on the date of manufacture.

3.1.9 Air pollution control. The vehicle shall comply with EPA regulations governing controls of emissions from new motor vehicles and new motor vehicle engines in effect on the date of manufacture when unleaded fuel is used (see 3.3.1.1). In addition, vehicles destined for use in the state of California regulations governing air pollution control in effect on the date of manufacture.

3.1.10 Curb weight. The vehicle fully equipped with a full compartment of fuel, lubricants and coolant shall have a curb weight of not less than that shown below. This weight shall include all standard equipment and accessories required by this specification.

Type I - 4300 Pounds
Type II - 2800 Pounds

3.1.11 Gross vehicle weight. The Gross Vehicle Weight (GVW) shall be the vehicle curb weight plus a driver, assistant and the number of passengers shown in 3.4.1 computed at 175 pounds each.

3.1.12 Decor. The interior decor shall be the manufacturer's standard or optional commercial decor and requires approval of the procuring agency. All materials and colors shall be coordinated and shall be entirely suitable for the intended purpose.

3.2 Performance. The vehicle shall be capable of transporting the rated payload (see 3.1.11) at a continuous speed of not less than 55 miles per hour (MPH) on level pavement. The vehicle shall also be capable of accelerating from a standing start to 55 MPH in not more than 20 seconds on level pavement while transporting the rated payload.

3.3 Chassis.

3.3.1 Powertrain. The powertrain shall be the chassis manufacturer's standard or optional powertrain, shall not be modified and shall be adequate in all respects to develop and transmit torque necessary for full performance as specified.

3.3.1.1 Engine. The vehicle shall be equipped with a liquid cooled, internal combustion, four-stroke cycle gasoline engine with not less than the number of cylinders listed below. The engine furnished shall provide the required vehicle performance when operated on unleaded fuel with a research octane rating of 91 at engine speed of not more than the chassis manufacturer's recommended operating speed. The

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:29Z
Check the source to verify that this is the current version before use.

engine shall be capable of continuous warranted operation on unleaded fuel. Unless otherwise specified or required by foreign laws, vehicle for overseas use shall be capable of accepting and operating on leaded gasoline. A full flow oil filter shall be provided.

Type I - 8 Cylinders
Type II - 6 Cylinders

3.3.1.1.1 Engine cooling system. A heavy duty cooling system shall be provided. The coolant shall be maintained at a temperature below the boiling point when the vehicle is operated in a fully loaded condition at an altitude of 10,000 feet above sea level or in ambient temperatures of not less than 125 degrees fahrenheit (°F) during normal driving conditions and for periods of engine idling with air conditioning running of at least one hour.

3.3.1.1.2 Engine starting system. The engine shall start within 15 seconds in any ambient temperature within the required operating range of the vehicle. The starting system shall be equipped with an interlock device to prevent starter engagement when the transmission is in any position other than neutral or park.

3.3.1.1.3 Exhaust system. The engine exhaust system shall conform to Federal Motor Carrier Safety Regulation 393.83(a). The exhaust system shall be of corrosion resistant, leakproof construction. Extension of the exhaust or tailpipe shall not result in a reduced cross sectional area. Installation shall be such that exhaust fumes will not enter the vehicle interior. The exhaust system shall be suspended using not less than 3 hangers.

3.3.1.2 Transmission. The chassis manufacturer's standard automatic transmission for the engine and chassis furnished shall be provided.

3.3.1.2.1 Transmission cooler. The manufacturer's optional or heavy duty transmission cooler shall be provided.

3.3.1.3 Axles. The load rating of each axle shall be not less than the imposed load on the axle, measured at the ground, with the vehicle at gross weight.

3.3.2 Steering system. The chassis manufacturer's standard power steering shall be provided.

3.3.3 Brakes.

3.3.3.1 Service brakes. The service brakes shall control and hold the vehicle, when loaded to it's specified GVW, on a 30 percent grade, under specified conditions of loading (see 3.1.10), the service brakes shall stop the vehicle from a speed of 20 MPH in not more than 30 feet from the point at which movement of the brake pedal begins. Deceleration and stopping distance shall be demonstrated on a dry, hard, approximately level road service that is free from loose material.

3.3.3.2 Parking brakes. The chassis manufacturer's standard parking brakes shall be provided.

3.3.3.3 Silicone brake fluid. When silicone brake fluid conforming to MIL-B-46176 is the chassis manufacturer's standard or optional brake fluid, it shall be provided in the hydraulic brake system. A tag stating "CAUTION: use silicone brake system only, MIL-B-46176" shall be placed near the master cylinder.

3.3.4 Frame. Chassis frame rails or other structural members shall not be spliced or otherwise extended to provide the specified wheelbase.

Source: https://assist.dla.mil -- Downloaded: 202610-23T12:29Z
Check the source to verify that this is the current version before use.

3.3.5 Suspension system. The chassis manufacturer's suspension system shall be provided as listed below and shall be equipped with hydraulic double-acting shock absorbers on front and rear axles. This suspension system shall have a rated capacity at least equal to the load imposed on each member measured at the ground with the vehicle loaded to the rated GVW as specified in 3.1.11.

Type I - Manufacturer's Standard Suspension
Type II - Manufacturer's Heavy Duty Suspension

3.3.6 Wheels and tires. Steel belted white-wall radial tires shall be provided. Tires shall be of the tubeless type with highway thread. Tires shall be of a rated capacity at least equal to the load imposed on each tire, measured at each wheel at the ground with the vehicle loaded to the specified GVW. Rim and tire ratings shall conform to the Tire and Rim Association recommendations for the type and size of the tire provided. Deluxe chrome wire wheel covers shall be provided.

3.3.6.1 Spare tire assembly. A spare wheel and tire assembly shall be provided, mounted and concealed within the vehicle body. The location of the spare tire assembly shall neither interfere with the function of the vehicle nor necessitate moving the casket when removal of the spare tire is required.

3.3.7 Fuel system.

3.3.7.1 Fuel tank. The chassis manufacturer's standard fuel tank mounted in the original location shall be provided. Vehicles destined for overseas use shall be provided with fill openings designed to accept leaded fuel.

3.3.7.2 Fuel filter. At least one fuel filter shall be provided and located in the fuel line between the fuel tank and engine.

3.3.8 Wheelbase. The wheelbase shall be within the range shown below. Chassis frame rails or other structural members shall not be spliced or otherwise modified to provide the specified wheelbase.

Type I - Not less than 125 inches or greater than 140 inches
Type II - Not less than 112 inches or greater than 120 inches

3.4 Body. The van body shall be essentially of sheet steel construction with provisions for doors and windows specified herein. Hardware and other exposed metal trim shall be chrome plated steel, stainless steel or anodized aluminum. Structural framing of the body shall support the exterior body surfaces without evidence of distortion under operating conditions. Sound deadening material shall be applied on sides, roof, door panel interiors and on framing to prevent drumming of panels and to inhibit rusting. Interior lining and trim material shall be treated to withstand exposure without spotting, shrinking or warping.

3.4.1 Seats. All seats, except for the rear most seat, shall be manufacturer's deluxe conversion package high-back fully adjustable bucket type seats. The individual seats shall also have folding armrests and swivel 360 degrees. The rear seat shall be the couch type. All seats shall be upholstered in deluxe cloth trim and be provided with seat belts and seat belt retractors. All seats except the driver and assistant seats shall have a clean unobstructed floor. Seating shall be provided for at least the number of passengers listed below. All seats, except for the 2 front seats, shall be quickly and easily removed.

Type I - 7 Passengers
Type II - 5 Passengers

3.4.2 Doors. Seals shall be provided around all doors to prevent entry of water and dust into the vehicle.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:29Z
Check the source to verify that this is the current version before use.

3.4.2.1 Driver's compartment doors. Doors shall be provided on each side of the vehicle and shall be provided with power windows and door locks.

3.4.2.2 Side door. A sliding side door with a window shall be provided on the curb side of the casket/passenger compartment. Door shall be equipped with a lock.

3.4.2.3 Rear doors. One or two rear doors with inner and outer panels shall be provided that will permit unhampered loading and unloading of the casket and cots. The rear door(s) shall be arranged to open and close from the inside and outside. Locks shall use the same key as the driver's door. Each door shall have a glass window permanently set in the door. Rear door openings shall have a minimum size as follows:

Type I - Height; chassis manufacturer's standard full window van width; chassis manufacturer's standard full window van but in no case less than 52"
Type II - Height; 39 inches
Width; 50 inches

3.4.3 Windshield, windows, wipers and washers.

3.4.3.1 Windshield. The vehicle shall be provided with the chassis manufacturer's standard tinted safety plate glass windshield.

3.4.3.2 Wipers. The vehicle shall be provided with the chassis manufacturer's standard windshield wipers with at least two operating speeds.

3.4.3.3 Washers. The vehicle shall be provided with the chassis manufacturer's standard van windshield washers.

3.4.3.4 Windows. The vehicle shall be provided with the chassis manufacturer's standard tinted safety plate or safety sheet glass in all windows.

3.4.4 Mirrors. The vehicle shall be provided with the manufacturer's standard van inside rearview mirror and outside rearview mirror on each side. The outside rearview mirrors shall be adjustable by remote control from the driver's seat.

3.4.5 Instruments and controls. The driver's instruments and controls shall be the chassis manufacturer's van type and shall include the following as a minimum:

a. Speedometer and recording odometer
b. Engine oil pressure gage or indicator
c. Engine coolant temperature gage or indicator
d. Ammeter, voltmeter or charging indicator
e. Fuel level gage
i. Key operated ignition switch

3.4.6 Climate control system. The chassis manufacturer's standard or optional van heating and cooling system shall be provided that will circulate conditioned air and maintain even temperature throughout the vehicle. This system shall provide controlled heating, cooling and fresh air flow as desired. The heating and cooling system shall be fully controlled and shall have not less than three blower speeds.

3.4.6.1 Heating system. The heating system shall be of the engine coolant type and shall include a heavy duty windshield defroster to maintain a clear windshield under high humidity conditions. The heater shall maintain a temperature of at least 60°F throughout the vehicle with outside temperatures down to minimum 20°F. The heater shall have a means of controlling air flow to the heating and defrosting ducts.

Source: https://assist.dla.mil -- Downloaded: 202640-23T12:29Z
Check the source to verify that this is the current version before use.

3.4.6.2 Air conditioning system. The chassis manufacturer's standard or optional air conditioning system shall be provided. The air conditioning system shall maintain an even temperature of not more than 80°F throughout the fully occupied vehicle when in direct sunlight and an outside temperature of 100°F with engine at idle speed.

3.4.7 Dual padded sunvisors. The vehicle shall be provided with overhead control console and dual padded sunvisors for the windshield.

3.4.8 Arm rest. The vehicle shall be provided with a padded armrest on inside of each front door.

3.4.9 Insulation. The vehicle shall be provided with the chassis manufacturer's standard or optional body thermal insulation. Body insulation shall be non-hygroscopic, non-combustible, fibrous material and shall be resistant to fungus growth. Insulation shall be anchored to prevent sag and voids.

3.4.10 Bumpers. The chassis manufacturer's deluxe front and rear bumpers with chrome bumper guards or bumper protective covers shall be provided. Bumpers shall be chrome plated or shall have a protective cover to match body finish.

3.4.11 Carpeting. The manufacturer's deluxe plush type carpeting shall be fitted and attached to cover the entire vehicle floor. The carpet shall present a neat appearance and the color and style will be compatible with other elements of the decor. Visible carpet edges will not be acceptable.

3.4.12 Casket/passenger compartment. With the passenger seats removed, the casket/passenger compartment shall be of a size and arrangement adequate for the transportation, loading and unloading through the rear door(s) of a casket case having a maximum gross weight, including weight of deceased, of 600 pounds or two side by side mortuary cots with remains with maximum weights of 300 pounds each. The manufacturer's standard or optional tiedowns shall be provided for both mortuary cots. The compartment length (from rear of driver's seat in rearmost position to the rear of body at the floor) shall be not less than that listed below. The height shall be not less than the chassis manufacturer's standard full window van height and the minimum distance between wheel housing shall be not less than 48 inches. The interior shall be of currently available materials with all accessories and decor in matching or compatible colors.

Type I - 113 inches
Type II - 104 inches

3.4.13 Floor. The floor in the casket/passenger compartment shall be essentially flat and unobstructed. The floor covering shall be cemented to the wood or metal floor and shall be current production carpet material. Exposed edges of carpet flooring material shall be covered with rustproof, corrosion resistant metal or moldings.

3.5 Electrical system. The vehicle ignition and electrical system shall be of 12 volt potential. The entire vehicle electrical system including the alternator shall be capable of sustaining all vehicle electrical loads operating simultaneously under all conditions of vehicle operation including prolonged periods of normal engine idle without discharge from the battery.

3.5.1 Alternator. The vehicle shall be equipped with a single alternator mounted in original alternator location and of sufficient capacity to satisfy the requirements of 3.5 above but in no case shall capacity be less than 50 amperes peak output or 30 amperes at normal engine idle speed.

3.5.2 Battery. The battery furnished shall be chassis manufacturer's recommended standard or optional item for the vehicle provided. The battery shall be of the maintenance free type having the maintenance free characteristics listed in federal specification W-B-131.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:29Z
Check the source to verify that this is the current version before use.

3.5.3 Lighting.

3.5.3.1 Exterior lighting. The vehicle shall be equipped with the chassis manufacturer's standard headlights, parking lights, taillights, stop lights, back up lights, directional signal lights and a four-way flasher, all in accordance with FMVSS. Headlights shall be furnished with a control for selecting a high or low beam. Directional signal lights may be combined with stop lights at the rear and with parking lights at the front. Taillights and stop lights may be incorporated into the same housing. The control for directional signals shall be the self cancelling type with visible and audible indicators and shall be wired through the ignition circuit.

3.5.3.2 Interior lighting. The vehicle shall be equipped with at least two casket/passenger compartment lights. The casket/passenger compartment lights shall be shrouded indirect type and shall operate when any door is opened. Indirect lighting shall be furnished for the instrument panel. Dual flood lamps shall be mounted adjacent to the rear and left side sliding doors. The flood lamps shall operate when rear or sliding door is opened.

3.6 Auxiliary equipment.

3.6.1 Appearance group. The manufacturer's optional commercial exterior appearance group shall be provided.

3.6.2 Casket rack. A casket table and rollers for rear loading shall be provided. Locking devices shall be provided for properly positioning and holding the casket case or casket in fully extended position at the rear door for loading or off-loading and in retracted position while being transported. The casket rack shall be constructed of chrome plated or stainless steel and shall be capable of supporting a casket case having a maximum gross weight of 600 pounds including weight of the deceased, (see 3.4.12).

3.6.3 Casket roller board. The manufacturer's standard commercial carpeted roller board with chrome adjustable restraints for casket loading and off-loading shall be provided. The roller board carpet shall match the carpet on the casket/passenger compartment floor (see 3.4.13). The roller board shall be easily installed and removed. If tools are required for removal or installation of the roller board, such tools shall be provided for each vehicle.

3.6.4 Removable window panels. (Type II only) when specified (see 6.2), the manufacturer's standard commercial removable window panels with landau bars shall be provided for the rearmost side windows of each type II vehicle. Panel colors shall match the vehicle exterior and interior. Panels shall be easily installed and removed and shall be resistant to damage from the elements and usage. When installed, the panels shall completely cover the window exterior and present a neat appearance and fit.

3.6.5 Draperies. Draperies and venetian blinds shall be provided for all side and rear windows of the casket/passenger compartment. These draperies and venetian blinds shall be easily removed and replaced. Materials shall conform to the decor specified for the interior (see 3.1.12) and shall be treated to prevent spotting, shrinking or fading due to exposure to the elements or from contact with floral arrangements.

3.6.6 Name plate holders. Three pairs of the manufacturer's standard commercial name plate holders shall be provided with each vehicle.

3.6.7 AM/FM stereo cassette system. The chassis manufacturer's standard or option AM/FM stereo cassette sound system shall be provided.

3.6.8 Tools. Each vehicle shall be provided with tools required for exchanging a mounted wheel and tire assembly with the spare assembly and shall include at least a jack, handle and wheel nut wrench. The jack shall be of such closed height as to permit its location under the axle or other satisfactory lift

Source: https://assist.dla.mil -- Downloaded: 202610-23T12:29Z
Check the source to verify that this is the current version before use.

point at any wheel with the tire flat. The jack shall be capable of safely raising and holding the loaded vehicle to a height adequate to permit removal and replacement of the wheel and tire assembly. Storage shall be provided that will not interfere with the function of the vehicle or necessitate moving the casket when access is required.

3.6.9 Electric side door locks. When specified (see 6.2) electric side door locks shall be provided.

3.6.10 Casket table and bier pin set. When specified (see 6.2), the manufacturer's standard or optional commercial casket table and bier pin set shall be provided.

3.7 Finish and protective coatings.

3.7.1 Finish. The vehicle paint color shall be the chassis manufacturer's silver gray. The manufacturer's standard or optional color keyed pin stripping shall also be provided. The exterior paint finish shall show no evidence of uneven application, curtains, runs, sags, orange peel, lack of adhesion or other defects. The paint shall be in accordance with MIL-C-83286 or shall be DuPont Imron or equal.

3.7.2 Rustproofing. Unless otherwise specified (see 6.2), the vehicle shall be rustproofed in accordance with the manufacturer's standard commercial practice.

3.8 Markings. Unless otherwise specified, markings shall be applied with black paint, color number 37038 of FED-STD-595.

3.8.1 Identification markings. Unless otherwise specified (see 6.2), concealed markings in accordance with MIL-STD-1223 shall be provided. When specified, the vehicle shall be marked for the appropriate service in accordance with MIL-STD-1223.

3.9 Identification plate. An identification plate permanently marked in accordance with MIL-STD-130, shall be securely attached to the vehicle in a readily accessible location. The identification shall contain the following information:

NOMENCLATURE
MANUFACTURER'S MODEL NUMBER
MANUFACTURER'S SERIAL NUMBER
MANUFACTURER'S NAME
MANUFACTURER'S ADDRESS
MANUFACTURER'S SERVICE PHONE NUMBER
DATE OF MANUFACTURE
CONTRACT NUMBER
NATIONAL STOCK NUMBER

3.10 Dimensions. The vehicle in fully operational condition, including all equipment and accessories, shall not exceed the following dimensions:

a. Length, Type I - 206 inches bumper to bumper
Type II - 198 inches bumper to bumper
b. Width (except for mirrors and their brackets), chassis manufacturer's standard full window van width.
c. Height, chassis manufacturer's standard full window van height.

3.11 Servicing and adjusting. Prior to acceptance of the vehicle by the government inspector, the contractor shall service and adjust each vehicle and its mounted equipment for operational use including at least the following: Alignment of lights; adjustment of the engine and brake system; filling and charging of the battery; proper inflation of all tires; complete lubrication of chassis, engine, running gear and

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:29Z
Check the source to verify that this is the current version before use.

mounted equipment with grade of lubricants recommended for the ambient air temperature at the delivery point; servicing of the cooling system with a solution of ethylene glycol type antifreeze and water in equal parts by volume; and servicing of the windshield washer reservoir with water and appropriate additives.

3.12 Workmanship. The vehicle, including all parts and accessories, shall be constructed and finished in a thoroughly workmanlike manner. Particular attention shall be given to freedom from blemishes, defects, burrs and sharp corners and edges, accuracy of dimensions and surfaces finish. Defective components or parts and assemblies which have been repaired or modified to overcome deficiencies shall not be furnished. Welded, bolted and riveted construction utilized shall be in accordance with the highest standards of the industry.

4. QUALITY ASSURANCE PROVISIONS.

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Government verification. Quality assurance operations performed by the contractor will be subject to government verifications at unscheduled intervals. Verification will consist of observation of the operations to determine that practices, methods and procedures of the contractor's inspection are being properly applied. Failure of the contractor to promptly correct product deficiencies discovered shall be cause for suspension of acceptance until correction has been made or until conformance of product to specification criteria has been demonstrated.

4.3 First production vehicle inspection. The first production vehicle produced under the contract shall be inspected by the contractor at his plant under the direction and in the presence of government representatives. The purpose of the inspection shall be to determine vehicle conformance to the contract. Acceptance of the first production vehicle shall not constitute a waiver by the government of its rights under the provisions of the contract.

4.3.1 Vehicle weight. The first production vehicle shall be weighed to determine curb weight and the distribution of curb weight on front and rear axles. The imposed loading on front and rear axles will be computed using the curb weight, the operator and passengers (see 3.1.10) to provide the specified GVW. The calculated imposed loads on front and rear axles will be utilized to ascertain that the suspension, axles and tires furnished are of adequate capacity to meet contractual requirements.

4.3.2 Road test. The first production vehicle will be examined and road tested (with payload) by the contractor to assure that the vehicle will operate in accordance with contractual requirements. The road test shall include 10 right and left hand turns and 5 sudden stops from 20 MPH.

Source: https://assist.dla.mil -- Downloaded: 202640-23T12:29Z
Check the source to verify that this is the current version before use.

4.3.3 Air conditioning test. The air conditioning system shall be tested to show compliance with paragraph 3.4.6.2. Temperature readings shall be taken at various interior locations every 15 minutes for a period of 1 hour. The engine cooling system shall not show signs of overheating.

4.3.4 Radio frequency suppression verification. The vehicle manufacturer shall furnish with the questionnaire (commercial vehicle engineering data), a description of all interference suppression devices used to suppress vehicle electromagnetic radiation in accordance with SAE J551. Data shall be sufficient for visual determination that all required suppression devices are installed on the vehicle.

4.3.5 Production sample. Upon acceptance of the first production vehicle, it shall remain at the manufacturing facility as a production sample and shall be the last vehicle shipped on the contract. The contractor shall maintain the vehicle in a serviceable condition for the duration of the contract.

4.3.6 Failure. Failure of the first production vehicle to meet requirements of the contract shall be cause for the government to refuse acceptance of all vehicles under contract until corrective action has been taken.

4.4 Inspection of production vehicles. The contractor's inspection system shall, as a minimum, assure that the vehicle conforms to the physical and dimensional requirements and is capable of meeting performance requirements contained herein. For each vehicle under contract, the contractor shall make available to the government, at the point of final acceptance, records acceptable to the government indicating that the servicing and adjusting required by 3.12 has been accomplished.

5. PREPARATION FOR DELIVERY.

5.1 Preparation for delivery shall be in accordance with the terms of the contract.

6. NOTES.

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The vehicles covered by the specification are intended for use by the armed services as a multi-purpose funeral service vehicle. Its use will include: Effect recovery or removal of remains: transport next of kin; transport casket and/or casket case between storage facility and mortuary; and transport casketed remains and floral contribution to the cemetery in conducting funeral services. Transportation will be over improved roads and highways under all conditions of weather equivalent to those which may be encountered on highways and access roads near bases and posts.

6.2 Ordering data. Procurement documents should specify the following:

a. Title, number and date of this specification.
b. Type (type I or type II) vehicle (see 1.2).
c. Identification markings required (see 3.8.1).
d. Casket table and bier pin set (see 3.6.11).
e. Rustproofing, if other than the manufacturer's standard commercial practice is required (see 3.7.2).
f. Removable window panels, if required (see 3.6.4) (Type II only).
g. Electric side door locks (see 3.6.10).
h. Standard markings, if required (see 3.8.1).
i. Leaded or unleaded fuel.
j. Interior trim package and accessories.

Source: https://assist.dla.mil -Downloaded: 202640-23T12:29Z
Check the source to verify that this is the current version before use.

6.3.1 Commercial. A manufacturer's standard product having been marketed, in production and sold in substantial quantities to the general public for a minimum of one year prior to the date of invitation for bid or request for proposal. An item is "sold in substantial quantities" only when the quantities regularly sold are sufficient to constitute a real commercial market. Nominal quantities such as models, samples, prototypes or experimental units do not meet this requirement. The "general public" is a significant number of buyers other than the government or affiliates of the offeror; the item involved must not be for government end use. For the purpose of this specification, items acquired for "government end use" include items acquired for foreign military sales.

6.4 Consideration of data requirements. The following data requirements should be considered when this specification is applied on a contract. The applicable Data Item Descriptions (DID's) should be reviewed in conjunction with the specific acquisition to ensure that only essential data are requested/provided and that the DID's are tailored to reflect the requirements of the specific acquisition. To ensure correct contractual application of the data requirements, a Contract Data Requirements List (DD Form 1423) must be prepared to obtain the data, except where DOD FAR Supplement 27.475-1 exempts the requirement for a DD Form 1423.

6.5 Subject term (Key Word) listing.

Casket
Commercial Chassis
Front Wheel Drive
Full Size
Mini-Size
Mortuary Vehicle
Rear Wheel Drive

Custodians:
Air Force - 99

Preparing activity:
Air Force - 84

Project No: 2320-F417

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:29Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:29Z
Check the source to verify that this is the current version before use.