INTERIM FEDERAL SPECIFICATION

BOOKREST

This Interim Federal Specification was developed by the Standardization Division, Federal Supply Service, General Services Administration, Washington, D.C. 20406, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

1. SCOPE

1.1 Scope. This specification covers a stand-type folding metal bookrest to hold books, notebooks, letters, documents and other reading material for an unobstructed view of the exposed page(s). The bookrest shall be of one type.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specifications:

PPP-B-566 - Boxes, Folding, Paperboard.
PPP-B-636 - Box, Fiberboard.
PPP-B-665 - Boxes, Paperboard, Metal Stayed (Including Stay Material).
PPP-B-676 - Boxes, Setup.

Federal Standards:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civilian Agencies).
Fed. Std. No. 595 - Colors.

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington, D.C. 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, D.C., Atlanta, Chicago, Kansas City, Mo., Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, Washington.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:54Z
Check the source to verify that this is the current version before use.

2.2. Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

Uniform Classification Committee:

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, 202 Union Station, 516 West Jackson Boulevard, Chicago, Ill. 60606.)

National Classification Board:

National Motor Frieght Classification.

(Application for copies should be addressed to the National Classification Board, 1616 P Street, N. W., Washington, D. C. 20036.)

3. REQUIREMENTS

3.1 Material. The material shall be as specified. Where material is not definitely defined, it shall be of the quality and composition best suited for the intended purpose. When the dimension(s) of the material is not specified, it shall be at the discretion of the manufacturer.

3.1.1 Steel wire. The steel wire shall be plain carbon steel, and shall be finished as specified in 3.6.

3.1.2 Sheet steel. The sheet steel shall be plain carbon steel, hot or cold rolled at the manufacturer's option. The sheet steel shall be finished as specified in 3.6.

3.2 Design. The bookrest shall be capable of being erected (set up) and folded flat. The bookrest shall be designed to permit the user to place or remove reading material from the holding device with ease; to permit adjustment of the bookrest to the desired reading angle, and retain this position; to give the reader an unobstructed view of the reading material, and hold the page(s) in the proper position; and permit page(s) of reading material to be turned without removing it from the bookrest (see 4.4.2.1). The bookrest shall be capable of supporting a minimum weight of ten pounds without bending or sagging (see 4.4.2.2).

3.3 Construction. The bookrest shall be fabricated from steel wire 0.119 inch diameter or greater, conforming to 3.1.1, or a combination of 3.1.1 and sheet steel 0.018 inch, or greater, as defined in 3.1.2. The dimensions of the bookrest shall be as specified in 3.4. All wire legs or page holders with sharp flat edges shall be covered with plastic, rubber or other suitable tips to prevent scratching. When the base is fabricated from sheet steel it shall have the appropriate number of reinforcing ribs, and all corners and edges of the base shall be rounded and smooth.

3.4 Dimensions. The width of the erected (set up) bookrest shall be not less than 6 inches, and not more than 9 inches; the height shall be not less than 5 inches, and not more than 8 inches. The dimensions between the back of the bookrest and page holder shall be not less than 1-1/4 inches and not more than 2-1/2 inches.

3.5 Color. When enamel or pigmented lacquer is used, the color of the finish shall be gray, conforming to color chip No. 26134 of Fed. Std. No. 595, or commercial gray.

3.6 Finish. The bookrest shall be coated or plated with nickel, cadmium, zinc, or chromium, and having a bright finish (see 4.4.1), or coated with enamel or pigmented lacquer, or a combination thereof. The minimum total dry coating of enamel or pigmented lacquer shall be not less than 1.0 Mil, when tested in accordance with 4.4.1.3. The finish shall be smooth and uniform without runs, wrinkles, blisters, grit, or foreign matter, lumpy areas, areas of thin or no film, or separation of color.

3.7 Identification marking. Each bookrest shall be permanently and legibly marked with the name or trademark of the manufacturer.

3.8 Workmanship. The bookrest shall be free from defects or imperfection which may affect appearance, or impair serviceability. It shall be devoid of sharp corners, edges, or other imperfections that may be hazardous to the user.

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:54Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Inspection of materials. The supplier is responsible for assuring that materials conform to the physical properties specified in this specification.

4.2 Sampling.

4.2.1 Size of lot. All bookrests presented for inspection at one time shall be considered a lot for the purpose of examinations and test.

4.2.2 Sampling for inspection. Sampling for inspection shall be performed in accordance with MIL-STD-105, except where otherwise specified.

4.2.3 Sampling for visual and dimensional examination. Random sample of bookrests shall be taken from each lot in accordance with MIL-STD-105. A sample unit shall be one bookrest. The bookrest shall be examined for defects listed in table I. The Inspection Level shall be S-3, and the Acceptable Quality Level (AQL) shall be 4.0 percent defective.

4.2.4 Sampling for preparation for delivery requirements. Sampling shall be in accordance with MIL-STD-105. The sample unit shall be one shipping container fully prepared for delivery at one time with the exception that it need not be sealed, and shall be examined for defects listed in table II. The lot shall be the number of shipping container offered for delivery at one time. The inspection level shall be S-2, and the AQL shall be 4.0 defects per hundred units.

4.2.5 Sampling for coating or plating tests. One sample unit shall be taken from each lot and tested as specified in 4.4.1.1, 4.4.1.2, 4.4.1.3, or 4.4.1.4.

4.2.6 Sampling for performance tests. Random samples of bookrests shall be taken from each lot in accordance with MIL-STD-105. The sample unit shall be one bookrest and shall be tested as specified in 4.4.2.1 and 4.4.2.2. The inspection level shall be S-2, and the AQL shall be 4.0 percent defective.

4.3 Examination.

4.3.1 Visual and dimensional examination for end item. Samples taken in accordance with 4.2.3 shall be examined for defects listed in table I. Any sample having one or more defects shall be rejected. If the number of defective units in the sample exceeds the acceptance number for that sample, the entire lot represented by the sample shall be rejected.

TABLE I. Classification of defects

Examine	Defects
Material	Not as specified (see 3.1). Not of the gage specified (see 3.3).
Design	Not the stand-type folding bookrest (see 3.2).
Construction	The sharp flat edges of the wire legs or page holder not covered as specified (see 3.3). When base is manufactured of sheet steel, not constructed as specified (see 3.3).
Dimension	Not as specified (see 3.4).
Color	Not as specified (see 3.5).

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:54Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of defects (cont'd)

Examine	Defects
Finish	Not as specified (see 3.6).
Identification marking	Not as specified (see 3.7).
Workmanship	Not in accordance with 3.8.

4.3.2 Examination of preparation for delivery. Samples selected in accordance with 4.2.4 shall be examined for defects listed in table II to determine that packaging, packing and marking comply with the requirements of section 5. Defects of closure listed shall be examined on shipping containers fully prepared for delivery.

TABLE II. Classification of preparation for delivery defects

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; or improper size, location, sequence or method of application.
Materials	Any component missing, or not as specified. Any component damaged, affecting serviceability.
Workmanship	Inadequate application of components, such as: incomplete closure of container flaps, loose strapping, improper taping, inadequate stapling. Bulging or distortion of containers.
Content	Number per container is more, or less than required.

4.4 Tests.

4.4.1 Test for coating or plating. Samples selected in accordance with 4.2.5 shall be subjected to one of the following tests applicable to the finish of the end product. Failure to identify an authorized plating or coating, or not meeting the thickness requirement of the enamel or pigmented lacquer of 3.6 shall be cause for rejection of the entire lot.

4.4.1.1 Identification for presence of nickel. Using a medicine dropper, apply several drops of nitric acid (HNO_3), Sp. gr. 1.42 to the metal surface. At the end of one minute observe acid drop; a clear pale green color indicates presence of nickel.

4.4.1.2 Identification for presence of zinc and cadmium. Place part, or the entire bookrest in a beaker of nitric acid (HNO_3), Sp. gr. 1.42. At the end of 1 minute observe the reaction. A vigorous reaction and no recipitate identifies zinc. A slight reaction and a yellow-colored solution identifies cadmium.

4.4.1.3 Identification for presence of chromium. Using a medicine dropper, apply several drops of concentrated hydrochloric acid (HCl), Sp. gr. 1.18. A green solution identifies presence of chromium.

4.4.1.4 Thickness of enamel or lacquer coating test. The thickness of the final coating of the bookrest shall be determined to the nearest 0.0001 inch by standard methods, for compliance with 3.6.

4.4.2 End item test. Samples selected in accordance with 4.2.6 shall be subjected to the following tests. Any bookrest in the sample failing one or more tests shall be considered defective. If the number of defective units exceeds the acceptance number of the sample, the lot represented by the sample shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:54Z
Check the source to verify that this is the currenversion before use.

4.4.2.1 Operational test. The operational tests shall insure compliance with the requirements defined in 3.2. A book not less than 1-1/4 inches thick, 6 inches wide and 10 inches high shall be utilized to perform the tests.

4.4.2.2 Structural test. A book, or a book and weight, weighing ten pounds, and conforming to the dimensional requirements of 4.4.2.1 shall be placed on an erected bookrest. The bookrest shall not bend or sag (see 3.2).

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B, or C as specified (see 6.2).

5.1.1 Levels A and B. Each bookrest shall be packaged in kraft paper envelope for the type normally used for the item.

5.1.1.1 Intermediate packaging. Twelve unit packages shall be intermediate packaged in a close-fitting box conforming to PPP-B-566, PPP-B-665, PPP-B-676 or PPP-B-636. Each box shall be adequately closed to prevent accidental opening.

5.1.2 Level C. Bookrests shall be packaged in accordance with the supplier's commercial practice.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A. Bookrests, intermediate packaged in accordance with 5.1.1.1 and in quantities as specified (see 6.2), shall be packed in a close-fitting box conforming to PPP-B-636, class weather-resistant. The box shall be closed, waterproofed and strapped in accordance with the appendix to PPP-B-636.

5.2.2 Level B. Eight intermediate packages (96 bookrests) shall be packed in a close-fitting box conforming to PPP-B-636, class domestic. The box shall be closed in accordance with the appendix to PPP-B-636.

5.2.3 Level C. Intermediate packages shall be packed in containers to assure carrier acceptance and safe arrival at destination in compliance with Uniform Freight Classification Rules and National Motor Freight Classification Rules.

5.3 Marking. In addition to any special marking required by the contract or order, interior packages and shipping container shall be marked in accordance with Fed. Std. No. 123 or MIL-STD-129 as applicable.

6. NOTES

6.1 Intended use. The bookrests are intended to hold books, notebooks, letters, documents and other reading material to facilitate reading and viewing.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in the procurement document.

(a) Title, number, and date of this specification.
(b) Selection of the applicable levels of packaging and packing (see 5.1 and 5.2).
(c) Quantity of intermediate packages required (see 5.2.1).
(d) Any special marking required.

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:54Z
Check the source to verify that this is the current version before use.