GG-H-1314A
August 1, 1973
SUPERSEDING
Int. Fed. Spec. GG-H-001314(GSA-FSS)
December 14, 1967

FEDERAL SPECIFICATION

HOLDERS, BINDER LABEL

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers the requirements for loose-leaf binder label holders with insertable labels.

1.2 Classification (see 6.3).

1.2.1 Sizes. The label holders shall be of the following sizes as specified (see 6.2):

Size 1 - One inch binder capacity.
Size 2 - Two inch binder capacity.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

Federal Specifications:

QQ-W-428 - Wire, Steel, Carbon (High Carbon, Round, for Mechanical Springs, General Purpose).
PPP-B-566 - Boxes, Folding, Paperboard.
PPP-B-636 - Boxes, Shipping, Fiberboard.
PPP-B-665 - Boxes; Paperboard, Metal Edged and Components.
PPP-B-676 - Boxes, Setup.

Federal Standard:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civil Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:53Z
Check the source to verify that this is the current version before use.

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bid or request for proposal shall apply.

American Society for Testing and Materials (ASTM) Standards:

D 1562 - Cellulose Propionate Molding and Extrusion Compounds.

(Application for copies should be addressed to the American Society for Testing and Materials (ASTM) Standards, 1916 Race Street, Philadelphia, PA 19103.)

Technical Association of the Pulp and Paper Industry (TAPPI) Publications:

T411 - Thickness (Caliper) of Paper and Paperboard.

(Application for copies should be addressed to the Technical Association of the Pulp and Paper Industry, 360 Lexington Avenue, New York, NY 10017.)

National Motor Freight Traffic Association, Incorporated, Agent:

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Associations, Inc., Tariff Order Section, 1616 P Street, N.W., Washington, DC 20036.)

Uniform Classification Committee, Agent:

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.

3. REQUIREMENTS

3.1 Materials.

3.1.1 Strip steel. Steel shall be cold rolled strip, and not less than 0.012 inch in thickness.

3.1.2 Steel spring wire. Spring wire shall be any of the types and classes in QQ-W-428. The diameter of the wire shall be 0.054 inch. Dimensional tolerances in diameter of wire and out-of-round of QQ-W-428 apply.

3.1.3 Paper for insert labels. Paper for labels shall be a good commercial quality white unruled index or ledger paper with a thickness of not less than 0.0072 inch.

3.1.4 Plastic for holder body. Plastic for the holder body shall be cellulose propionate meeting the physical property requirements of grade 1, ASTM D 1562. Plastic shall be not less than 0.020 inch in thickness. Unless otherwise specified (see 6.2), the plastic shall be clear, colorless, and transparent.

3.1.5 Plastic for window cover. Plastic for the window cover shall be not less than 0.0065 inch in thickness. Unless otherwise specified (see 6.2), the plastic shall be clear, colorless and transparent.

3.2 Design. The holder shall consist of a steel body (3.1.1) or shall be of all plastic construction, including the window area (3.1.4). The steel bodied holder shall have a plastic window cover (3.1.5). Both steel and plastic bodied holders shall have a steel slip-on-clip (3.1.2), and a paper insert label (3.1.3). When the label holder is attached to a loose-leaf binder, the label shall be visible from one side.

3.2.1 Body. The body shall be of one continuous piece of strip steel or plastic. Provision shall be made on the back for assembly of the slip-on clip, and for retention of the insert label, and plastic window (steel body only). The two outer edges along the entire height dimension, shall be turned or extruded to the inside to form either folds or cylindrical sleeves. The folds or sleeves shall also retain the insert label, and plastic window (steel body only), in a manner to prevent their separation or loss. The plastic body shall have cut-outs on the reverse inside end to positively lock-in the steel wire assembly, and shall have a 45° notch on both inside top ends to provide easy label insertion. Either rounded or square corners will be permitted. The steel body shall have a window space in accordance with table I. The plastic body shall have a window space in accordance with table II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:53Z
Check the source to verify that this is the current version before use.

3.2.1.1 Alternatively, steel bodied holder may have a combination of folds and sleeves for retention of the slip-on clip, plastic window, and insert label. A sleeve shall be provided at no less than one point along each outer edge on the height dimension, and on the bottom width dimension, for retention of the slip-on clip in a manner to prevent its separation from the body. In addition to the sleeves, each outer edge along the height dimension shall be turned to the inside to form a fold of not less than 2 inches in length. The fold shall retain the window and label and prevent their separation or loss.

3.2.1.2 Dimensions and tolerances. Dimensions and tolerances for the holder body shall be as specified in table I for steel, and table II for plastic.

TABLE I. Dimensions and tolerances (steel body)

Size	Window space		Overall size	
	Width, minimum	Height, minimum	Width, minimum	Height, minimum
	Inches	Inches	Inches	Inches
1	3/4	2	1-1/4	2-3/4
2	1-3/4	2	2-7/16	2-3/4

TABLE II. Dimensions and tolerances (plastic body)

Size	Window space		Overall size	
	Width, minimum	Height, minimum	Width, minimum	Height, minimum
	Inches	Inches	Inches	Inches
1	1-1/8	2-5/8	1-1/4	2-3/4
2	2-3/8	2-5/8	2-1/2	2-3/4

3.2.2 Slip-on clip. The slip-on clip shall be of one continuous piece of steel spring wire. The clip shall be of a "⌊ ⌋" shape, having two prongs not less than 2 inches in length each, for attachment to the binder back. The prongs shall be curved, bent, or rounded near the ends in a manner to prevent damage and permit easy attachment to the binder. The clip shall be formed in a manner to induce rigidity when assembled with the body. When assembled with the body, the clip shall retain the window and label in a manner to prevent their separation or loss along the bottom width dimension of the holder body. Either a removable clip or a permanently assembled clip will be permitted.

3.3 Insert label. The insert label shall be of paper, (see 3.1.3). The label shall cover the entire area of the window space (opening) when inserted in the body, and shall be of a size adequate to prevent separation or loss (see 3.2.1).

3.4 Window (steel body only). The window shall be of plastic (see 3.1.5). When inserted in the body, the window shall cover the entire window space (opening), and shall be of a size adequate to prevent separation or loss (see 3.2.1 and 3.2.1.1).

3.5 Finish. All steel component parts shall have a black luster finish, which shall render the assembled label holder rust resistant. The finish may be applied by an oxidation or similar process, or may be a high quality lacquer. The finish shall not crack, chip, or peel during label holder use. All surfaces shall be smooth and all edges straight. All plastic component parts shall be free from cold bonds, delaminations, porosity, warpage, checks, cracks, chips, blisters, scratches, rough edges or sharp protrusions.

3.6 Workmanship. Label holders shall be free from any defects or imperfections which affect appearance, or which might impair serviceability.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Sampling.

4.2.1 Lot. A lot shall consist of all label holders offered for inspection at one time as defined in MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:53Z
Check the source to verify that this is the current version before use.

4.2.2 Sampling of end-item for visual defects. A random sample of label holders shall be taken from each lot in accordance with MIL-STD-105, inspection level S-4. The acceptable quality level (AQL) shall not exceed 4.0 percent defective. The sample unit shall be one label holder.

4.2.3 Sampling for preparation for delivery requirements. For examination of interior packages the sample unit shall be one shipping container fully prepared for delivery, and selected at random just prior to the closing operation. Closure defects shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. Sampling shall be in accordance with MIL-STD-105, inspection level S-2. The acceptable quality level (AQL) shall not exceed 4.0 percent defective.

4.2.4 Sampling for test. A random sample of label holders shall be taken from each lot in accordance with MIL-STD-105, inspection level S-1. The AQL shall not exceed 4.0 percent defective. The sample unit shall be one label holder.

4.3 Examination.

4.3.1 Visual and dimensional examination of end-item. Samples taken in accordance with 4.2.2 shall be examined for defects listed in table III.

TABLE III. Classification of label holder defects

Examine	Defects
Material:	
Strip steel	Not as specified in 3.1.1.
Steel spring wire	Not as specified in 3.1.2.
Plastic for holder body	Not as specified in 3.1.4.
Plastic for window cover	Not as specified in 3.1.5.
Design	Not as specified in 3.2 through 3.2.2.
Insert label	Not as specified in 3.3.
Window (steel bodied)	Not as specified in 3.4.
Finish	Not as specified in 3.5.
Workmanship	Not as specified in 3.6.

4.3.2 Examination of preparation for delivery. Samples selected in accordance with 4.2.3 shall be examined to determine that the preservation, packaging, packing, and marking requirements of section 5 of this specification are complied with. Defects shall be scored in accordance with table IV.

TABLE IV. Classification of preparation for delivery defects

Examine	Defects
Markings	Omitted; incorrect; illegible; improper size, location, sequence, or method of application.
Materials	Any component missing or damaged.
Workmanship	Inadequate application of components such as incomplete closure of container flaps, loose strapping, inadequate stapling. Distortion of container.
Contents	Number per container is more or less than required. Gross weight exceeds the requirements of the box specification.

4.4 Tests. Thickness of paper labels on sample taken in accordance with 4.2.4 shall be determined by TAPPI test method T411.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A or C, as specified (see 6.2).

5.1.1 Level A. Six holders, with six plastic windows and six blank labels, of one size, shall be packaged in a box conforming to PPP-B-566. Boxes shall be secured to prevent accidental opening during shipment and storage.

5.1.1.1 Intermediate packaging. Thirty unit packages shall be intermediate packaged in a close-fitting box conforming to PPP-B-566, PPP-B-665, PPP-B-676, or PPP-B-636. Boxes shall be secured to prevent accidental opening during shipment and storage.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:53Z
Check the source to verify that this is the current version before use.

5.1.2 Level C. Holders shall be packaged to insure protection during shipment and safe delivery to destination.

5.2 Packing. Packing shall be level A, B or C, as specified (see 6.2).

5.2.1 Level A. Holders, in quantities as specified (see 6.2), shall be packed in a box conforming to PPP-B-636, class weather-resistant. The box shall be closed, reinforced and waterproofed in accordance with the appendix to PPP-B-636.

5.2.2 Level B. Ten intermediate packages shall be packed in a box conforming to PPP-B-636, class domestic. The box shall be closed in accordance with method II of the appendix to PPP-B-636.

5.2.3 Level C. Holders packaged as specified in 5.1 shall be packed to comply with the National Motor Freight Classification Rules or Uniform Freight Classification Rules, as applicable.

5.3 Marking. In addition to any special marking required by the contract or order, all marking shall be in accordance with 5.3.1 or 5.3.2, as specified (see 6.2).

5.3.1 Civil agencies. Marking shall be in accordance with Fed. Std. No. 123.

5.3.2 Military agencies. Marking shall be in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. Label holders are intended for the display of labels on the backs of closed-back loose-leaf binders.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(a) Title, number and date of this specification.
(b) Size label holder desired (see 1.2.1).
(c) Color of plastic body and plastic window cover, if desired (see 3.1.4 and 3.1.5).
(d) Selection of applicable levels of packaging and packing required (see 5.1 and 5.2).
(e) Selection of civil or military marking, as applicable (see 5.3).
(f) Number of intermediate packages per shipping container for Level A packing (see 5.2.1).

6.3 The type II (adhesive type), class a (plastic flange), and class b (paper flange) holders in GG-H-001314(GSA-FSS) have been deleted in this document since no items were described thereunder.

DOD WAIVED COORDINATION

User Interest:

Army - GL

PREPARING ACTIVITY:

GSA-FSS

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein. Price 10 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:53Z
Check the source to verify that this is the current version before use.