GG-M-001342 (GSA-FSS)
JULY 2, 1968

INTERIM FEDERAL SPECIFICATION

MARKER, TUBE TYPE, FINE TIP, TRANSPARENCY

This Interim Federal Specification was developed by the Standardization Division, Federal Supply Service, General Services Administration, Washington, D.C. 20406, based upon currently available technical information. It is recommended that Federal Agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers a tube type, fine tip marker for use in freehand marking, writing, and drawing on visual-aid transparencies.

1.2 Classification

1.2.1 Colors of ink. The markers shall be furnished with inks of the following colors, as specified (see 6.1):

Black	Green	Brown
Blue	Orange	Purple
Red	Yellow	

2. APPLICABLE DOCUMENTS

2.1 The following specifications and standards, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specifications:

L-P-504 - Plastic Sheet and Film, Cellulose Acetate.
UU-P-121 - Paper, Bond and Writing, White and Colored.
PPP-B-566 - Boxes, Folding, Paperboard
PPP-B-636 - Box, Fiberboard.
PPP-B-665 - Boxes, Paperboard, Metal Stayed (Including Stay Material).
PPP-B-676 - Boxes, Setup.

Federal Standard:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civilian Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington, D.C. 20402.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D.C., Atlanta, Chicago, Kansas City, Mo., Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, Wash.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

FSC 7520

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:54Z
Check the source to verify that this is the current version before use.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Bid samples. Bid samples, when required (see 6.1), shall be submitted for each item offered in the quantities specified, and shall be examined as specified in 4.2.

3.2 Hazardous substances. The marker ink shall contain no quantities of irritants, toxics, or flammable substances that may cause personal harm as a result of any reasonably foreseeable handling or use, including reasonably foreseeable ingestion by children.

3.3 Materials.

3.3.1 Plastic. Plastic used shall be nonflammable or shall have a burning rate not exceeding 3 inches per minute when tested as specified in 4.3.5.13.

3.3.2 Metal. Metal used shall be of a material appropriate for the intended purpose and when used externally shall be suitable for coating as required by 3.6.

3.4 Design and construction. The marker shall be a non-refillable type, designed to operate by capillary action. The marker shall be constructed to provide good protection against evaporation and leakage and shall have a minimum ink content of 2.2 grams when tested as specified in 4.3.5.12. The ink shall be free from obnoxious odors, and shall be held within the marker by an absorbent material so that there is no free liquid within the marker. The marker shall be equipped with a tight-fitting plastic or metal protective cap and the over-all length of the marker with cap in place shall be not less than 5-1/4 inches. The cap or barrel shall be equipped with a plastic or metal pocket clip.

3.4.1 Marker barrel. The marker barrel shall be made of plastic or metal or a combination of these materials. The barrel diameter shall be not less than 0.310 inch, excluding tapered and recessed ends, and not more than 0.500 inch, and shall be constructed so that the ink will emerge only through the writing nib.

3.4.2 Writing nib. The writing nib may be of any material suitable for the intended purpose. The nib shall be permanently secured in position.

3.5 Performance characteristics.

3.5.1 Drying time. The writing shall not smear and the paper which is drawn across the writing shall not be smudged when tested as specified in 4.3.5.1.

3.5.2 Writing characteristics. The markings shall be solid continuous lines free from breaks, splits, separations, uneven concentrations, and runs when tested as specified in 4.3.5.2.

3.5.3 Projectability. The projected markings on the screen shall be sharp and clear when observed from a distance of 20 feet and shall be of the same color identity as the markings on the transparency when tested as specified in 4.3.5.3.

3.5.4 Removability. The markings shall be completely removed (leaving no color residue) from the transparency without hard rubbing when tested as specified in 4.3.5.4.

3.5.5 Light-fastness. After being exposed to the light for four hours in accordance with 4.3.5.5 the projected markings shall be sharp and clear and shall retain their color identity when observed from a distance of 20 feet.

3.5.6 Strength of nib. The writing nib shall not break, crack, split, spread, or fray under the 700 gram load and the mark shall have a line width in the 0.015 to 0.050 inch range when tested as specified in 4.3.5.6.

3.5.7 Pocket clip tension. The clip shall have sufficient tension to support the marker in the inverted position when tested as described in 4.3.5.7.

3.5.8 Startability. The marker shall produce a solid continuous mark not less than 0.015 inch wide within four strokes after laying with the cap off for thirty minutes in accordance with 4.3.5.8.

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:54Z
Check the source to verify that this is the current version before use.

3.5.9 Accelerated aging. The marker shall not leak, crack, or show visible distortion and the markings shall not show a change in color when tested as specified in 4.3.5.9.

3.5.10 Body and cap tightness. The cap shall show no impairment and shall continue to fit securely on the marker barrel, and the weight loss shall not exceed 1.0 mg. when tested as specified in 4.3.5.10.

3.5.11 Impact resistance. There shall be no evidence of leakage, the cap or barrel of the marker shall show no impairment, and the writing nib shall show no signs of loosening when tested as described in 4.3.5.11.

3.6 Finish. The cap or body of the marker shall be colored, or shall have a colored marking, to indicate the color of ink content. All externally exposed metal shall be coated with a protective finish and shall show no corrosion when tested in accordance with 4.3.5.14. The surface of the marker and all components shall have a smooth, uniform appearance and shall be free from gold bonds, delaminations, porosity, warpage, cracks, checks, chips, rough or sharp edges, burrs, blisters, or scratches.

3.7 Identification marking. The markers shall be legibly and permanently marked with the manufacturer's name or trademark, and an indication that the marker is to be used for marking transparencies.

3.8 Shelf life. The markers shall be able to meet all the requirements of this specification from the time of delivery to a minimum of 12 months in storage. Suppliers shall replace, without cost to the Government, all markers failing to meet this requirement.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.1.1 Test markers. For testing purposes (See 4.3.5.12) the contractor shall furnish with each lot of markers offered for acceptance at one time, two markers identical in structure and composition to the markers offered except that they shall contain no ink and shall be identified as such.

4.2 Bid samples. Bid samples submitted in accordance with 3.1 will be examined for:

Balance.
Facility of use.
Comfortable grip.
Suitability of ink color.
Odor of ink.
General appearance and workmanship.

4.3 Sampling and inspection.

4.3.1 Lot. For sampling purposes, a lot shall consist of all markers of one color offered for acceptance at one time.

4.3.2 Inspection of marker. Examine sample markers for the defects listed in table I. Sampling shall be in accordance with MIL-STD-105. The inspection level shall be S-3 with an acceptable quality level (AQL) of 4.0 defects per hundred units. The sample unit (unit of product) shall be one marker.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:54Z
Check the source to verify that this is the current version before use.

TABLE I. Inspection for marker defects

Examine	Defects
Materials	Marker body and cap not plastic or metal or a combination of these materials; materials unsuitable for the purpose intended; ink gives off an obnoxious odor.
Design and construction	Marker not non-refillable type; other than capillary action feed; cap not tight-fitting; over-all length less than 5-1/2 inches; evidence of leakage.
	Pocket clip missing.
	Barrel diameter less than 0.310 inch (excludes tapered and recessed ends) or more than 0.500 inch.
	Writing nib not permanently secured in position.
Ink color	Not as specified (see 6.1).
Finish	No color on cap or body to indicate color of ink content; externally exposed metal not coated with a corrosion-resistant finish; surface (including components) not free from cold bonds, delaminations, porosity, warpage, cracks, checks, chips, rough or sharp edges, burrs, blisters, or scratches.
Identification marking	Marker not legibly and permanently marked with the manufacturer's name or trademark, and an indication that the marker is to be used for marking transparencies.

4.3.3 Inspection of preparation for delivery. An inspection shall be made to determine that the packaging, packing, and marking comply with the requirements of section 5. Defects shall be scored in accordance with table II. For examination of interior packaging the sample unit shall be one shipping container fully prepared for delivery, selected at random just prior to the closing operations. Sampling shall be in accordance with MIL-STD-105. Defects of closure listed shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lots. The inspection level shall be S-2 with an AQL of 4.0 defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:54Z
Check the source to verify that this is the current version before use.

TABLE II. Inspection for preparation for delivery defects

Examine	Defects
Markings (exterior and interior)	Omitted; incorrect; illegible; improper size, location, sequence, or method of application.
Materials	Any component missing or damaged.
Workmanship	Inadequate application of components such as incomplete closure of container flaps, loose strapping, or distortion of container.
Contents (exterior and interior container)	Number per container is more or less than required. Net weight exceeds requirements.

4.3.4 Sampling for tests. Sampling for tests shall be in accordance with MIL-STD-105, inspection level S-1, with an AQL of 6.5 defects per hundred units. The sample unit shall be six markers: one marker for tests 4.3.5.1 through 4.3.5.7; one for test 4.3.5.8; one for test 4.3.5.9; one for tests 4.3.5.10 and 4.3.5.11; and two for tests 4.3.5.12 through 4.3.5.14. The sample size shall be the number of sample units. The failure of a marker to pass one test shall constitute a defect. In selecting the samples take not more than three markers from each package of 12.

4.3.5 Tests. Unless otherwise specified, the tests shall be conducted in an atmosphere of 23° ± 1.1°C. (73.5 ± 2°F.) and at a relative humidity of 50 ± 4 percent. Tests involving writing shall be conducted with the markers held at an angle approximately 50° from the horizontal and with a writing pressure so that the markings are clearly visible. Transparencies used in tests shall be in accordance with L-P-504, type II, high polish finish, with a nominal thickness of 0.005 inch. All test paper used shall conform to UU-P-121, type III, white (17 x 22 - 1000 sheets, 32 pound weight), with a maximum smoothness of 30 seconds on the felt side. The projecter used in tests 4.3.5.3 and 4.3.5.5 shall be equipped with a 600 watt, quartz bromide or quartz iodine lamp.

4.3.5.1 Drying time. Place a transparency on a smooth, flat surface and partially cover with a sheet of paper. Place a 4 ounce weight, approximately one inch in diameter, on top of the sheet of paper. Write a five-letter word on the exposed portion of the transparency, allow to dry 15 seconds and immediately draw the paper and weight across the writing at a rate of approximately four inches per second. Examine the paper and the writing on the transparency for compliance with 3.5.1.

4.3.5.2 Writing tests. Select the marker from the preceding test and write a minimum of 4 five-letter words on a transparency. Check for compliance with 3.5.2. Retain the marked transparency for the next test.

4.3.5.3 Projectability. Place the transparency prepared in 4.3.5.2 on a projector (see 4.3.5) and project the words on a white screen approximately 8 feet away. Check for compliance with 3.5.3. Retain the marked transparency for the next test.

4.3.5.4 Removability. Wipe the markings from the transparency prepared in 4.3.5.2 with a clean, water-dampened, cloth. Check for compliance with 3.5.4.

4.3.5.5 Light fastness. Using the marker from the preceding tests write four five-letter words on a transparency. Place the transparency on a projector (see 4.3.5) and project the words on a white screen approximately 8 feet away. Operate the machine for repeated cycles of one hour "on" and one hour "off" for a total period of eight hours. Check for compliance with 3.5.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:54Z
Check the source to verify that this is the current version before use.

4.3.5.6 Strength test. Place a sheet of paper on a platform scale. Grip the uncapped marker (use marker tested in preceding test) between 1 1/4 and 1-1/2 inches from the writing end. Hold the writing nib to the paper in a normal writing position and at an angle of 50 ° from the horizontal without the hand touching the paper. Apply a force of 700 grams gradually and uniformly, observing the effects on the nib. Immediately release after 5 seconds of full pressure. Draw one 6-inch linear mark with the tested marker and examine for compliance with 3.5.6.

4.3.5.7 Pocket clip test. Using the marker tested previously, slide the clip over stiff material 0.125 inch thick. Repeat this operation 25 times. Then slide the clip over stiff material 0.016 inch thick and invert so that only the tension of the clip is supporting the full weight of the marker. Check for compliance with 3.5.7.

4.3.5.8 Startability. Write four five-letter words with an unused sample marker. Then place marker on its side with cap off for thirty minutes. Immediately draw the marker nib across a transparency at a rate of approximately 4 inches per second, in increments of 8 inches, until a solid continuous mark at least 0.015 inch wide is attained. Examine markings for compliance with 3.5.8.

4.3.5.9 Accelerated aging. Draw an 8-inch linear mark on a transparency with an unused marker. Recap the marker tightly and place horizontally in a convection-type oven at a constant temperature of 60° ± 1° C. (140° ± 1.8°F.) for 7 days. At the end of the aging period remove the marker from the oven and examine it for leaks and distortion. Then place the marker on its side and allow it to cool at room temperature for 24 hours. After the 24 hour period, remove the cap and draw a mark parallel to the existing mark and check for compliance with 3.5.9.

4.3.5.10 Body and cap tightness. Select an unused sample marker and uncap and recap to a normal hand tightness 20 consecutive times. Then uncap the marker and draw a three-foot linear mark and recap tightly. Immediately take and record the weight of the marker. Then allow the marker to stand tightly capped for 24 hours. At the end of the 24-hour period, again take and record the weight of the marker and determine the weight loss. Check the cap and the weight loss for compliance with 3.5.10.

4.3.5.11 Impact test. Select the marker tested in the previous test, making sure the cap is in place. Drop the marker on a wood floor 5 times fromaa height of 4 feet. Position the marker so it will hit the floor at the end equipped with the writing nib. After the fifth drop examine the inside of the cap and the area around the writing nib for evidence of leakage. Examine the cap and barrel for defects. Then write a few sharp turns, reversals, and circles and chedk for compliance with 3.5.11.

4.3.5.12 Ink content. Select the two test markers with no ink (see 4.1.1) and then select two unused sample markers. To determine the ink content weigh the two markers with ink and compute the average weight per marker by dividing by two. Then weigh the two markers containing no ink, compute their average weight, and subtract this figure from the first average. Check the ink content for compliance with 3.4.

4.3.5.13 Flammability test for plastic. Select a marker previously tested and perform the following test on the cap, if plastic; the barrel, if plastic; or both, if both the cap and barrel are plastic. Remove the contents and metal components from the cap and barrel before performing this test. In a draft-free area, hold the plastic specimen horizontally above a bunsen burner having a 1 to 1-1/4 inch blue flame just touching the end of the specimen until it ignites, or for a period not over 30 seconds. Remove the flame. If the specimen will not support combustion, it is nonflammable. If the specimen burns, measure the burning rate in inches per minute and check for compliance with 3.3.1.

4.3.5.14 Corrosion resistance test. Remove externally exposed metal parts from a marker previously tested and place them in a boiling water and sodium chloride (10% by weight) solution for fifteen minutes. Remove metal parts from this solution and immediately immerse them in a water and sodium chloride (10% by weight) solution for one hour at room temperature. Then remove them and without wiping the adhering liquid off allow to dry for 24 hours at room temperature. Examine metal parts for presence of corrosion and check for compliance with 3.6.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B, or C, as specified (see 6.1).

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:54Z
Check the source to verify that this is the currentversion before use.

5.1.1 Level A. Twelve markers of one color shall be packaged in a close-fitting box conforming to PPP-B-566, PPP-B-665, or PPP-B-676.

5.1.2 Level B. The markers shall be packaged as specified in 5.1.1.

5.1.3 Level C. The markers shall be packaged to afford adequate protection against corrosion, deterioration, and damage during shipment from the supply source to the first receiving activity for immediate use. The supplier's commercial practice will be acceptable when it fulfills the above requirements.

5.2 Packing. Packing shall be level A, B, or C, as specified (see 6.1).

5.2.1 Level A. Thirty-six unit packages of markers shall be packed in a close-fitting box conforming to PPP-B-636, class weather-resistant. The box shall be closed, waterproof sealed, and strapped in accordance with the appendix to the box specification.

5.2.2 Level B. Thirty-six unit packages of markers shall be packed in a close-fitting box conforming to PPP-B-636, class-domestic. The box shall be closed in accordance with the appendix to the box specification.

5.2.3 Level C. The markers shall be packed to insure carrier acceptance and safe delivery to destination at the lowest rates in containers complying with the rules and regulations applicable to the mode of transportation.

5.3 Marking.

5.3.1 Civil agencies. In addition to markings required by the contract or order, the interior packages and shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.3.2 Military activities. In adddition to the markings required by the contract or order, the interior packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Color required (see 1.2.1).
(c) Bid samples, if required, and quantity required (see 3.1).
(d) Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:54Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:54Z
Check the source to verify that this is the current version before use.