[INCH-POUND]
A-A-59269
30 June 1998
SUPERSEDING
(See 7.)

COMMERCIAL ITEM DESCRIPTION

SCALES, DRAFTING AND SCALES, PLOTTING

The General Services Administration has authorized the use of this commercial item description for all federal agencies.

1. SCOPE. This commercial item description covers the requirements for drafting and plotting scales for measuring and laying out linear dimensions.

2. CLASSIFICATION

Type I. Scales drafting: combination English and metric measurement system

Type II. Scale, drafting: surveyor's

Type III. Scale, plotting

Type IV. Scale, plotting: plotting and drafting

Type V. Scales, plotting: metric

Type VI. Scales, plotting: meters and yards

3. SALIENT CHARACTERISTICS

3.1 Types. The types of scales shall be as specified herein:

3.1.1 Type I. Type I scales shall be fully divided, with one edge divided to a minimum reading of 0.5 millimeter, with every centimeter numbered. The other edge shall be divided into 12 inches, subdivided into thirty-seconds of an inch, with each inch numbered. Type I scales shall have the following shape: two bevels, flat, opposite (parallelogram). The scales shall be made of wood with plastic facings. Type I scales shall be furnished in 30-centimeter nominal lengths.

Beneficial comments, recommendations, additions, deletions, clarifications, etc., and any other data which may improve this document should be sent by letter to: Defense Supply Center Richmond (DSCR), ATTN: DSCR-VBD, 8000 Jefferson Davis Highway, Richmond, VA 23297-5610.

AMSC N/A FSC 6675

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:08Z
Check the source to verify that this is the current version before use.

3.1.2 Type II. Type II scales shall be fully divided to 1,000 parts per foot on one edge and to 0.5 millimeters on the other edge. Scales shall be numbered at each tenth of a foot and at each centimeter. Type II scales shall have the following shape: two bevels, flat, same side (trapezoid). The scales shall be made of wood with plastic facings. Type II scales shall be furnished in 12-inch nominal lengths.

3.1.3 Type III. Type III scales shall be direct numbered, with scale graduations open divided. The type III scale shall be divided in meters on both edges, graduated at 1:25,000 and 1:50,000. The scale ratio shall be marked as a representative fraction. In addition, the scale ratio may also be marked in words and figures. Type III scales shall have the following shape: two bevels, flat, same side (trapezoid). The scales shall be made of wood with plastic facings. The type III scale shall be furnished in 30-centimeter nominal lengths.

3.1.4 Type IV. Type IV scales shall be open divided, with four plotting and two drafting edges. All scales shall be numbered direct, with every 1,000th unit of plotting scales and every single unit of the drafting scales numbered. Plotting scales shall have 1,000 units and drafting scales one unit to the left of the zero mark. Plotting scales shall have every 500th unit graduated. The first edge shall be graduated in yards at 1:25,000, with 7,000 yards to the right of the zero. The two 500-yard intervals to the left of the zero shall be subdivided at 20-yard intervals, with each 100 yards emphasized and every 500 yards numbered from right to left. The second edge shall be graduated in inches, divided to half inches, with 11 inches to the right of the zero. The two half-inch intervals to the left of the zero shall be subdivided at 0.02-inch intervals, with each 0.1 emphasized. The third edge shall be graduated in meters at 1:50,000, with 14,000 to the right of the zero. The fourth edge shall be graduated in meters at 1:62,500, with 18,000 to the right of zero. On both third and fourth edges, the two 500 intervals to the left of the zero shall be subdivided at 50 intervals, with each 100 emphasized. The fifth edge shall be graduated in meters at 1:25,000, with 6,000 to the right of the zero. The two intervals to the left of the zero shall be subdivided at 20 intervals, with each 100 emphasized, and 500 meters and 1,000 meters numbered from right to left. The sixth edge shall be graduated in centimeters, with 29 cm to the right of the zero. The centimeter to the left of the zero shall be subdivided into millimeters, with each fifth millimeter emphasized. The graduations shall be placed so that as the scale is rolled over, the sequence shall be (1) yards, 1:25,000; (2) inches; and (3) meters, 1:50,000. Meters 1:62,500 shall be on the same side as (1); centimeters as (2); and meters 1:25,000 as (3). The scale ratio shall be marked as a representative fraction. In addition, the scale ratio may also be marked in words and figures. Type IV scales shall have the following shape: Six bevels, triangular, flat or regular. The scales shall be made of wood with plastic facings. Type IV scales shall be furnished in 12-inch nominal lengths. The scales shall be furnished with an artificial leather or heavy vinyl plastic sheath as specified in the contract or purchase order.

3.1.5 Type V. Type V scales shall be fully divided, direct numbered, with one edge in the ratio of 1:10,000, and 1:20,000, reading to 3,000 and 6,000 meters respectively, double numbered at every 100 and 200 meters. The other edge shall be divided in the ratio of 1:50,000 reading to 15,000 meters, single number at every 1,000 meters. Type V scales shall have the following

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:08Z
Check the source to verify that this is the current version before use.

shape: two bevels, flat, same side (trapezoid). The scales shall be made of wood with plastic facings. Type V scales shall be furnished in 30-centimeter nominal lengths.

3.1.6 Type VI. Type VI scales shall be fully divided in a ratio of 1:10,000 and 1:20,000, double numbered. One edge shall be graduated 5,500/11,000 yards and the other edge shall be graduated 5,000/10,000 meters. Minimum readings shall be 10/20 units, and each 250-/500-unit graduation shall be numbered. Type VI scales shall have the following shape: two bevels, flat, same side (trapezoid). Type VI scales shall be made of wood with plastic facings. Type VI scales shall be furnished in 50-centimeter nominal lengths.

3.2 Tests. All scales shall be visually evaluated for conformance to the specified type. The wood shall be visually inspected. It shall be straight grained and clear throughout, and free from imperfections such as chips, dents, or flaws.

4. REGULATORY REQUIREMENTS. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

5. QUALITY ASSURANCE PROVISIONS

5.1 Product conformance. The product provided shall meet the salient characteristics of this commercial item description, conform to the producer's own drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial market. The government reserves the right to require proof of such conformance.

5.2 Market acceptability. With the exception of the markings, the offeror must currently sell scales of the identical construction (i.e. type and quality of wood and plastic, construction, accuracy, straightness, flatness, etc.) on the commercial market.

6. PACKAGING. Preservation, packing, and marking shall be as specified in the contract or order.

7. NOTES

(This section contains information of a general or explanatory nature which is helpful, but is not mandatory.)

7.1 Part identification number (PIN). The following part identification numbering procedure is for Government purposes and does not constitute a requirement for the contractor.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:08Z
Check the source to verify that this is the current version before use.

This example describes a part numbering system for A-A-59269.

A-A-59269 -2

Type - 1, 2, 3, 4, 5, 6 (use Arabic numerals)

CID number

7.2 Referenced documents.

7.2.1 Copies of the Federal Acquisition Regulation (FAR) may be obtained from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402-0001.

7.3 Ordering data. Acquisition documents must specify the following:

7.3.1 Title, number, and date of this commercial item description.

7.3.2 The type of material desired (see 2).

7.3.3 Packaging requirements (see 6).

7.4 Supersession information. This commercial item description supersedes: GG-S-161D of 1 May 1985, GG-S-161/4D of 1 May 1985, GG-S-161/5D of 1 May 1985, GG-S-161/7D of 1 May 1985, GG-S-161/8D of 1 May 1985, GG-S-161/10D of 1 May 1985.

7.5 Cross-reference of classification. Table I cross-references the classification of GG-S-161/4D, GG-S-161/5D, GG-S-161/7D, GG-S-161/8D, and GG-S-161/10D with this CID.

TABLE I. Cross-reference table.

Federal Specification GG-S-161D			Commercial Item Description A-A-59269
Specification sheet	Type	Style	Type
GG-S-161/4D	IV	B	I
GG-S-161/5D	V	A	II
GG-S-161/7D	VII	C	III
GG-S-161/7D	VII	E	IV
GG-S-161/8D	VIII	A	V
GG-S-161/10D	X	C	VI

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:08Z
Check the source to verify that this is the current version before use.

MILITARY INTERESTS:

Custodians
Army - CE
Air Force - 99
Navy - YD1

Reviewers
Navy - MC
Air Force - 82
Army - GL

CIVIL AGENCY COORDINATING ACTIVITIES:

GSA - FCGC

Preparing Activity:
DLA - GS

(Project 6675-0033)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:08Z
Check the source to verify that this is the current version before use.