MILITARY SPECIFICATION

AMMETERS AND SHUNTS, AUTOMOTIVE

This amendment forms a part of Military Specification MIL-A-3427A, 29 May 1956, and has been approved by the Department of Defense and is mandatory for use of the Departments of the Army, the Navy, and the Air Force.

Page 2, paragraph 2.1, add under "SPECIFICATIONS MILITARY:"

MIL-P-17667 — Paper, Wrapping, Chemically Neutral."

Paragraph 3.1, delete and substitute:

"3.1 **Preproduction sample.** Ammeters and shunts furnished under this specification shall be products which have passed the preproduction inspection specified in paragraph 4.2.3.1."

Page 3, paragraph 3.4.6.2, add to beginning of last sentence "Where required,"

Paragraph 3.4.7, add to beginning of second sentence "Where required,"

Paragraph 3.4.8, second line, delete "flat" and substitute "cup shaped."

Page 5, paragraph 4.2.3.1, delete and substitute:

"4.2.3.1 *Preproduction.* As soon as possible after award of contract, preproduction inspection will be performed by the manufacturer at the manufacturer's plant. Certification by the contractor shall be submitted to verify conformance of the preproduction sample to this specification, upon approval of the contracting officer. In addition, samples shall be submitted to the procuring activity for testing and evaluation, when specified by the contracting officer (see 6.1)."

Paragraph 4.3.1, delete and substitute:

"4.3.1 *Preproduction.* Each preproduction sample shall be examined for appearance, finish, construction, completeness of manufacture and assembly, conformance to specified dimensions, dial and product markings, and workmanship. In addition, samples shall be subject to the tests specified in table I in the sequence listed."

Delete "Table II. Tests for qualification" and substitute "Table I. Preproduction tests."

Page 6, paragraph 4.3.1.1, delete.

Paragraph 4.3.3, last sentence, delete "shall" and substitute "may."

Paragraph 4.3.4.2, line 5, delete "30°" and substitute "10°."

Page 7, paragraph 4.3.8.2, second sentence,

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:39Z
Check the source to verify that this is the current version before use.

delete and substitute "The unit shall be vibrated for one hour in each direction of each of the three major axes with continually varying frequencies being accomplished each minute."

Page 8, paragraph 5.1.1.8, first sentence, delete and substitute "type I ammeters shall be packaged in accordance with Method 1–A, type II ammeters in accordance with Method II–E, and shunts in accordance with Method III of Specification MIL–P–116."

Paragraph 5.1.1.8, second and third sentence, delete and substitute "Each ammeter and each shunt shall be individually wrapped with paper conforming to Specification MIL–P–17667."

Page 9, paragraph 6.1, add the following:

"(e) Provisions for preproduction sample(s)."

Paragraph 6.2, delete.

Custodians:
Army—Ordnance Corps
Navy—Bureau of Yards and Docks
Air Force

Preparing activity:
Army—Ordnance Corps

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:39Z
Check the source to verify that this is the current version before use.