INCH-POUND

MIL-C-3363D(GL)
26 October 1992
SUPERSEDING
MIL-C-3363C(GL)
16 September 1982

MILITARY SPECIFICATION

CHEST, MEDICAL EQUIPMENT MAINTENANCE AND REPAIR TOOL KIT

This specification is approved for use by the Natick Research, Development, and Engineering Center, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.2 Scope. This specification covers one type and size of a wooden tool chest with a removable tray.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be used in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5017 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 5140

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:34Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

A-A-472	-	Hasp, Hinged
FF-S-111	-	Screw, Wood
RR-C-271	-	Chains and Attachments, Welded and Weldless
TT-C-490	-	Cleaning Methods for Ferrous Surfaces and Pretreatments for Organic Coatings
TT-E-529	-	Enamel, Alkyd, Semigloss, Low Voc Content
TT-P-25	-	Primer Coating, Exterior Undercoating For Wood Ready-Mixed, White and Tints
TT-W-572	-	Wood Preservative: Water-Repellent
MMM-A-181	-	Adhesive, Phenol, Resorcimal or Melamine Base
PPP-F-320	-	Fiberboard: Corrugated and Solid, Sheet
PPP-P-60	-	Tape: Packaging, Waterproof
PPP-T-76	-	Tape, Packaging, Paper (for Carton Sealing)

STANDARDS

FEDERAL

FED-STD-595	-	Colors Used in Government Procurement

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	-	Marking for Shipment and Storage
MIL-STD-130	-	Identification Marking of U.S. Military Property
MIL-STD-147	-	Palletized Unit Loads
MS-35647	-	Padlocks, Key Operated

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS

U.S. ARMY NATICK RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER

10-1-529	-	Chest, Medical Equipment Maintenance and Repair Tool Kit; Assembly

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:34Z
Check the source to verify that this is the current version before use.

(Copies of drawings are available from the U.S. Army Natick Research, Development, and Engineering Center, ATTN: SATNC-UX, Natick, MA 01760-5017.)

2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

UNITED STATES DEPARTMENT OF COMMERCE

Product Standard PS-1 - Softwood Plywood - Construction and Industrial

(Application for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

A 109 - Steel, Carbon, Cold-Rolled Strip
D 4442 - Direct Moisture Content Measurement of Wood and Wood-Base Materials
D 3950 - Strapping, Plastic (and Seals)
D 3951 - Standard Practice for Commercial Packaging
D 3953 - Strapping, Flat Steel and Seals

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection (see 6.3) in accordance with 4.3.

3.2 Materials. Materials shall conform to the requirements specified herein and the subsidiary documents applicable thereto. It is encouraged that recycled material be used when practical as long as it meets the requirements of this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:34Z
Check the source to verify that this is the current version before use.

3.2.1 Steel strip. The strip steel used in the chest shall conform to ASTM A 109.

3.2.2 Plywood. Plywood used in the construction of the bottom of the tray shall conform to group 1, exterior type, grade B-B medium density overlay of Product Standard PS 1.

3.2.3 Lumber. Lumber for solid wooden parts of the chest shall be any of the following species: white ash, beech, birch, hickory, hard maple, oak or pecan. Lumber shall be uniformly dried to an average moisture content of from 8 to 12 percent at the time of machining (see 4.4.1.1). The minimum board width shall be 2 inches. Slope of grain of machined components shall not exceed one inch in fifteen. Machined components shall be free of decay, splits, wane, warp and unsound knots.

3.2.4 Adhesives.

3.2.4.1 High temperature setting resin. The high temperature setting resin adhesive shall conform to the requirements of type III of MMM-A-181, except that the shear strength by compression loading requirement and the curing cycle requirement shall not apply.

3.2.4.2 Room temperature and intermediate temperature setting resin. The room temperature and intermediate temperature setting resin adhesive shall conform to any grade of types I or II of MMM-A-181.

3.2.5 Screws. The screws shall conform to FF-S-111, of the types and sizes shown on Drawing 10-1-529.

3.2.6 Hinge hasps. The hinge hasps shall conform to size 2 of A-A-472. Holes in the hasps shall be countersunk to accept flat countersunk head rivets.

3.2.7 Padlocks. The padlocks shall conform to MS 35647-3.

3.2.8 Chain. The chain shall conform to Trade No. 40, type II, class 3, steel sash chain of RR-C-271. The required chain has approximately 22 links per foot with a nominal metal link thickness of 0.042.

3.2.9 Primer. The primer shall conform to TT-P-25.

3.2.10 Enamel. The enamel shall conform to TT-E-529. Unless otherwise specified (see 6.2), the color for the chest shall be olive drab conforming to Color No. 24084 of FED-STD-595. The color of identification marking shall be black conforming to Color No. 37038 of FED-STD-595.

3.2.11 Wood sealer. The wood sealer shall conform to composition B of TT-W-572.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:34Z
Check the source to verify that this is the current version before use.

3.3 Design. The chest shall consist of a body, a lid, partitions, a removable tray, and shall be equipped with metal hardware and handles, all as shown on Drawing 10-1-529.

3.4 Construction. Construction shall conform to the requirements shown on Drawing 10-1-529 and as specified herein. When panels are made from two or more boards, they shall be joined by means of tongue-and-grooving and gluing. All exposed wooden surfaces shall be evenly and smoothly dressed. The chest shall be assembled to true 90 degree angles. The lid shall fit down on the body with not more than 1/32 inch opening at any point. Steel binding shall fit flush to wood without ripples. Rivets shall be fabricated from rivet-grade steel wire, and shall have flat countersunk heads. Handles and hinge hasps shall be attached to the chest with rivets specified above, and applied so as not to interfere with the proper positioning of the removable tray. Corner braces shall be fabricated from low carbon sheet or strip steel specified in 3.2.1 having a thickness of 0.058 inch $\pm$ 0.007. Hinge bodies shall be fabricated from low carbon sheet or strip steel specified in 3.2.1 having a thickness of 0.075 inch $\pm$ 0.010 inch. Hinge pins shall be made of 3/16 inch diameter steel wire, shall be neatly headed, and shall fasten the leaves of the hinges securely. All wood screws shall be screwed into place and not driven. Predrilled holes for screws shall be no larger than the minor diameter of the screw and shall not exceed 3/8 inch in wood penetration.

3.5 Finish.

3.5.1 Wood surfaces preparation. After assembly of the wooden components of the chest, but before hardware components are attached, the inside and outside wooden surfaces, including partitions and tray, shall be sanded smooth and given one coat of wood sealer specified in 3.2.11.

3.5.2 Metal surface preparation. The surface of steel parts, excluding screws, rivets, padlock and chain, shall be given a cleaning and surface preparation treatment conforming to method 1, type 1 of TT-C-490.

3.5.3 Priming.

3.5.3.1 Lid and body. Prior to attachment of hardware, a coat of the primer specified in 3.2.9 shall be applied to all inside and outside surfaces of the lid and body. Forced drying is permitted, provided a surface temperature of 140°F is not exceeded and the relative humidity of the surrounding air is maintained between 30 to 50 percent. The coating shall level out to a dry uniform film thickness without objectionable orange peel, runs, wrinkles, drops, streaks, or areas of no film, and shall be free from grit or coarse particles. All parts shall be thoroughly dry prior to assembly of hardware.

3.5.3.2 Metal parts. All metal parts, excluding screws, rivets, padlock and chain, after the treatment specified in 3.5.2 and before assembly, shall be given a coat of primer specified in 3.2.9.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:34Z
Check the source to verify that this is the current version before use.

3.5.4 Enameling. Prior to the attachment of the hardware a coat of enamel specified in 3.2.10 shall be applied to all inside and outside surfaces of the lid and body. All parts shall be thoroughly dry prior to assembly of hardware. After complete assembly of the chest, all accessible surfaces (including the hardware components), shall be given a second coat of enamel. The enamel shall level out to produce a smooth and uniform film without objectionable orange peel, runs, wrinkles, drops, streaks or area of no film and shall be free of grit or coarse particles. All surfaces of the lid and body shall be thoroughly dry before stacking or packing.

3.6 Marking for identification. In accordance with MIL-STD-130, each chest shall be marked with the enamel specified in 3.2.10, in the location as shown on Drawing 10-1-529.

3.7 Workmanship. The chest shall have no splintered, jagged or sharp wood or metal edges. Nails shall be driven so as not to split the wooden members. Rivets shall not be over driven or protrude so as to cause damage to the chest. The end item shall conform to the quality of product established by this specification and the occurrence of defects shall not exceed the applicable acceptable quality levels.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.1.2 Responsibility for dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for ensuring that all specified dimensions have been met. When dimensions cannot be examined on the end item, inspection shall be made at any point, or

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:34Z
Check the source to verify that this is the current version before use.

at all points in the manufacturing process necessary to ensure compliance with all dimensional requirements.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required (see 3.1 and 6.2), it shall be examined for the defects specified in 4.4.3 and 4.4.4. The presence of any defect shall be cause for rejection of the first article.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.4.1.1 Component testing. Lumber shall be tested prior to machining for moisture content in accordance with ASTM D 4442 to determine conformance to 3.2.3. The lot shall be all the lumber offered to inspection at one time. The sample unit shall be one piece of lumber. Three determinations shall be made on each sample unit and the results shall be the average of the three determinations. The inspection level shall be S-2 and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 6.5.

4.4.2 In-process inspection. Prior to assembly, machined plywood and wood components shall be inspected for the defects listed in table I. The sample unit shall be one machined component. The lot shall be all the machined components offered for inspection at one time. The inspection level shall be I and the AQL, expressed in terms of defects per hundred units, shall be 4.0.

TABLE I. In-process inspection

Examine	Defect
Wood components	Not species specified Slope of grain exceeds 1 inch in 15 Evidence of decay, splits, wane, warp, and unsound knots

4.4.2.1 In-process examination. Examination shall be made during the manufacturing process to determine that the components are being fabricated in accordance with the specified requirements. Whenever nonconformance is noted, the affected items and processes shall be corrected. Items that cannot be corrected shall be removed from the process. The Government

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:34Z
Check the source to verify that this is the current version before use.

reserves the right to exclude from consideration for acceptance, any material or service for which in-process inspection has indicated nonconformance.

TABLE II. In-process examination

Examine	Requirement paragraph
a. Fabrication and dressing of wooden chest surfaces	3.4
b. Fitting of lid to body	3.4
c. Application of steel binding to chest	3.4
d. Attachment of hardware components to chest	3.4
e. Predrilling of holes and method for securing screws	3.4
f. Preparation of wood surfaces	3.5.1
g. Preparation of steel component surfaces	3.5.2
h. Priming of lid and body	3.5.3.1
i. Forced drying of primer coat (if applicable)	3.5.3.1
j. Priming of hardware components prior to assembly	3.5.3.2
k. Application of enamel coatings	3.5.4

4.4.3 End item visual examination. The end items shall be examined for the defects listed in table III. The lot size shall be expressed in units of chests. The sample unit shall be one chest. The inspection level shall be II and the AQL, expressed in terms of defects per hundred units, shall be 2.5 for major defects and 10 for total (major and minor combined) defects.

TABLE III. End item visual defects

Examine	Defect	Classification Major	Minor
Finish	Color of finish not as specified		201
	Finish is not smooth or uniform e.g., has runs, streaks, orange peel, wrinkles, drops		202
	Area of no film		203
	Wet or tacky finish	101	
	Not free of grit or coarse particles	102	

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:34Z
Check the source to verify that this is the current version before use.

TABLE III. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor
Workmanship	Chest not assembled to true 90° angles	103	
	Lid does not fit down into body	104	
	Steel binding does not fit flush to wood without ripples	105	
	Rivet heads not countersunk	106	
	Handles and hinges not attached as specified	107	
	Component missing	108	
	Component not securely attached or joined as specified	109	
	Lid does not align evenly with body when in the closed position - openings exceed 1/32 inch at any point	110	
	Splintered, jagged or sharp wooden or metal edge	111	
Fastening devices	Rivet not properly set, peened or clinched		204
	Rivet overdrawn or protruding from chest		205
	Screw not tight		206
	One rivet or screw missing		207
	More than one rivet or screw missing	112	
	Nail protrudes from or splits wooden member	113	
Identification marking	Missing, illegible, incorrect, wrong location, wrong color, or not as specified		208

4.4.4 End item dimensional examination. The end items shall be examined for conformance to the dimensions specified on the drawings. Only those dimensions that can be evaluated without damaging or disassembling the end items shall be examined. Any dimension not within the specified tolerance shall be classified as a defect. The lot size shall be expressed in units of chests. The sample unit shall be one chest. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 4.0.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:34Z
Check the source to verify that this is the current version before use.

4.4.5 Packaging examination. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application
Materials	Any component missing, damaged, or not as specified
Workmanship	Inadequate application of components, such as: incomplete sealing or closure of flap, improper taping, loose strapping, or inadequate stapling Bulged or distorted container
Content	Number per container is more or less than required

4.4.6 Palletization examination. The fully packaged and palletized end items shall be examined for the defects listed below. The lot size shall be expressed in units of palletized unit loads. The sample unit shall be one palletized unit load, fully packaged. The inspection level shall be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirement
Palletization	Pallet pattern not as specified Load not bonded as specified
Weight	Exceeds maximum load limits
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application

5. PACKAGING

5.1 Preservation. Preservation shall be level A.

5.1 Level A preservation. The tray shall be immobilized in place within each chest in a manner as to preclude movement or damage while in transit. Each chest shall be closed and the lid secured with the padlock provided. The keys shall be secured with the padlock provided. The keys shall be secured to the lock with not less than 0.072 inch diameter, commercially available annealed wire, and then further secured with pressure sensitive tape conforming to PPP-P-76 or PPP-T-60.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:34Z
Check the source to verify that this is the current version before use.

5.2 Packing. Packing shall be level A or Commercial as specified (see 6.2).

5.2.1 Level A packing. Each chest, preserved as specified in 5.1.1 , shall be protected with a solid fiberboard cap tray completely covering the top and extending down not less than 8 inches on all sides and ends of the chest. The cap tray shall be fabricated from fiberboard conforming to type SF, class domestic, grade 200 of PPP-F-320. The cap tray shall be secured to the chest with flat steel strapping, 3/8 inch wide by 0.015 inch thick, conforming to ASTM D 3953, or with type II or III nonmetallic strapping of ASTM D 3950 having a minimum breaking strength of 390 pounds. Three straps shall be used to secure the cap tray to the chest: (a) one lengthwise strap shall be centered and secured to the chest, and (b) two girthwise straps shall be equally spaced and secured to the chest. The bottom edges of the chest shall be protected from indentation by the steel strapping at each point of contact with edge protectors. The edge protectors may be eliminated when nonmetallic strapping is used.

5.2.2 Commercial packing. Chest, preserved as specified in 5.1.1 shall be packed in accordance with ASTM D 3951.

5.3 Palletization. When specified (see 6.2) chests packed as specified in 5.2 shall be palletized in accordance with load type I of MIL-STD-147. Each prepared load shall be bonded with straps in accordance with bonding means C and D or film bonding means F or G. Pallet pattern shall be in accordance with the appendix of MIL-STD-147.

5.4 Marking. In addition to any special marking required by the contract or purchase order, each chest and palletized unit load shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable. All markings shall be printed or stenciled on the fiberboard cap tray. Markings shall not be applied directly to the surface of the chest. Service color marking and symbol are not required on containers when addressed to domestic establishments.

5.4.1 Name of item. The following nomenclature shall be used for identification purposes: "Chest, Medical Equipment Maintenance and Repair Tool Kit".

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The chest is intended to be used to contain and protect selected tools and equipment required for maintenance and repair of medical service equipment.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:34Z
Check the source to verify that this is the current version before use.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this specification.
b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
c. When a first article is required (see 3.1, 4.3, and 6.3).
d. Color, if other than specified (see 3.2.10).
e. Levels of packing required (see 5.2).
f. When palletization is required (see 5.3).

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of Federal Acquisition Regulation (FAR) 52.209-4. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

6.4 Subject term (key word) listing.

Container
Storage

6.5 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:

Army - GL

Review activity:

Army - MD

Civil agency coordinating activity:

GSA - FSS

Preparing activity:

Army - GL

(Project 5140-A108)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:34Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-C-3363D(GL)	1992 October 26

3. DOCUMENT TITLE

CHEST, MEDICAL EQUIPMENT MAINTENANCE AND REPAIR TOOL KIT

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code) (1) Commercial	(2) AUTOVON/DSN
U.S. Army Natick RD&E Center	508-651-4531	256-4531
c. ADDRESS (Include Zip Code) Commander, U.S. Army Natick RD&E Center ATTN: SATNC-UXT Natick, MA 01760-5017	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

DD Form 1426, OCT 89 NATICK OP3, JUL 91 Previous editions are obsolete. 1987

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:34Z
Check the source to verify that this is the current version before use.