MIL-C-3367C

8 Arpil 1968
SUPERSEDING
MIL-C-003367B(MU)
16 May 1966
MIL-C-3367A
6 September 1957

MILITARY SPECIFICATION

CANISTER, SMOKE, FOR CHEMICAL

SHELL (BASE EJECTION); COMPONENTS FOR

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the components for canisters for 3 sized of base ejection shells.

2. APPLICABLE DOCUMENTS

2.1 Government documents. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

DRAWINGS

US ARMY MUNITIONS COMMAND

EDGEWOOD ARSENAL

C15-11-44 - Canister, Smoke, HC, M1, For 75 MM Chemical Shell T19 (Base Ejection) - Bill of Material.
C15-11-63 - Canister, Smoke, Colored, M2, For 75 MM Chemical Shell T19 (Base Ejection) - Bill of Material.

FSC 1315
FSC 1320

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:34Z
Check the source to verify that this is the current version before use.

DL15-11-22 - Canister, Smoke, HC, 105 MM Shell, M1.
DL15-11-60 - Canister, Colored Smoke, 105 MM Shell, M2.
DL15-11-33 - Canister, Smoke, HC, 155 MM Shell, M1.
DL15-11-41 - Canister, Smoke, HC, 155 MM Shell, M2.
D15-11-66 - Canister, Colored Smoke, 155 MM Shell, M3-Bill of Material.
D15-11-69 - Canister, Colored Smoke, 155 MM Shell, M4-Bill of Material.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

UNIFORM CLASSIFICATION COMMITTEE

Uniform Freight Classification

(Application for copies of these ratings, rules and regulations should be addressed to Uniform Classification Committee, 202 Union Station, 516 West Jackson Boulevard, Chicago, Illinois 60606.)

3. REQUIREMENTS

3.1 Materials and components.

3.1.1 Materials. All materials cited on the applicable drawings (see 6.2) or on the subsidiary drawings shall conform to the specifications listed thereon or to the specific characteristics set forth on the drawings.

3.1.2 Components. All components of the canister shall conform to the specifications and drawings listed on the applicable drawing (see 6.2) and subsidiary drawings.

3.2 Assembly. The components of the canister shall be assembled in accordance with the applicable drawing (see 6.2).

3.3 Workmanship. The components of the canister shall be free from contamination (foreign matter, oil or grease) and damage such as dents, cracks or deformations which could affect their intended use.



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:34Z
Check the source to verify that this is the current version before use.

## 4. QUALITY ASSURANCE PROVISIONS

### 4.1 Responsibility for inspection.

4.1.1 Supplier's responsibility. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.2 Objective evidence. The supplier shall provide objective evidence acceptable to the contracting officer that the requirements of 3.1 for which specific inspection has not been provided in this specification have been satisfied.

### 4.2 Quality conformance inspection.

4.2.1 Lotting. A lot shall consist of like components of one interfix number, produced by one manufacturer, from the same materials, under essentially the same manufacturing conditions.

4.2.2 Sampling.

4.2.2.1 For examination. Sampling shall be conducted in accordance with MIL-STD-105.

4.2.3 Inspection procedure.

4.2.3.1 For examination. Sample components shall be examined in accordance with the classification of defects and MIL-STD-105.

4.2.3.2 For critical defects. Each component shall be examined for the critical characteristic listed in the classification of defects.



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:34Z
Check the source to verify that this is the current version before use.

4.2.3.3 Classification of defects.

(a) Disk, closing (Dwg as specified - 6.2).

| Categories | Defects |
|---|---|
| Critical: | None defined |
| Major: | AQL 1.0 percent defective |
| 101 | Outside diameter incorrect |
| 102 | Hole eccentric with outside diameter |
| 103 | Workmanship (3.3) |
| Minor: | AQL 2.5 percent defective |
| 201 | Hole diameter incorrect |
| 202 | Coating incorrect |
| 203 | Edge radius incorrect |

(b) Body, assembly (Dwg as specified - 6.2).

| Categories | Defects |
|---|---|
| Critical: | |
| 1 | Tube to body weld incorrect |
| Major: | AQL 1.0 percent defective |
| 101 | Body open end cracks or tears |
| 102 | Tube welded and protrusion incorrect |
| 103 | Body outside diameter (both ends of tapered design) incorrect |
| 104 | Body open end not in plane perpendicular to tube, or irregular |
| 105 | Tube diameter incorrect |
| 106 | Central tube excessively open near closed end of body |
| 107 | Body length incorrect |
| 108 | Vent hole missing |
| 109 | Tube length incorrect |
| 110 | Workmanship (3.3) |



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:34Z
Check the source to verify that this is the current version before use.

(b) Body, assembly (Dwg as specified - 6.2) (continued).

| Categories | Defects |
|---|---|
| Minor: | AQL 2.5 percent defective |
| 201 | Tube slits (min depth) incorrect |
| 202 | Number of tube slits incorrect |
| 203 | Coating incorrect |

(c) Sleeve (Dwg as specified - 6.2).

| Categories | Defects |
|---|---|
| Critical: | None defined |
| Major: | AQL 1.0 percent defective |
| 101 | Length incorrect |
| 102 | Inside diameter incorrect |
| 103 | Thickness incorrect |
| 104 | Workmanship (3.3) |

5. PREPARATION FOR DELIVERY

5.1 Packaging, level C. The canisters shall be packaged to provide adequate protection against corrosion, deterioration, and damage from the supply source to the first receiving activity for immediate use or for controlled humidity storage.

5.2 Packing, level C. Canisters, packaged as specified in 5.1, shall be packed to insure carrier acceptance and safe delivery to the first domestic destination. Containers shall be in compliance with Uniform Freight Classification rules or the regulations of other common carriers applicable to the mode of transportation.

5.3 Marking. In addition to any special marking required by the contract or order, unit packages, intermediate packages, and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. These components are intended for canisters for the 75 MM, 105 MM and 155 MM smoke shell.



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:34Z
Check the source to verify that this is the current version before use.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Title, number, and date of applicable drawings.

Custodians:

Army - MU
Navy - OS

Preparing activity:

Army - MU (EA)

Review activity:

Air Force - 70

Project No. 1320-0054



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:34Z
Check the source to verify that this is the current version before use.