INCH-POUND

MIL-C-3372F
12 December 1990
SUPERSEDING
MIL-C-3372E
13 September 1982

MILITARY SPECIFICATION

CASE, TENTAGE REPAIR KIT

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers one type and size tentage repair kit case made of cotton duck and webbing.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be used in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8340

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:35Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

C-F-206	-	Felt, Sheet: Cloth, Felt, Wool, Pressed
T-T-881	-	Twine, Cotton, Seine
V-T-285	-	Thread, Polyester
KK-L-271	-	Leather, Cattlehide, Strap, Vegetable-Tanned
CCC-C-419	-	Cloth, Duck, Cotton, Unbleached, Plied-Yarns, Army and Numbered
CCC-D-950	-	Dyeing and Aftertreating Processes for Cotton Cloths
DDD-L-20	-	Label, for Clothing, Equipage and Tentage, (General Use)
PPP-B-636	-	Boxes, Shipping, Fiberboard

MILITARY

MIL-C-496	-	Clips, End, Strap
MIL-W-530	-	Webbing, Textile, Cotton, General Purpose, Natural or in Colors
MIL-B-543	-	Buckles, Tongueless and Web Strap
MIL-F-2312	-	Felt, Hair or Wool: Mildew Resistant and Moisture Resistant Treatment for
MIL-R-3390	-	Rings, Dee
MIL-F-10884	-	Fasteners, Snap
MIL-T-43566	-	Tape, Textile, Cotton or Polyester, General Purpose, Natural or in Colors

STANDARDS

FEDERAL

FED-STD-751	-	Stitches, Seams and Stitchings

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	-	Marking for Shipment and Storage
MIL-STD-147	-	Palletized Unit Loads

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:35Z
Check the source to verify that this is the current version before use.

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS

US ARMY NATICK RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER

5-7-54	-	Case, Tentage Repair Kit; Illustration, Assemblies and Details.
5-7-55	-	Case Tentage Repair Kit; Assemblies and Details.
5-7-56	-	Case Tentage Repair Kit; Details.

(Copies of drawings are available from the U.S. Army Natick Research, Development, and Engineering Center, ATTN: STRNC-EMSS, Natick, MA 01760-5014.)

2.2 Non-Government publications. The following document forms a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3951 - Standard Practice for Commercial Packaging

(Copies may be obtained from the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:35Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection (see 6.3), in accordance with 4.3.

3.2 Materials. The materials shall be as specified herein, and as indicated on drawings 5-7-54, 5-7-55 and 5-7-56. It is encouraged that recycled material be used when practical as long as it meets the requirements of this specification.

3.2.1 Cloth, duck, cotton. Cloth, before finishing, shall conform to type I, No. 6, hard texture of CCC-C-419 for the body of the case and to type III, 8.25 ounces per square yard of CCC-C-419 for pockets "D" and bags for rings and grommets.

3.2.1.1 Color and treatment. The finished cloth shall conform to type I, class B of CCC-D-950, shade Olive Drab 7.

3.2.2 Tape, textile, cotton. Cotton tape shall conform to type I, class 4 of MIL-T-43566, 1-inch width, shade Olive Drab 7.

3.2.3 Webbing, textile, cotton. Cotton webbing shall conform to type II and type IIb, class 4 of MIL-W-530, shade Olive Drab 7. Type II webbing shall be 2-inch width and type IIb shall be one inch width.

3.2.4 Thread, polyester. The thread shall conform to type I, class 1, sub-class B, dyed to match shade Olive Drab S-1 (CA 66022) of V-T-285. Dyed thread shall show fastness to chlorine bleaching equal to or better than the standard shade sample. If no standard shade sample is available, the thread shall show good fastness to weathering. Thread sizes shall be as follows:

For all stitching except overedge stitching	Size FF for needle and bobbin
For overedge stitching	Size E

3.2.5 Felt. The pressed wool felt shall conform to type I, classification number 9R5, of C-F-206 and shall be mildew resistant treated to conform to type I of MIL-F-2312.

3.2.6 Leather. The leather shall conform to any type, class 1 of KK-L-271, 6 ounce color russet. Application of a finish to the grain side is not required.

3.2.7 Twine, cotton, seine. The cotton seine twine shall conform to type II, size number 120 of T-T-881.

3.2.8 Buckle, tongueless, 2-bar. The buckles shall conform to type II, style 1, class 1 of MIL-B-543.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:35Z
Check the source to verify that this is the current version before use.

3.2.9 Clip, end, strap. The end clips shall conform to type I, class 1, size 1-inch of MIL-C-496.

3.2.10 Fasteners, snap. The snap fasteners shall conform to style 1, finish 2, regular prong socket and stud, eyelet base with washer, size 1; and style 2, finish 2, button, 24 line, size 1, of MIL-F-10884.

3.2.11 Ring, dee. The dee ring shall conform to configuration K, class 1 or 2, size 1-inch of MIL-R-3390.

3.3 Construction. The construction of the case and bags for rings and grommets shall conform to the drawings listed in section 2 and as specified herein.

3.3.1 Stitching, machine.

3.3.1.1 Types of stitching. All stitch types shall conform to FED-STD-751 as follows:

For all stitching except overedge stitching	Type 301, 6 to 8 stitches per inch
For overedge stitching	Type 304, 14 to 16 stitches per inch; types 502, 504, or 505, 6 to 8 stitches per inch

3.3.1.2 Thread breaks. Thread breaks in stitching shall be overstitched not less than 1 inch at each break on stitch type 301 and not less than 3/4 inch at each break on stitch types 304, 503, 504 or 505. Thread breaks noted during inspection shall be repaired by starting the overstitching at least 1 inch before the break and ending it at least 1 inch beyond the break. The ends of repair stitching are not required to be backstitched.

3.3.1.3 Stitching ends. The ends of type 301 stitching shall be overstitched not less than 1 inch except where ends are turned under in a hem or held down by other stitching. Where 301 stitching is perfomed automatically on stitch patterns such as box, box with cross-stitch, "W" stitching or straight line tacking, at least 3 or more tying, overlapping or backstitches shall be used to secure the ends of stitching. The ends of type 304, 503, 504 or 505 stitching shall be firmly secured by backstitching or overstitching or by increasing the number of stitches per inch at the ends for a minimum of 1/4 inch.

3.3.1.4 Skipped stitches. Two or more consecutively skipped stitches occurring in type 301, 304, 503, 504, or 505 stitching shall be overstitched not less than 1 inch. Skipped stitches noted during inspection shall be repaired in the same manner as specified under thread breaks.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:35Z
Check the source to verify that this is the current version before use.

3.3.1.5 Lubrication of thread. The addition of any lubricant to the polyester thread prior to or during the sewing operation is prohibited (see 4.4.1).

3.3.2 Setting of end clips. The webbing shall be inserted the full depth of the clip. Clips shall be securely attached without cutting the webbing and the webbing shall lie flat at the point of entrance.

3.3.3 Setting of snap fasteners.

3.3.3.1 Style 1. The hole for the male part of the snap fastener shall be formed when the fastener is driven into the material. The hole punched before insertion of the female part of the fastener shall be no larger than that made by a standard number 10 round drive punch (5/16 inch diameter hole). Fasteners shall be securely clinched. Not more than one score or split shall be allowed on the roll of the eyelet base of the stud.

3.3.3.2 Style 2. When a hole is punched before insertion of the male or female part of the fastener it shall be smaller than the outside diameter of the fastener tube so that the tube must be forced through the hole. Fasteners shall be securely clinched. Not more than one score of split shall be allowed on the roll of the eyelet of either male or female half of the fastener.

3.4 Marking. Identification marking shall be applied in the location shown on the drawing and shall conform to type IV, class 5 labels of DDD-L-20. The letters "U.S.", the item name, list of contents, pocket numbers and bag markings shall be located and applied in the size characters indicated on the drawings and shall conform to type IV, class 9 labels of DDD-L-20. Fastness of class 9 marking shall be as specified for the class 5 labels.

3.5 Workmanship. Cloth components shall be clean and free of holes, cuts, tears or cloth defects such as multiple floats or broken or missing yarns. Webbing and tape shall not have frayed or scalloped edges. Thread tension shall be maintained so that there will be no loose stitching and seam allowances shall be maintained with seams properly sewed so that no runoffs, twists, pleats or open seams shall result. Care shall be taken in sewing to see that no needle chews occur. All thread ends shall be trimmed to 1/2 inch or less. Metal components shall be free of burrs, sharp edges, or corroded areas and shall not be broken or malformed. The end items shall conform to the quality of product established by this specification and the occurence of defects shall not exceed the applicable acceptable quality levels.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:35Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.1.2 Responsibility for dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for ensuring that all specified dimensions have been met. When dimensions cannot be examined on the end item, inspection shall be made at any point, or at all points in the manufacturing process necessary to ensure compliance with all dimensional requirements.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3)
b. Quality conformance inspection (see 4.4)

4.3 First article inspection. When a first article is required (see 3.1 and 6.2), it shall be examined for the defects specified in 4.4.3 and 4.4.4. Any non-conformance shall be cause for rejection of the first article.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:35Z
Check the source to verify that this is the current version before use.

4.4.2 In-process inspection. Inspection shall be made during the manufacturing process to insure that no lubrication of the polyester thread occurs prior to or during sewing operations for compliance with 3.3.1.5. In addition, inspection shall be made to insure that holes punched to receive female part of style 1 snap fasteners or male and female part of style 2 snap fasteners shall be smaller in diameter than the tube of the parts to be inserted for compliance with 3.3.3. Whenever nonconformance is noted, corrections shall be made to the parts affected and lot in-process. Components which cannot be corrected shall be removed from production.

4.4.3 End item visual examination. The end items shall be tested for the characteristics listed in table I. The lot size shall be expressed in units of repair kit cases. The sample unit shall be one complete repair kit case. The inspection level shall be II and the acceptable quality level (AQL) expressed in terms of defects per hundred units, shall be 4.0 for major defects and 10 for total (major and minor A and minor B combined) defects.

Table I. End item visual examination.

Examine	Defect	Classification Major	Minor A	Minor B
Fabric	Any hole, cut or tear	101		
	Broken or missing yarn, multiple floats clearly visible at normal inspection distance (approximately 3 feet)		201	
Felt	Any hole, cut or tear		202	
Leather (shears scabbard)	Hole, cut or tear	102		
	Loose, spongy, flanky, weak or thin spot		203	
	Scabbard not removable from pocket; corners not clipped as specified			301
	Fabricated with flesh side on inside		204	
	Not color specified			302
Hardware	Broken	103		
	Malformed:			
	- fails to perform intended function	104		
	- will perform intended function		205	

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:35Z
Check the source to verify that this is the current version before use.

Table I. End item visual examination. (cont'd)

Examine	Defect	Classification Major	Minor A	Minor B
Hardware (cont'd)	Corroded area			303
	Burr or sharp edge which may cause injury in handling or damage to fabric	105		
End clips	Webbing not flat at point of entrance into clip			304
	Clinched tight, cutting webbing	106		
Seams and stitching	Open seam on stitch type 301:			
	- for more than 1 inch	107		
	- for more than 1/2 inch but not more than 1 inch		206	
	- for more than 1/4 inch but not more than 1/2 inch			305
	NOTE: A seam shall be classified as open when one or more stitches joining a seam are broken, or when one or more skipped or runoff stitches occur. On double stitched seams, a seam shall be classified as open when either one or both sides of a seam are open.			
	Raw edges caught in stitching (except end of inside binding):			
	- more than 1 inch		207	
	- more than 1/2 inch but not more than 1 inch			306
	Thread breaks:			
	- overstitched less than 1 inch on stitch type 301			307
	- overstitched less than 3/4 inch on stitch type 304			308
	NOTE: Thread breaks not overstitched shall be classified as open seams.			

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:35Z
Check the source to verify that this is the current version before use.

Table I. End item visual examination. (cont'd)

Examine	Defect	Classification Major	Minor A	Minor B
Seams and stitching (cont'd)	Needle chew resulting in hole, cut or tear	108		
	Skipped stitches overstitched less than 1 inch on stitch type 301, 304, 503, 504, or 505 when 2 or more skipped stitches occur consecutively			309
	NOTE: Skipped stitches not overstitched shall be classified as open seams.			
	One or more required rows of stitching omitted (except on boxstitching)	109		
Boxstitching	Incomplete:			
	- one row of stitching omitted			310
	- two or more rows of stitching omitted		208	
	Any boxstitching less than specified length by more than 1/8 inch			311
Stitching ends	Overstitched less than 1 inch on stitch type 301 (except where ends are held down by other stitching, turned under in a hem, or where stitching is performed automatically)		209	
	Secured with less than 3 tying, overlapping or backstitches where automatic stitching is performed			312
	Secured with less than 1/4 inch of backstitching, overstitching or by an increased number of stitches at the end of stitch type 304, 503, 504, or 505			313
Seam type	Wrong seam type	110		
Stitch type	Wrong stitch type		210	
Stitch tension	Loose, resulting in exposed bobbin or top thread for more than 2 inches			314
	Tight, as evidenced by puckering of fabric for more than 2 inches		211	

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:35Z
Check the source to verify that this is the current version before use.

Table I. End item visual examination. (cont'd)

Examine	Defect	Classification Major	Minor A	Minor B
Stitches per inch	Less than minimum specified:			
	- one stitch			315
	- two or more stitches		212	
	NOTE: Variation in the number of stitches per inch caused by the operator speeding up the machine and pulling the fabric in order to sew over heavy seams or heavy places or in turning corners shall be classified as follows:			
	a. Within the minor B defect classification - no defect			
	b. Within the minor A defect classification - minor B defect			
Stitching margin	Larger than specified by more than 1/8 inch:			
	- for more than 1 inch but not more than 2 inches in length			316
	- for more than 2 inches in length		213	
	Less than specified:			
	- for more than 1 inch but not more more than 2 inches in length			317
	- for more than 2 inches in length		214	
Components and assembly	Any component part missing or not fabricated of applicable referenced material	111		
Construction details				
Facing	Ends of facing A or B not caught in binding stitching		215	
Pockets and bags	Fold of pocket piece B not formed as specified, or not stitched through body and handle where applicable		216	

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:35Z
Check the source to verify that this is the current version before use.

Table I. End item visual examination. (cont'd)

Examine	Defect	Classification Major	Minor A	Minor B
Pockets and bags (cont'd)	Stitching across bottom of pockets 6 through 9 omitted, or interferes with clearance in pockets 5 or 10		217	
Drawstring	Drawstring cut or abraded		218	
	Drawstring caught in hem stitching causing failure to draw freely		219	
	Drawstring hem improperly formed, badly puckered, twisted or pleated			318
Binding	Loosely or improperly applied: - badly pleated			319
	- ends of binding not finished as specified			320
Buckle chape and strap	Buckle reversed		220	
	Misplaced; i.e. failing to effect a smooth and secure closure		221	
	Chape reinforcement improperly applied	112		
Handles	Set beyond location indicated on drawing by more than 1/4 inch		222	
	Edges of grip section overlapped; edges not folded or not stitched as indicated on drawing		223	
	Ends of carrying strap not finished as specified		224	
Snap fasteners	Not functioning properly	113		
	Not securely clinched, allowing components to separate	114		
	Clinched excessively tight, cutting surrounding fabric	115		
	Two or more splits on roll of any eyelet		225	
Marking: "U.S.", nomenclature, identification, list of contents, numbering of pockets	Omitted, incorrect, illegible or size of characters not as specified		226	

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:35Z
Check the source to verify that this is the current version before use.

Table I. End item visual examination. (cont'd)

Examine	Defect	Classification Major	Minor A	Minor B
Cleanness	Grease or oil stains		321	
	Thread ends not trimmed to 1/2 inch or less throughout			322
	Ink spots or stains	227		

4.4.4 End item dimensional examination. The end items shall be examined for conformance to the dimensions specified on the drawings. Only those dimensions that can be evaluated without damaging or disassembling the end items shall be examined. Any dimension not within the specified tolerance shall be classified as a defect. The lot size shall be expressed in units of repair kit cases. The sample unit shall be one complete repair kit case. The inspection level shall be S-3 and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

4.4.5 Packaging examination. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application
Materials	Any component missing, damaged, or not as specified
Workmanship	Inadequate application of components, such as: incomplete sealing or closure of flap, improper taping, loose strapping or inadequate stapling Bulged or distorted container
Content	Number per container is more or less than required

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:35Z
Check the source to verify that this is the current version before use.

4.4.6 Palletization examination. The fully packaged and palletized end items shall be examined for the defects listed below. The lot size shall be expressed in units of palletized unit loads. The sample unit shall be one palletized unit load, fully packaged. The inspection level shall be S-1 the AQL, expressed in terms of defects per hundred units, shall be 6.5.

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirement
Palletization	Pallet pattern not as specified Load not bonded as specified
Weight	Exceeds maximum load limits
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial as specified (see 6.2).

5.1.1 Level A preservation. Each case shall be laid out flat with flaps extended. The two cotton bags shall be placed within the large pocket and the pocket then pressed flat by hand. The "A" billets shall be laid out flat, the "B" billets shall be folded over and laid flat, and the flaps snap fastened. The case shall then be folded in half and securely closed by buckling the "C" billets. The case shall again be folded in half with the U.S. facing up. The folded case shall measure 16-1/2 inches in length, 9-3/4 inches in width and 2-1/4 inches in depth.

5.1.2 Commercial preservation. Each complete tentage repair kit case shall be preserved in accordance with ASTM D 3591.

5.2 Packing. Packing shall be level A, B, or Commercial as specified (see 6.2).

5.2.1 Level A packing. Twenty cases, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container, conforming to style RSC-L, grade V2s of PPP-B-636. The inside of each shipping container shall be fitted with a box liner conforming to type CF, class weather-resistant, variety DW, grade V15c of PPP-B-636. Level A unit packs shall be packed on end 10 in

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:35Z
Check the source to verify that this is the current version before use.

length, 2 in width, and 1 in depth within a shipping container. Inside dimensions of each container shall approximate 22-1/2 inches in length, 19-1/2 inches in width, and 16-1/2 inches in depth. Approximate dimensions are furnished as a guide only. Each shipping container shall be closed in accordance with method III, waterproofed in accordance with method V, and reinforced as specified in the appendix of PPP-B-601, except that the inspection shall be in accordance with 4.4.5.

5.2.2 Level B packing. Twenty cases, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container, conforming to style RSC-L, type CF (variety SW) or SF, class domestic, grade 275 of PPP-B-636. The inside of each shipping container shall be fitted with a box liner conforming to type CF, class domestic, variety DW, grade 275 of PPP-B-636. Level A unit packs shall be packed on end 10 in length, 2 in width and 1 in depth within a shipping container. Inside dimensions of each container shall approximate 22-1/2 inches in length, 19-1/2 inches in width and 16-1/2 inches in depth. Approximate dimensions are furnished as a guide only. Each shipping container shall be closed in accordance with method II as specified in the appendix of PPP-B-636, except that the inspection shall be in accordance with 4.4.5.

5.2.2.1 Weather-resistant fiberboard container. When specified, (see 6.2) the shipping container shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of the container specification, except the inspection shall be in accordance with 4.4.5.

5.2.3 Commercial packing. Cases, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

5.3 Palletization. When specified (see 6.2), tentage repair kit cases, packed as specified in 5.2.1, 5.2.2 and 5.2.3, shall be palletized on a 4-way entry pallet in accordance with load type Ia of MIL-STD-147. Pallet types shall be type I (4-way entry), type IV, or type V in accordance with MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with the bonding means C and D or film bonding F or G. Pallet pattern shall be number 6 in accordance with the appendix of MIL-STD-147.

5.4 Marking. In addition to any special marking required by the contract or purchase order, shipping containers and palletized unit loads shall be marked in accordance with MIL-STD-129 or ASTM D 3951 as applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:35Z
Check the source to verify that this is the current version before use.

5.4.1 Special markings. Special markings for type I shelf life items shall be in accordance with the shelf life markings required in the appendix of MIL-STD-129. Additionally, shipping containers and palletized unit loads shall be marked as follows:

1. Repair kit cases includes adhesive - 8 cans each
   NSN: 8440-00-266-0850
   Expiration date:

2. Repair kit cases includes lubricant - 1 box each
   NSN: 9150-00-999-7548
   Expiration date:

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The repair kit case is designed to contain tools, materials, and components used in the repair of tentage items. This specification does not cover the contents of the case (see 6.4).

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this specification.
b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
c. When a first article is required (see 3.1, 4.3, and 6.3).
d. Levels of preservation and packing (see 5.1 and 5.2).
e. When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).
f. When palletization is required (see 5.3).

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of Federal Acquisition Regulation (FAR) 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:35Z
Check the source to verify that this is the current version before use.

6.4 List of contents. The list of contents of the case for general information is:

List of contents

Pocket No.	Item	Quantity
1	Cloth duck, cotton, OD, 9.85 ounce, FWWMR	2 yards
1	Cloth, duck, polyester, FWWR, Army Desert Tan, Shade 459	2 yards
1	Cloth, duck polyester, FWWR, Camouflage Green 483	2 yards
1	Grommet, metallic, black chemical finish, rolled rim w/washer, spur type, No 4 (in bag)	1 gross
1	Grommet, metallic, black chemical finish, rolled rim w/washer, spur type, No 5 (in bag)	1 hundred
1	Mallet, rawhide, 2-3/4 inch face	1 each
1	FM 10-16, Field Manual General Repair for Tents, Canvas and Webbing	1 each
1	Palm, sewing	1 each
1	Punch and die, inserting, spur grommet No. 4 (in bag)	1 each
1	Punch and die, inserting, spur grommet No. 5 (in bag)	1 each
1	Ring, connecting, round, galvanized, 1/2 inch (in bag)	50 each
1	Ring, connecting, round, galvanized, 3/4 inch (in bag)	25 each
1	Ring, connecting, round, galvanized, 1 inch (in bag)	10 each
1	Sling, carrying, bag and case	1 each
1	Slip, tent line, magnesium casting	10 each

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:35Z
Check the source to verify that this is the current version before use.

List of contents (cont'd)

Pocket No.	Item	Quantity
1	Twine, cotton, wrapping, 5-ply, MRT	1 cone or 2 pounds
2	Thread, polyester, type I or II, class 1, size FF	1 tube
2, 3	Adhesive, nitrile butadiene rubber, tent patching (6 oz cans)	8 cans
4	Needle, sailmaker's, No. 14	12 each
5	Brush, wire, scratch	1 each
6	Punch, cutting, for No. 4 grommet	1 each
7	Awl, saddler's sewing	1 each
8	Lubricant, slide fastener	1 box (24 sticks)
9	Punch, cutting, for No. 5 grommet	1 each
10	Shears, bent trimmers, length overall, 10 inches	1 each

6.5 International standardization agreements. Certain provisions of this specification are the subject of international standardization agreement as cited in NATO, STANAG No. 2882, relative to camouflage requirements for tents, shelters and subsidiary components. When amendment, revision, or cancellation of this specification is proposed which will affect or violate the international standardization agreement concerned, the preparing activity will take appropriate reconciliation action through international standardization channels including departmental standardization offices, if required.

6.6 Subject term (key word) listing.

Maintenance
Restore shelter

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:35Z
Check the source to verify that this is the current version before use.

6.7 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:

Army - GL
Navy - MC
Air Force - 99

Review activities:

Army - MD
Air Force - 82
DLA - CT

User activity:

Air Force - 45

Preparing activity:

Army - GL

(Project 8340-0543)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:35Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-C-3372F	1990 December 12

3. DOCUMENT TITLE

CASE, TENTAGE REPAIR KIT

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code)	
U.S. Army Natick RD&E Center	(1) Commercial 508-651-4531	(2) AUTOVON 256-4531
c. ADDRESS (Include Zip Code) Commander, U.S. Army Natick RD&E Center ATTN: STRNC-UXT Natick, MA 01760-5017	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:35Z
Check the source to verify that this is the current version before use.