INCH POUND

MIL-DTL-3372G
4 February, 2000

SUPERSEDING
MIL-C-3372F
12 December 1990

DETAILED SPECIFICATION

CASE, TENTAGE REPAIR KIT

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers one type and size tentage repair kit case made of cotton duck and webbing.

2. APPLICABLE DOCUMENTS

* 2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements documents cited in sections 3 and 4 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issue of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Defense Supply Center Philadelphia, Clothing and Textiles Directorate, Attn: DSCP-CNR, 700 Robbins Avenue, Building 6D, Philadelphia, PA 19111-5094, by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:35Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

C-F-206	- Felt, Sheet: Cloth, Felt, Wool, Pressed
A-A-2917	- Twine, Cotton, Seine
V-T-295	- Thread, Nylon
KK-L-271	- Leather, Cattlehide, Strap, Vegetable-Tanned
DDD-L-20	- Label, for Clothing, Equipage and Tentage, (General Use)

MILITARY

MIL-C-496	- Clips, End, Strap
MIL-W-4088	- Webbing, Textile, Woven Nylon
MIL-B-543	- Buckles, Tongueless and Web Strap
MIL-F-2312	- Felt, Hair or Wool: Mildew Resistant and Moisture Resistant Treatment for
MIL-R-3390	- Rings, Dee
MIL-F-10884	- Fasteners, Snap
MIL-T-5038	- Tape, Textile and Webbing, Textile, Reinforcing, Nylon
MIL-C-43734	- Cloth, Duck, Textured Nylon

(Unless otherwise indicated, copies of federal and military specifications, standards and handbooks are available from the Defense Automated Printed Service, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

* 2.2.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein.

DRAWINGS

U.S. ARMY NATICK RESEARCH, DEVELOPMENT & ENGINEERING CENTER

5-7-54	- Case, Tentage Repair Kit; Illustration, Assemblies and Details.
5-7-55	- Case, Tentage Repair Kit; Assemblies and Details.
5-7-56	- Case Tentage Repair Kit; Details.

(Copies of drawings are available from the U.S. Army Natick Research, Development and Engineering Center, ATTN: SSCNC-EMSS, NATICK, MA 01760-5017.)

* 2.3 Non-Government publications. The following document forms a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DoDISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DoDISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:35Z
Check the source to verify that this is the current version before use.

D 6193 - Seams, Stitching and Sewing

(Copies may be obtained from the American Society for testing and Materials, 100 Barr Harbor Drive, West Conshohocken, PA 19428.)

* 2.4 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification takes precedence. Nothing in this specification, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. **REQUIREMENTS**

3.1 First article. When specified, (see 6.2), a sample shall be subjected to first article inspection (see 4.2 and 6.2).

3.2 Materials and components. Materials and components shall be as specified herein and in referenced documents and drawings. Materials not definitely specified shall be of the quality normally used by the manufacturer provided the complete item complies with all provisions of this document. It is encouraged that recycled material be used when practical as long as it meets the requirements of this document.

* 3.2.1 Cloth, Duck, Textured Nylon. The cloth for the body and pockets shall be conform to class 3 of MIL-C-43734, shade Camouflage green 483.

3.2.2 Tape, textile and webbing, textile, reinforcing nylon. The nylon tape shall conform to type II, class 2 of MIL-T-5038, shade Camouflage green 483.

3.2.3 Webbing, textile, woven, nylon. The nylon webbing shall conform to type II and type XV of MIL-W-4088, shade Camouflage green 483. Type II will be 1 inch wide and type XV will be 2 inches wide.

3.2.4 Thread, Nylon. The thread shall conform to type I, class A of V-T-295, and shall be dyed to match olive drab S-1. Dyed thread shall show fastness to chlorine bleaching equal to or better than the standard shade sample. If no standard shade sample is available, The thread shall show good fastness to weathering. Thread sizes shall be as follows:

For all stitching except overedge stitching	Size FF for needle and bobbin
For overedge stitching	Size E

3.2.5 Felt. The pressed wool felt shall conform to type I, classification number 9R5, of C-F-206 and shall be mildew resistant treated to conform to type I of MIL-F-2312.

3.2.6 Leather. The leather shall conform to any type, class 1 of KK-L-271, 6 ounce color russet. Application of a finish to the grain side is not required.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:35Z
Check the source to verify that this is the current version before use.

3.2.7 Twine, cotton, seine. The cotton seine twine shall conform to size number 120 of A-A-2917.

3.2.8 Buckle, tongueless, 2-bar. The buckles shall conform to type II, style 1, class 1 of MIL-B-543.

3.2.9 Clip, end, strap. The end clips shall conform to type I, class 1, size 1-inch of MIL-C-496.

3.2.10 Fasteners, snap. The snap fasteners shall conform to style 1, finish 2, regular prong socket and stud, eyelet base with washer, size 1; and style 2, finish 2, button, 24 line size 1, of MIL-F-10884.

3.2.11 Ring, dee. The dee ring shall conform to configuration K, class 1 or 2, size 1-inch of MIL-R-3390.

3.3 Construction. The construction of the case and bags for rings and grommets shall conform to the drawings listed in section 2 and as specified herein.

3.3.1 Stitching.

3.3.1.1 Types of stitching. All stitch types shall conform to ASTM – D 6193 as follows:

For all stitching except overedge stitching	Type 301, 6 to 8 stitches per inch
For overedge stitching	Type 304, 14 to 16 stitches per inch; types 502, 504, or 505, 6 to 8 stitches per inch

3.3.1.2 Thread breaks. Thread breaks in stitching shall be overstitched not less than 1 inch at each break on stitch type 301 and not less than ¾ inch at each break on stitch types 304, 503, 504 or 505. Thread breaks noted during inspection shall be repaired by starting the overstitching at least 1 inch before the break and ending it at least 1 inch beyond the break. The ends of repair stitching are not required to be backstitched.

3.3.1.3 Stitching ends. The ends of type 301 stitching shall be overstitched not less than 1 inch except where ends are turned under in a hem or held down by other stitching. Where 301 stitching is performed automatically on stitch patterns such as box, box with cross-stitch, “W” stitching or straight line tacking , at least 3 or more tying, overlapping or backstitches shall be used to secure the ends of stitching. The ends of type 304, 503, 504 or 505 stitching shall be firmly secured by backstitching or overstitching or by increasing the number of stitches per inch at the ends for a minimum of ¼ inch.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:35Z
Check the source to verify that this is the current version before use.

3.3.1.4 Skipped stitches. Two or more consecutively skipped stitches occurring in type 301, 304, 503, 504, or 505 stitching shall be overstitched not less than 1 inch. Skipped stitches noted during inspection shall be repaired in the same manner as specified under thread breaks.

3.3.2 Setting of end clips. The webbing shall be shall be inserted the full depth of the clip. Clips shall be securely attached without cutting the webbing and the webbing shall lie flat at the point of entrance.

3.3.3 Setting of snap fasteners.

3.3.3.1 Style 1. The hole for the male part of the snap fastener shall be formed when the fastener is driven into the material. The hole punched before insertion of the female part of the fastener shall be no larger than that made by a standard number 10 round drive punch (5/16 inch diameter hole). Fasteners shall be securely clinched. Not more than one score or split shall be allowed on the roll of the eyelet base of the stud.

3.3.3.2 Style 2. When a hole is punched before insertion of the male or female part of the fastener it shall be smaller than the outside diameter of the fastener tube so that the tube must be forced through the hole. Fasteners shall be securely clinched. Not more than one score or split shall be allowed on the roll of the eyelet of either male or female half of the fastener.

3.4 Marking. Identification marking shall be applied in the location shown on the drawing and shall conform to type IV, class 5 of DDD-L-20. The letters "U.S.", the item name, list of contents, pocket numbers and bag markings shall be located and applied in the size characters indicated on the drawings and shall conform to type IV, class 9 of DDD-L-20. Fastness of class 9 marking shall be as specified for the class 5 labels.

3.5 Workmanship. Cloth components shall be clean and free of holes, cuts, tears or cloth defects such as multiple floats or broken or missing yarns. Webbing and tape shall not have frayed or scalloped edges. Thread tension shall be maintained so that there will be no loose stitching and seam allowances shall be maintained with seams properly sewed so that no runoffs, twists, pleats or open seams shall result. Care shall be taken in sewing to see that no needle chews occur. All thread ends shall be trimmed to ½ inch or less. Metal components shall be free of burrs, sharp edges, or corroded areas and shall not be broken or malformed. The end item shall conform to the quality of product established by this specification.

4. **VERIFICATION**

4.1 Responsibility for dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for ensuring that all specified dimensions in the applicable drawings have been met. When dimensions cannot be examined on the end item, inspection shall be made at any point, or at all points in the manufacturing process necessary to ensure compliance with all dimensional requirements.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:35Z
Check the source to verify that this is the current version before use.

a. First article inspection (see 4.3)
b. Conformance inspection (see 4.4)

4.3 First article inspection. When a first article is required (see 6.2) it shall be examined for the defects listed in 4.4.3.

4.4 Conformance inspection. Sampling for inspection shall be as specified in the contract or purchase order.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified or qualified in this specification or applicable purchase document.

4.4.2 In-process inspection. Inspection shall be made during the manufacturing process to insure that holes punched to receive female part of style 1 snap fasteners or male and female part of style 2 snap fasteners shall be smaller in diameter than the tube of the parts to be inserted for compliance with 3.3.3. Whenever nonconformance is noted, corrections shall be made to the parts affected and lot in-process. Components which cannot be corrected shall be removed from production.

4.4.3 End item visual examination. The end item shall be tested for the characteristics listed in table I. The lot size shall be expressed in units of repair kit cases. The sample unit shall be one complete repair kit case.

Table I. End item visual examination.

Examine	Defect	Classification Major	Minor A	Minor B
Fabric	Any hole, cut or tear	101		
	Broken or missing yarn, multiple floats clearly visible at normal inspection distance (approximately 3 feet)		201	
Felt	Any hole, cut or tear		202	
Leather (shears scabbard)	Hole, cut or tear	102		
	Loose, spongy, flaky, weak or thin spot		203	
	Scabbard not removable from pocket; corners not clipped as specified			301
	Fabricated with flesh side on inside		204	
	Color not as specified			302
Hardware	Broken	103		
	Malformed:			

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:35Z
Check the source to verify that this is the current version before use.

Table I. End item visual examination.

Examine	Defect	Classification Major	Minor A	Minor B
Hardware (cont'd)	-fails to perform intended function	104		
	-will perform intended function		205	
	Corroded area			303
	Burr or sharp edges which may cause injury in handling or damage to fabric	105		
End clips	Webbing not flat at point of entrance into clip			304
	Clinched tight, cutting webbing	106		
Seams and stitching	Open seam on stitch type 301:			
	-for more than 1 inch	107		
	-for more than ½ inch but not more than 1 inch		206	
	-for more than ¼ inch but not more than ½ inch			305
	NOTE: A seam shall be classified as open when one or more stitches joining a seam are broken, or when one or more skipped or runoff, stitches occur. On double stitched seams, a seam shall be classified as open when either one or both sides of a seam are open.			
	Raw edges caught in stitching (except end of inside binding):			
	-more than 1 inch		207	
	-more than ½ inch but not more than 1 inch			306
	Thread breaks:			
	-overstitched less than 1 inch on stitch type 301			307
	-overstitched less than ¾ inch on stitch type 304			308
	NOTE: Thread breaks not overstitched shall be classified as open seams.			
	Needle chew resulting in hole, cut or tear	108		
	Skipped stitches overstitched less than 1 inch on stitch type 301, 304, 503, 504, or 505 when 2 or			

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:35Z
Check the source to verify that this is the current version before use.

Table I. End item visual examination (continued).

Examine	Defect	Classification Major	Minor A	Minor B
	more skipped stitches occur consecutively			309
	NOTE: Skipped stitches not overstitched shall be classified as open seams			
	One or more required rows of stitching omitted (except on boxstitching)	109		
Boxstitching	Incomplete:			
	-one row of stitching omitted			310
	–two or more rows of stitching omitted		208	
	Any boxstitching less than specified length by more than 1/8 inch			311
Stitching ends	Overstitched less than 1 inch on stitch type 301 (except where ends are held down by other stitching, turned under a hem, or where stitching is performed automatically)		209	
	Secured with less than 3 tying, overlapping or backstitches where automatic stitching is performed			312
	Secured with less than ¼ inch of backstitching, overstitching or by an increased number of stitches at the end of stitch type 304, 503, 504, or 505			313
Seam type	Wrong seam type	110		
Stitch type	Wrong stitch type		210	
Stitch tension	Loose, resulting in exposed bobbin or top thread for more than 2 inches			314
	Tight, as evidenced by puckering of fabric for more than 2 inches		211	
Stitches per inch	Less than minimum specified:			
	-one stitch			315
	–two or more stitches		212	
	NOTE: Variation in the number of stitches per inch caused by the operator speeding up the machine and pulling the fabric in order to sew over heavy places or in turning			

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:35Z
Check the source to verify that this is the current version before use.

Table I. End item visual examination.

Examine	Defect	Classification Major	Minor A	Minor B
	corners shall be classified as follows: a. Within the minor B defect classification - no defect b. Within the minor A defect classification - minor B defect			
Stitching margin	Larger than specified by more than 1/8 inch:			
	-for more than 1 inch but not more than 2 inches in length			316
	–for more than 2 inches in length		213	
	Less than specified:			
	-for more than 1 inch but not more than 2 inches in length			317
	–for more than 2 inches in length		214	
Components and assembly	Any component part missing or not fabricated of applicable referenced material	111		
Construction details:				
Facings	Ends of facing A or B not caught in binding stitching		215	
Pockets and bags	Fold of pocket piece B not formed as specified, or not stitched through body and handle where applicable		216	
	Stitching across bottom of pockets 6 through 9 omitted, or interferes with clearance in pockets 5 to 10		217	
Drawstring	Drawstring cut or abraded		218	
	Drawstring caught in hem stitching causing failure to draw freely		219	
	Drawstring hem improperly formed, badly puckered, twisted or pleated			318
Binding	Loosely or improperly applied:			
	-badly pleated			319
	–ends of binding not finished as specified			320
Buckle chape and strap	Buckle reversed		220	
	Misplaced; i.e. failing to effect a smooth and secure closure		221	
	Chape reinforcement improperly applied	112		

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:35Z
Check the source to verify that this is the current version before use.

Table I. End item visual examination.

Examine	Defect	Classification Major	Minor A	Minor B
Handles	Set beyond location indicated on drawing by more than ¼ inch		222	
	Edges of grip section overlapped; edges not folded or not stitched as indicated on drawing		223	
	Ends of carrying strap not finished as specified		224	
Snap fasteners	Not functioning properly	113		
	Not securely clinched, allowing components to separate	114		
	Clinched excessively tight, cutting surrounding fabric	115		
	Two or more splits on roll of any eyelet		225	
Marking: "U.S.", nomenclature, identification, list of contents, numbering of pockets	Omitted, incorrect, illegible or size of characters not as specified		226	
Cleanness	Grease or oil stains			321
	thread ends not trimmed to ½ inch or less throughout			322
	Ink spots or stains		227	

4.5 End item dimensional examination. The end item shall be examined for conformance to the dimensions specified on the drawings. Only those dimensions that can be evaluated without damaging or disassembling the end item shall be examined. Any dimension not within the specified tolerance shall be classified as a defect. The lot size shall be expressed in units of repair cases. The sample unit shall be one complete repair kit case.

5. **PACKAGING**

* 5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When actual packaging of materiel is to be performed by DoD personnel, these personnel need to contact the responsible packaging activity to ascertain requisite packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activity within the Military Department or Defense Agency, or within the Military Department's System Command. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:35Z
Check the source to verify that this is the current version before use.

6. **NOTES**

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The repair kit case is designed to contain tools, materials, and components used in the repair of tentage items. This specification does not cover the contents of the case (see 6.4).

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number and date of this specification.
b. Issue of DODISS to be cited in the solicitation and, if required, the specific issue of individual documents referenced (see 2.1).
c. When first article inspection is required, (see 3.1) the item will be tested and should be a first article sample. The contracting officer should include specific instructions in acquisition documents regarding arrangement for examinations, quantity, and testing and approval.
d. Packaging and preservation requirements (see 5.1).

6. 3 Sample. For access to standard sample , address the contracting activity issuing the invitation for bids.

* 6.4 List of contents. The list of contents of the case for general information is (see 6.1):

List of contents

Pocket No.	Item	Quantity
1	Cloth, WWR, Camouflage Green 483 (Type II, Class 2 of MIL-PRF-20696)	2 yards
1	Cloth, WWR, Desert Tan 459 (Type II, Class 2 of MIL-PRF-20696)	2 yards
1	3 Inch Wide By 50 Yards Long Seam Sealing Tape	2 rolls
1	Cloth, duck, cotton, OD, 9.85 ounce, FWWMR	2 yards
1	Cloth, FWWR, Army Desert Tan, Shade 459	2 yards
1	Cloth, FWWR, Camouflage Green 483	2 yards
1	Grommet, metalic, black chemical finish, rolled rim w/washer, spur type, No. 4 (in bag)	1 gross

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:35Z
Check the source to verify that this is the current version before use.

List of contents cont'd.

Pocket No.	Item	Quantity
1	Grommet, metalic, black, chemical finish, rolled rim w/washer, spur type, No. 5 (in bag)	1 hundred
1	Mallet, rawhide, 2-3/4 inch face	1 each
1	FM 10-16, Field Manual General Repair for Tents, Canvas and Webbing	1 each
1	Palm, sewing	1 each
1	Punch and die, inserting, spur grommet No. 4 (in bag)	1 each
1	Punch and die, inserting, spur grommet No. 5 (in bag)	1 each
1	Ring, connecting, round, galvanized, ½ inch (in bag)	50 each
1	Ring, connecting, round, galvanized, ¾ inch (in bag)	25 each
1	Ring, connecting, round, galvanized 1 inch (in bag)	10 each
1	Sling, carrying, bag and case	1 each
1	Slip, tent line	10 each
1	Twine, cotton, wrapping, 5-ply MRT	1 cone or 2 pounds
2	Thread, polyester, type I or II, class 1, size FF	1 tube
2, 3	Adhesive, nitrile, rubber base Minnesota Mining Co. (Part No. EC-847) R-H Products Co. Inc. (Part No. HH-66) or equal tent patching	8 tubes
4	Needle, sailmaker's, No. 14	12 each
5	Brush, wire, scratch	1 each

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:35Z
Check the source to verify that this is the current version before use.

List of contents cont'd.

Pocket No.	Item	Quantity
6	Punch, cutting, for No. 4 grommet	1 each
7	Awl, saddler's sewing	1 each
8	Lubricant, slide fastener	1 box (24 sticks)
9	Punch, cutting, for No. 5 grommet	1 each
10	Shears, bent trimmers, length overall, 10 inches	1 each

6.5 International standardization agreements. Certain provisions of this specification are the subject of international agreement as cited in NATO, STANAG No. 2882, relative to camouflage requirements for tents, shelters and subsidiary components. When amendment, revision, or cancellation of this specification is proposed which will affect or violate the international standardization agreement concerned, the preparing activity will take appropriate reconciliation action through international standardization channels including departmental standardization offices, if required.

6.6 Subject term (key word) listing.
Maintenance
Restore shelter

6.7 Changes from previous issue. The margins of this document have been marked with an asterisk (*) to indicate where changes (additions, modifications, corrections deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content, as written, irrespective of the marginal notations and relationship to the last previous issue.

MILITARY INTERESTS:
Custodians:
Army – GL
Navy – MC
Air Force – 99

Preparing activity:
DLA - CT

(Project 8430-0188)

Review activities:

Army – MD
Air Force – 45, 82

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:35Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7 and send to preparing activity.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	**1. DOCUMENT NUMBER** MIL-DTL-3372G	**2. DOCUMENT DATE *(YYYYMMDD)*** February 4, 2000

3. DOCUMENT TITLE

Case, Tentage Repair Kit

NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME *(Last, First, Middle Initial)*	b. ORGANIZATION	
c. ADDRESS *(Include Zip Code)*	d. TELEPHONE *(Include Area Code)* (1) Commercial (2) DSN *(If applicable)*	7. DATE SUBMIT *(YYYYMMDD)*

8. PREPARING ACTIVITY

a. NAME DEFENSE SUPPLY CENTER PHILADELPHIA DSCP-CNRP	b. TELEPHONE *(Include Area Code)* (1) Commercial (2) DSN (215) 737- 5653 444-5653
c. ADDRESS *(Include Zip Code)* 700 Robbins Ave (Bldg 6, C&T) PHILADELPHIA, PA 19111-5092	**IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT:** Defense Standardization Program Office (DLSC-LM) 8725 John J. Kingman Road, Suite 2533 Fort Belvoir, Virginia 22060-6221 Telephone (703) 767-6888 DSN 427-6888

DD Form 1426, FEB 1999 (EG) PREVIOUS EDITION IS OBSOLETE
WHS/DIOR, Feb 99

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:35Z
Check the source to verify that this is the current version before use.