MIL-T-3368
13 DECEMBER 1950
SUPERSEDING
FXS-661
21 February 1944

MILITARY SPECIFICATION

TRIPOD, M19

This specification was approved by the Departments of the Army, the Navy, and the Air Force for use of procurement services of the respective Departments.

1. SCOPE

1.1 This specification covers one type of tripod known as Tripod, M19, used as support for Directors M5 and M6.

2. APPLICABLE SPECIFICATIONS, OTHER PUBLICATIONS, AND DRAWINGS

2.1 Specifications.—The following specifications and specifications referenced on drawings in 2.3, of the issue in effect on date of invitation for bids, form a part of this specification:

FEDERAL SPECIFICATION

UU–T–111 —Tape: Paper, Gummed, (Kraft).

MILITARY SPECIFICATIONS

JAN–P–106—Packaging and Packing for Overseas Shipment — Boxes; Wood, Nailed.

JAN–P–116—Packaging and Packing for Overseas Shipment — Preservation, Methods of.

JAN–B–121—Barrier Material, Greaseproof.

JAN–P–125—Packaging and Packing for Overseas Shipment — Barrier Materials, Waterproof, Flexible.

JAN–P–127—Packaging and Packing for Overseas Shipment—Tape, Adhesive, Pressure-Sensitive, Water-Resistant.

U. S. ARMY SPECIFICATIONS

51–7 —Instruments, Fire-Control; General Specification Governing the Manufacture, and Inspection of.

100–2 —Standard Specification for Marking Shipments by Contractors.

(*Army.*—Copies of specifications should be obtained from the procuring agency or as directed by that agency. Both the title and identifying number or symbol should be stipulated when requesting copies.)

(*Marine Corps.*—Copies of Federal and Military specifications may be obtained upon application to the Quartermaster General, Headquarters, U. S. Marine Corps, Navy Building, Washington 25, D. C., or the Depot Quartermaster, Marine Corps Depot of Supplies, 1100 South Broad Street, Philadelphia 46, Pa. Both the title and identifying number or symbol should be stipulated when requesting copies.)

2.2 Drawings. — The following drawings and all drawings referenced thereon, of the issue in effect on the date of invitation for bids, form a part of this specification:

ARMY ORDNANCE CORPS DRAWINGS

D84308 —Tripod, M19.

D7633839—Cleaning, Preserving, Packaging (Methods O, I, and IA), Packing and Marking of Fire Control Materiel Spare Parts for Domestic Shipment and Storage, and Export Shipment.

(Copies of drawings should be obtained from the procuring agency or as directed by that agency. Both the title and the identifying number should be stipulated when requesting copies.)

905081—50—(362)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:34Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 General requirements and associated tests common to all fire control instruments as contained in Specification 51–7 shall be mandatory in so far as they are applicable.

3.2 Materials.—Materials shall be in accordance with the drawings, general specifications and material specifications forming part of this specification.

3.3 Workmanship. — Workmanship shall be in accordance with Specification 51–7.

4. SAMPLING, INSPECTION, AND TEST PROCEDURES

4.1 Unless otherwise specified, each tripod and spare part shall be inspected for conformance with this specification and as specified in Specification 51–7.

5. PREPARATION FOR DELIVERY

5.1 Preservation.—The legs shall be disassembled from the base and head. All unprotected metal surfaces shall be cleaned in accordance with method C–5 (scrub with a brush or wipe with saturated cloths) and the cleaned surfaces shall be coated with P5 preservative as specified in Specification JAN–P–116.

5.2 Packaging.—The preserved surfaces on the tripod head and six legs shall be covered with greaseproof barrier material conforming to type II, grade C, class 2 of Specification JAN–B–121. The barrier material shall be overwrapped on the leveling screws with flexible single-face corrugated paper. The wrap shall be secured with pressure sensitive tape conforming to Specification JAN–P–127. The preserved mounting hardware and wrenches shall be placed in a bag fabricated from material conforming to Specification JAN–B–121. The tripod legs shall be placed together and wrapped with flexible single-face corrugated paper. The wrap shall be secured with gummed tape conforming to grade B of Specification UU–T–111. The fabricated bag containing mounting hardware and wrenches shall be secured to the package containing six legs by means of pressure sensitive tape conforming to Specification JAN–P–127.

5.3 Packing.—The prepared components of the tripod shall be immobilized in a nailed wood box conforming to style 2 or 4, group I or II of Specification JAN–P–106. Steel strapping need not be applied for domestic shipments.

5.4 Identification and marking.—In addition to any special markings required by the contract or order, shipments for the Army shall be marked in accordance with Specification 100–2, and for the Navy in accordance with the Navy Shipment Marking Handbook.

5.5 Spare parts.—Packaging, packing, and marking of spare parts shall be in accordance with Drawing B7633839 and supplementary instructions supplied by the contracting officer.

6. NOTES

6.1 Ordering data. — Invitation for bids and contracts or orders should specify the following:

a. Title, number, and date of this specification.

Notice.—This specification, together with specifications and drawings pertaining to it and bearing a "NOTICE" of similar restrictions, is intended for use only in connection with procurement by the United States Government; and shall not be reproduced either wholly or in part except when authorized in connection with Government procurement, nor be used for any other purpose except when specifically authorized by the Chief of Ordnance.

Custodian:
Army—Ordnance Corps

Other interest:
Navy—*MC.*

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:34Z
Check the source to verify that this is the current version before use.