MILITARY SPECIFICATION SHEET

TUBING, PLASTIC, HEAT SHRINKABLE, ELECTRICALLY INSULATING IRRADIATED POLY (VINYLIDENE FLOURIDE), SEMI RIGID: SHRINK RATIO 2 TO 1

The complete requirements for procuring the plastic tubing described herein shall consist of this document and the issue in effect of MIL-K-81786(AS).

REQUIREMENTS: The tubing shall meet the requirements of MIL-I-23053/8

Sizes - See table I
Type - tubular
Material - Irradiated Poly (Vinylidene Flouride)
Color - Clear
Length - 4 inches

TABLE I

Part No.	Dimensions (inch)			
	As Supplied	After Heating		
	ID, min	ID, max	Nominal Wall Thickness	Wall Thickness Tolerance
M81786/2-1	.046	.023	.010	± .002
M81786/2-2	.063	.031	.010	± .002
M81786/2-3	.093	.046	.010	± .002
M81786/2-4	.125	.062	.010	± .002
M81786/2-5	.500	.250	.012	± .003
M81786/2-6	.750	.375	.017	± .003
M81786/2-7	1.000	.500	.019	± .003

Preparing Activity:
Navy-AS

☆ U. S. GOVERNMENT PRINTING OFFICE: 1974 -713-153 4699

FSC-4940

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:09Z
Check the source to verify that this is the current version before use.