NOTE: The document identifier and heading has been changed on this page to reflect that this is a performance specification. There are no other changes to this document. The document identifier on subsequent pages has not been changed, but will be changed the next time this document is revised.

INCH-POUND


MIL-PRF-39012/27G
26 September 1994
SUPERSEDING
MIL-C-39012/27F
3 October 1986

PERFORMANCE SPECIFICATION SHEET

CONNECTORS, PLUGS, ELECTRICAL, COAXIAL, RADIO FREQUENCY,
(SERIES TNC (CABLED), SOCKET CONTACT, CLASS 2)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-PRF-39012.




NOTES:
1. Dimensions are in inches.
2. For dimension A, see tables I and III.
3. Metric equivalents are given for information only.
4. Wrench flats are to accommodate standard wrench opening in accordance with FED-STD-H28, appendix 10.
5. Dimension A defines the maximum length of the connector when assembled to the appropriate cable.
6. All undimensioned pictorial representations are for reference purposes only.
7. Series TNC, socket contact interface in accordance with MIL-STD-348.
8. Metric equivalents are in parentheses.

FIGURE 1. General configuration.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-21T16:50Z
Check the source to verify that this is the current version before use.



CATEGORY D

Inches	mm
.002	0.05
.009	0.23
.010	0.25
.015	0.38
.036	0.91
.077	1.96
.276	6.78
	11.112

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Chamfer is optional.
4. All undimensioned pictorial configuration are for reference purposes only.

FIGURE 2. Category D captivation detail.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:50Z
Check the source to verify that this is the current version before use.

TABLE I. Dash numbers, cross-reference, and dimensions.

Dash number 1/	Applicable cable 2/ M17/	Dimensions	Inches (millimeters) maximum
Category A - Field serviceable (no special tools required) 3/			
0101 (Superseding -0104 4/) Cable grouping VI	28-RG058 155-00001 183-00001 197-00001 111-RG303 170-00001 60-RG142 5/ 158-00001 84-RG223 167-00001 194-00001 200-00001 128-RG400 6/ 175-00001	A	1.250 (31.75)
0102 (Superseding -0117 4/) Cable grouping VII	29-RG59 7/ 184-00001 7/ 110-RG302 5/ 6/ 7/ 30-RG062 7/ 185-00001 7/ 97-RG210 7/ 90-RG71 7/ 195-00001 7/		
0103 Cable grouping IV	54-RG122 6/ 157-00001 187-00001 198-00001		
0018 Cable grouping II	113-RG316 5/ 6/ 119-RG174 173-00001 196-00001 172-00001 94-RG179 7/		
0225 Cable grouping X	74-RG213 6-RG11 7/ 181-00001 7/ 62-RG144 7/ 65-RG165 159-00001 189-00001 163-00001 75-RG214 190-00001 164-00001 86-00001 127-RG393 5/ 6/ 174-00001 77-RG216 7/ 191-00001 7/		

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 202610-21T16:50Z
Check the source to verify that this is the current version before use.

TABLE I. Dash numbers, cross-reference, and dimensions - Continued.

Dash number 1/	Applicable cable 2/ M17/	Dimensions	Inches (millimeters) maximum
Category C - Field replaceable (MIL-C-22520 crimp tool) See footnote next to applicable cable for crimp die 3/ 8/			
0010 Cable grouping VIA	28-RG058 9/ 155-00001 9/ 183-00001 9/ 197-00001 9/ 111-RG303 5/ 6/ 9/ 170-00001 9/	A	1.500 (38.10)
0011 Cable grouping VIB	84-RG223 9/ 60-RG142 5/ 9/ 158-00001 9/ 167-00001 9/ 194-00001 9/ 200-00001 9/ 128-RG400 6/ 9/ 175-00001 9/		
0012 (Superseding -0021 4/) VIIA	29-RG59 7/ 10/ 184-00001 7/ 10/ 110-RG302 5/ 6/ 7/ 10/ 30-RG062 7/ 10/ 185-00001 7/ 10/ 97-RG210 7/ 10/		
0013 Cable grouping IV	54-RG122 6/ 11/ 157-00001 11/ 187-00001 11/ 198-00001 11/		
0014 Cable grouping VIIB	90-RG71 6/ 7/ 10/ 195-00001 7/ 10/		
0022 Cable grouping IIA	113-RG316 5/ 6/ 12/ 119-RG174 12/ 173-00001 12/ 196-00001 12/ 172-00001 12/		
0023 Cable grouping V	95-RG180 6/ 7/ 11/		
Category D - Field replaceable - Defined piece part 3/ 8/ 13/ 14/			
0501 Cable grouping IV	54-RG122 6/ 157-00001 187-00001 198-0000	A	1.234 (31.35)
0502 Cable grouping V	95-RG180 5/ 6/ 7/		
0503 Cable grouping VIB	60-RG142 5/ 158-00001 84-RG223 167-00001 194-00001 200-00001 128-RG400 6/ 175-00001		
0504 Cable grouping VIA	28-RG058 155-00001 183-00001 197-00001 111-RG303 5/ 6/ 170-00001		

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:50Z
Check the source to verify that this is the current version before use.

TABLE I. Dash numbers, cross-reference, and dimensions - Continued.

1/ For cross-reference of dash number to superseded PIN or type designation, see table IV.

2/ The latest version of each cable shall be applicable.

3/ These connectors have captivated center contacts.

4/ The superseded PIN are acceptable for Government use until stock is purged or 3 years from the date of this specification which ever is earlier.

5/ Cable to be used for the +200°C temperature cycling tests.

6/ Cable to be used when performing tests requiring cable except as in 5/ and 7/.

7/ These are not 50-ohm cables; therefore, when attached to the specified connectors, VSWR, RF, leakage and insertion loss are not applicable.

8/ These connectors are assembled using the applicable crimp tool, to the specified cables stripped as shown on figure 4.

9/ M22520/5-19 closure B or M22520/5-05 closure A.
M22520/5-11 closure A.
M22520/5-57 closure A.

10/ M22520/5-19 closure A or M22520/5-07 closure A.
M22520/5-13 closure A.
M22520/5-59 closure A.


11/ M22520/5-41 closure B or M22520/5-05 closure B.
M22520/5-09 closure A.

12/ M22520/5-35 closure B or M22520/5-03 closure A.

13/ Complete connector assembly shall consist of a body, center contact, ferrule and assembly instructions.

14/ Not to be used in Army equipment.

Source: https://assist.dla.mil -- Downloaded: 202610-21T16:50Z
Check the source to verify that this is the current version before use.




CRIMP FERRULE

Dash number	Ferrule number 1/	A ±.003	B ±.003	Basic crimp tool 2/	Crimp die or positioner M22520/5
0501 0502	27-50	.212	.175	M22520/5-01	05, 41 Closure B or 9 Closure A
0503	27-51	.250	.220		05, 11, 57 Closure A or 19 Closure B
0504	27-52	.245	.206		

1/ Contact numbers and ferrule numbers are for identification only.
2/ Class 2 tool may be used by OEM (see MIL-C-22520).

FIGURE 3. Contact and ferrule dimensions for category D only.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:50Z
Check the source to verify that this is the current version before use.



Inches	mm	Inches	mm
.001	0.03	.145	3.68
.002	0.05	.175	4.45
.003	0.08	.183	4.65
.005	0.13	.206	5.23
.015	0.38	.210	5.33
.017	0.43	.212	5.38
.033	0.84	.220	5.59
.035	0.89	.230	5.84
.040	1.02	.235	5.97
.043	1.09	.250	6.35
.067	1.70	.478	12.14
.083	2.11	.500	12.70


Dash no.	Contact no. 1/	A +.001 -.002	Basic crimp tool 2/	Crimp die or positioner	Crimp tensile min	Color band □	Color band ○
0501	27-12	.033	M22520/1-01	M22520/1-12	10 lbs	Orn	Green
0502	27-11	.017			6 lbs	Blue	
0503 0504	27-10	.043	M22520/1-01	M22520/1-12	20 lbs	Red	

1/ Contact numbers and ferrule numbers are for identification only.
2/ Class 2 tool may be used by OEM (see MIL-C-22520).

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Contact material shall be phosphor bronze or copper beryllium.
4. Crimp tensile test shall be in accordance with MIL-C-39029.
5. Copyright notice: All information disclosed in these specification sheets which is or may be copyright is reproduced herein with the express permission of the copyright owner.
6. .003 maximum break.
7. Color bands shall be positioned so that no coloring material enters the inspection hole.

FIGURE 3. Contact and ferrule dimensions for category D only - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:50Z
Check the source to verify that this is the current version before use.



Inches	mm
.146	3.71
.166	4.22
.333	8.46
.353	8.97
.427	10.85
.447	11.35
.593	15.06

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.

FIGURE 4. Cable stripping dimensions for field replaceable connectors.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:50Z
Check the source to verify that this is the current version before use.

ENGINEERING DATA:

Nominal impedance: 50 ohms.

Frequency range: 0 to 11,000 MHz.

Voltage rating:

500 volts rms, maximum working voltage at sea level.

125 volts rms, maximum at 70,000 feet.

Temperature rating: -65°C to +165°C.

REQUIREMENTS:

Dimensions and configuration: See figure 1.

Force to engage and disengage:

Longitudinal force: Not applicable.

Torque: 2 inch-pounds, maximum.

Coupling proof torque: Not applicable.

Inspection conditions:

Coupling torque: 4 to 6 inch-pounds.

Mating characteristics:

Reference MIL-STD-348 and figure 2 for dimensions.

Center contact (socket):

Oversize test pin: .057 diameter, minimum (nonclosed entry contacts only).

Insertion depth: .125, minimum.

Number of insertions: One.

Insertion force test: Steel test pin diameter .054, minimum.

Test pin finish: 16 microinches.

Insertion force: 2 pounds, maximum.

Withdrawal force test: Steel test pin diameter .052, maximum.

Withdrawal force: 2 ounces, minimum.

Test pin finish: 16 microinches.

Hermetic seal: Not applicable.

Leakage (pressurized connectors): Not applicable.

Insulation resistance: Method 302 of MIL-STD-202, test condition B, 5,000 megohms, minimum.

Center contact retention: 6 pounds, minimum axial force. Applicable to captivated-center-contact connectors only.

Corrosion (salt spray): Method 101 of MIL-STD-202, test condition B.

Voltage standing wave ratio (VSWR): From 500 to 11,000 MHz, or approximately 80 percent of upper cutoff frequency of the cable, whichever is lower.; 1.30, maximum.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:50Z
Check the source to verify that this is the current version before use.

Swept frequency VSWR test setup:

Item 6: VSWR shall be less than 1.02+.003 F (F in GHz).

Item 16: VSWR shall be less than 1.02+.003 F (F in GHz).

Second step of VSWR checkout procedure - VSWR shall be less than 1.06+.007 F (F in GHz).

Group B inspection: VSWR shall be less than 1.05+.005 F (F in GHz).

Qualification and group C inspection: VSWR shall not exceed 1.10.

Connector durability: 500 cycles, minimum at 12 cycles per minute, maximum. The connector shall meet the mating characteristics and force to engage and disengage requirements.

Contact resistance: In milliohms, maximum:

	Initial	After environment
Center contact	1.5	2.0
Outer contact	.2	Not applicable
Braid to body	.1	Not applicable

Dielectric withstanding voltage: Method 301 of MIL-STD-202, 1,500 volts rms, minimum at sea level.

Vibration, high frequency: Method 204 of MIL-STD-202, test condition B. No discontinuity permitted.

Shock: Method 213 of MIL-STD-202, test condition I. No discontinuity permitted.

Thermal shock: Method 107 of MIL-STD-202, test condition B, except test high temperature shall be +85°C. High temperature shall be +200°C for connectors using +200°C cables (see tables I and III).

Moisture resistance: Method 106 of MIL-STD-202. No measurements at high humidity. Insulation resistance shall be at least 200 megohms within 5 minutes after removal from humidity.

Corona level:

Voltage: 375 volts rms, minimum.

Altitude: 70,000 feet.

RF high potential withstanding voltage:

Voltage and frequency: 1,000 volts rms at a frequency from 5 to 7.5 MHz.

Leakage current: Not applicable.

Cable retention force:

Noncrimp assemblies: 40 pounds, minimum.

Crimp assemblies:

10 pounds, minimum for cables .155 - .189 OD.

20 pounds, minimum for cables .190 - .229 OD.

30 pounds, minimum for cables .230 - .249 OD.

40 pounds, minimum for cables .250 OD and larger.

Coupling mechanism retention force: Not applicable.

RF leakage: -60 dB minimum, tested at a frequency between 2 and 3 GHz.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:50Z
Check the source to verify that this is the current version before use.

Insertion loss:

.18 dB maximum tested at 9 GHz.

.06 $\sqrt{F\ (GHz)}$ dB max tested at 3 GHz and 6 GHz.

Part or Idendifying Number (PIN): M39012/27 (dash number from table I or "B" number from table III).

Group qualification: See table II.

TABLE II. Group qualification. 1/

Group	Submission and qualification of 2/ any of the following connectors	Qualifies the following connectors
	M39012/	M39012/
I	27-0101 27-0103 27-0104 27-0018 28-0101 28-0103 28-0104 28-0018 29-0101 29-0103 29-0104 29-0018	27-0101 27-0002 27-0103 27-0104 27-0117 27-0018 28-0101 28-0102 28-0103 28-0104 28-0117 28-0018 29-0101 29-0102 29-0103 29-0104 29-0117 29-0018
II	27-0002 27-0117 28-0102 28-0117 29-0102 29-0117	27-0002 27-0117 28-0102 28-0117 29-0102 29-0117
III	27B0005 27B0006 27B0008 27B0015 27B0016 27B0020 28B0005 28B0006 28B0008 28B0015 28B0016 28B0020	27B0005 27B0006 27B0007 27B0008 27B0009 27B0015 27B0016 27B0019 27B0020 28B0005 28B0006 28B0007

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:50Z
Check the source to verify that this is the current version before use.

TABLE II. Group qualification - Continued. 1/

Group	Submission and qualification of 2/ any of the following connectors	Qualifies the following connectors
	M39012/	M39012/
III	29B0005 29B0006 29B0008 29B0015 29B0016 29B0020	28B0008 28B0009 28B0015 28B0016 28B0019 28B0020 29B0005 29B0006 29B0007 29B0008 29B0009 29B0015 29B0016 29B0019 29B0020
IV	27B0007 27B0009 27B0019 28B0007 28B0009 28B0019 29B0007 29B0009 29B0019	27B0007 27B0009 27B0019 28B0007 28B0009 28B0019 29B0007 29B0009 29B0019
V	27-0010 27-0011 27-0013 27-0022 27-0023 28-0010 28-0011 28-0013 28-0022 29-0010 29-0011 29-0013 29-0022	27-0010 27-0011 27-0012 27-0013 27-0023 27-0014 27-0021 27-0022 28-0010 28-0011 28-0012 28-0013 28-0014 28-0021 28-0022 29-0010 29-0011 29-0012 29-0013 29-0014 29-0021 29-0022
VI	27-0012 27-0014 27-0021 27-0023 28-0012 28-0014 28-0021 29-0012 29-0014 29-0021	27-0012 27-0014 27-0021 27-0023 28-0012 28-0014 28-0021 29-0012 29-0014 29-0021

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:50Z
Check the source to verify that this is the current version before use.

TABLE II. Group qualification - Continued. 1/

Group	Submission and qualification of 2/ any of the following connectors	Qualifies the following connectors
	M39012/	M39012/
VII	27-0501 27-0503 27-0504	27-0501 27-0502 27-0503 27-0504
VIII	27-0502	27-0502

1/ If a connector manufacturer produces a connector which meets all the requirements for two or more connector PIN's (within the same series), the manufacturer may receive qualification approval for two or more connector PIN's qualifying the one connector. It is not necessary that such connectors be in the same group. Each connector, however, must be marked with its own appropriate PIN. For group qualification, the connectors must be of similar design.

2/ For qualification retention, where more than one part is listed in a group in this column, data may be supplied on any of those parts in order to retain qualification for those parts in the corresponding right hand column. The part does not necessarily have to be the part initially qualified.

TABLE III. Category B - Nonfield replaceable (special tools may be required).

Not for Air Force, Army or Navy use. For OEM use only.

Dash number 1/ 2/ 3/	Applicable cable M17/ 4/	Dimensions	Inches (millimeters) maximum
M39012/27B0005	028-RG058*		
M39012/27B0006	060-RG142@* 128-RG400		
M39012/27B0007	29-RG59*Δ 030-RG062Δ 97-RG210Δ	A	1.500 (38.10)
M39012/27B0008	054-RG122*		
M39012/27B0009	90-RG71*Δ		
M39012/27B0015	111-RG303*@		
M39012/27B0016	084-RG223*		
M39012/27B0019	110-RG302@*Δ		
M39012/27B0020	113-RG316@* 119-RG174		

1/ For cross-reference of dash number to superseded PIN or type designation, see table IV.
2/ For maintenance replacements for category B, see table V.
3/ Inactive for new design.
4/ The latest version of each cable shall be applicable.
* Cable to be used when performing tests requiring cable except as in notes @ and Δ.
@ Cable to be used for the +200°C temperature cycling tests.
Δ These are not 50 ohm cables; therefore, when attached to the specified connectors, VSWR, RF leakage, and insertion loss are not applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:50Z
Check the source to verify that this is the current version before use.

TABLE IV. Cross-reference of PIN's.

Preferred PIN M39012/27-	Substitute for PIN or type designation 1/ 2/
B0005	M39012/27-0005
B0006	M39012/27-0006
B0007	M39012/27-0007
B0008	M39012/27-0008
B0009	M39012/27-0009
B0015	M39012/27-0015
B0016	M39012/27-0016
B0019	M39012/27-0019
B0020	M39012/27-0020
0010	M23329/4-07, M23329/4-09
0011	M23329/4-08, M23329/4-10
0012	M23329/4-11
0023	M23329/4-12
0101	M39012/27-0001
0103	M39012/27-0003
0104	M39012/27-0004
0117	M39012/27-0017

1/ The superseded PIN or the type designation is for cross-reference only. Where a superseded PIN or type designation is not given, none was assigned or will be assigned. The PIN M39012/27-XXXX shall be used in all cases for marking and identifying the connector.

2/ The basic type designation includes all letter versions of the specified number, e.g. UG-18/U includes UG-18 A/U, UG-18B/U, etc.

TABLE V. Maintenance replacements for category B.

Category B number* Inactive for new design	Category C dash number	Category A dash number	Category D dash number
B0005	0010	0101	0504
B0006	0011	0101	0503
B0007	0012	0002	---
B0008	0013	0103	0501
B0009	0014	0002	---
B0015	0010	0104	---
B0016	0011	0101	---
B0019	0021	0117	---
B0020	0022	0018	---

*Category B connectors are for original installation only. They will not be stocked or acquired by the Government.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:50Z
Check the source to verify that this is the current version before use.

Revisions letters are not used to denote changes due to the extensiveness of the changes.

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 85
NASA - NA

Review activities:
Army - AT, AV, CR, EA, MI
Navy - AS, MC, OS, SH
Air Force - 11, 19, 99
DLA - ES

Preparing activity:
DLA - ES

(Project 5935-3932-17)

Source: https://assist.dla.mil -- Downloaded: 202610-21T16:50Z
Check the source to verify that this is the current version before use.