MIL-A-16288/11
1 October 1973
SUPERSEDING
MS39011
11 November 1968

MILITARY SPECIFICATION SHEET

ADAPTER, COMPRESSED GAS CYLINDER VALVE CONNECTIONS:

U. S. REGULATOR TO GERMAN AND DUTCH HYDROGEN VALVE

This specification sheet is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the adapter described herein shall consist of this document and the issue in effect of MIL-A-16288.

REQUIREMENTS:

1. The adapter shall be as specified in figure 1. Unless otherwise specified herein, dimensions are in inches, linear tolerances shall be plus or minus 1/64 inch, and angular tolerance shall be plus or minus 1/2 degree.

2. Permanently mark on surface in 1/8-inch-minimum characters: "U.S.-GERMAN/DUTCH H_2."

3. Maximum service pressure 3600 psi.

4. Material: Washer, conforming to MIL-P-15047 "Plastic Sheets, Laminated Thermosetting, Nylon Fabric Base, Phenolic - Resin."

INTENDED USE: The adapter is intended to connect a U. S. hydrogen regulator to a German or Dutch hydrogen valve.

Custodians:

Army - ME
Navy - YD
Air Force - 68

Preparing activity:

Army - ME

Project No. 8120-0349

Review activities:

Army - MD
Navy - SH, MS

User activities:

Army - AV
Navy - MC, AS

FSC 8120

Source: https://assist.dla.mil -- Downloaded: 202610-18T08:30Z
Check the source to verify that this is the currentversion before use.




FIGURE I. ADAPTER U.S. REGULATOR TO GERMAN OR DUTCH VALVE, HYDROGEN.

X-2387

Source: https://assist.dla.mil -- Downloaded: 202610-18T08:30Z
Check the source to verify that this is the current version before use.