MILITARY SPECIFICATION SHEET

ADAPTER, COMPRESSED GAS CYLINDER VALVE CONNECTIONS:

CLASS 520-300, ACETYLENE

This specification sheet is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the adapter described herein shall consist of this document and the issue in effect of MIL-A-16288.

REQUIREMENTS:

1. The adapter shall be as specified in figure 1. Unless otherwise specified herein, dimensions are in inches, linear tolerances shall be plus or minus 1/64 inch, and angular tolerance shall be plus or minus 1/2 degree.

2. Permanently mark on surface in 1/8-inch-minimum characters: "520-300 C_2H_2".

3. Maximum service pressure 600 psi.

INTENDED USE: The adapter is intended to connect a No. 300 regulator or charging manifold to a No. 520 valve for acetylene service.

Custodians:

Army - ME
Navy - YD
Air Force - 68

Preparing activity:

Army - ME

Project No. 8120-0263

Review activities:

Army - MD
Navy - SH, MS

User activities:

Army - AV
Navy - MC, AS

FSC 8120

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T08:33Z
Check the source to verify that this is the current version before use.




FIGURE 1. ADAPTER, NO. 300 REGULATOR TO NO. 520 VALVE, ACETYLENE.

X-2395

☆ U. S. GOVERNMENT PRINTING OFFICE: 1974-713-151/3653

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T08:33Z
Check the source to verify that this is the current version before use.