
MILITARY SPECIFICATION SHEET

CONNECTORS, ELECTRICAL, CIRCULAR, MINIATURE, HIGH DENSITY, QUICK DISCONNECT (BAYONET, THREADED, AND BREECH COUPLING), ENVIRONMENT RESISTANT, REMOVABLE CRIMP AND HERMETIC SOLDER CONTACTS, RECEPTACLE, SOLDER MOUNTING, HERMETIC, TRIPLE START THREADED COUPLING, HERMETIC SOLDER CONTACTS, SERIES III, METRIC

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the connectors described herein shall consist of this document and the latest issue of Specification MIL-C-38999.



Shell Size	Shell Size Code	F MAX	L MAX	S MAX	V With Pins	V With Sockets	Z MAX
9	A	17.1	5.1	19 4	17.2	19.4	23.8
11	B	19.9		21.8			
13	C	23.1		24.9			
15	D	26 2		28 1			
17	E	29.4		31.3			
19	F	31.8		33.6			
21	G	35 0	5 1	36.8			23.8
23	H	38.2	5.9	40.0			24.6
25	J	41.3	5.9	43 2	17 2	19 4	24.6

NOTES
1 Dimensions are in millimeters
2 Polarizing position N is shown

FIGURE 1. Receptacle, classes N and Y

FSC 5935

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:46Z
Check the source to verify that this is the current version before use.

Requirements.

Dimensions and configurations. See figure 1. Interface dimensions shall conform to MIL-C-38999

This connector mates with: DOD-C-38999/26.

Eyelet contact termination available in size 16 and 20 only.

For insert arrangements See MIL-STD-1560

Part number example: D38999/ 25 Y A 35 P N

- DOD No. prefix
- Specification sheet No.
- Class
- Shell size code
- Insert arrangement
- Contact style
- Polarizing position.
  - N is required for normal position

Custodians:
Army - EL
Navy - AS
Air Force - 85

Review activities
Army - MI, AR
Navy - EC, MC, OS
Air Force - 11, 15, 17, 99
DLA - ES

Preparing activity
Air Force - 85

(Project 5935-2096-5)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:46Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF AIR FORCE
DOD 318



OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

AFLC/LOIE/Standardization
Wright-Patterson AFB OH 45433

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:46Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS This form is provided to solicit beneficial comments which may improve this document and enhance its use DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government Fold on lines on reverse side, staple in corner, and send to preparing activity Attach any pertinent data which may be of use in improving this document If there are additional papers, attach to form and place both in an envelope addressed to preparing activity A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed

NOTE This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements

DOCUMENT IDENTIFIER *(Number)* AND TITLE

DOD-C-38999/25 Connectors, Electrical, Circular, Miniature, High Density FSC 5935

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1 ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW

A GIVE PARAGRAPH NUMBER AND WORDING

B RECOMMENDED WORDING CHANGE

C REASON FOR RECOMMENDED CHANGE(S)

2 REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*	TELEPHONE NO
	DATE

DD FORM 1426 1 OCT 76 PREVIOUS EDITION WILL BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:46Z
Check the source to verify that this is the current version before use.