[INCH-POUND]
A-A-2944
October 5, 1995
SUPERSEDING
W-C-001749
May 15, 1973

COMMERCIAL ITEM DESCRIPTION

CLEANER, VACUUM, ELECTRIC (INSTITUTIONAL/HOSPITAL)

The General Services Administration has authorized the use of this Commercial Item Description (CID) for all federal agencies.

1. SCOPE

1.1 Scope. This CID covers electric motor-powered vertical tank type vacuum cleaners to be used for wet and dry pickup in hospitals and institutions where aseptic conditions must be maintained. These cleaners shall be designed to operate on a single phase power source of 120 volts ac, 60 Hz.

2. CLASSIFICATION

2.1 Classification. The vacuum cleaners shall be of the following sizes (see 7.2). All sizes are minimum recoverable capacities. To assure close adherence to the specified sizes, maximum recoverable capacity shall be limited to 3 gallons (11.4 L) greater than minimum recoverable capacity.

Size 1 - 5 gallons (18.9 L).

Size 2 - 10 gallons (37.8 L).

3. SALIENT CHARACTERISTICS

3.1 Standard Commercial Product. The vacuum cleaner shall be the manufacturer's standard commercial product except for any changes necessary for compliance with this commercial item description.

3.2 UL Conformance. The vacuum cleaner shall meet the applicable requirements of UL 1017. Evidence of conformance with UL 1017 shall be a UL label or listing mark, or a certified test report (based on tests conducted within the past two years) from an independent testing laboratory acceptable to the Government, indicating the vacuum cleaner has passed all applicable tests.

3.3 Construction.

3.3.1 General. Each cleaner shall be complete, lubricated, and ready to operate (minor assembly is permitted). The design shall be simple in construction, shall permit easy accessibility to component parts for cleaning, inspection, adjustment, or replacement, and shall provide reliable operation. Similar component parts and assemblies of identical model number cleaners shall be fully interchangeable. Interchangeability shall not require alteration or modification.

3.3.2 Wet pickup. The cleaner shall be designed for wet pickup, i.e., retrieval of water or liquid cleaning solutions. The cleaner shall be provided with an automatic shutoff mechanism and accessories required to convert the machine from wet to dry pickup.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to: General Services Administration, Engineering Group (7FXEE), 819 Taylor St., Fort Worth, TX 76102.

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:27Z
Check the source to verify that this is the current version before use.

3.4 Switch. Each cleaner shall be provided with a quick make-and-break type power switch.

3.5 Cord. The power cord assembly shall have three conductors and a three-prong attachment plug, and shall have a minimum length of 35 feet (10.7 m).

3.6 Cord storage. Each cleaner shall be provided with a means for coiling, wrapping, or otherwise storing the power cord when the cleaner is not in use.

3.7 Filtration system.

3.7.1 General. The filtration system shall consist of the filter assemblies and the tank assembly. When the cleaner is employed for dry pickup, all filter assemblies shall be employed. When the cleaner is converted for liquid retrieval, the separator and automatic shutoff assembly may take the place of the primary filter(s).

3.7.2 Filters. The primary filter shall filter particulate matter approximately 1 µm and larger and shall retain this matter for easy disposal. This filter may be disposable. The additional filter(s) shall be of the high-efficiency particulate air impaction type in accordance with UL 586, entrapping 99.97% of all matter and microorganisms 0.3 µm and larger. No ingested unfiltered air shall be exhausted from the cleaner.

3.7.3 Tank. The tank shall be of stainless steel, plastic, or shall have a durable interior epoxy-coating. The tank shall hold the minimum liquid capacity for the size specified before the shutoff mechanism activates.

3.7.4 Wet pickup. When the cleaner is to be used for liquid retrieval, the only filter which must remain installed is the 0.3-µm high-efficiency particulate air impaction filter. The machine shall be equipped with an effective separator which will prevent liquids and nonparticulate solid objects from passing through to the impaction filter and vacuum producer. An automatic shutoff assembly shall be provided which interrupts the air intake or power to the cleaner when the minimum liquid capacity is reached.

3.8 Mobility. The cleaner shall have a bearing-equipped wheeled chassis or bearing-equipped wheels mounted on the tank to provide mobility. Wheels and casters are acceptable in any combination. The cleaner shall be equipped with a handle assembly suitable for use in cleaner movement. The cleaner shall be freewheeling and easily transportable.

3.9 Attachments.

3.9.1 General. The cleaner shall be furnished with one dusting brush, one wall brush, one 14-inch (356 mm) minimum squeegee tool, one 12-inch (305 mm) minimum bare floor tool, one crevice tool, one wand assembly, and one 10-foot (3.05 m) minimum hose assembly. The automatic shutoff assembly and the necessary attachments for conversion from dry to wet pickup shall be furnished as accessories with each cleaner.

3.9.2 Tool construction. Tools and their assembly hardware shall be fabricated from synthetics, ferrous metals, or nonferrous metals. Tools and assembly hardware fabricated from ferrous metal shall be plated or finished to resist corrosion and prevent marking. The brush and squeegee inserts shall be replaceable. The tools shall mechanically lock on the wand assembly or the hose assembly (if a metal connector is employed). A friction fit between the tool and the hose is acceptable if the hose end is of rubber or synthetic.

3.10 Hose construction. The hose shall be fabricated from nonmarking materials impervious to attack from common cleaning solutions. The hose shall have a minimum inside diameter of 1-1/2 inches (38.1 mm), and a minimum length of 10 feet (3.05 m). A swivel coupling shall be provided on the hose end attaching to

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:27Z
Check the source to verify that this is the current version before use.

the cleaner. The use of a swivel coupling on the wand end of the hose shall be optional.

3.11 Performance.

3.11.1 Noise. The maximum noise generated by the cleaner shall be 60 dbA when tested in accordance with ASTM F1334.

3.11.2 Continuous Duty. The cleaner shall be designed for continuous duty. Continuous duty is defined as constant operation for an 8-hour workday. As evidence of the continuous duty capability, the cleaner shall be capable of withstanding a continuous 10-hour run with the orifice wide open. All lubrication points except sealed bearings shall be visually checked after this run. The lubricant shall be visually examined and shall not contain any metallic particles and lubricant quantity shall be ample. Evidence of galling or similar deficiency or lack of lubrication shall be cause for rejection. The commutator(s) shall be visually examined. There shall be no evidence of burning or pitting.

3.11.3 Vacuum producer water lift. When tested in accordance with ASTM F558, the vacuum producer shall develop a minimum of 40 inches (1.02 m) of sealed water lift through a 3/4-inch (19.0 mm) orifice and 8 inches (203 mm) of sealed water lift through a 1-1/2-inch (38.1 mm) orifice.

3.11.4 Filtration. The contractor shall certify, or shall contract an independent laboratory to certify, that the filter system entraps and retains 99.97% of all microorganisms 0.3 µm and larger ingested by the cleaner. This certification shall detail the test methods, the aerosols, the culture mediums, the sample count, the bacterial count of the ingested air, the bacterial count of the exhausted air, and the collection efficiency expressed as a percentage. Culture mediums shall be exposed to the flow of the exhaust air for 5 ±0.5 minutes for the efficiency samplings. Certification tests shall also demonstrate that organisms cannot migrate through the filters. This shall be demonstrated by sampling exhaust air for at least 30 minutes after shutdown of the bacterial aerosol which the cleaner had been ingesting for the prior 30 minutes. Clean, new filter efficiencies shall be a minimum of 99.97%. Collection efficiencies shall show an upward trend as the cleaner is used.

3.11.5 Hose Compression. The hose shall withstand a minimum compressive load of 150 lb (667 N) applied to any portion of the hose no closer than 12 inches (305 mm) from any fitting by means of parallel flat surfaces having lengths of not more than 3 inches (76.2 mm) parallel to the axis of the hose for not less than 2 minutes. The compressive load shall cause no rupture of any portion of the hose and the resulting hose diameter shall not differ more than 1/16 inch (1.59 mm) from the diameter prior to the compressive load.

3.11.6 Couplings. The engaged wand, hose, and tools shall be able to withstand a tensile force of 25 lb (111 N) for 2 minutes at each coupling without separation. Couplings shall engage and release satisfactorily before and after being subjected to the 25-lb (111 N) tensile force.

3.12 Workmanship. The cleaner and all accessories shall be constructed, assembled, and finished in a manner to assure good quality equipment of a neat general appearance and free from imperfections which may affect durability, serviceability, and appearance.

3.13 Measurement system. The values stated in inch-pound units are to be regarded as the standard. The metric values stated in parentheses are provided to an accuracy of three significant digits and are for informational purposes only.

3.14 Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units,

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:27Z
Check the source to verify that this is the current version before use.

providing they fall within the tolerances specified and all other requirements of this document are met. If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request should be made to the contracting officer to determine if the product is acceptable.

3.15 Commercial item. The use of the term "commercial item" in this document does not imply that any item or items offered are not required to conform with all requirements specified herein.

4. REGULATORY REQUIREMENTS

4.1 Regulatory requirements. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

5. QUALITY ASSURANCE PROVISIONS

5.1 Contractor Certification. The contractor shall certify and maintain substantiating evidence that the product offered meets the salient characteristics of this Commercial Item Description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices, and is the same product offered for sale in the commercial marketplace. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

6. PACKAGING

6.1 Packaging. Preservation, packing, and marking shall be as specified in the contract or order.

7. NOTES

7.1 Referenced Documents. The documents referenced in this CID shall be the issues in effect on the date of issuance of the invitation for bids or request for proposals unless otherwise specified. The documents form a part of this CID to the extent specified. In the event of a conflict between this CID and the documents referenced herein, this CID shall take precedence.

American Society for Testing and Materials Standards:

ASTM F558 - Standard Test Method for Measuring Air Performance Characteristics of Vacuum Cleaners.

ASTM F1334 - Standard Test Method for Determining Sound Power Level of Vacuum Cleaners.

Application for copies of ASTM standards should be addressed to the American Society for Testing and Materials, 100 Barr Harbor Drive, West Conshohocken, PA 19428-2959.

Underwriters Laboratories Inc., Standards:

UL 586 - Safety High-Efficiency, Particulate, Air Filter Units.

UL 1017 - Safety Vacuum Cleaners and Blower Cleaners.

Application for copies of UL standards should be addressed to Underwriters Laboratories Inc., Publication Stock, 333 Pfingsten Road, Northbrook, IL 60062.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:27Z
Check the source to verify that this is the current version before use.

7.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents (if applicable).

a. Title, number and date of this commercial item description.
b. Size (see 2.1).
c. Preservation, packing, and marking desired.

MILITARY INTERESTS:

Preparing Activity:
GSA-FSS

Custodians
Air Force - 99

Review Activities
Air Force - 84

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:27Z
Check the source to verify that this is the current version before use.