[INCH-POUND]
A-A-3027
November 6, 1996

COMMERCIAL ITEM DESCRIPTION

CUTTER, WIRE ROPE, IMPACT (HAMMER ACTION)

The General Services Administration has authorized the use of this Commercial Item Description for the procurement of the type III cutters specified in GGG-C-800B for all federal agencies.

1. SCOPE.

1.1 Scope. This Commercial Item Description covers impact (hammer action) wire rope cutters suitable for cutting wire rope used in general purpose rigging by striking with a sledge or heavy-hand hammer.

2. CLASSIFICATION.

2.1 Classification. Not applicable.

3. SALIENT CHARACTERISTICS.

3.1 Design. The cutter shall consist of a body and base, plunger, cutting blade, and die. The parts shall be castings, forgings, molded, or welded, and in no event shall processes such as peening or plugging be used on castings or forgings for reclaiming any parts of the cutter. Surfaces of the cutter not otherwise plated, or of corrosion-resistant material shall be primed and painted with a good grade of enamel. All parts having the same manufacturer's part number shall be completely interchangeable, replaced, or adjusted without requiring modification. The cutter shall be similar to Figure 1, and the capacity, weight, and dimensions for various rope size cutters shall be as specified in Table I.




Figure 1. Cutter, wire rope, impact (hammer action).

Beneficial comments, recommendations, additions, deletions, clarifications, etc., and any other data which may improve this document should be sent to: General Services Administration, Federal Supply Service, Tools and Appliances Commodity Center, Kansas City, MO 64131.

Distribution Statement A. Approved for public release; distribution is unlimited. FSC 5110

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:28Z
Check the source to verify that this is the current version before use.

TABLE I. Cutter, wire rope, impact (hammer action)

Size number	Capacity range of wire rope diameter (Inches)	Weight (maximum) (Pounds)	Closed height (maximum) (Inches)	Base diameter	
				Minimum (Inches)	Maximum (Inches)
1	0 - 1 1/	10	6-3/4	3	3-3/4
2	0 - 1-1/16	20	7-1/4	5-3/4	6-1/4
3	0 - 1-1/2	38	9-5/8	7	8

1/ Occasional cutting only of wire rope over 5/8-inch diameter.

3.1.1 Body and base. The body and base of the cutter shall be of one-piece malleable or ductile iron casting having a heavy rib support and carrying handle. The upper part of the body shall have a shell-cored cast to provide a standard sliding fit with the plunger. The axis of the hole shall be 90 degrees with the underside of the base. The base shall be suitably finished to prevent rocking when the base is set upon a flat surface. The base of the cutter for sizes 2 and 3 (see Table I) shall have three holes that can be used for securely mounting the cutter on a firm support or foundation when desired.

3.1.2 Plunger. The plunger shall be of steel, properly rounded to a crown shape, and hardened to resist mushrooming or chipping and shall not bind in the reamed hole in the body as a result of hard usage. A means shall be provided for mounting the cutting blade in the plunger in such a manner that it will not become detached during hard use. The plunger shall have a longitudinal keyway or other suitable means provided to prevent rotation of the plunger or misalignment of the cutting blade.

3.1.3 Cutting blade. The cutting blade shall be of high grade tool steel properly hardened between 56 and 58 on the Rockwell C scale, and the cutting edge shall be shaped to the contour of the largest diameter wire rope for which the cutter is designed to aid in retaining the original roundness of the wire rope.

3.1.4 Die. The die shall be shaped to fit the contour of the wire rope as specified for the cutting blade. The die shall be of high grade tool steel hardened between 48-58 on the Rockwell C scale. The die shall be securely fastened in the upper side of the base directly in line with the descending cutting blade.

3.2 Identification marking. The tool shall be marked with the manufacturer's name or identifying symbol and the state or country of manufacture, unless otherwise specified. All identification markings shall be engraved, etched, molded, or indented directly on the item's surface in such a manner that it remains clearly legible throughout the life of the item.

3.3 Workmanship. Details of workmanship shall be in accordance with the best commercial practice. Paints, coatings, platings, and finishes shall be smooth, adherent, continuous, and not stained or discolored. External surfaces shall be free of tool and gouge marks, nicks, or other surface imperfections. The item shall be free from manufacturing workmanship defects (e.g., sharp or rough external edges, corners, or surfaces) and material workmanship defects (e.g., pits, rips, fins, burrs, tears, nodules, cracks, blisters) which may adversely impact the item's serviceability, durability, safety, or appearance.

4. REGULATORY REQUIREMENTS.

4.1 Recovered materials. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:28Z
Check the source to verify that this is the current version before use.

4.2 Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within the tolerances specified (using conversion tables contained in the latest revision of Federal Standard 376) and all other requirements of this document are met. If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request should be made to the contracting officer to determine if the product is acceptable.

5. QUALITY ASSURANCE PROVISIONS.

5.1 Product conformance. The product provided to the Government shall conform to the contractually specified requirements. For product characteristics and requirements which are not contractually specified, the provided product shall conform to the producer's own drawings, standards, specifications, and quality assurance practices for the highest quality product commercially offered by the producer. If the product is not commercially offered by the producer, the best commercial practices shall apply. The Government reserves the right to require proof of such conformances prior to first delivery and thereafter as provided for under the provisions of the contract.

5.2 Responsibility for inspection. Unless otherwise specified, the contractor is responsible for the performance of all inspection requirements and may use any commercial facilities (including the contractor's own facilities) suitable for performance of the inspection requirements, unless disapproved by the Government. The Government reserves the right to perform any inspections deemed necessary to assure the item conforms to the specified requirements.

5.3 Bid sample(s). When a bid sample requirement is specified in the solicitation, the bid sample(s) shall be inspected for all salient characteristics by the Government. A failure of any bid sample to meet the salient characteristics shall be cause for rejection.

5.4 First article sample(s). When a first article requirement is specified in the contract, the first article sample(s) shall be inspected for all salient characteristics. A failure of any first article sample to meet the salient characteristics shall be cause for rejection.

5.5 Hardness test. Each sample cutting blade shall be tested to determine conformance to the hardness requirement of 48-58 on the Rockwell C scale when tested in accordance with ASTM E18. Each sample die shall be tested in accordance with ASTM E18 to verify conformance to the requirement of 58 to 66 on the Rockwell C scale. Any sample failing to pass the hardness test shall cause the lot represented to be rejected.

5.6 Performance test. Sample cutters shall cut three pieces of plow steel wire rope of the maximum size specified for the applicable cutter. One sample shall be required to cut an additional 12 pieces of plow steel wire rope of the maximum size specified for the applicable cutter, except that 5/8 inch shall be used instead of 1 inch for the size 1 cutter in making the additional 12 cuts. The cutter shall make clean cuts without appreciable deformation of the wire rope. Performance of the cutter shall show no excessive rounding, chipping, or the edge turning over on the cutting blades which will render the cutter unsatisfactory for further severing of wire rope. All components shall function properly and show no evidence of damage. Any sample failing to pass the performance test shall be rejected and also the lot represented by the sample shall be rejected.

6. PACKAGING.

6.1 Packaging. Requirements of preservation, packing, packaging, and marking of packages shall be as specified in the contract or order.

7. NOTES.

(This section contains information of a general or explanatory nature that is not mandatory.)

7.1 Addresses for obtaining copies of referenced documents:

Federal Specifications and Standards: Federal Supply Service Bureau, Specification Section, Suite 8100, 470 L'Enfant Plaza, SW, Washington, DC 20407.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:28Z
Check the source to verify that this is the current version before use.

Federal Acquisition Regulations (FAR): Government Printing Office, Superintendent of Documents, Washington, DC 20402-9371.

ANSI/ASQC Z1.4: American Society for Quality Control, P.O. Box 3005, 611 East Wisconsin Avenue, Milwaukee, WI 43201-4606.

ASTM E18: American Society for Testing and Materials, 100 Barr Harbor Drive, West Conshohocken, PA 19428-2959.

7.2 Ordering data. Purchasers should select the preferred options permitted herein and should include the following information in procurement documents:

(a) Title, number, and date of this Commercial Item Description.
(b) When applicable, the appropriate NSN(s).
(c) If bid samples are required, the number of samples required, and the subjective inspection requirements.
(d) If first article samples are required and the number of samples required.
(e) If lot sampling inspection is required and the applicable lot sampling requirements. For example:

Sampling for inspection. Sampling for inspection (both examinations and testing) shall be in accordance with ANSI/ASQC Z1.4.

Inspection. Each sample tool shall be examined and tested for all salient characteristics. The Inspection Level shall be S-2 with an Acceptable Quality Level of 4.0, expressed in terms of defects per hundred units.

(f) What preservation, packing, packaging, and marking of packages are required.

7.3 National Stock Numbers (NSNs). The following list of NSNs corresponds to the cutters specified in this CID. This list may not be indicative of all possible NSNs associated with this CID.

NSN	
5110-00-242-8807	Size 1, 1 inch capacity
5110-00-293-1066	Size 3, 1-1/2 inch capacity

MILITARY INTERESTS:

NONE: DoD has no registered interest in revisions or notices to this Commercial Item Description until further notice.

PREPARING ACTIVITY:

GSA - FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:28Z
Check the source to verify that this is the current version before use.