A-A-50308
January 31, 1991

COMMERCIAL ITEM DESCRIPTION

BALANCER, VEHICLE WHEEL, BUBBLE-TYPE, PORTABLE

The General Services Administration has authorized the use of this Commercial Item Description (CID) as a replacement for Military Specification MIL-B-45989C(AL).

Abstract. This description covers a portable, bubble-type vehicle wheel balancer to balance wheel and tire assemblies of passenger cars and trucks through 1.25 ton.

Salient characteristics.

1. The balancer shall be equipped with an operator controlled mechanism for engaging and disengaging the contact between the balancing head assembly and its mating pivot point. When wheel and tire assemblies are lifted from the balancing head, contact between the balancing head assembly and the mating pivot point shall automatically disengage through a self activating mechanism without operator influence.

2. The balancer shall require no external energy source.

3. The balancer shall be equipped with a circular spirit level with a sensitivity of no less than 0.1 inch movement of bubble for zero degrees ten minute (10') angular displacement. The bubble balancer indicator shall be recessed in the balancing assembly head to prevent damage to the spirit level.

4. The balancing head assembly shall be equipped with a method or form of dampener to accommodate stabilization from oscillations or movement to completely stabilize within a period of 10 seconds from extreme amplitude or oscillating limits to stable level, using a balanced L 78-15 (9.00 x 15) wheel-tire assembly.

5. The balancer shall be equipped with a centering cone and leveling plate with accurately controlled surfaces. They shall accommodate all American passenger cars and trucks wheel and tire assemblies up to and including 1.25

Beneficial comments, recommendations, clarifications, additions, deletions, etc. and any data which may improve this document should be sent: Commander, US Army Armament Research, Development and Engineering Center, ATTN: SMCAR-EST-S, Rock Island, IL 61299-7300

AMSC N/A FSC 4910

DISTRIBUTION STATEMENT A. Approved for public release; distribution is

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:41Z
Check the source to verify that this is the current version before use.

ton having 2.00 through 5.00 inch inside diameter centering hole. If necessary, one machined adapter plate shall be furnished to fit wheel-to-hub bolt mounting holes of the 5, 6, and 8 hole patterns to accommodate vehicles 1.00 through 1.25 ton.

6. The balance accuracy shall be such that once a tire and wheel assembly have been balanced, the tire and wheel assembly can be lifted off of the balancer head, turned 90 degrees relative to the balancer head, replaced on the head, the balancer shall indicate no more unbalanced condition than that which requires a 0.25 ounce or less wheel weight to return the bubble to the center of the level indicator circle. The same accuracy shall be repeatable when the tire and wheel assembly are removed, rotated, and replaced in the same manner at 180 degrees, 270 degrees, and 360 degrees of rotation.

7. The balancer shall be provided with a base for floor mounting. The base may be fabricated of metal or high impact plastic. The base shall be provided with externally adjustable leveling device(s) to permit three-point leveling. The balance shall be capable of being leveled using its own balancer head spirit level bubble.

8. The balance shall be provided with all tools to perform its intended use, including passenger car and truck wheel weight removal and application tools.

9. Wheel weights shall be included in separate boxes of 50 each of 0.25, 0.50, 0.75, 1.00, 1.25, 1.50, 1.75, 2.00, 2.50, and 3.00 ounce and separate boxes of 25 each of 3.50 and 4.00 ounce wheel weights for passenger cars. There shall also be included separate boxes of 25 each of 0.5, 1.00, 2.00, 3.00, 4.00, 5.00, and 6.00 ounce wheel weights for Chrysler wheel Part Number 4026506 and for trucks up to 1.25 ton.

Contractor certification. The contractor shall certify and maintain substantiating evidence that the product offered meets the salient characteristics of this Commercial Item Description, and that the product conforms to the producer's own drawings, specifications, standards and quality assurance practices. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practicable.

Packaging. The preservation, packaging, packing, and marking shall be as specified in the contract or order.

NOTES.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:41Z
Check the source to verify that this is the current version before use.

Ordering data. Acquisition documents should specify the following:

Title, CID number, and date of this document.

As the result of a market acceptability survey, the following companies have shown to be manufacturers of an acceptable product described within this Commercial Item Description. This list does not limit or exclude the selection of other manufacturers who have an acceptable product provided that they meet the market acceptability survey criteria, as verified by the CID developer, that has been established for the CID. Other manufacturers' products will be considered for a current procurement if market acceptability qualification can be established before the specified date of contract award; otherwise other manufacturers' products will be considered for future solicitations.

Hennessy Industries, Incorporated
1601 J. P. Hennessy Drive
La Vergne, Tennessee 37086

MILITARY INTERESTS:

Custodian

Army - AL

CIVIL AGENCY COORDINATION ACTIVITY:

GSA - FSS

PREPARING ACTIVITY:

Army - AL

Project No. 4910-0698

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:41Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:41Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314



OFFICIAL BUSINESS

Commander
US Army Armament Research Development
and Engineering Center
ATTN: SMCAR-EST-S
Rock Island, IL 61299-7300

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:41Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 68 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:41Z
Check the source to verify that this is the current version before use.