A-A-50897A
24 March 1989
SUPERSEDING
A-A-50897
16 August 1983

COMMERCIAL ITEM DESCRIPTION

DESK, FLAT TOP

Corrosion-Resisting Steel

The General Services Administration has authorized the use of this Commercial Item Description as a replacement for Federal Specification AA-D-170 which is cancelled.

This Commercial Item Description covers a nurse's single pedestal, flat top corrosion-resisting steel desk.

Salient characteristics:

The flat top desk shall be a corrosion-resisting steel nurse's desk of the single pedestal type. The steel shall be American Iron and Steel Institute (AISI) Series 300 corrosion-resisting steel. The pedestal shall be located at the right end of the desk and shall be fitted with a minimum of three drawers. The desk shall have four or six tubular legs, each a minimum of 1 inch in diameter and fitted with a rubber crutch-type tip. The legs and pedestal shall be joined, braced, and welded into a rigid unit. The desk shall rest evenly with all leg crutch tips contacting a flat surface and shall not shake nor wobble when tested as specified.

Desk top shall be one continuous sheet of No. 16 U.S. Standard Gage (0.060 thick), or thicker, with all edges turned down and hemmed. Corners of the top shall be rounded to conform to the contour of the legs, and shall be fully welded, ground and polished to eliminate all traces of the seams. The top working surface shall measure a nominal 36 inches wide and 24 inches deep.

AMSC N/A FSC 6530

DISTRIBUTION STATEMENT A. Approved for public release, distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:48Z
Check the source to verify that this is the current version before use.

The desk top shall have a guardrail which shall be continuous around the back and ends of the desk and shall be made of 3/8 inch minimum diameter stainless steel rod. The guardrail shall be bent at each end to form uprights, and shall have a minimum of two additional uprights of similar material continuously welded to the rail. All uprights shall be properly flattened at their lower ends, drilled, and secured to the desk.

The inside dimensions of the drawers shall be not less than 20-1/2 inches by 11-3/8 inches. The drawers shall operate smoothly with a minimum of sideway. Sideway is excessive if the drawer binds or leaves its track under normal use. The drawers shall close silently against suitable rubber bumpers. The drawer slides shall have stops to prevent inadvertent removal of the drawer; however the stops shall not preclude removal of the drawer for cleaning purposes, when desired. Each drawer shall be supplied with a full handle, shaped for convenient and comfortable handling, and secured by screws.

The drawer slides shall have detents or shall be pitched at a slight angle towards the rear to prevent drawers from rolling open, if the desk is placed on a floor slightly out of level. The drawer shall operate on rubber or nylon tired ball-bearing rollers.

All drawers shall have double wall fronts with sound insulation, such as a suitable mastic or foam and shall be constructed of No. 20 U.S. Standard Gage (0.036 inch thick) steel. The top drawer shall be fitted with a lock and supplied with two keys. Each desk shall be keyed individually. The locking mechanism shall be of such a design that with the top drawer locked, the lower drawers shall lock automatically when closed.

All welds shall be durable and sound in every detail. Spotwelding shall be accomplished in such a manner as to assure thorough, well-fused welds of maximum strength. All normally visible butt and fillet welds, including welds which are visible when the drawers are open, shall be ground smooth and polished so as to blend in with the adjacent surfaces. All indentations, extrusions, and discolorations due to spotwelding that are normally visible, including those visible with drawers open, shall be cleaned and polished.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:48Z
Check the source to verify that this is the current version before use.

All normally visible surfaces of the desk shall have a No. 4 commercial finish or better. The finish of the drawer handles shall match that of the desk. All burrs shall be removed and all sharp edges shall be broken to eliminate completely any possibility of injury and the catching or tearing of clothing of personnel working at or about the desk. The finished desk shall be cleaned of all foreign matter including, but not limited to, dirt, grease, oil and metal chips.

Workmanship. The flat top desk shall be free from defects which detract from its appearance or impair its serviceability.

Unit. Each (EA). One desk, as specified, constitutes one unit.

Quality Assurance Provisions.

Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Records. Records of examinations and tests performed by or for the contractor shall be maintained by the contractor and made available to the Government upon the Government's request, at any time, or from time to time, during the performance of the contract and for a period of three years after delivery of the supplies to which such records relate.

Inspection. Inspection, as used herein, is defined as both examination (such as visual or auditory investigation without the use of special laboratory appliances or procedures) and testing (determination by technical means of physical and chemical properties) of the item.

Tests. Tests shall be conducted to determine compliance with specification requirements. Where feasible, the same sample shall be used for the determination of two or more test characteristics.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:48Z
Check the source to verify that this is the current version before use.

Sampling for examination. Sampling for examination shall be conducted in accordance with MIL-STD-105, with an AQL of 2.5 (percent defective) and an inspection level of S-2. The unit of product for examination purposes shall be one flat top desk as specified in this description.

Defects.

Desk assembly is not complete with all specified components.

Desk is not rigidly and squarely assembled.

Desk legs do not bear uniformly on a flat level surface.

Component parts or surfaces of desks are buckled or otherwise not free of deformed areas.

Drawers fail to operate smoothly or do not close flush with face of pedestal.

Keys for top drawer lock missing.

Visible internal and external welds do not blend with adjacent surfaces.

Desk edges and corners are not free of burrs or sharp edges.

Desk finish is not a No. 4 commercial finish or better.

Desk is not free of excessive surface scratches, foreign matter, metal chips, oil, or grease.

Sampling for tests. Sampling for tests including dimensional tests, shall be conducted in accordance with MIL-STD-105, with an AQL of 2.5 (percent defective) and an inspection level of S-1. The unit of product for test purposes shall be one flat top desk.

a. First article. Where a first article sample is required, all tests shall be performed on that unit.

b. Acceptance testing. When a first article sample has not been required, one unit shall be subjected to the performance test specified herein. If a test article sample has successfully passed all tests, performance test shall not be required at acceptance.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:48Z
Check the source to verify that this is the current version before use.

Tests

Stability. Desk shall be tested for shake or wobble, by shaking by hand, while the desk is resting in a flat surface. Any shake or wobble of the desk while testing shall constitute a defect.

Drawer Locking Mechanism. With the top drawer closed and locked, the ability of the locking mechanism to automatically lock the lower drawers closed shall be tested. Failure to lock the lower drawers closed shall constitute a defect.

Drawer Slide and Stops. Each drawer shall be tested for smooth, sway-free operation and ability of the slide stops to prevent inadvertent removal of the drawer. A five pound weight shall be in each drawer during the testing. Any failure to function as specified shall constitute a defect.

Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, providing they fall within the tolerances specified using conversion tables contained in the latest revision of Federal Standard 376, and all other requirements of this document are met.

If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch/pound units, a request should be made to the contracting officer to determine if the product is acceptable.

The contracting officer has the option of accepting or rejecting the product.

Contractor certification. The contractor shall certify that the product offered meets the salient characteristics of this description and conforms to the producers' own drawings, specifications, standards, and quality assurance practices. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:48Z
Check the source to verify that this is the current version before use.

Regulatory requirements.

Federal Food, Drug and Cosmetic Act. If the product covered by this document has been determined by the U.S. Food and Drug Administration to be under its jurisdiction, the offeror/contractor shall comply, and be responsible for compliance by its subcontractors/suppliers, with the requirements of the Federal Food, Drug and Cosmetic Act, as amended, and regulations promulgated thereunder. In addition, the offeror/contractor shall comply, and be responsible for compliance by its subcontractors/suppliers, with the requirements of all other applicable Federal, State, and local statutes, ordinances, and regulations.

Recovered materials. The offeror/contractor is encouraged to use recovered material in accordance with Public Law 94-580, as amended, and as implemented by Federal Acquisition Regulation Subpart 23.4 to the maximum extent practical.

Preservation, packaging, packing, labeling, and marking. Unless otherwise specified, preservation, packaging, and packing shall be to a degree of protection to preclude damage to containers and/or contents thereof under normal shipping conditions, handling, etc., involving shipment from the supply source to the receiving activity, plus reshipment from receiving activity, and shall conform to applicable carrier's rules and regulations. Intermediate and exterior package quantities and labeling and marking shall be as specified in the contract and/or order.

NOTE: The following National Stock Number is covered by this document:

6530-00-705-4975

Ordering data. Intermediate/exterior package quantities, labeling, and marking must be specified in the contract and/or order.

MILITARY INTERESTS:

Custodians:

Army - MD
Navy - MS
Air Force - 03

PREPARING ACTIVITY:

DoD - MB

Agent:

DLA-DM

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:48Z
Check the source to verify that this is the current version before use.

CIVIL AGENCY COORDINATING ACTIVITIES:

VA-OSS
PHS
FDA-MPQAS

Project No. 6530-2046

Location: CID/DESK/H13-33

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:48Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions - Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
A-A-30897A	DESK, FLAT TOP

NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION (Mark one)
	☐ VENDOR
	☐ USER
b. ADDRESS (Street, City, State, ZIP Code)	☐ MANUFACTURER
	☐ OTHER (Specify)

5. PROBLEM AREAS

a. Paragraph Number and Wording

b. Recommended Wording

c. Reason/Rationale for Recommendation

6. REMARKS

NAME OF SUBMITTER (Last, First, MI) - Optional	b. WORK TELEPHONE NUMBER (Include Area Code) - Optional
c. MAILING ADDRESS (Street, City, State, ZIP Code) - Optional	8. DATE OF SUBMISSION (YYMMDD)

DD FORM 1426

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:48Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge (DO NOT STAPLE), and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation was too rigid, restrictive, loose, ambiguous or was incompatible and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEFENSE LOGISTICS AGENCY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO 4948 WASH D C

POSTAGE WILL BE PAID BY THE DEFENSE LOGISTICS AGENCY

Commander
Defense Personnel Support Center
ATTN: DPSC-BSTE
2800 South 20th Street
Philadelphia, Pennsylvania 19101-8419

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:48Z
Check the source to verify that this is the current version before use.