NOTE.—This drawing was approved by joint action of the Air Force and Navy Department as the Air Force-Navy standard for this product. This drawing supersedes all antecedent standard drawings for the same product and shall become effective for the procurement of aeronautical supplies, or for use in new design, not later than six months after the latest date of approval shown.

NOTICE.—When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

PROCUREMENT SPECIFICATION

MIL-V-5529

AIR FORCE-NAVY AERONAUTICAL STANDARD

VALVE - RADIAL TYPE 6 GPM HYDRAULIC DIRECTIONAL CONTROL

AN6214

RETURN OUTLET CONNECTION BOSS IN ACCORDANCE WITH AND10050 FOR 1/2 OD TUBE

$1\frac{1}{4}$ MAX

$1\frac{1}{4}$ MAX

$\frac{15}{16}$

$1\frac{7}{8}$

RETURN

CYL B

CYL A

PRESSURE

5 MAX

$\frac{15}{16}$

$1\frac{7}{8}$

5 MAX

NOT RESTRICTIVE AS TO SHAPE BUT VALVE SHALL BE WITHIN MAX ENVELOPE DIMENSIONS

CYLINDER CONNECTION BOSS IN ACCORDANCE WITH AND10050 FOR 1/2 OD TUBE

PRESSURE INLET CONNECTION BOSS IN ACCORDANCE WITH AND10050 FOR 1/2 OD TUBE

SLOT IN END OF CAM SHAFT ALIGNS WITH NEUTRAL MARK WHEN VALVE IS IN NEUTRAL POSITION

FACE OF MOUNTING HOLES

5/8 DIA SPOTFACE 4 HOLES

THREAD NO. 10-32 NF-3 PERFECT THREADS 5/16

$\frac{1}{2}$ MAX DIA

$\frac{1}{2}$

$\frac{27}{32}$

$\frac{51}{64}$

$1\frac{5}{8}$

$1\frac{3}{16}$

5/16 DIA SERRATED SHAFT SEE DETAIL A

.193 DIA 4 HOLES THROUGH FOR MOUNTING

3.437

1.719

1.312

2.625

45°

NEUTRAL POSITION

THREE SERRATIONS REMOVED TO .291 $^{+.000}_{-.005}$ DIA. CENTER TOOTH ALIGNS WITH INDEX MARK ON SHAFT AND ℄ OF CAM PEAK WITHIN ±1°

STRAIGHT CUT OPTIONAL

90°

36 SERRATIONS

80°

.291 INSIDE DIA MAX

.302 ±.001 PITCH DIA

.311 $^{+.000}_{-.001}$ OD

DETAIL A (ENLARGED)

AN PART NO.
(a) AN6214-2

INACTIVE FOR DESIGN ③ AFTER 10 JULY 1950. SEE DRAWING AN6293 OR, WHERE SUITABLE, AN6294.

(a) PREVIOUS PART NO. AN6214-1 INACTIVE FOR DESIGN AFTER 23 MAY 1945. PART NO. AN6214-2, INCORPORATING HANDLE STOPS, REPLACES AND IS INTERCHANGEABLE WITH AN6214-1.

FOR DEFINITION AND APPLICATION OF DRAWING STATUS NOTES, SEE ANA BULLETIN NO. 337.
FOR ACCEPTABLE PRODUCTS, SEE ANA BULLETIN NO. 119.
THE AIRPLANE OR ENGINE MANUFACTURER SHALL ALLOW CLEARANCE FOR THE MAXIMUM DIMENSIONS SHOWN ON THIS DRAWING FOR INSTALLATIONS.
DIMENSIONS IN INCHES. UNLESS OTHERWISE SPECIFIED, TOLERANCES: FRACTIONS ±1/64, DECIMALS ±.005, ANGLES ±1/2°.

APPROVED 28 May 43 REVISED ① 23 May 45 ② 19 Jul 48 ③ 10 Jul 50

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T14:22Z
Check the source to verify that this is the current version before use.