MIL-C-9075A(USAF)
AMENDMENT 3
19 JUNE 1987
SUPERSEDING
AMENDMENT 2
28 AUGUST 1981

MILITARY SPECIFICATION

COMPUTER AND TRANSMITTER, TRUE AIRSPEED, PITOT-STATIC,
150-900 KNOTS, TYPE MA-1

This amendment forms a part of MIL-C-9075A(USAF), dated 15 October 1968, and is approved for use within the Department of the Air Force and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

* 2.1 Delete "first sentence" and add: Government documents.

* Add: "2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation."

Under "SPECIFICATIONS, Federal", delete "QQ-P-416" and add the following:

"PPP-B-601	Boxes, Wood, Cleated Plywood
PPP-B-636	Box, Shipping, Fiberboard"

* Under "SPECIFICATION, Military", delete "MIL-E-5272", change "MIL-D-1000" to read "DOD-D-1000" and add the following:

"MIL-C-83488	Coating, Aluminum, Ion Vapor Deposited"

Add boxed paragraph at bottom center of page:

Beneficial comments (recommedations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Oklahoma City Air Logistics Center/MMEDO, Tinker AFB OK 73145-5990 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

PAGE 2

Under "STANDARDS, Military" delete "MIL-STD-105", "MIL-STD-834" and add the following:

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:55Z
Check the source to verify that this is the current version before use.

"MIL-STD-810 Environmental Test Methods"

* Add: "2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issue of the nongovernment documents which is current on the date of the solicitation."

ASTM B117 Standard Method of Salt Spray (Fog) Testing

ASTM D3951 Packaging, Commercial

(Application for copies should be addressed to: ASTM, 1916 Race St, Philadelphia PA 19103.)

(Nongovernment standards and other publications are normally available from the organization which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)"

Add: "2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained."

* 3.1 Delete existing paragraph and add:

"3.1 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.3 and 6.4)."

PAGE 3

* Add: "3.3.4 Recycled and reclaimed materials. The use of recycled and reclaimed materials shall be encouraged to the maximum extent possible without jeopardizing the intended end use of the item."

PAGE 7

3.6 Line 4 delete "MIL-D-1000" and add: "DOD-D-1000".

PAGE 8

3.9.2 Delete existing paragraph and add:

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:55Z
Check the source to verify that this is the current version before use.

"3.9.2 Steel parts. Steel parts shall be coated with ion vapor deposited aluminum, where practicable, in accordance with MIL-C-83488, type I or II as applicable and of a class that is adequate to achieve the degree of protection required. Other protective coating, in lieu of MIL-C-83488, may be used if demonstrated to the satisfactory and approved by the cognizant engineering activity. Cadmium plating must be avoided when satisfactory alternative processes can be used."

PAGE 9

* Add: "4.1.1 Respnsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsiblity of assurinig that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material."

Delete "4.2" and "a" and add new: "4.2 Classification of inspections. The inspection requirements specified herein are classified as follows: a. First article inspection (see 4.3)."

PAGE 11

4.3 Title and line 1 delete "Qualification" and add: "First article".

PAGE 12

Delete "4.5 and add: "4.5 Inspection conditions. Unless otherwise specified, all inspection shall be performed in accordance with the test conditions specified in 4.5.1 of this specification.

PAGE 27

4.6.14 Renumber present paragraph to "4.6.14.1". Add new preceding paragraph title as follows:

"4.6.14 Vibration.

Add new paragraph 4.6.14.2 as follows:

"4.6.14.2 Vibration failure. The computer and transmitter shall be mounted on the vibration stand in its normal operating position. The test shall be conducted while a differential pressure of 400 knots is applied to the computer and transmitter. With pressure applied, the instrument assembly shall be vibrated with circular motion of 0.018 to 0.020 inch diameter in a plane inclined 45 degrees of the horizontal plane and the frequency of vibration shall be varied uniformly from 5-50 Hz and return once each hour for a 3-hour period.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:55Z
Check the source to verify that this is the current version before use.

The difference between the indication of the pointer at the beginning and at the end of the 3-hour vibration period shall not exceed the tolerance specified in Table VIII and no looseness in the mechanism nor damage shall result in any part of the computer and transmitter."

4.6.15 Delete "MIL-E-5272" and add: "MIL-STD-810".

4.6.15.1 Line 1 delete "Procedure II" and add: "Method 502.1, Procedure I, except that the temperature for step 2 shall be -62°C (-80°F) and the period shall be 72 hours. The chamber temperature for step 4 is -54°C (-65°F)."

PAGE 29

4.6.15.2 Delete the first sentence and add: "Method 501.1, Procedure I, except that steps 4 and 5 shall be deleted for a period of 24 hours.

4.6.15.3 Delete paragraph in its entirety.

4.6.15.4 Delete "Procedure I" and add: "Method 507.1, Procedure I, except that the temperature in step 2 shall be 71°C (160°F) and step 6 shall be deleted."

4.6.15.5 Delete "Procedure I" and add: "Method 508.1, Procedure I, except that substitute test fungi may be used in 3.1.2, with the approval of the preparing activity."

4.6.17 Lines 1 and 2 Delete "Procedure I of MI1-E-5272" and add: "Method 509.1, Procedure I of MIL-STD-810."

Add new paragraph as follows:

"4.6.17.1 Alternate method. This method shall be in accordance with the American Society for Testing and Materials Standard ASTM B117, except as otherwise specified herein. The computer and transmitter shall be pretested, installed in the test faciltiy and post exposure inspected in accordance with the general requirements (section 3) of MIL-STD-810. Upon completion of the 50 hour exposure and inspection, the individual tests shall be repeated. No damage shall result from the test and the tolerances specified for the individual tests shall apply."

PAGE 30

4.8 Delete paragraph in its entirety and add:

* 4.8 Inspection of packaging. The inspection of the preservation packaging and interior package marking shall be in accordance with group A and B quality conformance inspection requirements, section 4 of MIL-P-116. The sampling and inspection of the packing and marking for shipment and storage shall be in accordance with the quality assurance provisions of applicable container specification and the marking requirements of MIL-STD-129.

* Delete Section 5 in its enirety and add:

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:55Z
Check the source to verify that this is the current version before use.

"5. Packaging

5.1 Preservation. Preservation shall be level A, C, or industrial as specified (see 6.5).

5.1.1 Level A.

5.1.1.1 Cleaning. Computer and transmitter shall be cleaned in accordance with process C-1 of MIL-P-116.

5.1.1.2 Drying. Computer and transmitter shall be dried in accordance with process D-4 of MIL-P-116.

5.1.1.3 Preservation application. Not applicable.

5.1.1.4 Unit packaging. Unless otherwise specified by the contracting activity, each computer and transmitter shall be packed in quantity unit packs of one each in accordance with Method IC-2 of MIL-P-116. Each computer and transmitter shall be placed in a PPP-B-636 Fiberboard container weather resistant, with sufficient cushioning material between bag and unit container of a type, density, and thickness to insure shock transmission does not exceed peak values in G's established for the computer and transmitter when completed packs are subjected to the rough handling drop tests of MIL-P-116.

5.2.1 Level C. Each computer and transmitter shall be clean, dry, and individually packaged in a manner that will afford adequate protection against corrosion, deterioration, and physical damage during shipment from supply source to the first receiving activity.

5.1.3 Industrial. The Industrial preservation of computer and transmitter shall be in accordance with ASTM D3951.

5.2 Packing. Packing shall be level A, B, C, or Industrial as specified (see 6.5).

5.2.1 Level A. Computer and transmitter packaged as specified in 5.1.1 shall be packed in shipping containers conforming to PPP-B-601, Styles A or B, Class overseas, unless otherwise specified by the contracting activity. Insofar as practical, exterior shipping container shall be of uniform shape, size, minimum tare and cube consistent with the protection required.

5.2.2 Level B. Computer and transmitter packaged as specified in 5.1.1 shall be packed in shipping containers conforming to PPP-B-636, class weather-resistant, unless otherwise specified by the contracting activity. Other requirements as specified in 5.2.1 apply.

5.2.3 Level C. Packing shall be applied which affords protection from domestic shipment from the supply source to the first receiving activity for immediate use. This level shall conform to applicable carrier rules and regulations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:55Z
Check the source to verify that this is the current version before use.

5.2.4 Industrial. The packaged computer and transmitter shall be packed in accordance with ASTM D3951.

5.3 Marking. In addition to any other markings required by the contract or order (see 6.5), interior and exterior containers shall be marked in accordance with MIL-STD-129.

PAGE 32

6.4 Delete existing paragraph and add:

"6.4 First article. A first article is required for inspection and it shall be tested and approved under the appropriate provisions of 7-104.55 of the Defense Aquisition Regulation. First article test are described in 4.3. The contracting officer should include specific instructions in all procurement instruments, regarding arrangements for examinations, test and approval of the first article."

Add: "6.5 Ordering data. Procurement documents should specify the following:

a. Title, number, and date of this specification.

b. The quantity, part number and class number of the instrument desired.

c. Whether sampling plan B tests are to be conducted.

d. Reinspection date marking.

e. Level of packaging (5.1) and packing (5.2) desired.

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
AIR FORCE-99

Preparing Activity:
AIR FORCE-71

Project No:
6610-F163

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:55Z
Check the source to verify that this is the current version before use.