INCH-POUND
MIL-C-9075A(USAF)
AMENDMENT 4
15 APRIL 1994
SUPERSEDING
AMENDMENT 3
19 JUNE 1987

MILITARY SPECIFICATION

COMPUTER AND TRANSMITTER, TRUE
AIRSPEED, PITOT-STATIC, 150-900
KNOTS, TYPE MA-1

This amendment forms a part of
MIL-C-9075A(USAF), dated 15 October 1968,
and is approved for use by the Department of the Air Force
and is available for use by all Departments and Agencies of
the Department of Defense.

PAGE1

2.1 Delete "first sentence" and add: Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

Under SPECIFICATIONS, Federal, delete "QQ-P-416" and add: "PPP-B-636 Box, Shipping, Fiberboard".

Under "SPECIFICATION, Military", delete "MIL-E-5272", change "MIL-D-1000" to read "MIL-STD-100" and add the following: "MIL-C-83488 Coating, Aluminum, Ion Vapor Deposited"

Add boxed paragraph at bottom center of page:

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Oklahoma City Air Logistics Center/TICLA, Tinker AFB, OK 73145-5990 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

PAGE 2

* Under STANDARDS, add: "Federal" and under federal add: "FED-STD-101 Preservation, Packing And Materials: Test Procedures".

* Under STANDARDS, Military, delete "MIL-STD-105", "MIL-STD-143", "MIL-STD-794", "MIL-STD-834" and add: "MIL-STD-810 Environmental Test Methods", "MIL-STD-970 Standards & Specifications, Order Of Preference For The Selection Of" and "MIL-STD-2073-1 DOD Materiel Procedures For Development & Application Of Packaging Requirements".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:55Z
Check the source to verify that this is the current version before use.

Delete the following parenthetical source statement and add new: "(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Document Order Desk, 700 Robbins Ave, Building #4, Section d, Philadelphia, PA 19111-5094.)"

*Add: "2.2 Non-Government publications. The following document (s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2)

American Society For Testing and Materials (ASTM)
ASTM B117 Standard Method Of Salt Spray (Fog) Testing

(Application for copies should be addressed to: ASTM, 1916 Race St, Philadelphia, PA 19103.)

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)"

*Add: "2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein (except for related associated detail specifications, specification sheets, or MS standards), the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained."

3.1 Delete existing paragraph and add: "3.1 First article. When specified (see 6.4), a sample shall be subjected to first article inspection (see 6.4) in accordance with 4.3."

* 3.2 Line 3 delete "MIL-STD-143" and add: "MIL-STD-970".

PAGE 3

Add: "3.3.4 Recycled and reclaimed materials. The use of recycled and reclaimed materials shall be encouraged to the maximum extent possible without jeopardizing the intended end use of the item."

PAGE 7

3.6 Line 4 delete "MIL-D-1000" and add: "MIL-STD-100".

PAGE 8

3.9.2 Delete existing paragraph and add: "3.9.2 Steel parts. Steel parts shall be coated with ion vapor deposited aluminum, where practicable, in accordance with MIL-C-83488, type I or II as applicable and of a class that is adequate to achieve the degree of protection required. Other protective coating, in lieu of MIL-C-83488, may be used if demonstrated to the satisfactory and approved by the cognizant engineering activity. Cadmium plating must be avoided when satisfactory alternative processes can be used."

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:55Z
Check the source to verify that this is the current version before use.

PAGE 9

* Delete "4.1" entirely and add: "4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements."

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system ar quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

Delete "4.2" and "a" and add new: "4.2 Classification of inspections. The inspection requirements specified herein are classified as follows: a. First article inspection (see 4.3)."

PAGE 11

4.3 Title and line 1 delete "Qualification" and add: "First article".

PAGE 12

Delete "4.5 and add: "4.5 Inspection conditions. Unless otherwise specified, all inspection shall be performed in accordance with the test conditions specified in 4.5.1 of this specification.

PAGE 27

4.6.14 Renumber present paragraph to "4.6.14.1". Add new preceding paragraph title as follows:

"4.6.14 Vibration.

Add new paragraph 4.6.14.2 as follows:

"4.6.14.2 Vibration failure. The computer and transmitter shall be mounted on the vibration stand in its normal operating position. The test shall be conducted while a differential pressure of 400 knots is applied to the computer and transmitter. With pressure applied, the instrument assembly shall be vibrated with circular motion of 0.018 to 0.020 inch diameter in a plane inclined 45 degrees of the horizontal plane and the frequency of vibration shall be varied uniformly from 5-50 Hz and return once each hour for a 3-hour period. The difference between the indication of the pointer at the beginning and at the end of the 3-hour vibration period shall not exceed the tolerance specified in Table VIII and no looseness in the mechanism nor damage shall result in any part of the computer and transmitter."

4.6.15 Delete "MIL-E-5272" and add: "MIL-STD-810".

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:55Z
Check the source to verify that this is the current version before use.

4.6.15.1 Line 1 delete "Procedure II" and add: "Method 502.1, Procedure I, except that the temperature for step 2 shall be -62°C (-80°F) and the period shall be 72 hours. The chamber temperature for step 4 is -54°C (-65°F)."

4.6.15.2 Delete the first sentence and add: "Method 501.1, Procedure I, except that steps 4 and 5 shall be deleted for a period of 24 hours.

4.6.15.3 Delete paragraph in its entirety.

4.6.15.4 Delete "Procedure I" and add: "Method 507.1, Procedure I, except that the temperature in step 2 shall be 71°C (160°F) and step 6 shall be deleted."

4.6.15.5 Delete "Procedure I" and add: "Method 508.1, Procedure I, except that substitute test fungi may be used in 3.1.2, with the approval of the preparing activity."

4.6.17 Lines 1 and 2 Delete "Procedure I of MIL-E-5272" and add: "Method 509.1, Procedure I of MIL-STD-810."

Add new paragraph as follows:

"4.6.17.1 Alternate method. This method shall be in accordance with the American Society for Testing and Materials Standard ASTM B117, except as otherwise specified herein. The computer and transmitter shall be pretested, installed in the test facility and post exposure inspected in accordance with the general requirements (section 3) of MIL-STD-810. Upon completion of the 50 hour exposure and inspection, the individual tests shall be repeated. No damage shall result from the test and the tolerances specified for the individual tests shall apply."

4.8 Delete paragraph in its entirety and add:

4.8 Inspection of packaging. The inspection of the preservation packaging and interior package marking shall be in accordance with group A and B quality conformance inspection requirements, section 4 of MIL-P-116. The sampling and inspection of the packing and marking for shipment and storage shall be in accordance with the quality assurance provisions of applicable container specification and the marking requirements of MIL-STD-129.

* Delete Section 5 in its entirety and add:

*"5. PACKAGING.

5.1 Preservation. Preservation shall be level "A" or "C", as specified. (see 6.2)

5.1.1. Preservation-packaging. Unless otherwise specified by the contracting activity, item shall be packaged in Quantity Unit Pack (QUP) of one each. Each item will be provided a preservation method IA-14 In Accordance With (IAW) MIL-P-116.

5.1.2 Cleaning. Item shall be cleaned IAW MIL-P-116. C-1 process.

5.1.3 Drying. Immediately after cleaning, the item shall be dried following any one or combination of the drying procedures listed in MIL-P-116. The drying procedures employed shall not be injurious to the item.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:55Z
Check the source to verify that this is the current version before use.

5.1.4 Level A. Item shall be preserved IAW MIL-P-116 and MIL-STD-2073-1 to provide a method IA-14.

5.1.5 Level C Item shall be individually preserved in a manner that will afford adequate protection against corrosion, deterioration, and physical damage during shipment from the supply source to the first receiving activity as specified in MIL-P-116 and MIL-STD-2073-1.

5.2 Packing. Packing shall be level "A", "B", or "C", as specified. (see 6.2)

5.2.1 Container-cushioning. Unit container requirements shall conform to established procedures, as specified in OC-ALC/DSTD Special Packaging Instructions (SPI) 00-692-4460, unless otherwise specified by the contracting activity. Unit container shall be large enough to allow for the application of cushioning/wrap material, of sufficient density and thickness, to protect the unit container from punctures. Intermediate container requirements shall conform to OC-ALC/DSTD SPI 00-692-4460 unless otherwise specified by the contracting activity. Cushioning material requirements shall comply with OC-ALC/DSTD SPI 00--692-4460.

5.2.2 Level A. Fiberboard containers do not meet Level "A" container criteria.

5.2.3 Level B. Item will be preserved as specified in 5.1 and shall be packed in exterior containers as specified in OC-ALC/DSTD SPI 00-692-4460 unless otherwise specified by the contracting activity. Closure shall be in accordance with appropriate PPP-B-636 procedures, OC-ALC/DSTD SPI 00-692-4460, and contracting activity.

5.2.4 Level C. Item will be packed in such a manner that will afford adequate protection against physical damage during direct domestic shipment from the supply source to the first receiving activity.. These packs shall conform to MIL-STD-2073-1.

5.3 Marking. Unit, intermediate, and exterior containers shall be marked IAW special markings required by the contractor activity, OC-ALC/DSTD SPI 00-692-4460 and MIL-STD-129.

5.4 Inspection and test. Test of methods of preservation shall be accomplished in accordance with section 4 of MIL-P-116 to insure compliance with section 5 of this specification. Packaging tests shall be conducted IAW rough handling as specified in FED-STD-101.

PAGE 31

* Under 6. NOTES add: "(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)"

PAGE 32

6.4 Delete existing paragraph and add:

"6.4 First article. A first article is required for inspection and it shall be tested and approved under the appropriate provisions of 7-104.55 of the Defense Acquisition Regulation. First article test are described in 4.3. The contracting officer should include specific instructions in all procurement instruments, regarding arrangements for examinations, test and approval of the first article."

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:55Z
Check the source to verify that this is the current version before use.

AMENDMENT 4

* Add: "6.5 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of the specification.
b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced. (see 2.1).
c. The quantity, part number, and class number of the instrument desired.
d. Whether sampling plan B tests are to be conducted.
e. Reinspection date marking.
f. Level of packaging (5.1) and packing (5.2) desired.

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
AIR FORCE-99

Preparing Activity:
AIR FORCE-71

Project No:
6610-F368

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:55Z
Check the source to verify that this is the current version before use.