MILITARY SPECIFICATION

CONVERTER, OXYGEN, AIRCRAFT, LIQUID TO GASEOUS, GENERAL SPECIFICATION FOR

This specification is approved for use within the Department of the Air Force and is available for use by all Departments and agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the general requirements for liquid oxygen converters which convert liquid oxygen to gaseous oxygen at pressures of either 70 or 300 psig.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standard and handbooks form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

Federal

PPP-B-636	Box, Shipping, Fiberboard

Military

MIL-P-116	Preservation, Methods Of
MIL-P-7105	Pipe Threads; Taper, Aeronautical National Form, Symbol ANPT, General Requirements For
MIL-S-7742	Screw Threads, Standard, Optimum Selected Series, General Specification For
MIL-V-9050	Valves, Oxygen, Pressure Relief, Aircraft
MIL-L-25567	Leak Detection Compound, Oxygen Systems
MIL-O-27210	Oxygen, Aviator's Breathing, Liquid and Gas
MIL-T-27730	Tape, Antiseize, Tetrafluoroethylene, with Dispenser

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Oklahoma City Air Logistics Center/MMEDO, Tinker AFB 73145-5990 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1660
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:56Z
Check the source to verify that this is the current version before use.

STANDARDS

Federal

FED-STD-151	Metal, Test Methods
FED-STD-595	Colors

Military

DOD-STD-100	Engineering Drawing Practices
MIL-STD-129	Marking For Shipment And Storage
MIL-STD-130	Identification Marking Of U.S. Military Property
MIL-STD-143	Specification And Standard, Order Of Precedence For The Selection Of
MIL-STD-470	Maintainability Program Requirements (For Systems And Equipments
MIL-STD-471	Maintainability Demonstration
MIL-STD-785	Reliability Program For Systems And Equipments Development And Production
MIL-STD-794	Part And Equipment, Procedures For Packaging And Packing Of
MIL-STD-889	Dissimilar Metals
MS 33583	Tubing End, Double Flare, Standard Dimensions For

(Copies of specifications, standards, handbooks, drawings, publications, and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

3. REQUIREMENTS

3.1 Qualification. Converters furnished under this specification shall be products which are qualified for listing on the applicable qualified products list at the time set for opening of bids (see 4.3 and 6.3).

3.2 Component parts. The converter shall consist of the following major components:

a. Liquid oxygen container

b. Vaporizing and superheating coil

c. Pressure closing valve

d. Check valves

e. Relief valves

3.3 Selection of specifications and standards. Specifications and standards for necessary commodities and services not specified herein shall be selected in accordance with MIL-STD-143.

3.4 Materials. Materials shall conform to applicable specifications as identified herein. Materials that are not covered by specification shall be the best quality, shall be the lightest practical weight, or shall be suitable for the purpose intended.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:56Z
Check the source to verify that this is the current version before use.

3.4.1 Metals. Metals shall be of the corrosion-resistant type or suitably treated to resist corrosion due to fuels, salt spray or atmospheric conditions likely to be encountered during storage or normal service.

3.4.1.1 Dissimilar metals. Unless suitably protected against electrolytic corrosion, dissimilar metals shall not be used in intimate contact with each other. Dissimilar metals are defined in MIL-STD-889.

3.4.1.2 Protective treatment. Metallic materials that are subject to corrosion in oxygen, salt air, or any other atmospheric conditions likely to occur during usage of the converter shall be protected against such corrosion in a manner that will not in any way prevent compliance with the performance requirements of this specification.

3.4.1.3 Recovered materials. Recovered materials shall be used to the maximum extent possible without jeopardizing the end use of the item.

3.5 Design and Construction. The converters shall be designed to store liquid oxygen in aircraft with as little evaporation loss as possible, and to deliver gaseous oxygen warmed to near-ambient temperature, by atmospheric heat exchange, as needed by air crewman. The converters shall have a minimum capacity of liquid oxygen as specified in the applicable detail specification, and measured at one atmosphere. The converters shall be capable of providing gaseous oxygen at a pressure specified in the applicable detail specification.

3.5.1 Outer shell rupture point. The outer shell shall be provided with a rupture point which will provide not less than a 3/8 inch diameter escape area. The pressure required to open the escape area shall be at least 20 percent less than the burst pressure of the outer container. The rupture disc shall be in such a position that in case of rupture, the danger to personnel will be at a minimum.

3.5.2 Fittings. All openings and fittings shall be capped or plugged to prevent damage to the fittings and to prevent moisture and foreign matter from entering the converter during shipping and storage. The entrance to the filling line into the converter shall be baffled in such a way that the liquid is not aimed directly at the vent port when filling is initiated. All flare fitting shall be double-flared to conform to MS33583.

3.5.3 Design detail. The schematic diagram of the converter shall be shown in the applicable detail specification. Other figures regarding the design of the converters shall be referred to in the applicable detail specification.

3.5.4 Antiseize tape. Antiseize tape that conforms to MIL-T-27730 shall be used on tapered male pipe thread fittings. The antiseize tape shall not be used on the straight threads or the tubing fittings. Particles of the antiseize tape shall not be allowed to enter the inside of plumbing lines.

3.5.5 Design strength. The filled converters shall be designed to withstand the "g" forces specified in the applicable detail specification.

3.5.6 Liquid oxygen container. The liquid oxygen container shall consist of a double-walled vessel. Both inner and outer containers shall be of leakproof construction to insure a permanent vacuum. The vacuum shall be achieved by the conventional process which includes heating during evacuation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:56Z
Check the source to verify that this is the current version before use.

3.5.6.1 Gage connection. The container shall have a separate outlet for the liquid side of the contents gage. The length of the filling and gage pig tails shall not be less than 20 and 15 inches, respectively.

3.5.6.2 Vacuum space requirements. If insulating bumpers are used between the inner and outer vessels, they shall be made from any suitable non-combustible materials. A getter will be used in the vacuum space and it shall be any non-explosive non-combustible material.

3.5.7 Vaporizing and superheating coil. The evaporator shall consist of tubing formed around the container. All flare fittings shall be double-flared fittings conforming to MS 33583.

3.5.8 Check valves. The check valves shall be located in the system as shown in the schematic diagram of the applicable detail specification. The valves shall be spring-loaded.

3.5.9 Relief valves. The relief valves shall conform to Specification MIL-V-9050.

3.5.10 Threads.

3.5.10.1 Screw. Machine screw threads shall be in accordance with Specification MIL-S-7742.

3.5.10.2 Pipe. Pipe threads shall be in accordance with Specification MIL-P-7105.

3.5.11 Color. The color of the final coating shall be green No. 14187 in accordance with FED-STD-595.

3.6 Performance.

3.6.1 Permanent volumetric expansion. The permanent volumetric expansion shall not be in excess of 10 percent of the total volumetric expansion when the inner vessel is subjected to a hydrostatic pressure of 30 seconds or sufficiently longer to insure complete expansion of the vessel. The inner vessel shall be subjected to not more than one application of the specified internal pressure prior to the official test. The test shall be conducted prior to assembly.

3.6.2 Evaporation loss. The vaporization loss from a full converter with the converter in the vent or buildup position shall meet the tests as specified in 4.6.3.

3.6.3 Final assembly pressure test. The final assembly shall not leak,except for that allowed through the relief valves, when subjected to the pressure specified in the applicable detail specification.

3.6.4 Filling time. Filling time shall not exceed the time specified in the applicable detail specification when liquid is transferred into the converter under pressure of 20 psig.

3.6.5 Buildup time. The buildup time (the time required to reach the pressure-closing valve pressure setting) shall not exceed the time specified in the applicable detail specification. The test may start when the converter is fully charged.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:56Z
Check the source to verify that this is the current version before use.

3.6.6 Pressure closing valve leakage. The pressure closing valve shall be bellows-actuated and shall exhibit no leakage through the bellows. This test condition should be performed at build-up condition pressure which shall be 10% + 3% above the pressure necessary to close the valve. The leakage rate across the valve shall be no greater that .02 liter per minute when 10 inches of water pressure differential is applied across the valve. The valve shall be equipped with safety wires to prevent tampering by unauthorized personnel. The valve shall be located in the system as shown in the schematic diagram of the applicable detail specification.

3.6.7 Delivery rate. The converter shall be capable of delivering gaseous oxygen at constant flows at the temperture specified in the applicable detail specification.

3.6.8 Temperature range. The converter shall operate satisfactorily over a temperature range from minus 65 ot plus 160°F.

3.6.9 Vibration. The converter shall operate satisfactorily after being vibrated in all frequencies from 500 to 3,000 cpm with a constant displacement of 0.018 + 0.005 inch in three mutually perpendicular planes, for eight hours in each plane.

3.6.10 Gunfire. The converter shall remain in one piece without shattering when subjected to gunfire, while under full operating pressure. The mounting bracket of the converter shall withstand the forces exerted upon it during the gunfire test of the converter.

3.6.11 Salt spray. The converter shall operate satisfactorily after being subjected to salt spray procedure specified in 4.6.11. In addition, there shall be no excessive corrosion, nor shall there be any corrosion which would indicate the use of dissimilar metals.

3.7 Maintainability and Reliability.

3.7.1 Maintainability. The maximum corrective maintenance downtime (M_{max} ct, as defined in MIL-STD-471) shall not exceed M_{max} ct so stated in the applicable detail specification. If not stated in the detail specification, the M_{max} ct shall not exceed ninety (90) minutes. The mean corrective maintenance downtime ($\overline{M}$ct) shall be determined by the maintainability vertification specified herein (see 4.6.13). The provisions of MIL-STD-470 shall apply.

3.7.2 Reliability. a reliability program shall be estalbished in accordance with MIL-STD-785. The converter shall have a minimum acceptable Mean Time Between Failure (MTBF), θ, of 300 hours. Failure shall be defined as any condition of the equipment in which fully operational service is not possible within the performance requirements specified herein.

3.7.2.1 Service Life. The equipment shall have s service life of not less than 1,000 hours. Service Life is defined as that period of time during which the MTBF remains (i.e., there is no significant decrease in the equipment MTBF).

3.8 Interchangeability. All parts having the same manufacturer's part number shall be dimensionally and functionally interchangeable. The drawing number requirements of Specification DOD-STD-100 shall govern changes in the manufacturer's part numbers.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:56Z
Check the source to verify that this is the current version before use.

3.9 Weight. The weight of the complete converter shall not exceed the weight requirements specified in the applicable detail specification.

3.10 Identification of product. Marking shall be in accordance with MIL-STD-130. In addition, a warning decal or plate shall be located in a conspicuous location on the converter. The following indormation in 1/4 inch high red letters on a white background shall be provided:

3.11 Workmanship. Workmanship shall be in accordance with high-grade aircraft equipment manufacturing practice. The converter shall be cleaned of all oils and foreign matter at the proper stage of assembly.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification when such inspections are deemed necessry to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirments in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of tests. The inspection and testing of liquid oxygen converters shall be classified as follows:

a. Qualification tests

b. Acceptance tests

4.3 Qualification tests.

4.3.1 Qualification sample. The qualification test sample shall consist of one converter, representative of the manufacturer's production.

4.3.2 Tests. The manufacturer shall apply all the tests of this specification to the qualification test sample, as described under Test Methods.

4.4 Acceptance tests. Acceptance tests shall consist of individual tests and sampling tests.

4.4.1 Individual tests. Each converter submitted for acceptance under contract shall be subjected to the following tests, as described in 4.6:

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:56Z
Check the source to verify that this is the current version before use.

a. Examination of products (4.6.1)

b. Permanent volumetric expansion (4.6.2)

c. Evaporation loss (4.6.3)

d. Final assembly leakage test (4.6.4)

e. Filling time (4.6.5)

f. Buildup time (4.6.6)

g. Pressure closing valve leakage (4.6.7)

4.4.2 Sampling tests. Unless otherwise specified, a sample shall be selected from each lot of converters and subjected to the following tests, as decribed in 4.6:

a. Delivery rate (4.6.8)

b. Temperature exposure (4.6.9)

c. Vibration (4.6.10)

d. Salt spray (4.6.11)

e. Reliability test level (4.6.12)

f. Gunfire (4.6.14)

The lot shall be rejected if any defect is found in the sample. Three converters, selected at random from each lot shall be defined as a sample. A lot shall be defined as converters in a quantity of not greater than 100 and offered for delivery at approximately the same time. Sample converters shall not be submitted as a part of the contract order.

4.4.2.1 Rejection and retest. If a lot is rejected, the contractor shall:

a. Determine the cause of the defect.

b. Take necessary action to correct the defect.

c. Record the proposed corrective action.

d. Select six additional converters from the lot and subject them to another sampling test. If any defect is found in the second sample, the lot shall be rejected and disposition of the lot shall be determined by the procuring activity.

4.4.2.2 Defects in items already accepted. The investigation of a test failure could indicate that defects may exist in items already accepted. If so, the contractor shall fully advise the procuring activity of defects likely to be found and methods of correcting them.

4.5 Test conditions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:56Z
Check the source to verify that this is the current version before use.

4.5.1 Atmospheric pressure. Unless otherwise specified, all tests required by this specification shall be conducted at an atmospheric pressure of approximately 29.92 inches of mercury and a temperature of approximately 77°F. When tests are performed at a pressure or temperature substantially different from the above values, proper allowance shall be made for the difference from the specified values.

4.5.2 Oxygen. Gaseous and liquid oxygen used in testing converters shall conform to Specification MIL-O-27210, Type I or II, as applicable.

4.5.3 Leak test compound. Care shall be taken to remove all traces of leak test from the converter after leakage tests.

4.6 Test methods.

4.6.1 Examination of product. The converters shall be examined to determine conformance with the requirements of this specification with respect to materials, workmanship, weight and marking.

4.6.2 Permanent volumetric expansion. The inner vessel, complete with all lines and fittings which will normally be subjected to the rated pressure of the converter, shall be hydrostatically tested at the pressure specified in the applicable detail specification. The test may be conducted before the outer vessel is added, in order that in the event oof a failre, the outer vessel will not be damaged. The permanent set of the inner vessel shall not exceed 10 percent of the total volumetric expansion. The hydrostatic test shall precede the evaportion loss test, in order that any weakness in joints, which might develop leaks when subjected to pressure, will be revealed before the evaportion loss test.

4.6.3 Evaporation loss. Evaportion loss over a 24-hour period shall not exceed the maximum loss allowed in the applicable detail specification under any pf the following conditions and shall not increase over a period of time more than is allowed during the following procedures.

4.6.3.1 Vent condition. The evaporation loss of the converter in the vent condition shall be determined within three days after pinch-off of the container. This loss shall not exceed the maximum loss allowed.

4.6.3.2 Second test. A second evaporation loss test shall be conducted after a lapse of at least 30 days after completion of the first test. If the loss during the second test doe not exceed the first loss by more than 10 percent of the maximum loss allowed, the converter shall be acceptable with respect to the evaportion loss in the vent position and shall then be tested for evaporation loss in the buildup position. The loss in the buildup position shall not exceed the maximum loss allowed in the applicable detail specification.

4.6.3.3 Third test. If the loss durnig the second test (in the vent position) exceeds the loss during the first test by more than 10 percent of the maximum allowable loss (but is still less than the total allowable loss), a third test shall be conducted with the converter in the vent position and also in the buildup position after a lapse of at least 30 days from the second test. The loss during the third test in the vent position shall not exceed the loss that occurred during the second test. The loss in the buildup position shall not exceed the maximum loss allowed in the applicable detail specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:56Z
Check the source to verify that this is the current version before use.

4.6.4 Final assembly pressure test. After the converter has been completely assembled, all fittings and connections shall be subjected to the pressure specified in the applicable detail specification. This pressure shall be maintained while all fittings and connections are tested for leaks by applying a leak detection compund conforming to Specification MIL-L-25567, Type I. There shall be no evidence of leaks, except that allowed through relief valves.

4.6.5 Filling time. With the converter at approximately 70°F, the time required to fill the converter by transfer of liquid oxygen from a storage container to the converter shall be determined. The pressure at the converter inlet shall be maintained at 20 psig. The converter shall be considered full when the liquid issues from the vent valve. The time required to fill the converter shall not exceed that specified in the applicable detail specification.

4.6.6 Buildup time. The vent and buildup valves shall be closed and opended, respectively (manually controlled valves in the supply line, vent line and buildup circuit will be necessary to conduct the above tests. The buildup time or the time required for the pressure to reach the pressure closing valve setting shall not exceed that specified in the applicable detail specification. This test may be conducted immediately after filling has been accomplished.

4.6.7 Pressure closing valve leakage. A pressure equivalent to 10 inches of water shall be applied to the inlet port of the pressure closing valve. The leakage through the valve shall not exceed 0.02 liter per minute. All parts on the valve, with the exception of the part used to apply and measure leakage, shall be closed during the test.

4.6.8 Delivery rate. By means of a temporary valve in the supply line, the converter shall be adjusted to deliver the rated amount of gaseous oxygen per minute. The temperature of the gas measured at the discharged of the superheater coil shall not be colder than the temperature specified in the applicable detail specification. The converter shall be substantially full at the start of the test. The duration of the test shall be as specified in the applicable detail specification. The operating pressure shall remain within the specified range.

4.6.9 Temperature exposure.

4.6.9.1 Low temperature exposure. The converter shall be exposed to a temperature of not warmer than minus 65°F for a period of three hours. While at this temperature, the converter shall function normally and shall deliver the rated amount of gaseous oxygen for the duration of time specified in the applicable detail specification.

4.6.9.2 High temperature exposure. The converter shall be exposed to a temperature of not less than 160°F for a period of three hours. While at this temperature, the converter shall function normally and shall deliver the rated amount of gaseous oxygen for a duration of time specified in the applicable detail specification.

4.6.10 Vibration. The converter, filled with the required amount of liquid oxygen, at the beginning of the test shall be vibrated while mounted in a normal operating position with a constant displacement of 0.018 $\pm$ .005 inch for eight hours in each of the three mutually perpendicaular planes. The vibration frequency shall vary regularly from 500 to 3,000 cpm and back to 500 cpm, the rate of change in frequency being constant. The evaporation loss, determined within 48 hours after the vibration test, shall not increase more than 1/2 pound above the evaporation loss as specified in the applicable detail specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:56Z
Check the source to verify that this is the current version before use.

4.6.11 Salt spray test. The converter shall be subjected to the procedure outlined in FED-STD-11, Method 811, except as otherwise specified herein. The length of the salt spray test shall not be less than 50 hours. At the end of the test period, the converter shall be subjected to and meet the following tests. The tests shall be conducted approximately 48 hours after salt spray exposure, and the salt spray deposits resulting from the exposure condition may be removed by rinsing with tap water prior to operation.

a. Examination of product

b. Evaporation loss

c. Final assembly pressure test

d. Filling time

e. Buildup time

4.6.12 Reliability test level. The reliability test level shall consist of delivery rate testing as specified in the applicable detail specification. A failure shall be defined as any malfunction which casues the cnverter to deliver an insufficient flow of oxygen or to maintain an improper operating pressure. No parts shall be replaced as preventative maintenance during reliability testing. The converter shall be checked at least once every 24 hours during reliability testing to determine if a failure has occurred withstanding the maximum pressure which the converter will be subjected to by the gunfire effect. The converter shall be charged with the liquid oxygen and the operating pressure maintained at the maximum pressure of the converter. The converter will be fired upon from a distance of approximately 50 yards by a 50-caliber armor-piercing incendiary which has been tumbled. The bullet shall strike the converter in the liquid phase. There shall be no evidence of shattering.

4.6.13 Maintainability verification. Maintainability requirements shall be verified in accordance with MIL-STD-471. Task selection shall in accordance with the method of Appendix A. The accept/reject criteria of Test Method 2 shall apply.

4.6.14 Gunfire test. The converter shall be mounted on a frame capable of withstanding the maximum pressure which the converter will be subjected to by the gunfire effect. The converter shall be charged with the liquid oxygen and the operating pressure maintained at the maximum pressure of the converter. The converter will be fired upon from a distance of approximately 50 yards by a 50-caliber armour-piercing incendiary which has been tumbled. The bullet shall strike the converter in the liquid phase. There shall be no evidence of shattering.

4.6.15 Preservation and packaging. Unless otherwise specified in the purchase order or contract, the supplier is responsible for the performance of all inspections required as listed in Table III, MIL-P-116 for the method of preservation being accomplished.

5. PACKAGING:

5.1 Preservation-packaging: Preservation and packaging shall be level A, unless otherwise specified by the contracting activity (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:56Z
Check the source to verify that this is the current version before use.

5.1.1. Level A. Each converter pressurized to a maximum of 25 lbs PSI shall be preserved in accordance with Method III of MIL-P-116.

5.1.1.1. Cleaning and drying. Each converter shall be cleaned and dried for oxygen service in accordance with industry practice according to the applicable precessess of MIL-P-116. Petroleum and other flammable solvents shall not be used.

5.1.1.2. Unit packaging. Unless otherwise specified by the contracting activity, oxygen converters shall be individually packaged in accordance with MIL-P-116, Method III, insuring compliance with the applicable requirements of that specification.

5.2 PACKING. Packing shall be level A, B, or C as specified. (see 6.2)

5.2.1 Level A. Unless otherwise specified by the contracting activity, oxygen converters packaged as specified in 5.1 shall be packed in shipping containers applicable to level A requirements of MIL-STD-794. Insofar as practical, exterior shipping containers shall be of uniform shape, size, minimum tare and cube consistent with the protection required.

5.2.2 Level B. Unless otherwise specified by the contracting activity, oxygen converters shall be packed in shipping containers conforming to PPP-B-636, Style RSC, Type CG, Class WR, Grade V3C. Other requirements as specified in 5.2.1. are applicable.

5.2.3. Level C. Unless otherwise specified by the contracting activity, oxygen converters shall be packed in shipping containers conforming to PPP-B-636, Style RSC, Type CG, Class Dom Grade 275. Other requirements as specified in 5.2.1 are applicable.

5.3. Marking. In addition to any other markings required by the contract or order (see 6.2), interior and exterior containers shall be marked in acordance with MIL-STD-129.

5.3.1 Precautionary marking. The following precautionary marking shall appear on each package:

LIFE SUPPORT ITEM
All oil, grease, shop residual or other contaminants have been removed.
DO NOT OPEN UNTIL READY FOR USE

6. NOTES

6.1 Intended use. This specification covers the general requirements for liquid oxygen converters which convert liquid oxygen to gaseous oxygen at pressures of either 70 to 300 psig.

6.1.1 Qualification. "With respect to products qualification, awards will be made only for products which are, at the time set for opening of bids, qualified for inclusion in Qualified Products List (QPL No.) whether or not such products have actually been so listed by that date. The attention of the contractors I called to these requirements, and manufacturers are urged to arrance to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or purchase orders for the products covered by this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:56Z
Check the source to verify that this is the current version before use.

The actvity responsible for the Qualified Products List is OC-ALC/MMEDO, TINKER AFB, OK 73145-5990 and information pertaining to qualification of products may be obtained from that activity.

6.2 Ordering data. Procurement documents should specify the following:

a. Title, number and date of this specification.

b. List of interchangeable components and assemblies.

c. Level of packaging and packing required

6.3 Qualification. With respect to products requiring qualification, awards will be made only for products which are at the time set for opening of bids, qualified for inclusion in the applicable Qualified Products List whether or not such products have actually been so listed by the date. The attention of the suppliers is called to this requirement, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or orders for the products covered bt this specification. The activity responsible for the Qualfied Products List is OC-ALC/MMEDO, Tinker AFB OK 73145-5990 and information pertaining to qualification of products may be obtained from that activity.

6.4 Subject term (key word) listing.

Converter
Oxygen

6.4 International standardization. Certain provisions (see paragraph 1.1 & 6.1) of this specification are the subject of international standardization agreement ASCC Air STD 14/4A. When amendment, revision, or cancellation of this specification is proposed which will effect or violate the international agreement concerned, the preparing activity will take appropriate reconciliation action through international standardization channels including departmental standardization offices, if required.

6.5 Changes from previous issue. Asterisks (or vertical lines) are not used in this revision to identify changes with repect to the previous issue due to the extensiveness of the changes.

Custodian:
AIR FORCE-99

Preparing activity:
AIR FORCE-71

Project No:
1660-F556

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:56Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE AIR FORCE

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 73236 WASHINGTON D C

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE AIR FORCE

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:56Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-C-9082H	

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*:

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE

Source: https://assist.dla.mil – Downloaded: 2020-10-17T11:56Z
Check the source to verify that this is the current version before use.