INCH-POUND
A-A-52017A
November 4, 2002
SUPERSEDING
A-A-52017
12 January 1990

COMMERCIAL ITEM DESCRIPTION

COMPRESSOR UNIT: DIESEL-ENGINE-DRIVEN, 450-650 CFM, 350 PSI, WHEEL-MOUNTED

The General Services Administration has authorized the use of this commercial item description, for all federal agencies.

1. SCOPE. This commercial item description (CID) covers a commercial, four-wheel-mounted, diesel-engine-driven air compressor. The air compressor will be complete with all components that are customarily offered with the air compressor of this type, furnished as standard equipment whether or not stipulated herein, together with such other equipment as may be necessary to enable the air compressor to function reliably and efficiently in sustained operation, or to meet requirements set forth in this CID.

2. SALIENT CHARACTERISTICS.

2.1 Design. The air compressor shall be enclosed by a housing and mounted on a four-wheeled chassis with a roll bar and front axle knuckle and kingpin type steering. The chassis shall be designed for heavy-duty or extreme service. The fuel tank shall have sufficient capacity for 8 hours of normal operation in ambient temperatures ranging from -25 degrees Fahrenheit (°F) to +100°F. The fuel tank shall be an internal part of the unit.

2.2 Performance. The air compressor shall produce a minimum of 450 cubic feet per minute (ft^3/min) of free air at 350 pounds per square inch gage (psig) in ambient temperatures ranging from -25 to +110°F.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data that may improve this document should be sent by letter to: U.S. Army Tank-automotive and Armaments Command, ATTN: AMSTA-TR-D/210, 6501 E. 11 Mile Road, Warren, MI 48397-5000.

AMSC N/A FSC 4310

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:04Z
Check the source to verify that this is the current version before use.

2.3 Engine. The offeror shall furnish the diesel engine with all accessories offered on his commercial air compressors. The diesel engine shall operate on military fuels and lubricants. The engine must have Environmental Protection Agency (EPA) emissions certification for non-road diesel engines at the time of contract award.

2.4 Compressor. The compressor and all accessories shall be as offered on the commercial air compressor and may be of the rotary or reciprocating type.

2.5 Regulating device. The regulating device shall be capable of selecting an engine speed and a compressor air intake valve opening to suit any air demand by the air compressor in a smooth, stepless manner.

2.6 Receiver. The air receiver shall be of sufficient volume to provide a non-pulsating source of air pressure. The receiver shall be provided with a drain valve, a safety relief valve, and an automatic blow-down valve to fully discharge the receiver when the engine stops. The receiver shall be constructed in accordance with the ASME Boiler and Pressure Vessel Code.

2.7 Instrumentation. All instruments, gages, and controls supplied commercially as standard equipment shall be supplied on the air compressor.

2.8 Manifold. An air service manifold shall be provided with individually controlled 3/4-inch service outlet valves with standard universal pneumatic hose couplings and a 3-inch main outlet controlled by a globe valve.

2.9 Brakes. The air compressor shall be provided with a parking brake enabling it to be held in a stationary position while on a 15 percent grade.

2.10 Lubrication. The air compressor shall be capable of operating using standard military lubricants. All components requiring lubrication shall be provided with a means of lubrication. Lubricating points shall be easily visible and accessible. Parts requiring lubrication shall be properly lubricated before delivery. The equipment shall be permanently marked to indicate the temperature range and grades of lubricants used.

2.11 Maintenance characteristics. The air compressor design, together with the accessories, shall permit ready access to all items requiring periodic maintenance service in the field. Periodic maintenance shall be accomplished with the use of conventional general purpose tools normally associated with equipment of this nature. The replacement and adjustment of components and accessories shall be accomplished with minimum drainage requirements am minimum disturbance to other elements of the air compressor.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:04Z
Check the source to verify that this is the current version before use.

2.12 Lifting and tiedown. Lifting and tiedown attachments shall be provided. Instructions for the use of the attachments or procedures shall be included on plates permanently affixed to the air compressor.

2.13 Safety. All rotating or reciprocating parts and parts subject to high operational temperatures that are of such a nature or are so located as to be or become a hazard to the operating or attending personnel shall be guarded or insulated to the extent necessary to eliminate the hazard.

2.14 Noise. The noise level of the air compressor shall meet the requirements of CFR 40, Part 204 - Noise Emission Standards for Construction Equipment.

2.15 Treatment and painting. The parts of the air compressor normally painted shall be cleaned, treated, and painted in accordance with the offeror's standard commercial practice. The final color shall be color number 24084 of FED-STD-595.

3. REGULATORY REQUIREMENTS. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

4. PRODUCT CONFORMANCE. The products provided shall meet the salient characteristics of this CID, conform to the producer's own drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial marketplace. The Government reserves the right to require proof of such conformance.

4.1 Responsibility for inspection. The contractor is responsible for the performance of all inspections (examinations and tests).

5. PACKAGING. Preservation, packing, and marking shall be as specified in the contract or order (see 6.3).

6. NOTES.

6.1 Part or Identification Number (PIN). The following PIN procedure is for Government purposes and does not constitute a requirement for the contractor. The PINs to be used for wheel-mounted compressor unit acquired to this CID are created as follows:



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:04Z
Check the source to verify that this is the current version before use.

6.2 Source of documents.

6.2.1 The Code of Federal Regulations (CFR) 40, Part 204 "Noise Emission Standards for Construction Equipment" may be obtained from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402 or website: http://www.access.gpo.gov

6.2.2 FED-STD-595 "Colors Used in Government Procurement" is available from the Document Automation and Production Service, Building 4/D, 700 Robbins Avenue, Philadelphia, PA 19111-5094 or website: http://astimage.daps.dla.mil

6.2.3 The ASME Boiler and Pressure Vessel Code is available from the American Society of Mechanical Engineers, 3 Park Avenue, M/S 10D, New York, NY 10016 or website: http://www.asme.org

6.2.4 ASTM D413 "Standard Test Methods for Rubber Property - Adhesion to Flexible Substrate" is available from ASTM International, P.O. C700, 100 Barr Harbor Dr., West Conshohocken, PA 19428-2959 or website: http://www.astm.org

6.3 Ordering data. The contract or order should specify the following:

a. CID document number, revision, and CID PIN.
b. Product conformance provisions.
c. When additional marking is required.
d. Packaging requirements.

6.4 Key words.

Four-wheel-mounted
Heavy duty or extreme service

MILITARY INTERESTS:

Custodian:
Army - AT

CIVIL AGENCY COORDINATING ACTIVITY:
GSA-FSS

Preparing Activity:
Army - AT

(Project 4310-0039)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:04Z
Check the source to verify that this is the current version before use.