INCH-POUND

A-A-52031
May 15, 1991

PROPOSED COMMERCIAL ITEM DESCRIPTION

DRAWING BOARD, ILLUMINATED, PORTABLE

The General Services Administration has authorized the use of this commercial item description in preference to Military Specification MIL-D-52975.

This description covers illuminated portable drawing boards used by personnel to produce engineering drawings, schematics, or other graphic arts.

Salient characteristics:

Description. The drawing board shall be 48 inches by 32 inches by 3.25 inches, ± 0.031 inch. The frame shall be made of clear hardwood. The board shall have a 22 gauge steel reflector under entire bottom shaped to distribute the light evenly under glass. The reflector shall be painted with enamel, class and composition optional. The top of the board shall be recessed to take a 36.75 inch by 24 inch by 0.25 inch, ± 0.031 inch, tempered-glass. The glass shall be sandblasted or acid etched on bottom side to reduce glare and diffuse light. The glass shall be held in place with four corner clips. The front and back top rails shall be removable so that the lamps can be replaced. Adjustable hanger rods to hold the board in place when used on an inclined drawing surface shall be fastened to each end, and be movable to at least 10.5 inches. The board shall be wired for 110-125 volts alternating current with two 30-watt 36-inch fluorescent lamps. The power switch (off - on) shall be at either the top or the side of the board. The board shall have not less than a 10-foot cord with 18-gauge wire with plug, having a ground.

Material. Material shall be as specified herein. Materials not specified shall be slected by the contractor and shall be subject to all provisions of this commercial item description. Drawing boards shall be free from defects and imperfections which might affect their serviceability.

Beneficial comments recommendations, additions, clarifications, deletions, etc., and any data which may be of use in improving this document should be sent to: USA Belvoir Research, Development, and Engineering Center, ATTN: STRBE-TSE, Fort Belvoir, VA 22060-5606.

AMSC N/A FSC 6675

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:04Z
Check the source to verify that this is the current version before use.

Construction. Wood boards shall be made from the same species of wood for the entire working surface of one drawing board. The working surface shall be composed of continuous wood lengths, 1.75 to 5 inches, bonded together with waterproof resin adhesive. Bond joints, fully set, shall have a strength greater than the wood being bonded.

Finish. All fabricated wood and plastic surfaces shall be sanded smooth and shall be free of cracks, splits, and splintered edges. Surfaces shall be finished to a tolerance of 0.031 inch. Drawing board working surfaces shall be a true plane within 0.016 inch for 12 inches of length or width, and shall not be cumulative within any 12-inch increment. Any deviation shall be evenly distributed over the entire increment. All edges shall be straight within 0.125 inch end to end.

Protective finish. The drawing board, excluding glass, shall be protected with at least one coat of varnish.

Regulatory requirements. In accordance with Federal Acquisition Regulation, section 23.403, the Government's policy is to acquire items composed of the highest percentage of recovered materials practicable, consistent with maintaining a satisfactory level of competition without adversely affecting performance requirements or exposing the supplier's employees to undue hazards from the recovered materials.

Contractor Certification. The Contractor shall certify that the product offered to the Government meets the salient characteristics of this description and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices and is the same product as the manufacturer's current product offered by the contractor in the commercial marketplace for at least one year preceding the solicitation. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Metric product. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within specified tolerances using conversion tables contained in the latest revision of FED-STD-376, and all other requirements of this commercial item description are met.

If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request should be made to the contracting officer to determine if the product is acceptable.


The contracting office has the option of accepting or rejecting the product.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:04Z
Check the source to verify that this is the current version before use.

Preservation, packaging, packing, labeling, and marking. The preservation, packaging, packing, labeling, and marking shall be as specified in the contract or order.

CID based part identification number. The following part identification numbering procedure is for Government purposes and does not constitute a requirement for the contractor.

Part or identification number (PIN). The PIN to be used for drawing boards acquired to this commercial item description is created as follows:



Note:

a. FED-STD-376 is available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.

b. When this commercial item description is used for procurement, the commercial item certification clause must appear in the solicitation.

MILITARY INTERESTS:

Custodians:
Army - ME

Review Activity:
DLA-GS

User Activities:
Navy - MC

CIVILIAN AGENCY COORDINATING ACTIVITIES:

GSA-FSS
VA-OSS
COM-NBS

PREPARING ACTIVITY:
Army - ME

Project 6675-0946

Source: https://assist.dla.mil -- Downloaded: 202610-26T09:04Z
Check the source to verify that this is the current version before use.