INCH-POUND

A-A-52044
January 3, 1992

COMMERCIAL ITEM DESCRIPTION

POLE, RANGE, METAL, WITH CASE

The General Services Administration has authorized the use of this commercial item description in preference to Military specification MIL-P-20192D.

This description covers one type of range pole containing two sections of steel tubing. The assembled length of the range pole is 6.50 feet. Its intended use is to present a view for an instrument operator sighting a straight, relatively narrow line extending vertically above the point which marks a survey station.

Salient characteristics:

Design:

Range pole fabrication. The range pole shall be as specified herein. The range pole shall consist of two sections of steel tubing, a 3.50 to 6.0-inch hardened steel point and a carrying case. The range pole shall be made of two sections of steel tubing of nominal 1.125-inch outside diameter and of nominal 0.032-inch wall thickness. The assembled length shall be 6.50 feet, including a hardened steel point permanently fastened to the lower end. The steel point shall be concentric to the centerline of the pole within 0.050-inch. The construction of the telescopic sleeve joining the upper and lower sections shall be such that both sections of the pole are the same length. A spring catch, bayonet joint or 5/8 x 11 screw joint shall be provided to lock the two sections rigidly together.

Carrying case. The two sections of the pole shall be fitted to a two - pocket carrying case made of cotton duck cloth plied-yarns unbleached with a minimum weight per square yard 8.25 ounces for the body of the case and 18.48 ounces for the reinforcing duck at the closed end. The ,reinforcing duck shall be one piece wrapped around the outside bottom of the case body. The open end shall be provided with a strap, flap, and buckle to completely enclose and hold the sections. The case, with the flap in the closed position, shall be not less than 42 inches long.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any other data which may improve this document should be sent by letter to: Commander, US Army Belvoir Research, Development, and Engineering Center, ATTN: STRBE-TSE, Fort Belvoir, VA 22060-5606.

AMSC N/A FSC 6675

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:05Z
Check the source to verify that this is the current version before use.

Each of the two pockets shall have a width and depth of not less than 1.125 inches to accommodate the two range pole sections snugly, but without binding. The webbing shall be medium weight hard texture, width .75-inch, shall be used as binding around all edges, including the pocket opening the case. The cotton duck webbing shall be dyed light green and treated for mildew resistance.

Identification marking. The pole and case shall be identified with the manufacturer's identification.

Treatment and painting. The pole shall be treated and painted. The finish coat shall be as follows: The upper 12 inches of the pole shall be painted red or orange and the remainder shall be painted in alternating white and red or orange horizontal bands 12 inches long, except that the point at the lower end shall be painted black. The edges of the ring shall be normal to the axis of the pole.

Materials: Material shall be as specified herein.

Metal. The metal shall be corrosion resistant or coated to be made corrosion resistant.

Workmanship: All parts, components, and assemblies of the range pole shall be clean and free from sand, dirt, fins, pits, sprues, scale, flux, and other harmful extraneous material.

Certification of commercial item. The contractor shall certify that the product offered to the Government meets the salient characteristics of this description and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices and is the same product as the manufacturer's current product offered by the contractor in the commercial marketplace for at least one year preceding the solicitation. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Metric Products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within the tolerances specified using conversion tables contained in the latest revision of FED-STD-376, and all other requirements of this Commercial Item Description are met.

If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch/pound units, a request should be made to the contracting officer to determine if the product is acceptable.

The contracting officer has the option of accepting or rejecting the product.

Quality assurance: The range pole shall be examined for the following defects. Presence of one or more defects shall be cause for rejection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:05Z
Check the source to verify that this is the current version before use.


1. Dimension not as specified.
2. Steel point not permanently fastened to the lower end.
3. Steel point not concentric with the pole centerline.
4. Lock does not hold two sections rigidly together.
5. Carrying case not as specified.
6. Identification marking not as specified.
7. Treatment and painting not as specified.
8. Materials not as specified.
9. Workmanship not as specified.
10. Packaging and marking not as specified.

Regulatory requirements. In accordance with section 23.403 of the Federal Acquisition Regulations, the Government's policy is to acquire items composed of the highest percentage of recovered materials practicable, consistent with maintaining a satisfactory level of competition without adversely affecting performance requirements or exposing the supplier's employees to undue hazards from the recovered materials.

Preservation, packaging, packing, labeling, and marking. The preservation, packaging, packing, labeling, and marking shall be as specified in the contract or order.

CID based part identification number. The following part identification numbering procedure is for Government purposes and does not constitute a requirement for the contractor.

Part or identifying number (PIN): The part or identifying number for the range pole shall be as follows:



Notes: The procuring agency should specify the preferred options permitted herein and include the following information in procurement documents:

1. Title, number, and date of this item description.
2. When the commercial item description is used for acquisition, the commercial item certification clause must appear in the solicitation.

FED-STD-376 is available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.

The following are suggested sources of supply for this item description (competition is not limited to these sources.):

a. Sokkisha Co., LTD, 10 Hachimanyama 1-Chome, Setagaya-ku, Tokyo 156 Japan, Telephone: 813-302-7071.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:05Z
Check the source to verify that this is the current version before use.

b. North America Survey Supply Co., 2070-T Markem Rd., Philadelphia, PA 19116.

The preparing activity for this item description is the U.S. Army Belvoir Research, Development, and Engineering Center, ATTN: STRBE-TSE, Fort Belvoir, VA 22060-5606.

MILITARY INTERESTS:

Custodians
Army - ME

Review activity
DLA - GS

User activity
Navy - MC

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FCGC

PREPARING ACTIVITY:
Army - ME

Project 6675-0892

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:05Z
Check the source to verify that this is the current version before use.