INCH-POUND

A-A-52046
January 9, 1992

COMMERCIAL ITEM DESCRIPTION

ARROW SETS, SURVEYING

The General Services Administration has authorized the use of this commercial item description in preference to Military specification MIL-A-20383D.

This description covers surveyors' arrow sets, each consisting of 11 arrows and a carrying ring.

Salient Characteristics:

Design: The arrow sets shall be as specified herein. The arrow sets are designed for use by surveyors for the temporary marking of taped distances. The arrows are sometimes called chaining pins.

Arrows. The top of the arrow shall be formed into a ring in the vertical plane with an inside diameter of 1.50 inches, ±0.375-inch. The lower end of the arrow shall be a pyramidal or conical point, the length of which shall be not less than twice the diameter of the wire. The overall length from the bottom of the ring to the point of the arrow shall be 10 inches, ±1-inch, for type I arrows, and 14 inches, ±1-inch, for type II arrows.

Carrier ring. The carrier ring shall be formed into either a 6-inch diameter loop with the ends bent back in such a manner as to provide a means of hooking the arrows, or a triangular shape with sufficient spring action to permit easy placement and removal of the arrows.

Classification:

Types. The arrow sets shall be of the following types.

Type I - 10 inches long.
Type II - 14 inches long.

Material:
Material shall be as specified herein.

Beneficial comments, recommendations, additions, deletions, clarification, etc. and other data which may improve this document should be sent by letter to: Commander, U.S. Army Belvoir Research, Development and Engineering Center, ATTN: STRBE-TSE, Fort Belvoir, VA 22060-5606.

AMSC N/A FSC 6675

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:05Z
Check the source to verify that this is the current version before use.

Steel Wire. The arrow sets shall be manufactured from cold-drawn round steel wire between 0.1875-inch and 0.25-inch diameter, with a minimum Rockwell "B" hardness number of 85.

Metal. The metal shall be corrosion resistant or coated to be made corrosion resistant.

Treatment and painting: The arrow sets shall be cleaned, treated, and painted. The finish coat shall be enamel. The color of the arrow ring shall be either gloss red or alternate bands of gloss white and gloss red not less than 1-inch nor more than 2 inches wide. The color of the arrow shank shall be either gloss white or alternate bands of gloss white and gloss red not less than 1-inch wide. The color of the carrier ring shall be gloss white or plated.

Identification marking: The arrow sets shall be identified with manufacturer's identification.

Workmanship: The arrow sets shall be cleaned, treated, and painted. External surfaces shall be free from nonfunctional sharp edges and projecting points.

Certification of commercial item. The contractor shall certify that the product offered to the Government meets the salient characteristics of this description and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices and is the same product as the manufacturer's current product offered by the contractor in the commercial marketplace for at least one year preceding the solicitation. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Metric Products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within the tolerances specified using conversion tables contained in the latest revision of FED-STD-376, and all other requirements of this commercial item description are met.

If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch/pound units, a request should be made to the contracting officer to determine if the product is acceptable.

The contracting officer has the option of accepting or rejecting the product.

Quality Assurance: The arrow sets shall be examined for the following defects. Presence of one or more defects shall be cause for rejection.

1. Design not as specified.
2. Type not as specified.
3. Length not as specified.
4. Material not as specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:05Z
Check the source to verify that this is the current version before use.


5. Treatment and painting not as specified.
6. Identification marking not as specified.
7. Workmanship not as specified.
8. Packaging and marking not as specified.

Regulatory requirements. In accordance with Federal Acquisition Regulation, section 23.403, the Government's policy is to acquire items composed of the highest percentage of recovered materials practicable, consistent with maintaining a satisfactory level of competition without adversely affecting performance requirements or exposing the contractor's employees to undue hazards from the recovered materials.

Preservation, packaging, packing, labeling, and marking. The preservation, packaging, packing, labeling, and marking shall be as specified in the contract or order.

CID based part identification numbers. The following part identification numbering procedure is for Government purposes and does not constitute a requirement for the contractor.

Part or identifying number (PIN). The part or identifying number for arrow sets shall be as follows:



Notes: The procuring agency should specify the preferred options permitted herein and include the following information in procurement documents:

1. Title, number, and date of this item description.
2. Purchaser should specify type required.
3. When the commercial item description is used for acquisition, the commercial item certification clause must appear in the solicitation.

FED-STD-376 is available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.

The following are suggested sources of supply for this item description (competition is not limited to these sources):

1. Lietz Co., 9111 Barton St., P.O. Box 2934 Overland Park, Kansas 66201.
2. John Woods Survey Equipment Limited, 2380 Midland Ave., Scoborough, Ontario, Canada, MIS 1P8.
3. Warren, Knight Instrument Co., 2045 Bennett Rd., Philadelphia, PA 19116-3019.

The preparing activity for this item description is the U.S. Army Belvoir Research, Development, and Engineering Center, ATIN: STRBE-TSE, Fort Belvoir, VA 22060-5606.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:05Z
Check the source to verify that this is the current version before use.

MILITARY INTEREST:

Custodian
Army - ME
Navy - YD
Air Force - 99

Review Activity
DLA - GS

User Activity
Navy - MC

CIVIL AGENCY COORDINATING ACTIVITIES:

GSA - FCGC

Preparing Activity:

Army - ME

Project 6675-0896

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:05Z
Check the source to verify that this is the current version before use.