MIL-C-46523B (MU)
23 September 1968
Superseding
MIL-C-46523A (MU)
15 May 1964

MILITARY SPECIFICATION

CARTRIDGE, 76MM, AP-T, M339
LOADING, ASSEMBLING AND PACKING

1. SCOPE

1.1 This specification covers the loading, assembling and packing for one type of cartridge designated as Cartridge, 76MM, AP-T, M339 for use in 76MM Guns M32 and M48.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids, or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-2550 - Ammunition and Special Weapons; General Specification for
MIL-I-45607 - Inspection Equipment, Supply and Maintenance of

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)
MIL-STD-109 - Quality Assurance Terms and Definitions
MIL-STD-414 - Sampling Procedures and Tables for Inspection by Variables for Percent Defective
MIL-STD-1167 - Ammunition Data Card
MIL-STD-1168 - Lot Numbering of Ammunition
MIL-STD-1235 - Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

FSC: 1315

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:11Z
Check the source to verify that this is the current version before use.

DRAWINGS

ORDNANCE CORPS

8886612 - Cartridge, AP-T, M339, for 76MM Guns M32 and M48, Assembly and Marking Diagram
7548613 - Container, Ammunition, Fiber, M264, for Cartridge, 76MM, AP-T, M339 or TP-T, M340A1 for Guns M32 and M48
7548614 - Box, Packing, Ammunition, for 76MM Gun Ammunition in Fiber Container M264, Assembly, Details and Packing
8796521 - Marking and Sealing for Ammunition Fiber Containers
8796522 - Marking Diagram and Sealing for Wooden Packing Boxes

PUBLICATIONS

ORDNANCE CORPS

ET-8886612- Equipment Tabulation

(Copies of specifications, standards, drawings and publications required by contractors in connection with specific procurement function should be obtained from the procuring activity or as directed by the contracting officer).

3. REQUIREMENTS

3.1 Material.-Materials and parts shall be in accordance with applicable drawings and specifications.

3.2 Complete round.-The cartridge shall comply with all requirements specified on Drawing (dwg.) 8886612 and with all requirements specified in applicable specifications.

3.3 Propellant weight.-The weight of propellant shall not differ by more than plus or minus 0.25 ounce avoirdupois from that designated by the loading authorization for the particular lot of propellant used.

3.4 Proving ground.-The cartridge shall comply with the following requirements when tested as specified 4.3.2.

3.4.1 Muzzle velocity.-The corrected muzzle velocity of the cartridge when tested at ambient temperature shall not be more than 3250 feet per second (fps) nor less than 3150 fps and the standard deviation of the lot shall not exceed 6.5 fps.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:11Z
Check the source to verify that this is the current version before use.

3.4.2 Tracer functioning.-The tracer shall ignite and there shall be visible evidence of burning of the tracer composition to the 1000 meter target.

3.4.3 Security of parts.-There shall be no evidence of metal parts failure in the gun bore or in flight for a distance of 1000 meters, minimum, from the gun.

3.5 Workmanship.-The cartridge and all components shall be free from chips, dirt, grease, rust, burrs, cracks and other foreign material. The cleaning method shall not be injurious to any of the parts nor shall the parts be contaminated by the cleaning agents. The cartridge shall not be damaged in any manner during the loading operation. The painting and marking shall be restored by the loading and assembling contractor on any components furnished him when such painting and marking has been marred or obliterated.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.-Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to Standard MIL-STD-109 in order to define terms used herein. The provisions of Specification MIL-A-2550 shall apply.

4.1.1 Submission of product.-At the time the completed lot of product is submitted to the Government for acceptance, the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies with all of the quality assurance provisions specified within this specification.

b. Number of units of product inspected.

c. Results obtained, by defect code, for all inspections performed.

d. Drawing, specification number and date, together with an identification and date of changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:11Z
Check the source to verify that this is the current version before use.

e. Certificates of conformance on all material purchased by the contractor when such material is controlled by Government or commercial specifications referenced in any of the contractual documents.

f. Number of items in the lot.

g. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.2 Inspection Provisions

4.2.1 Lot formation.-The term "lot" as used throughout this specification refers to an inspection lot, which is defined as an essentially homogeneous collection of units of product from which a representative sample is drawn and inspected to determine conformance of the lot with applicable requirements. The sample selected shall represent only that quantity of units from which the sample was drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the lot has been produced by one manufacturer, in one unchanged process using the same materials and methods, in accordance with the same drawings, same drawing revisions, same specifications and same specification revisions. Changes to the process, specifications, or drawings, not affecting safety, performance, interchangeability, or storage, as determined by the Government, shall not be deemed to alter the homogeneity of the lot. Inspection lots shall comply with MIL-STD-105. Unless otherwise approved by the contracting officer, the inspection lot size of end items deliverable under the contract shall be not less than the smallest weekly estimate of quantities contractually scheduled for production during the contract period nor more than the largest monthly quantity contractually scheduled for delivery during the contract period. Inspection lots of components or subassemblies, other than the items of delivery, shall be homogeneous and of a size mutually convenient to both the contractor and the Government inspector. Lot numbering, as required, shall be in accordance with MIL-STD-1168. Each lot shall contain:

Source: https://assist.dla.mil -- Downloaded: 20260-22T06:11Z
Check the source to verify that this is the current version before use.

a. Cartridge cases from not more than one lot of resized cases, or
b. Cartridge cases of one lot interfix number from one manufacturer.
c. Projectiles of one lot interfix number from one manufacturer.
d. Tracers of one lot interfix number from one manufacturer.
e. Primers of one lot interfix number from one manufacturer.
f. Propellant from not more than one lot.

4.2.2 Examination.-Inspection for Critical defects (and Major defects, when so specified), shall be 100 percent. Sampling plans and procedures for Major and Minor defects shall be in accordance with MIL-STD-105 except that continuous sampling plans in accordance with MIL-STD-1235 may be used if approved by the procuring activity. Also, at the option of the procuring activity AQL's and sampling plans may be applied to individual characteristics listed using an AQL of 0.65 percent for each Minor defect and an AQL of 0.40 percent for each Major defect, except where 100 percent inspection is specified. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.2.4.

4.2.2.1 Primer, prior to assembly to cartridge case (see dwg. 8838153 covering a detail of dwg. 8886612)

Categories	Defects	Method of Inspection	Code No.
Critical:			
	1. Any flash hole missing.....	Gage	01001
Major: None defined.			
Minor: None defined.			

4.2.2.2 Projectile, prior to assembly to cartridge case (see dwg. 8886612)

Categories	Defects	Method of Inspection	Code No.
Critical: None defined.			

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:11Z
Check the source to verify that this is the current version before use.

Major:	AQL 0.65 percent		
101.	Tracer plug fails to withstand disassembly torque	Test	02001
102.	Tracer closing disc damaged	Visual	02002
103.	Sealing compound missing from rotating band	Visual	02003
Minor:	AQL 1.5 percent		
201.	Incorrect color code	Visual	02004
202.	Evidence of poor workmanship (see 3.5)	Visual	02005
203.	Cement on tracer threads inadequate or missing	Visual	02006

4.2.2.3 Cartridge case, prior to loading propellant (see dwg. 8886612).

Categories	Defects	Method of Inspection	Code No.
Critical: None defined.			
Major:	AQL 0.40 percent		
101.	Primer fails to withstand disassembly torque	Torque-Test	05001
Minor:	AQL 0.65 percent		
201.	Foreign matter in interior of case	Visual	05003

4.2.2.4 Cartridge (see dwg. 8886612).

Categories	Defects	Method of Inspection	Code No.
Critical:			
1.	Primer above flush	Gage	07001
Major:	AQL 0.40 percent		
101.	Total length, max.	Gage	07002
102.	Diameter of bourrelet after retouching, max.	Gage	07003
Minor:	AQL 1.5 percent		
201.	Exterior coating with an aggregate of bare spots in excess of 1/4 square inch	Visual	07004

Source: https://assist.dla.mil -- Downloaded: 202610-22T06:11Z
Check the source to verify that this is the current version before use.

202.	Marking missing, incorrect or unidentifiable including incorrect color code	Visual	07005
203.	Evidence of poor workmanship (see 3.5)	Visual	07006

4.2.2.5 Unsealed fiber container (see dwg. 7548613).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.40 percent		
101.	Packing component missing	Visual	08001
Minor:	AQL 1.5 percent		
201.	Cartridge not removable by hand	Manual	08002
202.	Container cap not removable by hand	Manual	08003
203.	Glue or asphalt on cartridge	Visual	08004
204.	Evidence of poor workmanship (see 3.5)	Visual	08005

4.2.2.6 Sealed fiber container (see dwg. 7548613).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.65 percent		
101.	Sealing strip incomplete or badly wrinkled	Visual	09001
102.	Container cut or damaged through all impregnated layers	Visual-Manual	09002
103.	Metal end loose or distorted	Visual-Manual	09003
Minor:	AQL 2.5 percent		
201.	Sealing strip tab length, min.	Gage	09004
202.	Marking missing, incorrect or unidentifiable	Visual	09005
203.	Cuts, scuffs or gouges in outer layer	Visual	09006

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:11Z
Check the source to verify that this is the current version before use.

4.3 Functional (applicable to Types II and III caps only).

204.	Contents loose	Manual	09007
205.	Color of tape incorrect	Visual	09008

4.2.2.7 Sealed wooden packing box (see dwg. 7548614).

Categories	Defects	Method of Inspection	Code No.
Critical: None defined.			
Major:	AQL 1.00 percent		
101.	Box damaged exposing contents	Visual-Manual	10001
102.	Strapping missing, broken or loose	Visual-Manual	10002
103.	Hardware missing, broken or loose	Visual-Manual	10003
104.	Boards loose, broken or nails protruding	Visual-Manual	10004
105.	DOD symbol missing or incorrect	Visual	10005
Minor:	AQL 2.5 percent		
201.	Car seal missing, unsealed or improperly positioned	Visual	10006
202.	Marking missing, incorrect or unidentifiable	Visual	10007
203.	Hardware improperly engaged	Visual-Manual	10008
204.	Strapping improperly assembled	Visual-Manual	10009
205.	Handle missing or insecure	Visual-Manual	10010

4.2.3 Testing

4.2.3.1 Check test for deterioration of primers (see applicable specification - Major defect - Code No. 01003.-If the total time between original acceptance of any primer lot and the assembly of that lot into the complete round exceeds two years, or if the primers have been subjected to adverse conditions, however brief, at any time since previous tests, the primer lot shall be subjected to, and must satisfactorily pass, the check test specified in the applicable loading specification

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:11Z
Check the source to verify that this is the current version before use.

immediately before the primer lot is assembled into the cartridges. The test shall be performed by the contractor on primers selected by the Government inspector at the facility assembling the cartridges (see 6.4).

4.2.3.2 Propellant weight (see 3.3) Major defect - Code No. 07007.-The propellant for each charge shall be weighed and check-weighed 100 percent. The check weighing shall be accomplished independently of the original weighing, using a different balance from that used to conduct the original weighing, and, if performed manually, shall be performed by another operator. Any charge which fails to comply with the applicable requirement shall be classed defective and shall be returned to the original weighing station for correction. Equipment shall be in accordance with 4.2.4.

4.2.3.3. Bullet pull (see dwg. 8886612) Major defect - Code No. 07008.-The sampling plan for this test shall be in accordance with Standard MIL-STD-414, Section B, Part II, Table B-3, Code letter F and an AQL of 1.5 percent. The test shall be performed as specified in 4.3.1 with equipment in accordance with 4.2.4.

4.2.3.4 Profile and alignment (see dwg. 8886612) Major defect - Code No. 07009.-The cartridges shall be gaged 100 percent for profile and alignment. Any cartridge which fails to meet the applicable requirement shall be classed defective and removed from the lot. Equipment shall be in accordance with 4.2.4.

4.2.3.5 Proving ground.-The following tests shall be performed as specified in 4.3.2.

4.2.3.5.1 Muzzle velocity (see 3.4.1) Major defect - Code No. 07010.

4.2.3.5.1.1 Beginning with the first lot produced and continuing until three consecutive lots have complied with the applicable requirements specified, the sampling plan for this test shall be in accordance with Standard MIL-STD-414, Section B, Part II, Table B-3, Code letter I and an AQL of 1.0 percent shall be used. In addition, if the velocity standard deviation of the sample cartridges multiplied by the factor 0.75 exceeds the lot requirement, the lot shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 202610-22T06:11Z
Check the source to verify that this is the current version before use.

4.2.3.5.1.2 After three consecutive lots have complied with the criteria of 4.2.3.5.1.1, the sampling plan for this test shall be in accordance with Standard MIL-STD-414, Section B, Part II, Table B-3, Code letter F and an AQL of 1.0 percent shall be used. In addition, if the velocity standard deviation of the sample cartridges multiplied by the factor 0.65 exceeds the applicable lot requirement, the lot shall be rejected.

4.2.3.5.2 Tracer functioning (see 3.4.2) Major defect- Code No. 07011.

4.2.3.5.2.1 Beginning with the first lot produced and continuing until three consecutive lots have complied with the applicable requirements specified, the sample cartridges fired in the test for muzzle velocity (see 4.2.3.5.1.1) shall be observed for tracer functioning. If three or more of the samples fired fail to comply with the applicable requirement, the lot shall be rejected.

4.2.3.5.2.2 After three consecutive lots have complied with the criteria of 4.2.3.5.2.1 the sample cartridges fired in the test for muzzle velocity in 4.2.3.5.1.2 shall be observed for tracer functioning. If two or more sample cartridges fail to comply with the applicable requirement, the lot shall be rejected.

4.2.3.5.3 Security of parts (see 3.4.3) Major defect - Code No. 07012.

4.2.3.5.3.1 For the first lot produced and continuing until three consective lots have complied with the applicable requirements specified, the sample cartridges fired in the test for muzzle velocity (see 4.2.3.5.1.1) shall be observed for security of parts. If one or more of the samples fired fail to comply with the applicable requirement, the lot shall be rejected.

4.2.3.5.3.2 After three consecutive lots have complied with the criteria of 4.2.3.5.3.1 the sample cartridges fired in the test for muzzle velocity in 4.2.3.5.1.2 shall be observed for security of parts. If one or more sample cartridges fail to comply with the applicable requirement, the lot shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:11Z
Check the source to verify that this is the current version before use.

4.2.3.5.4 Target-Impact Dispersion (for information only) (see 4.3.2.1).-The sample cartridges fired in the test for muzzle velocity and tracer functioning shall be observed for target-impact dispersion.

4.2.3.5.5 Extreme temperature firing (for information only) (see 4.3.2.2).-Twenty cartridges shall be selected from each of the first three production lots and fired for muzzle velocity, target-impact dispersion, and max. chamber pressure information at -40 degrees F. (10 rds.) and 125 degrees F. (10 rds.).

4.2.3.5.6 Refiring.-If for any reason the proof director considers that the test conditions have detrimentally affected the test results, he shall declare the results invalid and perform a new test on additional rounds as required.

4.2.4 Inspection Equipment.-Equipment Tabulation Number ET-8886612 identifies the inspection equipment required to perform the examinations and tests prescribed in this section. The contractor shall design inspection equipment in accordance with the instructions in 6.3.

4.2.4.1 Government rights to documentation.-Inspection equipment drawings and lists provided and revised in accordance with the requirements of the ET may be used by DOD activities for design, procurement, manufacture, testing, evaluation, production and receiving inspection, overhaul, shipping, storage, identification of stock, ordering and storage of replacement parts, inspection of items at overhaul, general maintenance of equipment, construction, survey and whenever inspection equipment drawings are needed.

4.2.4.2 Supply and maintenance.-Supply and maintenance of the equipment listed in the ET shall be in accordance with Specification MIL-I-45607.

4.2.4.3 Government use of contractor's inspection equipment.-the contractor shall make available to the Government all inspection equipment necessary for determining conformance with contract requirements. Personnel for operating the equipment and verification of its accuracy, shall be supplied by the contractor for the performance of examination or test by the Government.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:11Z
Check the source to verify that this is the current version before use.

4.3 Test methods and procedures.

4.3.1 Bullet pull.-The security of the cartridge case to projectile crimp shall be determined by applying a load in the axial direction at the rate of 0.125 inch per minute using test equipment in accordance with 4.2.4.

4.3.2 Proving ground test.-These tests shall be conducted at a Government proving ground in accordance with the applicable Acceptance Test Procedure. The sample cartridges shall be fired in a gun for which the cartridge is standard and observation made for conformance to all applicable requirements (see 6.5 and 6.6).

4.3.2.1 Velocity-Target Impact Dispersion.-The ammunition fired in this test shall be conditioned at a temperature of 70°F (± 2°F) for a period of 24 hours prior to firing. The cartridge shall be fired at a cloth target placed at a distance of 1,000 meters from the muzzle of the gun. The hit pattern results in vertical and horizontal probable errors in mils shall be recorded on the firing record for informational purposes. Muzzle velocity shall be determined and recorded for each round.

4.3.2.2 Extreme temperature firing. (Information only).-For this test ten rounds shall be temperature conditioned at -40 degrees F. and ten rounds shall be conditioned at 125 degrees F. for a period of 24 hours prior to firing. The cartridge shall be fired at a cloth target placed at a distance of 1000 meters from the muzzle of the gun. Muzzle velocity, max. chamber pressure and target-impact dispersion data shall be recorded.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging.

5.1.1 Level A.-The cartridge shall be preserved and packaged in accordance with dwg. 7548613 with marking and sealing in accordance with dwg. 8796521.

5.2 Packing.

5.2.1 Level A.-The container shall be packed in accordance with dwg. 7548614 with marking and sealing in accordance with dwg. 8796522.

6. NOTES

6.1 Ordering data.-Procurement documents shall specify the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:11Z
Check the source to verify that this is the current version before use.

a. Title, number and date of this specification.
b. Data cards.-Data cards shall be prepared for each lot in accordance with the information specified in Standard MIL-STD-1167.

6.2 Inspection code numbers.-The five digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government.

6.3 Inspection equipment.-The contractor shall design inspection equipment as required by the inspection Equipment Lists (EL) referenced on the applicable ET in accordance with the instructions of paragraphs 6.3.1 through 6.3.5.

6.3.1 Inspection equipment lists (EL).-Inspection equipment lists indicate the availability of inspection equipment designs by showing in the "number" column of the list of inspection equipment (Form SMUPA 1010) the numbers of drawings or Federal Stock numbers of existing equipment designs, or codes as indicated in paragraph 6.3.2. Design action required of the contractor is described in paragraphs 6.3.3 and 6.3.4. The contractor will be required to prepare detailed drawings in accordance with 6.3.4 for all the equipment coded as "Contractor Design" in the number column. These contractor designs must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.5.

6.3.2 Inspection equipment list codes.-The inspection equipment as defined in 6.3.3 and 6.3.4 will be designated in the EL by the following codes:

CD - Contractor design on controlled contractor format and/or commercial equipment.
MU - Army design, mandatory for use.

6.3.3 Army designs.-Army designs are reflected on detailed drawings which completely depict all the information necessary for the fabrication of the item of inspection equipment. The contractor need provide no design when an Army design is listed for an item of inspection equipment. Army designs fall into two basic classifications; mandatory (designated "MU") and non-mandatory (indicated by drawing or Federal Stock Number). When an inspection equipment list references mandatory Army designs, the contractor shall comply with, and use these designs accordingly. The contractor may, however, in connection with non-mandatory designs, design alternate inspection equipment or use comparable commercial equipment to facilitate his operations. Such contractor prepared designs or commercial equipment selections must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be

Source: https://assist.dla.mil -- Downloaded: 202610-22T06:11Z
Check the source to verify that this is the currentversion before use.

submitted for approval as specified in 6.3.5.

6.3.4 Contractor designs.-Contractor designs are designs of inspection equipment for which the Government has assigned design responsibility to the contractor. Contractor designs shall be supported by detailed drawings which depict all information necessary to completely fabricate, calibrate and operate an item of inspection equipment. This requires that the necessary views, dimensions, materials, finish, notes, operating and calibration instructions be properly depicted in accordance with approved practices to the extent that further calculation or clarification will not be required. Unless otherwise specified, contractor designs may be developed on the format the contractor normally employs in his equipment design procedure provided such format reflects the detail and information specified above, subject to the following controls: All submitted contractor designs shall conform to MIL-D-1000, Category E, Form 2. Legibility and reproducibility shall permit conventional making of clearly understandable, high contrast microfilms. Contractors shall submit two copies of final designs as a flat set. Designs shall be submitted for approval as specified in 6.3.5.

6.3.5 Submission of contractor designs.-All submitted designs shall contain a reference to the applicable five digit Code Number contained in Section 4 of this specification and the appropriate component or assembly drawing number and revision letter to which the specific design applies. Unless otherwise specified on the EL, all designs of equipment for inspection of defects classified as critical and major shall be submitted for approval to the Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-ND12. All other designs of inspection equipment shall be approved by the inspection element of the agency administering the contract; submission shall be as directed by the contracting officer. Partial submission of inspection equipment designs is permissible and encouraged. However, the Arsenal completion date for design review will be based on the date of the final submission of designs. Picatinny Arsenal design review will be accomplished normally within one month after receipt.

6.4 Cost of check tests.-The contracting officer will arrange for the contractor to be reimbursed for the expense incurred in the performance of the check test. The test shall be conducted at Government expense without cost to the contractor who loaded the primer or the contractor loading and assembling the cartridge, and shall not constitute a basis for rejection

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:11Z
Check the source to verify that this is the current version before use.

against either contractor, except where deterioration has occurred as a direct result of carelessness in handling, storage, etc, while the primers were under the jurisdiction of either contractor.

6.5 Submission of test data and ammunition data cards.- In addition to the normal distribution of records, when the cartridge is procured by the Army Munitions Command, one of all ballistic test data and ammunition data cards shall be forwarded to each of the following:

Commanding Officer
Picatinny Arsenal
ATTN: SMUPA-ND2 (1 copy)
SMUPA-DA2 (1 copy)
Dover, New Jersey 07801

Custodian:
Army-MU

Preparing activity:
Army-MU

Project No. 1315-A-666

☆ U. S. GOVERNMENT PRINTING OFFICE: 1968-341-513/A-2541

Source: https://assist.dla.mil -- Downloaded: 202610-22T06:11Z
Check the source to verify that this is the current version before use.