MIL-C-46553B
9 January 1974
SUPERSEDING
MIL-C-46553A
5 September 1969

MILITARY SPECIFICATIONS

CARTRIDGE, 20MM, TARGET PRACTICE, M99A1

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers one type of electric primed cartridge for use in Gun, 20mm, Automatic, M24 and M24A1.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation" for bid, or request for proposal, form a part of this specification to the extent specified herein.

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109	- Quality Assurance Terms and Definitions
MIL-STD-644	- Visual Inspection Standards and Inspection Procedures for Inspection of Packaging, Packing, and Marking of Small Arms Ammunition
MIL-STD-651	- Visual Inspection Standards for 20mm Ammunition and Components
MXL-STD-1168	- Lot Numbering of Ammunition
MIL-STD-1235	- Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

FSC 1305

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:16Z
Check the source to verify that this is the current version before use.

2.1 (Cont)

DRAWINGS

U.S. ARMY ARMAMENT COMMAND

D7258928	- Marking on Shipping and Storage Container, M548, for 20mm Cartridges
F7258967	- Method of Packing 150 20mm Cartridges, in M10 Links, Three 50-Round Belts, in M548 Container, Packed for Single-loop Right-hand Feed and Double-loop Left-hand Feed
F7259108	- Method of Bulk Packing ZOO Cartridges, 20mm, Target Practice, with M21A1 Type Cases, in M548 Container
F7259123	- Method of Bulk Packing 150 Cartridges, 20mm, Target Practice, with M21A1 Type Cases, in M548 Container
F7259188	- Method of Packing 150 20mm Cartridges, in M10 Links, Three 50-Round Belts, in M548 Container, Packed for Single-loop Left-hand Feed and Double-loop Right-hand Feed
F7259189	- Method of Packing 150 20mm Cartridges, in M10 Links, one belt, in M548 Container, Packed for Single-loop Left-hand Feed and Double-loop Right-hand Feed
D7259237	- Marking on Shipping and Storage Container, M548 for Cartridges, 20mm, Linked (Functional)
D7258849	- Cartridge, 20mm, Target Practice, M99A1
IEL 7259425	- Index of Inspection Equipment Lists for: Cartridge, 20mm, Target Practice, M99A1
F11075755	- Method of Packing 150 20mm Cartridges, in M10 Links, One Belt, in M548 Container, Packed for Single-loop Right-hand Feed and Double-loop Left-hand Feed

PUBLICATIONS

U.S. ARMY MATERIEL COMMAND

AMCR 715-505-	Ammunition Ballistics Acceptance Test Methods, Volume 8, Test Procedures for 20mm Cartridges

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:16Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 General .-The cartridge shall be in accordance with Drawing (Dwg.) D7258849, reference specifications, and other requirements specified herein.

3.2 First Article Sample.-Unless otherwise directed by the contracting officer, a First Article sample shall be required.

3.3 Manufacturing Process.-All parts and assemblies shall be manufactured by a process approved by the contracting officer, and no deviation from that process shall be made without his prior approval. (see 6.3)

3.4 Projectile Torque.-The projectile shall withstand a minimum torque without rotary movement as specified on Dug. D7258849.

3.5. Projectile Extraction. -The force necessary to extract the projectile from the cartridge case shall be as specified on Dwg. D7258849.

3.6 Electrical Resistance, Primed Cases.-The electrical resistance of the primed cases shall be not less than 500 ohms or more than 1,200,000 ohms.

3.7 Velocity.-The average velocity of the sample cartridges conditioned at 68 degrees (°) Fahrenheit (F) to 72°F shall be 2680 ± 50 feet per second (fps) at 78 feet from the test weapon muzzle and the sample standard deviation shall not exceed 40 fps.

3.8 Pressure. -The average chamber pressure (X) of the sample cartridges, conditioned at 68°F to 72°F, plus 0.84 times the average range (R) of the chamber pressure shall not exceed 51,000 pounds per square inch (psi).

3.9 Waterproofness. -The average velocity (wet) of projectiles of the sample cartridges conditioned at 68°F to 72°F shall not vary from the average velocity (dry) by more than 100 fps.

3.10 Accuracy. -The average mean radius of all targets of the sample cartridge projectiles at ambient temperature shall not exceed 15 inches at a range of 600 yards.

3.11 Action Time.-The action time of the cartridge ambient temperature shall not exceed 4.0 milliseconds.

3.12 Function and Casualty. -The cartridge, at ambient temperature, shall function without casualty.

3.13 Workmanship. -The requirements for workmanship are as specified in the applicable drawing, referenced specifications, and the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:16Z
Check the source to verify that this is the current version before use.

3.13.1 Process Defects. -The cartridge shall be free of defects such as folds, wrinkles, buckles, cracks, splits, severe scratches, cuts, dents, perforations, and other forms of substandard workmanship.

3.13.2 Cleanliness. -The cartridge and its components shall be free of all foreign matter. (see 6.7)

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for Inspection. -Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government . The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Quality Assurance Terms and Definitions .-Reference shall be made to MIL-STD-109 for definition of quality assurance terms.

4.2 Classification of Inspections. -The inspection requirements specified herein are classified as follows:

1. First Article Inspection (see 4.3).
2. Quality Conformance Inspection (see 4.4).

4.3 First Article Inspection.

4.3.1 First Article Sample. -At the beginning of production, a sample representative of the production material, equipment, processes and procedures shall be submitted in accordance with contract requirements and shall consist of 380 cartridges. Prior to approval of the first article sample, the acquisition of material or components for, or the commnencement of production of the balance of the contract quantity shall be at the sole risk of the contractor.

4.3.1.1 First Article Inspection. -Prior to submission of the first article sample to the Government, the contractor shall inspect all components and assemblies for all contract, drawings and specification requirements. The contractors inspection shall be subjected to verification by the Government representative.

4.3.1.2 Examination and Tests. -The first article sample will be inspected for all requirements of the drawings and specifications at a Government laboratory or such facility specified in the contract, Determination as to

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:16Z
Check the source to verify that this is the current version before use.

4.3.1.2 (Cont)

approval of any first article sample shall be based only upon results of initial examinations and tests.

4.4 Quality Conformance Inspection.

4.4.1 Submission of Product.-The product shall be submitted in accordance with MIL-STD-105 or MIL-STD-1235, as applicable.

4.4.1.1 Lot.-A lot shall consist of:

a. Cartridges loaded by one manufacturer, in one unchanged process, in accordance with the contract, the same drawings and drawing revisions, and same specification and specification revision.

b. Like parts and assemblies (cases, primers, projectiles) having one manufacturer's symbol and one interfix number.

c. Propellant from one lot.

4.4.1.2 Lot Identification.-Each cartridge and each packed ammnunition lot shall be identified in accordance with applicable drawings and MIL-STD-1168. Each packed lot shall be further identified by a federal stock number assigned by the procuring activity.

4.4.2 Examination.-One hundred percent examination shall be performed by the contractor for all critical defects. Examination for major and minor defects shall be performed as specified herein. Any cartridge found to be defective shall be rejected.

4.4.2.1 Sampling and Acceptance Criteria.-The sampling plans and procedures shall be in accordance with MIL-STD-105 Or MIL-STD-1235. To determine product acceptability, major or minor defects as listed herein may be considered collectively on a class basis or they may be considered Individually. However, where major defects are considered collectively on a class basis, the acceptance number for any individual defect of the class shall be limited by the assigned Acceptable Quality Level, (AQL) for individual defect associated with the class. (see 4.4.2.1.1.c) In addition, where three or less defects appear in a classification, or, where MIL-STD-1235 is used, sampling plans applicable to a class shall not be used for major defects. (see 6.5)

4.4.2.1.1 AQL's.-The following AQL's are assigned to major and minor defects:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:16Z
Check the source to verify that this is the current version before use.

4.4.2.1.1 (Cont)

a. Individual:

Major	0.25%
Minor	0. 40%

b. Class basis:

Major	1. 50%
Minor	2. 50%

c. Individual defects associatd with the class basis:

Major	0. 40%

4.4.3 Classification of Defects 1/. -The classification of defects shall be as follows:

4.4.3.1 Cartridge Assembly {see Dwg . D7258849) .

Category and Defect	Method of Inspection
Critical:	
1. Split or perforated case	Visual
2. Crack or split on projectile	Visual
Major:	
101. Loose, cocked, crushed, inverted or missing primer	Manual/Visual
102. Depth of primer seating	Gage
103. Over-all length, max.	Gage
104. Improper, incomplete, or missing crimp (case-projectile)	Visual
105. Profile and alignment, max.	Gage
106. Corrosion	Visual
107. Head configuration	Visual
108. Metal sliver on head face	Visual
Minor:	
201. Marking incorrect, incomplete, illegible or missing	Visual
202. Projectile protective coating damaged or incomplete	Visual
203. Waterproofing missing around primer	Visual
204. Scratch, dent, buckle, bulge, wrinkle or fold in case	Visual
205. Rotating band damaged	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:16Z
Check the source to verify that this is the current version before use.

4.4.3.1 (Cont)

Category and Defect	Method of Inspection
206. Primer crimp missing	Visual
207. Foreign matter, except corrosion	Visual
208. Incorrect type cartridge or component	Visual
209. Upset (cracked) or deformed nose	Visual
210. Lacquer on primer button	Visual

4.4.3.2 Cartridge Assembly after Application of Wax coating (see Dwg. D7258849).

Category and Defect	Method of Inspection
Critical: None defined.	
Major:	
101. Wax coating missing or incomplete	Visual
Minor:	
201. Wax coating on projectile	Visual
202. Wax coating flaky or otherwise unsatisfactory	Visual

1/ MIL-STD-651 shall apply in defining and evaluating cartridge visual defects.

4.4.4 Tests.-The tests listed in Table I shall be performed on each cartridge lot in accordance with the test methods prescribed in 4.5. Sample size and acceptance criteria for each test shall be as specified. The sample cartridges shall be selected in- such a manner that the sample is representative of the entire cartridge lot. The cartridge lot sample shall be examined in accordance with 4.4.2 and 4.4.3 and from this sample the cartridges for the various tests shall be selected at random. (see 6.6)

Table I

Test 1/		Sample Size Production Lot	Rqmt Para
Projectile torque	2/	20	3.4
Projectile extraction	3/	20	3.5
Propellant contamination	4/	20	3.13.2
Electrical resistance verification	5/	20	3.6
Velocity	6/	20	3.7
Pressure	7/	20	3.8
Waterproofness	8/	20	3.9
Accuracy	9/	50	3.10
Action Time	10/	50	3.11
Function and casualty	11/	200	3.12

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:16Z
Check the source to verify that this is the current version before use.

4.4.4 (Cont)

1/ The lot shall be rejected if in any firing test one or more of the following malfunctions or casualties of Table II occur:

a. Misfire associated with e or f of Note 1/ of Table II.

b. Projectile remaining in bore.

Metal parts separation, except rotating band separation (see Table II, Note 5/).

Except as otherwise specified and in the function and casualty test where the occurrence of a firing defect listed in Table II prevents the obtaining of a reliable result for the characteristic being tested, an additional shot shall be fired.

2/ Projectile Torque. -Failure of two or more of the sample cartridges to conform with the specified torque requirement shall cause rejection of the lot. If one cartridge of the sample fails to conform, a second sample of 20 cartridges shall be tested. The lot shall be rejected if two or more cartridges of the combined samples fail to conform with the applicable requirement.

3/ Projectile Extraction.

a. Failure of two or more sample cartridges to conform with the minimum requirement shall cause rejection of the lot. If one cartridge of the sample fails to conform with the minimum requirement, a second sample of 20 cartridges shall be tested. The lot shall be rejected if two or more cartridges of the combined samples fail to conform with the minimum requirement.

b. Failure of four or more cartridges to conform with the maximum requirement shall cause rejection of the lot. If more than one but less than four cartridges fail to conform with the maximum requirement, a second sample of 20 cartridges shall be tested. The lot shall be rejected if five or more cartridges of the combined samples fail to conform with the maximum requirement.

4/ Propellant Contamination. -The presence of foreign matter in the propellant of one or more of the test cartridges will cause rejection of the lot. (see 3.13.2 and 6.7).

5/ Electrical Resistance Verification. -The lot will be rejected if any primer of the sample cartridges fails to conform with either of the primer resistance requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:16Z
Check the source to verify that this is the current version before use.

4.4.4 (Cont)

6/ Velocity. -If the sample fails to conform with either or both requirements, a retest sample of 40 cartridges shall be tested for the failing parameter(s) (average, sample standard deviation). The lot shall be rejetted if the retest sample fails to conform with the applicable requirements. (see 6.8.1)

7/ Pressure. -If the average pressure (X) plus 0.84 times the average range (R)of the sample cartridges exceeds 51,000 psi, a retest sample of 40 cartridges shall be tested. The lot shall be rejected if the average pressure (X) plus 0.91 times the average range (R) of the retest sample fails to conform with the applicable requirement. (see 6.8.2)

8/ Waterproofness. -If the average velocity (wet) of the sample fails to conform with the applicable requirement, a retest sample of 40 cartridges shall be tested. The lot shall be rejected if the average velocity (wet) differs by more than 100 fps from the average velocity (dry) of 40 additional sample cartridges fired to establish a new base for comparison. The lot shall not be penalized for failure of the last named sample cartridges to conform with the requirement of 3.7.

9/ Accuracy. -If the average mean radius of the sample cartridges exceeds the applicable requirement, a retest sample of 100 cartridges shall be tested_. The lot shall be rejected if the average mean radius of ten accuracy targets exceeds 15 inches at the same range.

10/ Action Time. -If any sample cartridge fails to meet the requirement for action time, the lot shall be rejected.

11/ Function and Casualty. -The lot shall be rejected if any malfunction or firing casualty of Table 11 occurs in number(s) equal to or greater than the applicable “Rej” rider. Except as otherwise provided, if malfunctions or casualties occur in excess of the applicable “Acc” number, but less than the applicable “Rej” number, a second sample of 400 cartridges shall be selected. The lot shall be rejected if in the combined samples, malfunctions or casualties occur in numbers equal to or greater than the applicable “Rej” rider.

4.4.4.1 Firing Defects. -Firing defects and associated criteria shall be as specified in Table II. For defect definitions, see AMCR 715-505, Volume 8.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:16Z
Check the source to verify that this is the current version before use.

4.4.4.1 (Cont)

Table II

Firing Defects	Ace	Rej
Cartridge:		
Misfire 1/		
Failure to chamber	0	1
Failure to extract	0	1
Projectile remaining in bore	0	1
Primer:		
Missing primer or button missing from primer	0	2
Primer leak	9	25
Case:		
Longitudinal split 2/:		
I or S	10	31
J	4	11
K	0	2
L or M	0	1
Circumferential rupture (partial) 2/:		
S, J, or K	4	11
L	0	1
Circumferential rupture (complete) 2/:	0	1
Detached metal 3/:	0	1
Projectile:		
Rotating band separation:		
Complete or partial separation having band seat serration imprint 4/	0	3
Separation having length greater than 0.5 inch without band seat serration imprint	1	6
Metal parts separation, except rotating band separation 5/	0	1

1/ Misfiring sample cartridge(s), excepting those which occur in the water-proofness test (Table I), shall be retested as specified in 4.5.9. The lot shall not be penalized if the misfiring sample cartridge(s) fire in this test. If a misfiring cartridge fails to function in this test, examinations shall be conducted for the following conditions:

a. Excessive primer seating depth.

b. Metal slivers across primer insulator.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:16Z
Check the source to verify that this is the current version before use.

4.4.4.1 (Cent)

c. Electrical continuity.

d. Missing or obstructed case vent.

e. Missing or insufficient primer composition or propellant.

f. Partially burned or contaminated primer composition or propellant.

The "Acc" number shall be 0 and the "Rej" 3 for misfire(s) associated with a, b, c, or d. The second sample for evaluation of misfire(s) associated with condition a, b, c, or d shall consist of the function and casualty second sample (see Table I, Note 11/). The lot shall be rejected if either condition e or f is observed. Misfire(s) occurring in the waterproofness test shall be evaluated as specified in AMCR 715-505, Volume 8.

2/ Dwg. C7553663 (a detail of IEL 7259425) shall apply for classifying splits and ruptures in fired cartridge cases. If a longitudinal split or circumferential rupture (partial) extends into two or more defined areas, only the most severe defect criterion of Table II for the areas involved, shall apply. If a rupture results in separation of the cartridge case into two or more portions, the defect shall be classed as a complete circumferential rupture.

3/ Metal sheared or missing from the fired cartridge case exterior, such as a rim or neck shear, shall be classed as a defect. The lot shall not be penalized for metal shaved from the interior surface of the case neck in the crimped area.

4/ For classification as a defect, there must be evidence either by recovery of the band, or portion thereof, or by hole(s) in the fragmentation screen(s). The lot shall not be penalized for normal band fringing, or the separation of a band fragment having no evidence of a band seat knurling imprint, and having length of 0.5 inch or less.

5/ Separation or breakup of projectile part(s), except rotating band separation, as witnessed by recovery of the part(s), of fragment(s), or hole(s) in the fragmentation screen(s), shall be classed as a defect.

4.4.4.2 Unlisted Firing Defects.-The lot shall be suspended and referred to the contracting officer for disposition, if a malfunction or casualty not covered by this specification occurring in any firing test indicates that the product is unsuited for the purpose intended.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:16Z
Check the source to verify that this is the current version before use.

4.4.5 Packaging, Packing, and Marking Inspection.-Inspection for packaging, packing, and marking shall be in accordance with MIL-STD-644, as applicable.

4.4.6 Inspection Equipment.-Index of Inspection Equipment List No. IEL 7259425 identifies the applicable Inspection Equipment List (IEL) required to perform examination and tests prescribed herein. Equipment design shall be in accordance with code designation on the applicable IEL <reference is made to Inspection Equipment List for definition of coding, Dwg. B11075228, a detail of IEL 7259425).

4.5 Test Methods and Procedures.

4.5.1 Projectile Torque. -Each cartridge of the test sample shall be marked with a light scratch extending axially across the rotating band onto the case neck. Torque specified shall be applied slowly to the projectile. Movement of the projectile with respect to the cartridge case, detectable by misalignment in the scratch mark, shall be recorded.

4.5.2 Projectile Extraction.-The method of test shall be as specified in AMCR 715-505, Volume 8.

4.5.3 Propellant Contamination. -The propellant from each of the cartridges tested for projectile extraction shall be examined visually for contamination, as prescribed by AMCR 715-505, Volume 8.

4.5.4 Electrical Resistance.

4.5.4.1 Primed Cartridge Case. -The equipment and circuitry specified in IEL 7258849 (a detail of IEL 7259425) shall be used to measure the resistance of the primer in each primed cartridge case.

4.5.4.2 Verification. -A Simpson Volt-Ohm-Ammeter, M260, or approved equal, will be used to measure the resistance of the primer in each primed cartridge case from the projectile extraction test sample. Only the RX1OO and RX1O,OOO scales of the meter will be used in order to limit the applied voltage and current, respectively, to 7.5 volts and 1.4 milliamperes, maximum.

4.5.5 Velocity, Pressure and Waterproofness. -The methods of test shall be as specified in AMCR 715-505, Volume 8. Statistics necessary for testing of results against acceptance criteria shall be computed. (see 6.8)

4.5.6 Accuracy. -The method of test and measurement of targets shall be as specified in AMCR 715-505, Volume 8. The specified range may be shortened in decrements of 100 yards, to a minimum range of 200 yards. For ranges less than 600 yards the average mean radius shall be reduced in direct proportion to the reduction in range.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:16Z
Check the source to verify that this is the current version before use.

4.5.7 Action Time. -The method of test shall be as specified in AMCR 715-505, Volume 8.

4.5.8 Function and Casualty.-The method of test shall be as specified in AMCR 715-505, Volume 8. The test sample shall be fired in bursts of 50 cartridges. The weapon barrel shall be at ambient temperature at beginning of test and cooled to ambient after each 100 rounds. The cyclic rate of each burst shall not be less than 750 shots per minute (SPM) in the M24 gun. The cyclic rate for each burst shall be recorded.

4.5.9 Misfires.-Misfiring cartridges shall be retested in the test equipment specified by the IEL for the accuracy test. Results of examinations required by Table II shall be recorded.

4.5.10 Defective Weapon. -If a test weapon fails to conform with the minimum cyclic rate during a normal burst operation or is found to be defective during or at the end of burst, the test shall be suspended. The weapon shall be corrected or replaced and the test repeated in whole or in part, as indicated. Any firing defect that occurred shall be valid for lot penalty in accordance with Table II unless the defect is found to have been caused by the defective weapon.

5. PREPARATION FOR DELIVERY

5.1 Packing, Level A.-The type of ammunition pack shall be in accordance with instructions from the procuring activity. Linked ammunition shall be packed in accordance with Dwg. F7258967, F7259188, F7259189, or F11075755. Bulk ammunition shall be packed in accordance with Dwg. F7259108 or F7259123.

5.2 Marking. -Marking on the shipping and storage container shall be in accordance with Dwg. D7258928 or D7259237, as applicable.

60 NOTES

6.1 Intended Use.-These cartridges are intended for use in various automatic gun systems that have been designed for firing cartridges with the M21A1 type case configuration.

6.2 Ordering Data. -Invitation for bids and contracts or orders will specify the following:

6.2.1 Title, number and date of this specification.

6.2.2 Place of inspection, if not at place of manufacture.

6.2.3 First article sample requirements. (see 3.2, 4.2, and 6.4)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:16Z
Check the source to verify that this is the current version before use.

6.2.4 Detailed packing and marking instructions. (see 5.1 and 5.2)

6.2.5 Provision for the supply, maintenance and disposition of mandatory ballistic test equipment for acceptance inspection purposes.

6.2.6 Provision for the submission and approval of the manufacturing process. (see 3.3)

6.2.7 Instructions for shipment of first article lot sample for firing test.

6.3 Process Deviation.-A process deviation is defined as a change in the approved basic method of manufacture or an operational change which may alter the metallurgical or physical properties of the item.

6.4 First Article Sample.-In order to minimize inspection costs, the firing tests of 4.4.4 will be performed after the sample has been provisionally accepted by the Government for all other requirements. Additional cartridges may be required by the testing facility.

6.5 AQL's. -The optional use of AQL values for either individual defects or classes of defects, with individual major defect limitation, is intended to minimize inspection agency administrative burden which might result from an exclusive assignment of individual defect AQL's. The option also permits flexibility where sampling inspection for acceptance is integrated into the manufacturing process.

6.6 Combining Tests. -With approval of the procuring activity, tests may be performed concurrently on the same sample cartridges provided that the test results are not effected by this procedure. The test facility should make maximum use of this procedure in order to minimize testing costs.

6.7 Contamination of Explosive Components .-Particular care should be exercised to avoid contamination of primers and propellant by oil, grease, or other foreign matter since such contamination can cause misfires, increase action time and lot rejection.

6.8 Computations.

6.8.1 Standard Deviation.-Where computation of a sample standard deviation is specified for determination of lot acceptance, the method of computation will be:

$$s = \sqrt{\frac{\sum (X_i - \bar{X})^2}{n}}$$ or equivalent.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:16Z
Check the source to verify that this is the current version before use.

6.8.2 Range Plan.-Where a range plan is specified, the individual values will be recorded in subgroups of five in the order in which they are observed. The ranges for the subgroups will be added and the sum of the ranges will be divided by the number of subgroups to determine the average range (R).

NOTE : Asterisks not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Custodians:
Army - MU
Air Force - 70

Preparing Activity:
Army - MU

Review Activities:
Army-MU
Air Force - 70

Project No. 1305-0414

☆ U. S. GOVERNMENT PRINTING OFFICE: 1974 -713-164/1356

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:16Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:16Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

MIL-C-46553B

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 68 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 202610-22T06:16Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID



OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
Frankford Arsenal
ATTN: SMUFA-J4000
Philadelphia, Pa. 19137

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:16Z
Check the source to verify that this is the current version before use.