MIL-I-46521D (AR)
25 July 1979
SUPERSEDING
MIL-I-46521C (PA)
2 May 1975

MILITARY SPECIFICATION

IGNITER, PRIMER, ELECTRIC, M74 LOADING, ASSEMBLING AND PACKING

This Specification is approved for use by the US Army Armament Research and Development Command, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the loading, assembling and packing for one type of igniter designated as Igniter, Primer, Electric, M74 for use in electric primers for artillery ammunition.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids, or request for proposals, form a part of this specificatien to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-P-116 - Preservation, Methods of
MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification for

STANDARDS

MILITARY

MIL-STD-1234 - Pyrotechnics, Sampling, Inspection and Testing

FSC: 1390

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026l0-22T06:10Z
Check the source to verify that this is the currentversion before use.

DRAWINGS

U.S. ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND

PRODUCT AND PACKING DRAWINGS

8840277 - Igniter, Primer, Electric, M74 Loading Assembly
8796694 - Box, Packing, Ammunition for Igniter, Primer, Electric, M74

8796695 - Box, Set-Up, Packing Ammunition, for Igniter Primer, Electric, M74

INSPECTION EQUIPMENT DRAWINGS

8802085 - Fixture, Test
9200357 - Fixture, Adapter
9200358 - Schematic, Electrical
9200359 - Holder, Igniter
9200362 - Instructions, Operating

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

2.2 Other publications.-The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

AMERICAN SOCIETY FOR TESTING AND MATERIALS

ASTM E300 - Industrial Chemicals, Recommended Practice For Sampling

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race St., Philadelphia, Penn. 19103).

3. REQUIREMENTS

3.1 Material.-Materials and parts shall be in accordance with applicable drawings and specifications.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:10Z
Check the source to verify that this is the current version before use.

3.2 Igniters.-The igniters shall comply with all requirements specified on Drawing (dwg.) 8840277, and with all requirements specified in applicable specifications.

3.3 Moisture content of ignition charge composition.-The moisture content of the ignition charge composition at the loading station at the time of loading the ignition element, prior to assembling the igniters, shall not exceed 0.10 percent, when tested in accordance with 4.5.2.

3.4 Electrical resistance.-The igniters shall have an electrical resistance of not less than 0.80 ohms nor more than 1.80 ohms and shall not function when tested in accordance with 4.5.3.

3.5 Functioning.-The igniters shall function when energized with an electric current of 1.25 amperes maximum (max.) when tested in accordance with 4.5.4.

3.6 Non-Functioning.-The igniters shall not function when energized with an electric current of 190 to 200 milliamperes when tested in accordance with 4.5.5.

3.7 First article inspection.-This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.8 Workmanship.-All parts and assemblies shall be fabricated and loaded in a thorough workmanlike manner, and all manufacturing, processing, and assembly operations shall be correctly performed. They shall be clean and free of burrs, sharp edges, unblended radii, surface defects, chips, dirt, grease and oil (except where specifically required), corrosion products and other foreign matter. The cleaning method used shall not be injurious to any part or assembly nor shall they be contaminated by the cleaning agent. Exterior surface coatings shall be continuous except for a few light scratches not exposing base material. All required markings shall be neat and sharply defined. Required packing shall be dry.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions.-Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:10Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspections.-The following types of inspection shall be conducted on this item.

a. First Article Inspection

b. Quality Conformance Inspection

4.3 First article inspection

4.3.1 Submission.-The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with the provisions of 4.3.2. The first article sample shall consist of the following items in the sample quantities as indicated.

PART DESCRIPTION	DRAWING	QUANTITY
Ignition Element Assembly	8831026	50
Igniter Assembly, Prior to Inserting Closing Plug	8840277	50
Igniter, Primer, Electric, M74	8840277	490
Sealed Barrier Bag	8796695	10

4.3.2 Inspections to be performed.-See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection.-See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:10Z
Check the source to verify that this is the current version before use.

TABLE I - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-I-46521D (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
	Igniter, Primer, Electric, M74				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Ignition Element Assembly (Dwg. 8831026)				
	Examination for Defects	50		3.2	4.4.2.1
	Igniter Assembly, Prior to Inserting Closing Plug (Dwg. 8840277)				
	Examination for Defects	50		3.2	4.4.2.2
	Moisture Content of Charge Composition (Note 1)			3.3	4.5.2
	Determination of Charge Composition (Note 1)			3.2	4.5.6
	Igniter, Primer, Electric Assembly (Dwg. 8840277)				
	Examination for Defects	50			4.4.2.3
	Electrical Resistance Check	50		3.4	4.5.3
	Functioning Test	315		3.5	4.5.4
	Non-Functioning Test	125		3.6	4.5.5
	Sealed Barrier Bag (Dwg. 8796695)				
	Examination for Defects	10		3.2	4.4.2.5
	Heat Seal Test	10		3.2	4.4.3.7

NOTES: 1. A sufficient amount of the charge composition shall be taken from each batch of charge composition used in assembling the first article sample.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:10Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection

4.4.1 Inspection lot formation.-Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, inspection lots of igniters shall contain:

a. Metal parts or metal parts assemblies of one lot interfix number from one manufacturer.

b. Ignition charge composition of not more than one lot from one manufacturer.

c. Ignition elements of not more than one lot interfix number from one manufacturer.

4.4.2 Examination.-(See MIL-A-48078). Unless otherwise specified in the classification of defects and test tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.4.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:10Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-I-46521D (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.1	Ignition Element Assembly		8831026
			NEXT HIGHER ASSEMBLY 8840277

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Ignition charge above flush with metal surfaces			3.2	Visual/Straight Edge
2	Ignition charge present on exterior metal surfaces			3.2	Visual
Major					
101	Ignition charge missing or inadequate		0.40%	3.2	Visual
102	Ignition element, including electrode, damaged prior to assembly of charge		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:10Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-I-46521D (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.2	Assembly, Prior to Inserting Closing Plug				8840277
					NEXT HIGHER ASSEMBLY
					8840278
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Closing disc missing or damaged exposing ignition charge		0.40%	3.2	Visual
102	Two or more closing discs present in assembly		0.40%	3.2	Visual/Manual
103	Moisture content of ignition charge composition	(a)		3.3	Test/4.5.2
104	Determination of ignition charge composition	(b)		3.2	Test/4.5.6
Minor					
201	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES: (a) See Paragraph 4.4.3.2
(b) See Paragraph 4.4.3.5

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:10Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-I-46521D (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.3	Assembly				8840277
					NEXT HIGHER ASSEMBLY
					8840278
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Igniter non-functioning test	a		3.6	Test/4.5.5
Major					
101	Electrical resistance		100%	3.4	Test/4.5.3
102	Depth to electrode from rear of igniter body		0.40%	3.2	Gage
103	Flash hole obstructed		0.40%	3.2	Visual
104	Closing plug missing		0.40%	3.2	Visual
105	Igniter functioning test	b		3.5	Test/4.5.4
Minor					
201	Plug stake missing or improper		0.65%	3.2	Visual
202	Flange or thread on igniter body damaged		0.65%	3.2	Visual
203	Closing plug not seated or is loose to finger pressure		0.65%	3.2	Visual/Manual
204	Total length		0.65%	3.2	Gage
205	Marking improper or illegible		0.65%	3.2	Visual
206	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES: a. See 4.4.3.4 for sampling size.
b. See 4.4.3.5 for sampling size.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:10Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-I-46521D (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.4	Box, Setup				8796695
					NEXT HIGHER ASSEMBLY
					8796694
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Assembly damaged so that contents are exposed or liable to become exposed		0.40%	3.2	Visual
102	Sealing strip torn, badly wrinkled, incomplete or otherwise fails to seal the box completely		0.40%	3.2	Visual
103	Separator loose or missing		0.40%	3.2	Visual
104	Bottom cushion missing		0.40%	3.2	Visual
Minor					
201	Carton torn, cut or punctured		0.65%	3.2	Visual
202	Contents loose		0.65%	3.2	Manual
203	Carton corners not blunted prior to insertion into barrier bag		0.65%	3.2	Visual
204	Marking missing, incorrect or illegible		0.65%	3.2	Visual
205	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:10Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-I-46521D (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.5	Sealed Packed Barrier Bag, Prior to Packing in Box		8796695
			NEXT HIGHER ASSEMBLY
			8796694

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Waterproofness of barrier bag destroyed by rupture, puncture or separation of heat seal		0.40%	3.2	Visual
102	Box crushed (note 1)		0.40%	3.2	Visual
103	Excess air not exhausted from bag (prior to sealing)		0.40%	3.2	Visual
104	Heat seal test	Note 2		3.2	Test/4.5.7
Minor					
201	Heat seal of barrier bag located so that one or more subsequent seals cannot be applied		0.65%	3.2	Visual
202	Marking of bag misleading or unidentifiable		0.65%	3.2	Visual
203	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:
1. Package should be opened if there is evidence of crushing.
2. Sampling shall be in accordance with 4.4.3.6.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:10Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-I-46521D (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.6	Box, Packing				8796694
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Board broken or split		0.40%	3.2	Visual
102	Contents exposed		0.40%	3.2	Visual
103	Strapping missing, broken or loose		0.40%	3.2	Visual/Manual
Minor					
201	Marking misleading, incorrect or illegible		0.65%	3.2	Visual
202	Strapping improperly assembled		0.65%	3.2	Visual/Manual
203	Contents move when box is tilted		0.65%	3.2	Manual
204	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:10Z
Check the source to verify that this is the current version before use.

4.4.3 Testing

4.4.3.1 Chemical sampling.-A representative sample shall be randomly selected for the chemical tests specified in 4.4.3.5. The procedure described in ASTM E300 should be used to withdraw the samples. The chemical tests in 4.5 shall be performed using prescribed analytical procedure for replicate determinations given in standard analytical textbooks.

4.4.3.2 Moisture content of ignition charge composition.-The contractor shall test for verification at least one sample during each eight hours production of igniters. Composite samples shall not be used in determining compliance. Failure to comply with the applicable requirement shall be cause for rejection of the eight hour production represented by the sample. The test shall be performed as specified in 4.5.2.

4.4.3.3 Functioning

4.4.3.3.1 Initial production.-Beginning with the first lot produced and continuing until three consecutive lots have complied with the applicable requirements specified, three hundred and fifteen samples shall be randomly selected from each lot and shall be subjected to the test specified in 4.5.4 with equipment in accordance with 4.4.4. If 2 or more failures occur, the lot shall be rejected.

4.4.3.3.2 Subsequent production.-After three consecutive lots have met the criteria of 4.4.3.3.1, a sample of 200 igniters shall be selected from each lot for this test. If two or more igniters fail to comply with the applicable requirement, the lot shall be rejected.

4.4.3.4 Non-functioning

4.4.3.4.1 Initial production.-Beginning with the first lot produced and continuing until three consecutive lots have complied with the applicable requirements specified, one hundred and twenty-five samples shall be randomly selected from each lot and shall be subjected to the test specified in 4.5.5 with equipment in accordance with 4.4.4. If any failure occurs, the lot shall be rejected. Igniters subjected to this test shall not be returned to the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:10Z
Check the source to verify that this is the current version before use.

4.4.3.4.2 Subsequent production.-After three consecutive lots have met the criteria of 4.4.3.4.1, fifty samples shall be randomly selected from each lot and shall be subjected to the test specified in 4.5.4 with equipment in accordance with 4.4.4. If any failure occurs, the lot shall be rejected. Igniters subjected to this test shall not be returned to the lot.

4.4.3.5 Determination of ignition charge composition.-A sufficient amount of ignition charge composition shall be selected from each batch for analysis. The analysis shall be performed as specified in 4.5.6 and any failure to comply with the applicable requirement shall be cause for rejection of the production represented by the sample.

4.4.3.6 Heat seal test of sealed bag.-Sampling and acceptance criteria for this test shall be as prescribed by MIL-P-116 (see 4.5.7).

4.4.4 Inspection equipment.-The inspection equipment required to perform the inspections and tests prescribed in this specification is identified in the 'Paragraph Reference/Inspection Method' column in the tables starting with paragraph 4.4.2.1. The contractor shall submit for approval, inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078, and section 6.2 herein.

4.5 Test methods and procedures

4.5.1 Precaution.-This specification covers sampling and testing of chemical, toxic or explosive materials which are potentially hazardous to personnel. Accordingly, it is emphasized that all applicable safety rules, regulations and procedures must be followed in handling and processing these materials.

4.5.2 Moisture content of composition change.-Determination of moisture content of ignition charge composition shall be in accordance with method 101.5 of MIL-STD-1234, which describes the test procedure.

4.5.3 Electrical resistance.-The igniters shall be tested for electrical resistance by applying an electrical current of 20 milliamperes, max., using the electrode as one contact point and the igniter body as the other. Observation shall be made for compliance with the applicable requirement.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:10Z
Check the source to verify that this is the current version before use.

4.5.4 Functioning.-The igniters shall be tested for electrical functioning by applying an electrical current of 1.25 amperes, max., using the electrode for one contact point and the igniter body as the other. The time of the current flow shall be one tenth second maximum. Observation shall be made for functioning. Method of inspection shall be in accordance with dwg. 8802085, 9200357, 9200358, 9200359 and 9200362.

4.5.5 Non-functioning.-The igniters shall be tested for electrical functioning by applying an electrical current of 190 to 200 milliamperes, using the electrode as one contact point and the igniter body as the other. The time of the current flow shall be one second minimum. Observation shall be made for non-functioning. Method of inspection shall be in accordance with dwgs. specified in 4.5.4.

4.5.6 Determination of ignition charge composition mixture (see 6.6).-The chemical composition of the ignition charge shall be considered satisfactory if it is in accordance with the following:

Component	Percentage
Potassium Chlorate	44.5 plus or minus 2
Lead Thiocyanate	35.5 plus or minus 2
Charcoal	20.0 plus or minus 1.5
Lacquer Solids (added)	1.6 plus or minus 0.2

4.5.6.1 Lacquer solids.-Approximately 1.5 grams of the sample shall be transferred to a tared medium porosity filtering crucible and allowed to air dry for about an hour. The crucible and contents shall be placed in a vacuum oven for two hours maintained at a temperature of 55 plus or minus 2 degrees Celsius. The crucible and contents shall be cooled in a desiccator and weighed. The procedure shall be repeated until the change in weight does not exceed 0.5 milligrams. The contents of the crucible shall be extracted with ten 25 milliliter (ml.) portions of acetone saturated with potassium chlorate and lead thiocyanate. The crucible and contents shall be aspirated until the odor of acetone is no longer perceptible and then dried in a vacuum oven maintained at 55 plus or minus 2 degrees Celsius for two hours. The crucible and contents shall be cooled in a desiccator and weighed. The percent lacquer solids shall be calculated as follows:

Percent lacquer solids = 100 percent (A-B) divided by B

where:
A = the weight of the sample dried in the oven
B = the weight of dried sample after acetone extraction

Reserve contents of crucible for the charcoal content test

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:10Z
Check the source to verify that this is the current version before use.

4.5.6.2 Charcoal content.-With the aid of a Fisher High Form Filtrator, or equivalent, the contents of the crucible remaining after the lacquer solids determination shall be extracted with ten 25 ml portions of 5 percent potassium nitrate solution followed by 50 ml of distilled water. Use a small glass rod to break up any lumps in the sample during the extraction process. Preserve the filtrate for the determination for lead thiocyanate. Aspirate the residue for several minutes, place in an oven maintained at 100 plus or minus 5 degrees C. for 2 hours, cool in a desiccator and weigh. Calculate the percentage of charcoal as follows:

Percent charcoal = 100 percent times (A divided by B)

where:
A = the weight of sample after acetone and 5 percent potassium nitrate solution extraction
B = the weight of sample after acetone extraction

4.5.6.3 Lead thiocyanate.-Exactly 35 ml. of standardized 0.1 normal (N) silver nitrate shall be added to the filtrate reserved from the charcoal determination. The flask and contents shall be swirled and 100 ml. of 3N nitric acid (nitric acid used should be water-white and free of oxides of nitrogen) shall be added. The swirling of the mixture shall be continued for five minutes, 5 ml. of a saturated solution of ferric ammonium sulfate shall be added and the solution titrated with standardized 0.1 N potassium thiocyanate solution to the first permanent pale rose coloration. The percentage of lead thiocyanate in the sample shall be calculated on a dry basis as follows:

Percent lead thiocyanate = (16.17 (AE-CD) divided by B) times 100 percent

where:
A = Volume of silver nitrate solution used
B = Weight of the sample after acetone extraction (see 4.5.6.2)
C = Volume of the potassium thiocyanate solution used
D = Normality of potassium thiocyanate solution
E = Normality of the silver nitrate solution

4.5.6.4 Potassium chlorate.-The percent of potassium chlorate shall be determined by subtracting the total percentage of charcoal and lead thiocyanate from one hundred percent.

4.5.7 Barrier bag heat seal test.-The procedure for performing the test of the security of the heat seal shall be as specified in MIL-P-116.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:10Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging

5.1.1 Level B.-Packaging shall be as specified on dwg. 8796695.

5.2 Packing

5.2.1 Level B.-Packing shall be as specified on dwg. 8796694.

5.3 Marking.-Marking of all packaging and packing shall comply with dwgs. 8796695 and 8796694.

6. NOTES

6.1 Ordering data.-See MIL-A-48078.

6.2 Submission of designs for approval.-Submit equipment designs as required to: Commander, U.S. Army Armament Research and Development Command, ATTN: DRDAR-QAR-I, Dover, New Jersey 07801, (See MIL-A-48078).

6.3 Delivery of data cards to the technical agency.-In addition to the addresses listed in the contract (Form DD 1423), one copy of each Ammunition Data Card prepared by the contractor for the duration of the contract: Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QAR-E, Dover, New Jersey 07801.

6.4 Check test for possible deterioration.-The following test is designed to prevent igniters that have deteriorated from being assembled into major ammunition items. The test shall be performed on igniters from each lot which have been stored under normal conditions for more than two years or under adverse conditions for any period of time. If the specification for the ammunition item into which the igniters are assembled does not require that the check test be performed, the Contracting Officer should insert in the contract a provision for the performance of the check test. The Contracting Officer will arrange for the contractor to be reimbursed for expense incurred in his performance of the check test for possible deterioration. Igniter assemblies shall be selected from each lot for this test. Examples of exposure of igniters to adverse conditions are indications of corrosion products on the igniter body; moisture (water) marks or stains on the exterior packaging; or, cuts, scrapes, scuff marks, gouges or tears in the inner packaging, including the integrity of the barrier bag and the security of the seal.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:10Z
Check the source to verify that this is the current version before use.

6.4.1 Functioning.-Three hundred and fifteen (315) samples shall be randomly selected from each lot for this test. If three (3) or more failures occur, the lot shall be rejected. Test shall be performed as specified in 4.5.4.

6.4.2 Non-functioning.-One hundred and twenty-five (125) samples shall be randomly selected from each lot for this test. If any failure occurs, the lot shall be rejected. Igniters subjected to this test shall not be returned to the lot. Test shall be performed as specified in 4.5.5.

6.4.3 Electrical resistance.-This test shall be performed 100 percent. Any igniter which fails to comply with the applicable requirement shall be classed defective and removed from the lot. Test shall be performed as specified in 4.5.3.

6.5 Loading of charge.-Although the charge is part of the M18 Ignition Element, it is not applied until the element is ready to be assembled into the M74 Igniter.

6.6 Determination of ignition charge composition.-During the manufacture of the ignition charge composition up to two parts of solvent are added to one part of Egyptian lacquer (P/N 9327420) in order to facilitate the blending of the mixture. Because of the volatility of the solvent, the solvent content of the ignition charge composition is found to be a variable. Because of this the determination of the potassium chlorate, lead thiocyanate and charcoal content are determined on a lacquer free basis and the lacquer solids on an added basis.

6.7 Changes from previous issue.-Due to the extensiveness of the changes, asterisks are not used in this revision to identify changes with respect to the previous issue.

Custodian:
ARMY-AR

Preparing Activity:
ARMY-AR

Project No.: 1390-A216

☆U.S. GOVERNMENT PRINTING OFFICE: 1979 603 022 3575

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:10Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-I-46521D Igniter, Primer, Electric, M74 Loading, Assembling and Packing

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*	TELEPHONE NO.
	DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:10Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID



OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

COMMANDER
US ARMY ARMAMENT RESEARCH & DEVELOPMENT COMMAND
ATTN: DRDAR-QAR
DOVER, NJ 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:10Z
Check the source to verify that this is the current version before use.